10 October 2026 · Tested local application

Call timing for completed meetings.

Primary objective: **meeting_done**, under the user's override of PS03. Actual offline models use a separate linked physical **recorded-met proxy**; meeting_fixed remains unknown.

Read-only extraction → Frozen proxy datasets → Two offline models → Windows & retries → Live Luna review

Actual data and held-out evidence

39,284
real outbound calls
36,447 sellers · 10 fixed dates
Read-only source 13; fixed hash sampling

130
linked physical proxy events
canonical label unverified
Record insertion within 14 days

0.6432
general proxy ROC AUC
12,000 test calls / 43 positives
AUPRC 0.005209; prevalence 0.003583

2
frozen offline models
each final test evaluated once
Both remain unapproved for deployment

Measured performance, explicit limits

General winner: smoothed hour/day + validation-fitted calibration. Log loss **0.02310**; ranking and budget yield match the strong raw baseline.

Scoped first-contact logistic trained on 6,242 calls / 17 positives. Final test: **1,364 calls / zero positives**; discrimination undefined and acceptance unmet.

40 tests, lint, types, production build and HTTP/browser checks pass. Luna: 3 live tools, ~6.1 seconds, grounded review. Real Python/Node model scores agree within 9×10^{-19}.

KEEP RETRY RULE PENDING PILOT

No causal completed-meeting lift measured. Retain the 15-minute rule and verified stopping constraints; use a seller-randomized pilot at equal call budget after canonical label confirmation.

Clock features only; current seller metadata and outcomes excluded.
14-day maturity embargo; observed scope does not prove lifetime first contact.

Goal: ≥10% relative completed-meeting yield, positive 95% lower bound.
Canonical policy acceptance remains unmeasured.