Bank A

GND	1	2	GND
IO N	3	4	IO N
IO P	5	6	IO P
GND	7	8	GND
IO N	9	10	IO N
IO P	11	12	IO P
GND	13	14	GND
IO N	15	16	IO N
IO P	17	18	IO P
GND	19	20	GND
IO N	21	22	IO N
IO P	23	24	IO P
GND	25	26	GND
IO N	27	28	IO N
IO P	29	30	IO P
GND	31	32	GND
IO N	33	34	IO N
IO P	35	36	IO P
GND	37	38	GND
IO N - GCLK	39	40	IO N - LCLK
IO P - GCLK	41	42	IO P - LCLK
GND	43	44	GND
IO N - GCLK	45	46	IO N - LCLK
IO P - GCLK	47	48	IO P - LCLK
GND	49	50	GND
IO N	51	52	IO N
IO P	53	54	IO P
GND	55	56	GND
IO N A	57	58	IO N A
IO P A	59	60	IO P A
GND	61	62	GND
IO N A	63	64	IO N A
IO P A	65	66	IO P A
GND	67	68	GND
IO N A	69	70	IO N A
IO P A	71	72	IO P A
GND	73	74	GND
IO N A	75	76	IO N A
IO P A	77	78	IO P A
GND	79	80	GND

Bank B

GND	1	2	GND
IO N	3	4	IO N
IO P	5	6	IO P
GND	7	8	GND
IO N	9	10	IO N
IO P	11	12	IO P
GND	13	14	GND
IO N	15	16	IO N
IO P	17	18	IO P
GND	19	20	GND
IO N	21	22	IO N
IO P	23	24	IO P
GND	25	26	GND
IO N	27	28	IO N
IO P	29	30	IO P
GND	31	32	GND
IO - QWIIC	33	34	IO N
IO - QWIIC	35	36	IO P
GND	37	38	GND
IO N - LCLK	39	40	IO N - LCLK
IO P - LCLK	41	42	IO P - LCLK
GND	43	44	GND
IO N - GCLK	45	46	IO 1V35
IO P - GCLK	47	48	IO 1V35
GND	49	50	GND
IO N MV	51	52	IO N MV
IO P MV	53	54	IO P MV
GND	55	56	GND
IO N MV	57	58	IO N MV
IO P MV	59	60	IO P MV
GND	61	62	GND
IO N MV	63	64	IO N MV
IO P MV	65	66	IO P MV
GND	67	68	GND
IO N MV	69	70	IO N MV
IO P MV	71	72	IO P MV
GND	73	74	GND
IO MV	75	76	IO N MV
IO MV	77	78	IO P MV
GND	79	80	GND

Control

+3V3	1	2	RAW
+3V3	3	4	RAW
+3V3	5	6	RAW
+3V3	7	8	RAW
+3V3	9	10	RAW
+3V3	11	12	RAW
+3V3	13	14	RAW
+3V3	15	16	RAW
GND	17	18	GND
GND	19	20	GND
GND	21	22	GND
GND	23	24	GND
GND	25	26	GND
GND	27	28	GND
LED 0	29	30	LED 4
LED 1	31	32	LED 5
LED 2	33	34	LED 6
LED 3	35	36	LED 7
Reset	37	38	VBSEL_A
DONE	39	40	VBSEL_B
Program	41	42	A1V8
TMS	43	44	AVP
TCK	45	46	AVN
TDI	47	48	AREF
TDO	49	50	AGND

VBSEL Value Table

VBSEL_A	VBSEL_B	MV Voltage
floating	floating	3.3
low	low	3.3
low	high	3.3
high	low	1.8
high	high	2.5

low = 0-0.9
high = 1.1-3.3

Connecting VBSEL_A to VBSEL_B results in 2.5V

A = 1V analog input capable
MV = multi voltage
Orange = routed as 100ohm diff pair
Remaining pins routed as 50ohm singled ended