

Refreshment of the Shortest Path Cache with Change of Single Edge

Xiaohua Li^a, Tao Qiu^a, Ning Wang^{b,*}, Xiaochun Yang^a, Bin Wang^a, Ge Yu^a

^a*School of Computer Science and Engineering, Northeastern University, Liaoning, China*

^b*Department of Information Management, School of Management, Shanghai University, Shanghai, China*

Abstract

The problem of caching shortest paths has been widely studied. All existing methods that address this problem assume that the conditions of road networks do not change with time. In this paper, we study how to refresh a cache when one edge of the underlying road network (graph) changes. A bitmap-based cache structure is proposed to store and give access to shortest paths. In the following, algorithms are developed to detect shortest paths that are affected by the change of edge. After detecting affected paths, several heuristic-based refreshment strategies are proposed to update the cache. We have conducted a series of experiments to compare the performance of proposed methods. It shows that replacing affected shortest paths with new ones whose benefit values are largest should be applied in the shortest paths caching applications such as navigation and map services.

Keywords: shortest path caching, cache refreshment strategy, change of road network, affected shortest paths

1. Introduction

Shortest path query systems are now widely seen in our daily life (Wu et al., 2012; Potamias et al., 2009; Wei, 2010; Liu & Yang, 2011; Cheng et al., 2012). People who use Google or Baidu map usually request shortest paths to restaurants, parking lots,

*Corresponding author.

Email addresses: lixiaohua@ise.neu.edu.cn (Xiaohua Li), qiutaoneu@gmail.com (Tao Qiu), ningwang@shu.edu.cn (Ning Wang), yangxiaochun@ise.neu.edu.cn (Xiaochun Yang), wangbin@ise.neu.edu.cn (Bin Wang), yuge@ise.neu.edu.cn (Ge Yu)

5 cinemas, playgrounds, shopping malls and so on. When a user has a shortest path query,
a cache in a local server is accessed; the result, if exists, will be directly returned to the
user. If the cache does not have an off-the-shelf result to the query, the system accesses
a global server which runs a shortest path algorithm for the result. The latter situation
undoubtedly costs communication and computational time (Altingovde et al., 2009;
10 Baeza-Yates et al., 2007; Kriegel et al., 2008; Gan & Suel, 2009; Markatos, 2001). The
contents in caches are, therefore, very critical for the efficiency of the whole query
system.

In the shortest path caching problem, existing works all discuss the cache initial-
ization problem which addresses how to load an empty cache when a road network
15 and a query log is known, so that the cache works in a high-efficiency level in the fu-
ture. Researchers usually select paths with the highest query frequencies into caches,
or those paths that contain the most numbers of nodes (Thomsen et al., 2012; Li et al.,
2013). Existing works do not discuss how to refresh the cache when the road condition
or queries change. Actually, the road condition cannot remain the same all the time; on
20 contrast, it changes frequently. For example, rush hours or traffic congestion changes
weights of some edges on a road network. When a road network changes, if paths in the
cache are not adjusted, some paths in the cache may become invalid or the utilization
of the cache decreases. How to maintain a cache based on changes of a road network
is seldom discussed in the literature. Apparently, a straightforward way to refresh a
25 cache is to empty the cache and conduct an initialization process once more. Such a
method is too naive, because computing and evaluating all the shortest paths once more
are time-consuming.

In this paper, we discuss how to refresh a cache when the weight of a certain edge
changes. Assuming that only one edge changes its weight is reasonable. On one hand,
30 studying the change of single edge is a good point to start from. We can draw some
conclusions from the single-edge scenario and apply them to multi-edge scenario. On
the other hand, single-edge has some applications. For example, traffic congestion
may happen in main streets and these main streets are far away from each other and
unrelated; the congestion in every main street can be separately viewed as a single-edge
35 scenario.

We first develop a cache structure based on a structure of bitmap to store and retrieve shortest paths. We then introduce the concept of “affected paths” and develop algorithms to detect affected shortest paths due to the change of edge weight. Next, we design four strategies to refresh the cache and compare their performance. Our work
40 contributes to the literature in two aspects. First, to the best of our knowledge, our work is the first one to discuss the shortest path caching problem in a changing graph. This problem is undoubtedly more close to real applications. Second, four cache refreshment strategies are proposed to update the cache. It is noteworthy that this work is an extension of Li et al. (2014) which is published in a conference. This paper extends
45 the initial work, by 1) adopting a bitmap index to efficiently answer queries of shortest paths; 2) introducing several optimization techniques to further improve the efficiency of detecting affected shortest paths; 3) performing more comprehensive experiments on real data sets, including Aalborg, Beijing and Singapore road networks. Especially, the data set of Singapore is newly added and is not used in the conference version.

50 The rest of the paper is organized as follows. In Section 2, we review works related to the shortest path caching problem. In Section 3, we formally define the problem and design a bitmap-based cache structure to store shortest paths. Then we explore the properties of changed graphs and present our algorithm of detecting affected shortest paths in Section 4. In the following, four cache refreshment strategies are proposed in
55 Section 5. In Section 6, we conduct experimental comparisons of the proposed methods on real data sets. Finally, we give closing remarks in Section 7.

2. Literature Review

Our problem is related to works of two streams. One stream is to detect which shortest paths are changed after the graph changes. We call this kind of problem as
60 “affected shortest path detection” problem. The other stream addresses the problem of caching shortest paths. In the following, we introduce concrete works in the two streams.

2.1. *Affected Shortest Path Detection*

The shortest path of a certain node-pair may change after the weights of some edges change in a graph. The affected shortest path detection problem deals with finding node-pairs whose shortest paths are affected and update new shortest paths for these node-pairs. Based on whether the network changes in a regular manner, it has predictable and unpredictable networks.

Predictable Network Models aim at finding the expected fastest (shortest) paths based on the known distribution of predicted networks. In details, Kanoulas et al. (2006) developed the concept of speed pattern to specify the predicted network costs (weights) at different time, and the fastest paths corresponding to different time can be computed based on the predicted network cost. Fu & Rilett (1998) modeled the cost of each edge as a continuous stochastic process, and then they found the expected fastest paths. Similarly, Ding et al. (2008) used time-delay functions to represent the predicted edge costs.

Unpredictable Network Models assume that the costs of graph change randomly and cannot be depicted by a statistical distribution. Unpredictable network problem has offline and online versions.

For the offline research, it has pre-processing and needs extra space to store auxiliary information. In Tian et al. (2009), an index named QSI was used to identify the shortest paths affected by the change of network. QSI keeps the subnetworks that are involved in derivation of answering shortest paths. In Lee et al. (2007), in order to process more than one shortest path query simultaneously, a grid-based index structure was designed to record all the affecting areas. Besides, arc-flags is a typical index-based approach to compute the shortest paths. It has been adopted by Lauther (2004) for a static network. Berrettini et al. (2009); D'Angelo et al. (2014) studied the problem of updating arc-flags in dynamic networks.

For the online research, Bauer & Wagner (2009); D'Andrea et al. (2013); Frigioni et al. (1996); Narváez et al. (2000); McQuillan et al. (1980) studied how to update the shortest paths starting from a specified node. In general, these algorithms preprocess the shortest paths starting from a given source node, and store them in a shortest path tree (SPT). To update the SPT, the basic idea is to utilize the information of the outdated SPT and update only the part of the SPT that is affected by the changed edge. Lee et al.

95 (2007) studied the problem of continuous evaluating shortest path queries. For several queries, they developed an ellipse bound method (EBM) where each shortest path corresponds to an elliptic geographical area, called affected area, and all the updated edges are considered to affect their corresponding paths.

It can be seen from the above review, offline study of shortest path detection problem uses extra space. For the online problem, some research maintain a novel designed data structure or they can only detect known paths. In our problem, the space is reserved for the cache; it cannot tell which paths are affected (or no longer the shortest) before the graph changes. Thus, extant algorithms for detecting affected shortest paths cannot be used in our problem directly.

105

2.2. Caching Problem

Another steam is the caching problem. Caching techniques have been studied extensively in many domains (O’Neil et al., 1993; Markatos, 2001). The main focus is to decide the contents that are cached.

110 **Web Search Caching.** In Markatos (2001), caching strategies are classified into static caching and dynamic caching. Static caching does not change the contents of cache once the cache is loaded based on the historical log (Altingovde et al., 2009; Baeza-Yates & Saint-Jean, 2003; Baeza-Yates et al., 2007). The static caching usually updates periodically based on the latest query log. Dynamic caching focuses on suiting for new arrival queries and weeding out old contents (Gan & Suel, 2009; Long & Suel, 115 2005; Markatos, 2001).

Shortest Path Caching. Thomsen et al. (2012); Li et al. (2013); Thomsen et al. (2014) have studied the caching of shortest paths. In details, Thomsen et al. (2012) is the pioneer work on caching of shortest paths. They proposed a cost-oriented model to quantify the benefit of loading paths to a cache. Based on this model, a static caching strategy is proposed to initialize the cache. Li et al. (2013) also focuses on a static strategy. In order to store as many paths as possible, an improved cost-oriented model was proposed to measure paths appeared in the query log. Thomsen et al. (2014) proposed the notion of generically concise shortest paths that enables a trade-off between the 120

125 size of paths and the number of queries answered by paths. They considered both the static and dynamic caching strategies for selecting generically concise paths. For the dynamic strategy, they update the cache in a least-recently-used policy when missing targets occur.

In applications of caching problem such as web search caching, queries change with time while the data (answers) will change in no way. The inefficiency of cache is fully resulted from the change of queries. Hence, “dynamic” caching strategies are motivated by the change of queries. However, in the shortest path caching problem, the change of graph (data) may also lead to the incorrectness of the answer and inefficiency of the cache. In this paper, we investigate the problem of shortest path caching when the graph changes, and we extend the concept of “dynamic” caching to the change of data.

3. Problem Description and Cache Structure

3.1. Notation and Problem Description

The graph $G = (V, E)$ studied in this paper is undirected; $V = \{v_1, v_2, \dots, v_n\}$ is the set of nodes and $E = \{e_1, e_2, \dots, e_k\}$ is the set of edges. The weight of an edge e is denoted by w_e . $P_{a,b}$ represents the shortest path between v_a and v_b . If there exists more than one shortest paths between v_a and v_b , $P_{a,b}$ represents one of them. $Q_{a,b}$ represents a query of the shortest path between v_a and v_b . A cache is denoted by Ω and its capacity is $|\Omega|$. Ψ refers to cached contents. The size of a cache and cached contents are measured by the number of nodes. It is clear that the size of Ψ is always no larger than the cache capacity, i.e., $|\Psi| \leq |\Omega|$ all the time.

The problem is formally defined as follows: given an undirected graph G and a query log L , the query log records the queries of shortest paths of G . A cache Ω caches a part of shortest paths. Now the cache Ω has been fully loaded and the weight of a single edge e in G changes from w_e to w'_e . Some paths in the cache may not be the shortest paths any more. The objective of our problem is to refresh the content of cache Ω so that the hit ratio of future queries is as high as possible. The size of cache is assumed to be smaller than the size of shortest paths queried in L .

3.2. Cache Structure

155 In this paper, we design a cache structure to store and access paths in a cache. In essence, the cache structure needs to satisfy two requirements: fast response and space efficiency. We use a bitmap structure to index shortest paths. The bitmap structure was first developed for database use in the Model 204 product from Computer Corporation of America (O’Neil & Quass, 1997). Now bitmap is commonly used in databases and
160 data warehouses (Wang et al., 2016).

The cache structure proposed includes two parts of information: the path array that stores shortest paths and the bitmap that is used to index paths. A bitmap is a 2-dimensional array. The horizontal and vertical indices are paths and nodes, respectively. If a path contains a certain node, the unit crossed by the path and node is marked with 1; otherwise, it is marked with 0. The storage space of each unit only takes one bit. Here
165 the name, bitmap. The horizontal array indicated by a node v_i is called a node vector \vec{v}_i . Take Figure 1 as an example. Three shortest paths $P_{0,5}$, $P_{2,4}$ and $P_{3,6}$ are stored in the form of arrays (Figure 1(a)), and the bitmap of nodes is shown in Figure 1(b).

	$P_{0,5}$	$P_{2,4}$	$P_{3,6}$
v_0	1	0	0
v_1	1	0	0
v_2	0	1	0
v_3	0	1	1
v_4	1	1	1
v_5	1	0	0
v_6	0	0	1

(a)
(b)

Figure 1: An example of cache structure.

Given a query $Q_{s,e}$, we need to look up shortest paths that contain v_s and v_e . The
170 caching system looks up the bitmap and finds the node vectors \vec{v}_s and \vec{v}_e . An AND operate is conducted to acquire $\vec{v}_r = \vec{v}_s \text{ AND } \vec{v}_e$. In \vec{v}_r , the bits whose value are 1 correspond to paths that contain $P_{s,e}$.

Now we analyze the space complexity of bitmap. For a graph with N nodes, the maximum number of node-pair is $\frac{N*(N-1)}{2}$. For any node-pair, at most one short-

est path is loaded into the cache. Hence, the number of shortest paths in the cache is no larger than $\frac{N*(N-1)}{2}$. Moreover, the minimum size of a shortest path is 2, as a shortest path contains at least 2 nodes. Therefore, a cache Ω can store at most $\min\{\frac{|\Omega|}{2}, \frac{N*(N-1)}{2}\}$ shortest paths. Hence the number of columns in a bitmap is $\min\{\frac{|\Omega|}{2}, \frac{N*(N-1)}{2}\}$. The most number of rows is the number of nodes N . The number of bits needed in a bitmap is therefore $\min\{\frac{|\Omega|}{2}, \frac{N*(N-1)}{2}\} * N$; and the number of bytes needed is $\lceil \frac{\min\{\frac{|\Omega|}{2}, \frac{N*(N-1)}{2}\} * N}{8} \rceil$. The space complexity of bitmap is $\mathcal{O}(\min\{|\Omega| * N, N^3\})$.

4. Affected Shortest Path Detection

Before we refresh the cache, it is better for us to know which shortest paths are no longer shortest paths due to the change of an edge.

A shortest path $P_{i,j} = \langle v_i, \dots, v_j \rangle$ is **not affected** if the new shortest path $P'_{i,j} = \langle v_m, \dots, v_n \rangle$ due to the change of an edge e is totally the same with $P_{i,j}$ in the node sequence. Otherwise, $P_{i,j}$ is affected. Hereafter, “=” is used if two paths have the same sequence. e refers to the edge whose weight w_e changes. P and P' denote the shortest paths before and after w_e changes, respectively.

It is noteworthy that even though e is a part of $P_{i,j}$, if $P_{i,j} = P'_{i,j}$, $P_{i,j}$ is not affected. That is, the weight of a path has nothing to do with its being affected or not. The only thing that counts is the sequence.

Based on the definition of affected paths, we have the following corollaries.

Corollary 1. *When w_e increases, if $P_{i,j}$ is an affected path, then $P_{i,j}$ must contain e .*

Proof 1. *If $P_{i,j}$ does not contain e , then $P_{i,j}$ is still the shortest path when w_e increases, that is, $P_{i,j}$ is not an affected path. Hence, if $P_{i,j}$ is an affected path, $P_{i,j}$ must contain e*

Compared to the increase of w_e , it is more difficult to detect affected paths when w_e decreases, since paths that do not contain e before w_e decreases can also be affected paths. The following corollary deals with the case that w_e decreases.

Corollary 2. *When w_e decreases, if $P_{i,j}$ is an affected path, then $P'_{i,j}$ must contain e .*

Proof 2. Assume a shortest path $P_{i,j}$ is an affected path, and $P'_{i,j}$ does not contain edge e , then it has $P_{i,j} = P'_{i,j}$, indicating that $P_{i,j}$ is not an affected path. There is a
 205 conflict with the assumption. Therefore, $P'_{i,j}$ must contain edge e .

Corollary 3. The endpoints of e are v_a and v_b . v_i and v_j are two nodes where $v_j \neq v_a$, $v_j \neq v_b$. Suppose $P_{i,j}$ does not contain e (if there exist more than one shortest paths between v_i and v_j , we suppose that at least one shortest path does not contain e). For any adjacent node v_{adj} of v_j , if $P_{i,adj}$ is in the form of $P_{i,adj} = \langle v_i, \dots, v_j, v_{adj} \rangle$, $P_{i,adj}$
 210 does not contain e either.

Proof 3. Since $v_j \neq v_a$, $v_j \neq v_b$, no matter what v_{adj} is, $\langle v_j, v_{adj} \rangle$ can not be e . In addition, sequence $\langle v_i, \dots, v_j \rangle$ must be $P_{i,j}$ which does not contain e . Thus, $P_{i,adj}$ does not contain e .

Since v_a and v_b are symmetric, the following statement still stands: v_i and v_j are
 215 two nodes where $v_i \neq v_a$, $v_i \neq v_b$. Suppose at least one path of $P_{i,j}$ does not contain e . For any adjacent node v_{adj} of v_i , if $P_{adj,j}$ is in the form of $P_{adj,j} = \langle v_{adj}, v_i, \dots, v_j \rangle$, $P_{adj,j}$ does not contain e either.

4.1. Node Expansion Algorithm

Since it is easy to check affected shortest paths when w_e increases, in the following,
 220 we pay our attention to the algorithms of detecting affected paths when w_e decreases. We propose a node expansion algorithm (NEA) in this subsection.

For the affected shortest path detection problem, the key problem is to decide which paths are detected. The paths that contain e should be detected while the paths that do not contain e are not necessary to be detected. The graph in our problem is undirected,
 225 therefore a path from v_i to v_j is just the path from v_j to v_i . To avoid detecting a path two times, we artificially assign a direction for paths. C_s (C_t) is used to record start nodes (termination nodes) of to-be-detected paths. Every time, one node v_s from C_s and one node v_t from C_t comprise a node-pair, and we detect whether its shortest path is affected. C_s (C_t) is expanded by adding adjacent nodes of v_s (v_t).

230 For the general purpose of detecting affected paths, all the node-pair will be detected and the detection is time-consuming. Since our ultimate goal is to update the cache,

it is not necessary to detect all node-pair. We define that the **node distance** $d(i, j)$ between v_i and v_j represents the minimum number of nodes among all paths from v_i to v_j . When weights of edges in a graph become all-1, $w(i, j)$ is equal to $d(i, j)$. Suppose
235 the maximum node distances of paths in the cache is K , we will ignore the detection of node-pairs whose node distances are longer than K .

The pseudo code is illustrated in Algorithm 1. The endpoints of e are v_a and v_b . From the implementation perspective, both C_s and C_t are queues in a FIFO manner. First, C_s is initialized with the only start node v_a . In the outer loop, start node v_s is
240 the first node popped from C_s . If the new shortest path $P'_{s,b}$ contains e (line 5), then adjacent nodes of v_s are appended into C_s unless they have been added into C_s ever before. If $P'_{s,b}$ does not contain e , according to Corollary 3, the adjacent node v_{adj} of v_s are not necessarily put into C_s since $P'_{adj,b}$ does not contain e .

In the inner loop, v_s is a fixed node. C_t is initialized with v_b . v_t is obtained by
245 popping a node from C_t . If $P'_{s,t}$ contains e , then adjacent nodes of v_t are appended into C_t unless they have been added into C_t ever before. For any path $P_{s,t}$, the algorithm checks whether $P_{s,t} = P'_{s,t}$, if not, $P_{s,t}$ is put into the set of affected paths S_{aff} .

NEA satisfies both soundness and completeness. We first prove that the NEA is sound, i.e. any path in S_{aff} is an affected path. According to line 18 of the algorithm, if
250 a path $P_{s,t}$ belongs to S_{aff} , it has $P_{s,t} \neq P'_{s,t}$, so $P_{s,t}$ is an affected path.

Now we prove that NEA is complete. Assume that there exists an affected path $P_{s,t}$ that is not in S_{aff} . Based on Corollary 2, we know that $P'_{s,t}$ must contain the changed edge e . Hence, v_s (v_t) is direct or indirectly connected with v_a (v_b). According to NEA, v_s (v_t) must have been added into C_s (C_t). Thus, $P_{s,t}$ must have been compared
255 with $P'_{s,t}$. Therefore, NEA can recognize $P_{s,t}$ as affected, and the assumption does not hold. NEA is complete.

Figure 2 shows an example of computing affected paths when the weight of e ($\langle v_3, v_6 \rangle$) decreases from 5 to 3. Table 1 shows the iteration process.

4.2. Outward Node Expansion Algorithm

260 In the above subsection, we introduce a basic method NEA to compute affected shortest paths when the weight of a certain edge decreases. The above algorithm mainly

Algorithm 1: NEA

Input: A graph $G(V, E)$, the edge e which decreases its weight and its endpoints v_a and

v_b ;

Output: The set of affected paths S_{aff} ;

```
1 add  $v_a$  to  $C_s$ ;
2 while  $C_s$  is not empty do
3    $v_s \leftarrow$  pop the first element from  $C_s$ ;
4   calculate  $P'_{s,b}$ ;
5   if  $P'_{s,b}$  contains  $e$  &  $d'_{s,a} < K$  then
6     for each adjacent node  $v_{adj}$  of  $v_s$  do
7       if  $v_{adj}$  has not been added into  $C_s$  then
8         append  $v_{adj}$  to  $C_s$ ;
9   add  $v_b$  to  $C_t$ ;
10  while  $C_t$  is not empty do
11     $v_t \leftarrow$  pop the first element from  $C_t$ ;
12    calculate  $P'_{s,t}$ ;
13    if  $P'_{s,t}$  contains  $e$  &  $d'_{b,t} < K$  then
14      for each adjacent node  $v_{adj}$  of  $v_t$  do
15        if  $v_{adj}$  has not been added into  $C_t$  then
16          append  $v_{adj}$  to  $C_t$ ;
17    calculate  $P_{s,t}$ ;
18    if  $P_{s,t} \neq P'_{s,t}$  then
19      add  $P_{s,t}$  to  $S_{aff}$ ;
20 return  $S_{aff}$ ;
```




Figure 2: An example of w_e decreases.

Table 1: Iteration example of NEA.

	C_s	C_t	v_s	v_t	S_{aff}
1	$\{v3\}$	\emptyset	null	null	
2	\emptyset	\emptyset	$v3$	null	
3	\emptyset	$\{v6\}$	$v3$	null	
4	$\{v1, v2, v4\}$	\emptyset	$v3$	$v6$	
5	$\{v1, v2, v4\}$	$\{v4, v5, v7, v8\}$	$v3$	$v6$	$P_{3,6}$
6	$\{v1, v2, v4\}$	$\{v5, v7, v8\}$	$v3$	$v4$	$P_{3,6}$
7	$\{v1, v2, v4\}$	$\{v7, v8, v2\}$	$v3$	$v5$	$P_{3,6}, P_{3,5}$
8	$\{v1, v2, v4\}$	$\{v8, v2\}$	$v3$	$v7$	$P_{3,6}, P_{3,5}$
9	$\{v1, v2, v4\}$	$\{v2\}$	$v3$	$v8$	$P_{3,6}, P_{3,5}, P_{3,8}$
10	$\{v1, v2, v4\}$	\emptyset	$v3$	$v2$	$P_{3,6}, P_{3,5}, P_{3,8}$
11	$\{v2, v4\}$	\emptyset	$v1$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}$
12	$\{v4\}$	\emptyset	$v2$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}$
13	$\{v4, v0, v5\}$	$\{v4, v5, v7, v8\}$	$v2$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}$
14
15	$\{v4, v0, v5\}$	\emptyset	$v2$	$v8$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$
16	$\{v0, v5\}$	\emptyset	$v4$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$
17	$\{v5\}$	\emptyset	$v0$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$
18	\emptyset	\emptyset	$v5$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$

has two components: which paths are detected and how to check whether they are affected. In this part, we will present how to improve determining which paths are detected.

265 For ease of illustration, let $S_d(v_a)$ be the set of nodes whose node distance from a is d .

Corollary 4. *Suppose the endpoints of e are v_a and v_b , and v_i is an arbitrary node. If for any node $v_j \in S_d(v_b)$, $P_{i,j}$ does not contain e , then for any node $v_{j+1} \in S_{d+1}(v_b)$, one of the following stands: $S = \langle v_i, \dots, v_j, v_{j+1} \rangle$ is a shortest path and it does not
270 contain e ; S is not a shortest path.*

Proof 4. *For any node $v_{j+1} \in S_{d+1}(v_b)$, if $P_{i,j+1} = \langle v_i, \dots, v_j, v_{j+1} \rangle$, $v_j \in S_d(v_b)$, and $P_{i,j}$ does not contain e , then according to Corollary 3, $P_{i,j+1}$ does not contain e .*

Recall the algorithm NEA, although start nodes are added to C_s in a FIFO order i.e., nodes are expanded in a breath-first manner, the nodes in C_s are not discriminated
275 based on the node distance from v_a . In this subsection, we expand nodes based on their distances from v_a . Thus, the algorithm is called outward node expansion algorithm (ONE). An auxiliary set C'_s is employed to store the nodes that are expanded from the nodes in C_s , therefore, $C_s = S_d(v_a)$ while $C'_s = S_{d+1}(v_a)$. The pseudo code of ONE is described in Algorithm 2.

280 For fixed v_a , if a node v_t satisfies that (1) v_t is connected with v_b ; and (2) $P'_{a,t}$ contains e , we add v_t into C'_t (line 1-12). Starting from iteration $d = 0$, we try to reduce the size of C'_t . For a node $v_t \in C'_t$, if $P'_{s,t}$ does not contain e for any node $v_s \in S_d(v_a)$, then according to Corollary 4, $P'_{s,t}$ does not contain e for any node $v_s \in S_{d+1}(v_a)$. Therefore, v_t is deleted from C'_t , reflecting by not adding into C'_t . Hence, ONE saves
285 the time of visiting v_t in the $d+1$ th (and latter iterations) and calculating corresponding shortest paths.

Based on ONE, the iteration process of example Figure 2 is displayed in Table 2.

4.3. Inward Node Expansion Algorithm

In this section, we present another two techniques to improve the efficiency of
290 affected shortest path detection. We still focus on the order to generate node-pairs with

Algorithm 2: ONE

Input: A graph $G(V, E)$, the edge e which decreases its weight and its endpoints v_a and v_b ;

Output: The set of affected paths S_{aff} ;

```
1  add  $v_b$  to  $C_t$  and  $C'_t$ ;
2  while  $C_t$  is not empty do
3       $v_t \leftarrow$  pop the first element from  $C_t$ ;
4      calculate  $P'_{a,t}$ ;
5      if  $P'_{a,t}$  contains  $e$  then
6          for each adjacent node  $v_{adj}$  of  $v_t$  do
7              if  $v_{adj}$  has not been added into  $C_t$  then
8                  append  $v_{adj}$  to  $C_t$ ;
9                  append  $v_{adj}$  to  $C'_t$ ;
10         calculate  $P_{a,t}$ ;
11         if  $P_{a,t} \neq P'_{a,t}$  then
12             add  $P_{a,t}$  to  $S_{aff}$ ;
13  replace  $C_t$  with  $C'_t$ ;
14  for each adjacent node  $v_{adj}$  of  $v_a$  do
15      add  $v_{adj}$  to  $C_s$ ;
16  while  $C_s$  is not empty do
17       $C'_s \leftarrow \emptyset; C'_t \leftarrow \emptyset$ ; // initialize auxiliary sets
18      for each node  $v_s$  in  $C_s$  do
19          calculate  $P'_{s,b}$ ;
20          if  $P'_{s,b}$  contains  $e$  then
21              for each adjacent node  $v_{adj}$  of  $v_s$  do
22                  if  $v_{adj}$  has not been added into  $C_s$  then
23                      add  $v_{adj}$  to  $C'_s$ ; // store  $v_{adj}$  for the next round
24              for each  $v_t$  in  $C_t$  do
25                  calculate  $P'_{s,t}$ ;
26                  if  $P'_{s,t}$  contains  $e$  then
27                      add  $v_t$  to  $C'_t$ ; // store  $v_t$  for the next round
28                  calculate  $P_{s,t}$ ;
29                  if  $P_{s,t} \neq P'_{s,t}$  then
30                      add  $P_{s,t}$  to  $S_{aff}$ ; 14
31  replace  $C_s$  and  $C_t$  with  $C'_s$  and  $C'_t$ , respectively;
32  return  $S_{aff}$ 
```

Table 2: Iteration example of ONE.

	C_s	C_t	v_s	v_t	S_{aff}
1	$\{v3\}$	\emptyset	null	null	
2	\emptyset	\emptyset	$v3$	null	
3	\emptyset	$\{v6\}$	$v3$	null	
4	$\{v1, v2, v4\}$	\emptyset	$v3$	$v6$	
5	$\{v1, v2, v4\}$	$\{v4, v5, v7, v8\}$	$v3$	$v6$	$P_{3,6}$
6	$\{v1, v2, v4\}$	$\{v5, v7, v8\}$	$v3$	$v4$	$P_{3,6}$
7	$\{v1, v2, v4\}$	$\{v2, v7, v8\}$	$v3$	$v5$	$P_{3,6}, P_{3,5}$
8	$\{v1, v2, v4\}$	$\{v7, v8\}$	$v3$	$v2$	$P_{3,6}, P_{3,5}$
9	$\{v1, v2, v4\}$	$\{v8\}$	$v3$	$v7$	$P_{3,6}, P_{3,5}$
10	$\{v1, v2, v4\}$	\emptyset	$v3$	$v8$	$P_{3,6}, P_{3,5}, P_{3,8}$
11	$\{v2, v4\}$	\emptyset	$v1$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}$
12	$\{v4\}$	$\{v6, v5, v8\}$	$v2$	null	$P_{3,6}, P_{3,5}, P_{3,8}$
13	$\{v4, v0, v5\}$	$\{v5, v8\}$	$v2$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}$
14	$\{v4, v0, v5\}$	$\{v8\}$	$v2$	$v5$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}$
15	$\{v4, v0, v5\}$	\emptyset	$v2$	$v8$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$
16	$\{v0, v5\}$	\emptyset	$v4$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$
17	$\{v5\}$	\emptyset	$v0$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$
18	\emptyset	\emptyset	$v5$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$

each from C_s and C_t , respectively.

Corollary 5. *Suppose v_a and v_b are endpoints of e , v_s (v_t) is a node connected with v_a (v_b). If $P_{s,t}$ contains e , then $P_{s,t}$ must have the form $\langle v_s, \dots, v_a, v_b, \dots, v_k, \dots, v_t \rangle$ and at least one path of $P_{s,k}$ contains e .*

295 **Proof 5.** *Since $P_{s,t}$ is a shortest path, its subpath $\langle v_s, \dots, v_a, v_b, \dots, v_k \rangle$ is also a shortest path, i.e., $P_{s,k} = \langle v_s, \dots, v_a, v_b, \dots, v_k \rangle$ and $P_{s,k}$ contains e .*

Corollary 5 tells us that for a node v_s connected with v_a , if we have detected a path $P_{s,t}$ where $v_t \in S_d(v_b)$, then the nodes v_k on $P'_{s,t} = \langle v_s, \dots, v_b, \dots, v_k, \dots, v_t \rangle$ are not necessarily visited. If only $P'_{s,t}$ contains e , $P'_{s,k}$ contains e as well.

300 Next we consider how to optimize the process to check whether a shortest path is affected.

Corollary 6. *Suppose the end nodes of e are v_a and v_b . When w_e decreases, if $P_{a,b}$ is an affected path, then any shortest path $P'_{s,e}$ which contains e is an affected path, i.e., $P'_{s,e} \neq P_{s,e}$.*

305 **Proof 6.** *Assume there exists a path $P'_{s,e}$ which contains e and $P_{s,e} = P'_{s,e}$. As $P_{a,b}$ is an affected shortest path, we know $P_{a,b} = S1 = \langle v_a, v_m, \dots, v_n, v_b \rangle$ and $P'_{a,b} = S2 = \langle v_a, v_b \rangle = e$ and $w'_{S2} < w_{S1} = w'_{S1} < w_{S2}$. Since $P'_{s,e}$ contains e , the sequence of $P'_{s,e}$ must be $S3 = \langle v_s, \dots, v_a, v_b, \dots, v_e \rangle$. If we substitute $\langle v_a, v_b \rangle$ ($S2$) in $S3$ with $S1$, we have $S4 = \langle v_s, \dots, v_a, v_m, \dots, v_n, v_b, \dots, v_e \rangle$. It is clearly that $w_{S4} < w_{S3}$, therefore*
 310 *$P_{s,e}$ can not be $S3$. The assumption does not hold; therefore our corollary stands.*

According to Corollary 6, the process of detecting whether a path is affected is shortened. If $P_{a,b}$ is an affected shortest path, we can avoid the calculation of $P_{s,e}$ in line 28 and comparison with $P'_{a,b}$ in line 29 of Algorithm 2, since $P'_{s,e}$ contains e (line 20 of Algorithm 2), so we can know $P_{s,e}$ is an affected path directly.

315 We have another optimized algorithm inward node expansion algorithm (INE). The term “inward” is because nodes of C_t are visited from ones far way to v_b . Since the main logic of INE is the same with ONE, we only demonstrate the different lines. INE is to replace line 24-30 of ONE with the code in Algorithm 3.

Algorithm 3: INE

```
1 while  $C_t$  is not empty do
2    $v_t \leftarrow$  pop the node in  $C_t$  which has the largest node distance from  $v_b$ ;
3   calculate  $P'_{s,t}$ ;
4   if  $P'_{s,t}$  contains  $e$  then
5     for each  $v_k$  lies on path  $P'_{s,t}$  do
6       add  $v_k$  into  $C'_t$ ;
7       pop  $v_k$  from  $C_t$ ;
8       if  $P_{a,b}$  is an affected path then
9         add  $P_{s,k}$  to  $S_{aff}$ ;
10      else
11        calculate  $P_{s,k}$ ;
12        //  $P'_{s,k}$  is the subpath of  $P'_{s,t}$ 
13        if  $P_{s,t} \neq P'_{s,t}$  then
14          add  $P_{s,t}$  to  $S_{aff}$ ;
```

In Algorithm 3, line 6-7 indicate that if v_k is on a shortest path which contains e ,
 320 then v_k is added into C'_t for the next iteration directly even though it has not been visited
 in this round of iteration. The IF sentence in line 8 takes the advantage of Corollary 6.

Take Figure 2 as an example, the iteration process by INE is illustrated in Table 3.

Table 3: Iteration example of INE.

	C_s	C_t	v_s	v_t	S_{aff}
1	$\{v3\}$	\emptyset	null	null	
2	\emptyset	\emptyset	$v3$	null	
3	\emptyset	$\{v6\}$	$v3$	null	
4	$\{v1, v2, v4\}$	\emptyset	$v3$	$v6$	
5	$\{v1, v2, v4\}$	$\{v4, v5, v7, v8\}$	$v3$	$v6$	$P_{3,6}$
6	$\{v1, v2, v4\}$	$\{v5, v7, v8\}$	$v3$	$v4$	$P_{3,6}$
7	$\{v1, v2, v4\}$	$\{v2, v7, v8\}$	$v3$	$v5$	$P_{3,6}, P_{3,5}$
8	$\{v1, v2, v4\}$	$\{v7, v8\}$	$v3$	$v2$	$P_{3,6}, P_{3,5}$
9	$\{v1, v2, v4\}$	$\{v8\}$	$v3$	$v7$	$P_{3,6}, P_{3,5}$
10	$\{v1, v2, v4\}$	\emptyset	$v3$	$v8$	$P_{3,6}, P_{3,5}, P_{3,8}$
11	$\{v2, v4\}$	\emptyset	$v1$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}$
12	$\{v4\}$	$\{v6, v5, v8\}$	$v2$	null	$P_{3,6}, P_{3,5}, P_{3,8}$
13	$\{v4\}$	$\{v5\}$	$v2$	$v8$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$
14	$\{v4, v0, v5\}$	\emptyset	$v2$	$v5$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$
15	$\{v0, v5\}$	\emptyset	$v4$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$
16	$\{v5\}$	\emptyset	$v0$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$
17	\emptyset	\emptyset	$v5$	$v6$	$P_{3,6}, P_{3,5}, P_{3,8}, P_{2,6}, P_{2,8}$

Now we compare the performance of three algorithms. The nodes visited by the
 three proposed algorithms are displayed in Table 4. The numbers of nodes visited
 325 are NEA>ONE>INE, and the numbers of iterations for the three methods are still
 NEA>ONE>INE.

In terms of the time complexity, NEA computes nodes that are connected with start
 and end nodes, composing start and end sets. For a graph with N nodes, the time

Table 4: Performance comparison of algorithms.

	v_s	C_t (NEA)	C_t (ONE)	C_t (INE)
1	v_3	$\{v_2, v_4, v_5, v_6, v_7, v_8\}$	$\{v_2, v_4, v_5, v_6, v_7, v_8\}$	$\{v_2, v_4, v_5, v_6, v_7, v_8\}$
2	v_1	$\{v_6\}$	$\{v_6\}$	$\{v_6\}$
3	v_2	$\{v_4, v_5, v_6, v_7, v_8\}$	$\{v_5, v_6, v_8\}$	$\{v_5, v_8\}$
4	v_4	$\{v_6\}$	$\{v_6\}$	$\{v_6\}$
5	v_0	$\{v_6\}$	$\{v_6\}$	$\{v_6\}$
6	v_5	$\{v_6\}$	$\{v_6\}$	$\{v_6\}$

complexity is $\mathcal{O}(N^2)$. ONE and INE are improvements of NEA. In the worst case, the
 330 start and end sets still include all nodes. Thus, the time complexity of two optimized
 algorithms are still $\mathcal{O}(N^2)$.

5. Refreshment Strategies

In this section, we introduce four heuristic-based cache refreshment strategies.

5.1. Reload Whole Cache

335 The first refreshment strategy is to empty the whole cache and reload it based on
 benefit values. The strategy is abbreviated as RWC. This is the most straightforward
 idea to refresh the cache. The benefit value is proposed in Li et al. (2014). To make
 this paper self-contained, we briefly introduce how the benefit oriented model works.

All of us know that the cache utilization, or the cost reduction by using cache, is
 340 affected by the query frequency and the computational time of shortest paths. When
 calculating the cost saved by loading a path $P_{i,j}$ into a cache, we consider: 1) which
 queries can be answered by $P_{i,j}$; and 2) the saved computational cost if answering a
 query $Q_{i,j}$ by a cache directly.

For the first consideration, we know that a path can answer all the queries on its
 345 subpaths (Cormen et al., 2009). For the second consideration, it depends on how fre-
 quently a query arrives and the computational cost of that query. More specifically, it
 is the multiplier of the query frequency and the computational cost.

From the above analysis, the utilization of storing $P_{i,j}$ into a cache is:

$$B(P_{i,j}, \Psi) = \frac{\sum_{P_{s,t} \in S(P_{i,j}) \& P_{s,t} \notin S(\Psi)} F_{s,t} \cdot C_{s,t}}{|P_{i,j}|}. \quad (1)$$

Here, $S(P_{i,j})$ is the set of subpaths of $P_{i,j}$, and the numerator is the total cost reduction saved by caching path $P_{i,j}$. After normalized by the size of $P_{i,j}$, $B(P_{i,j})$ is the unit-size benefit brought by loading $P_{i,j}$ into a cache. Readers can understand this as the value of per unit weight in a knapsack problem. Paths with larger $B(P_{i,j})$ have higher priority to be loaded into a cache. When the cache is placed at the proxy, the time of computing shortest paths mainly lies on the round-trip communication time, which is the same for all queries (Thomsen et al., 2012).

Suppose the number of nodes in graph G is N , the size of query log is $|L|$, the number of paths in the path array is m , the number of node vector in the bitmap is n . For the RWC, all shortest paths queried in the query log are computed. The time complexity is $\mathcal{O}(|L| * N^2)$. The benefit values of shortest paths are computed and sorted. The complexity of such actions are $\mathcal{O}(|L| \log |L|)$. The time complexity of constructing path array and bitmap is $\mathcal{O}(m+n)$. The time complexity of this algorithm is $\mathcal{O}(|L| * N^2 + |L| \log |L| + m + n)$.

5.2. Update Affected Shortest Paths

The first method wastes a lot of time. Since only an edge changes its weight, its impact on the whole network is limited. The majority of shortest paths do not change at all. As a result, reloading the whole cache is redundant. To overcome the shortcoming of the first method, we update all the affected paths in the cache. If the size of affected paths exceed the available space of the cache, shortest paths with the largest benefit values are loaded into the cache.

Suppose the number of nodes in graph G is N , the size of query log is $|L|$, the number of paths in the path array is m , the number of node vector in the bitmap is n . The time complexity of affected shortest paths detection is $\mathcal{O}(N^2)$. In the worst case, all paths in the cache are updated. Therefore, the time complexity of updating affected shortest paths is $\mathcal{O}(m * N^2)$. The time complexity of sorting benefit values of affected shortest paths is $\mathcal{O}(m \log m)$. The complexity of UASP

375 5.3. Replace Affected Paths with Highest Frequency Paths

The above method need update benefit values of affected paths. In the third method, after we delete the affected paths we fill the cache with paths which have the highest query frequencies. Query frequencies, instead, can be easily obtained from the query log and never change even though the network changes. It avoids computing the benefit
380 of each path but it takes time to sort frequencies.

5.4. Replace Affected Paths Using Roulette Wheel Selection

At last, the fourth strategy is to delete all the affected paths in the cache and load new paths to the cache by the method of *roulette wheel*. As the historical queries are not the true queries in the future, on one hand, we consider it as a reference for the
385 future queries; on the other hand, we avoid over fitting the cache content to it.

We use a roulette wheel to determine which paths should be loaded into the cache. One feature of the roulette wheel selection is that alternatives with low attractiveness can also be selected, although with a relatively low possibility. We adopt the idea of roulette wheel as follows: for a path p in the query log, its probability of being selected
390 $\Pr(p)$ is proportional to its query frequency f_p , as shown in Equation 2.

$$\Pr(p) = \frac{f_p}{\sum_i f_i}. \quad (2)$$

The summation of the probabilities of all the paths is 1. The probability of selecting each path corresponds to the probability of a variable X with a standard uniform distribution falling into an interval as shown in Equation 3.

$$\Pr(p) = \Pr(X \in [\frac{\sum_{i=1}^{p-1} f_i}{\sum_i f_i}, \frac{\sum_{i=1}^p f_i}{\sum_i f_i}]). \quad (3)$$

In another word, to realize the probabilities for all the paths is equivalent to generate a
395 random number which falls at interval $[0, 1]$.

Take Table 5 for example, it records the path-interval correspondence. When we need to select a path into the cache, we generate a random number according to a standard uniform distribution. Suppose the randomly generated number is 0.6, then $P_{2,11}$ will be selected because 0.6 belongs to $[0.5, 0.75]$.

Table 5: A example of roulette wheel selection.

Path	Frequency	Probability	Interval
$P_{1,12}$	6	0.3	[0, 0.3]
$P_{1,10}$	3	0.15	[0.3, 0.45]
$P_{6,9}$	1	0.05	[0.45, 0.5]
$P_{2,11}$	5	0.25	[0.5, 0.75]
$P_{1,8}$	2	0.1	[0.75, 0.85]
$P_{7,12}$	3	0.15	[0.85, 1.0]

400 **Discussion.** In terms of the computational time, reloading the whole cache apparently costs the most time. Replacing affected paths with the highest frequency costs the second since it takes time to sort the frequencies of all shortest paths. Replacing affected paths using roulette wheel selection ranks the third, since it has a process of roulette wheel selection. Replacing affected paths using the largest benefit values costs
405 the least time since only a small set of affected paths update their benefit values.

6. Experiments

We used three data sets Aalborg¹, Beijing², and Singapore (Song et al., 2014) in our experiments. Each data set consists of a weighted road network and a query log. The query log of each data set is divided into two parts; one half is the training set and the
410 other half is the test set. Training sets act as historical logs while test sets act as future queries. The frequency statistics are extracted from the training set, and the cache is filled based on benefit values. Table 6 summarizes the information on the data sets. Columns “Size of training set” and “Size of test set” indicate the number of queries in the training set and test set, respectively. We assume that the query trend on training
415 sets and test sets are similar, and the statistic information from training sets can predict future queries to some extent.

¹<http://www.dbxr.org/experimental-guidelines/>

²<http://arxiv.org/abs/cs/04100001>

Table 6: Information of data sets.

Data set	No. of nodes	No. of edges	Size of training set	Size of test set
Aalborg	129k	137k	2372	2372
Beijing	76k	85k	6464	6464
Singapore	20,801	55,892	7500	7500

We generated 50 instances based on each data set; one half of the instances increase weights of edges and the other half decrease weights. The increased and decreased edges must have a relatively high impact on the response efficiency. To meet the criteria, we firstly generated instances with weights increased, then the decreased instances. Hereafter, we explain the process of generating instances for Aalborg. For the other data sets, the process is totally the same.

The cache was initialized based on the road network and training set of Aalborg. For each path in the cache, two consecutive nodes of the path forms an edge. We sorted all edges formed by the cached paths based on edges' frequencies of appearance. The 25 edges with the highest frequencies were marked. The road network in Aalborg act as the road network before the weight of one edge is increased (original network). Each time, we selected one marked edge e and increased w_e by 10 times, resulting in a changed road network (new network). The 25 edges were sequentially increased and 25 corresponding instances with weights increased were obtained. For the instances of weights decreased, new networks of increased instances act as the original networks. When w_e of marked edges recovered to their weights recorded in Aalborg, we yielded instances with decreased weights.

All the code was implemented in GNU C++. The experiments were run on a PC with an Intel i7 Quad Core CPU clocked at 3.10 GHz.

6.1. Effect of Cache Structure

We use a bitmap-based structure in Section 3 to facilitate the cache on answering users' queries. To have an impression of how the bitmap structure works, we compare it with a benchmark structure, which only records shortest paths in a path array. Queries are answered by scanning the array. The benchmark structure is called a basic cache.

For each data set, the cache is firstly initialized based on the largest benefit values of paths in the query log. Queries in the test sets arrive one by one and the total response time by two cache structure is displayed in Figure 3. We can see that the time performance of bitmap structure is much better than that of basic structure. The response time of bitmap is only 0.7ms when the cache size is 9MB for the Aalborg data set, while it costs 205ms for the basic structure. We can get consistent results on Beijing and Singapore data sets. Moreover, the response time is almost constant with the increase of cache size for the bitmap structure.




Figure 3: Response time of cache structures.

6.2. Efficiency of Detecting Affected Paths in the Cache

Detecting affected paths in a cache is an important step before refreshing a cache. To demonstrate the performance of our algorithms, a naive method (NM) is used as a benchmark method. Due to the size of graph, NM only re-computes new shortest paths for all pairs of nodes in the cache and compares them with the original ones. If the two shortest paths for a pair of nodes are different, then an affected path is detected. We

455 test our three affected paths detecting algorithms NEA, ONE, INE and NM on Aalborg,
Beijing and Singapore data sets and the detection time of the four detection methods is
regarded as the performance indicator.

The experimental result on each data set is the average of 50 instances. As seen
from Figure 4, all of our algorithms have a better performance than NM. For example,
460 in the Aalborg data set, when the cache size is 9MB, the algorithm INE achieves the
best time performance and its detection time is only 131ms, while NM costs 28.67s.
Meanwhile, we observe that INE is slightly superior to ONE and ONE is superior to
NEA. This is consistent with our expectation.




Figure 4: Performance of affected path detection methods.

6.3. Performance of Refreshment Strategies

465 For ease of illustration, reloading the whole cache, replacing affected paths with
the largest benefit values, replacing affected paths with the highest frequency paths and
replacing affected paths using roulette wheel selection are abbreviated as RWC, RLB,
RHF and RRWS, respectively.

Figure 5 shows the hit-ratios of four refreshment strategies under different scales
of caches. We sum up hit ratio of 50 instances for ease of read, since the differences
among strategies are tiny. We can observe that RWC and RLB achieve the highest hit
ratio. The reason is that even though RWC and RLB are based on different logics to
update caches, the paths which are loaded into the cache are actually the same. The
hit ratios of RHF and RRWS are similar and a little bit worse than the former two.
This result is consistent with the logics of methods, since RHF and RRWS are not
fully based on large benefit values. From the perspective of cache size, when the cache
size increases, the cache will hold more paths. The cache will answer more queries,
subsequently, the hit ratio increases.




Figure 5: Hit ratios of refreshment strategies.

Next we test the refreshment time of these four replacement strategies along with
various cache sizes on three data sets. The refreshment time includes three parts: the
time of detecting affected paths, the time of computing shortest paths by the server, and
the time of selecting new paths into the cache. For RWC, the time of detecting affected
paths is zero. The experimental result (rf. Figure 6) on each data set is the average of

50 instances. The performance on three data sets is consistent; each method displays similar trends on three data sets. RWC spends the most refreshment time, and the time increases as the cache size increases. It can be predicted that the disadvantage of RWC in refreshment time will amplify more if more shortest paths are queried, since RWC takes a lot of time to computing shortest paths every time the cache is emptied. RLB, RHF, and RRWS spend similar time. Precisely, RLB has the shortest refreshment time. This is consistent with our analysis in Section 5.




Figure 6: Refreshment time of refreshment strategies.

From the above experiments, we can see that RLB has the best running time and hit ratio. Hence, in the real applications, RLB is suggested to be used.

7. Conclusions

We address the problem of refreshing cache contents in a changed network. Changes of road conditions are commonly seen in the real world, i.e., traffic congestion or road constructions. Shortest path caches need refreshing periodically, so that the informa-

tion is accurate and valid and the cache utilization is maximized. To the best of our knowledge, our work is the first one to discuss the cache refreshment problem when an edge changes its weight. In order to store shortest paths and answer queries efficiently,
500 a bitmap-based cache structure is used. We introduce the concept of affected paths, and then exploit the properties associated with affected paths. In the following, we develop algorithms to detect affected shortest paths resulted from road network changes. Sequentially, four cache refreshment strategies are illustrated.

A series of experiments are conducted. The performance of cache structure and
505 affected path detection methods are considerable. Computational results showcase that RLB is as good as RWC in terms of hit ratio while the former has a much shorter refreshment time. Our work has many applications, such as refreshment of shortest paths caches of map companies. We suggest that RLB is used to refresh caches at short intervals and RWC is used at long intervals. How to trade off the use frequency of two
510 methods is based on the real applications.

The weakness of our work, even of most works of this kind, is that we rely heavily on the information of query logs, although we introduce roulette wheel selection to avoid over fitting. It is clearly that future queries are not a precise copy of query logs. Hence, the hit ratio is to some extent restricted by query logs. In the future, works may
515 focus on the following directions. The cache structure, the method to detect affected paths and the strategies to refresh caches can be studied solely and then consolidated, obtaining a strengthened cache refreshment solution. The problem of “batch of updates” should be considered. In this paper, we only consider the change of single edge. The story of batch changes is not a simple repetition of single change, since edges could
520 interfere. The impact of multiple edges is combinatorial. Currently we just consider the changes of the graph; it would be interesting to investigate the changes of query patterns. Of course, it may be possible to study directed networks in the future as in the real life one direction of a road may be closed for construction or other purposes while the other direction is still open.

525 *Acknowledgments.*

The work is partially supported by the National Basic Research Program of China

(973 Program) (No. 2012CB316201), the National Natural Science Foundation of China (No. 61322208, 61272178, 61129002), the Doctoral Fund of Ministry of Education of China (No. 20110042110028), and the Fundamental Research Funds for the Central Universities (No. N120504001, N110804002).

References

- Altingovde, I. S., Ozcan, R., & Ulusoy, Ö. (2009). A cost-aware strategy for query result caching in web search engines. In *Advances in Information Retrieval* (pp. 628–636). Springer.
- 535 Baeza-Yates, R., Gionis, A., Junqueira, F., Murdock, V., Plachouras, V., & Silvestri, F. (2007). The impact of caching on search engines. In *Proceedings of the 30th Annual International Conference on Research on Development in Information Retrieval* (pp. 183–190).
- Baeza-Yates, R., & Saint-Jean, F. (2003). A three level search engine index based in query log distribution. In *String Processing and Information Retrieval* (pp. 56–65). Springer.
- 540 Bauer, R., & Wagner, D. (2009). Batch dynamic single-source shortest-path algorithms: An experimental study. In *Experimental Algorithms* (pp. 51–62).
- Berrettini, E., D’Angelo, G., & Delling, D. (2009). Arc-flags in dynamic graphs. *OASICS-OpenAccess Series in Informatics*, 12.
- 545 Cheng, J., Ke, Y., Chu, S., & Cheng, C. (2012). Efficient processing of distance queries in large graphs: A vertex cover approach. In *Proceedings of the 2012 ACM Conference on Management of Data* (pp. 457–468).
- Cormen, T. H., Leiserson, C. E., Rivest, R. L., Stein, C. et al. (2009). *Introduction to algorithms*. (3rd ed.). MIT press Cambridge.
- 550 D’Andrea, A., D’Emidio, M., Frigioni, D., Leucci, S., & Proietti, G. (2013). Dynamically maintaining shortest path trees under batches of updates. In *Structural Information and Communication Complexity* (pp. 286–297).

- D'Angelo, G., D'Emidio, M., & Frigioni, D. (2014). Fully dynamic update of arc-flags.
555 *Networks*, 63 (3), 243–259.
- Ding, B., Yu, J. X., & Qin, L. (2008). Finding time-dependent shortest paths over large graphs. In *Proceedings of the 11th international conference on Extending database technology: Advances in database technology* (pp. 205–216).
- Frigioni, D., Marchetti-Spaccamela, A., & Nanni, U. (1996). Fully dynamic output
560 bounded single source shortest path problem. *ACM-SIAM Symposium on Discrete Algorithms*, 96, 212–221.
- Fu, L., & Rilett, L. R. (1998). Expected shortest paths in dynamic and stochastic traffic networks. *Transportation Research Part B: Methodological*, 32 (7), 499–516.
- Gan, Q., & Suel, T. (2009). Improved techniques for result caching in web search
565 engines. In *Proceedings of the 18th International Conference on World Wide Web* (pp. 431–440).
- Kanoulas, E., Du, Y., Xia, T., & Zhang, D. (2006). Finding fastest paths on a road network with speed patterns. In *Proceedings of the 22nd IEEE International Conference on Data Engineering* (pp. 10–10).
- 570 Kriegel, H.-P., Kroger, P., Renz, M., & Schmidt, T. (2008). Hierarchical graph embedding for efficient query processing in very large traffic networks. In *Scientific and Statistical Database Management Conference* (pp. 150–167).
- Lauther, U. (2004). An extremely fast, exact algorithm for finding shortest paths in static networks with geographical background. *Geoinformation und Mobilität-von
575 der Forschung zur praktischen Anwendung*, 22, 219–230.
- Lee, C.-C., Wu, Y.-H., & Chen, A. L. (2007). Continuous evaluation of fastest path queries on road networks. In *Advances in Spatial and Temporal Databases* (pp. 20–37).
- Li, X., Qiu, T., Yang, X., Wang, B., & Yu, G. (2014). Refreshment strategies for shortest
580 path caching problem with changing edge weight. In *Asia Pacific Web Conference* (pp. 331–342).

- Li, X., Wang, S., Yang, X., Wang, B., & Yu, G. (2013). An improved algorithm to enhance the utilization of shortest path caches. In *Web Information System and Application* (pp. 419–424).
- 585 Liu, X., & Yang, X. (2011). A generalization based approach for anonymizing weighted social network graphs. In *Web-Age Information Management* (pp. 118–130).
- Long, X., & Suel, T. (2005). Three-level caching for efficient query processing in large web search engines. In *World Wide Web Conference* (pp. 257–266).
- Markatos, E. P. (2001). On caching search engine query results. *Computer Communi-*
590 *cations*, 24 (2), 137–143.
- McQuillan, J. M., Richer, I., & Rosen, E. C. (1980). The new routing algorithm for the arpanet. *Communications, IEEE Transactions on*, 28 (5), 711–719.
- Narváez, P., Siu, K.-Y., & Tzeng, H.-Y. (2000). New dynamic algorithms for shortest path tree computation. *IEEE/ACM Transactions on Networking*, 8 (6), 734–746.
- 595 O’Neil, E. J., O’Neil, P. E., & Weikum, G. (1993). The LRU-K page replacement algorithm for database disk buffering. *ACM SIGMOD Record*, 22 (2), 297–306.
- O’Neil, P., & Quass, D. (1997). Improved query performance with variant indexes. In *Proceedings of the ACM Conference on Management of Data* (pp. 38–49).
- Potamias, M., Bonchi, F., Castillo, C., & Gionis, A. (2009). Fast shortest path dis-
600 *tance estimation in large networks. In Proceedings of the 18th ACM International Conference on Information and Knowledge Management* (pp. 867–876).
- Song, R., Sun, W., Zheng, B., & Zheng, Y. (2014). Press: A novel framework of trajectory compression in road networks. *Eprint Arxiv*, 7 (9), 661–672.
- Thomsen, J. R., Yiu, M. L., & Jensen, C. S. (2012). Effective caching of shortest
605 *paths for location-based services. In Proceedings of the 2012 ACM Conference on Management of Data* (pp. 313–324).

- Thomsen, J. R., Yiu, M. L., & Jensen, C. S. (2014). Concise caching of driving instructions. In *Proceedings of the 22nd ACM International Conference on Advances in Geographic Information Systems* (pp. 23–32).
- 610 Tian, Y., Lee, K. C., & Lee, W.-C. (2009). Monitoring minimum cost paths on road networks. In *Proceedings of the 17th ACM International Conference on Advances in Geographic Information Systems* (pp. 217–226).
- Wang, Q., Davis, D. N., & Ren, J. (2016). Mining frequent biological sequences based on bitmap without candidate sequence generation. *Computers in Biology and*
615 *Medicine*, 69, 152 – 157.
- Wei, F. (2010). Tedi: Efficient shortest path query answering on graphs. In *Proceedings of the 2010 ACM Conference on Management of Data* (pp. 99–110).
- Wu, L., Xiao, X., Deng, D., Cong, G., Zhu, A. D., & Zhou, S. (2012). Shortest path and distance queries on road networks: An experimental evaluation. *Proceedings of*
620 *the International Conference on Very Large Data Bases*, 5 (5), 406–417.