

Process Sync.

[1] Disable / Enable Interrupts

[2] Simple Hardware Instructions [atomic

→ Test and set

↳ First process that finds lock = FALSE, set to True and enters critical section

→ swap

(1)

n process
boolean waiting [n] } Init to FALSE
boolean lock;

(2)

```
Pi : do {
        waiting[i] = true;
```

```
    key = true;
    while (waiting[i] && key)
        key = TestAndSet(&lock);
    waiting[i] = false;
}
```

C.S (3)

```
j = (i+1) % n;
while ((j != i) && !waiting[j])
    j = (j+1) % n;
if (j == i)
    lock = false;
else
    waiting[j] = false;
```

exit

R.S (Remainder Section) (4)

} while (1);



Always comes back

P_2 ✓

P_5 ↻

↻

P_3

3 Semaphores

An integer value that can only be accessed by two automic operations.

- Wait()
- Signal()

```
Signal (s) {
    S++;
}
```

binary 0 1

counting

```
wait(s) {
    while (s <= 0) ;// do nothing
    s--;
}
```

```
Pi  do {
    wait(s)
    C.S
    Signal (s)
    R.S
} while (1)
```

S = 1 P_2 P_5 P_3 ... P_2 P_3 P_5

P_2: ↓ S = 0

P_5: ↻

P_3: ↻

P_2: ↑ S = 1

P_3: : S = 0 Enter

P_5: ↻

Init S = 0;

P_0 P_1

P_1: wait(s)

x_1

x_2



signal (s);

Counting Semaphores allows up to n processes inside the C.S.

→

Idea: block a process not a spin loop

```
typedef struct {
    int value;
    struct process * list;
} semaphore;
```

```
signal (Semaphore *s)
    s→value ++;
    if (s→value ≤ 0){
        remove P from s→list;
        wake up (P)
    }
}
```

```
wait (semaphore * s) {
    s→value --;
    if (s→value < 0)
        // Add this process to s→list block
}
```