

Perovskite 0031 | UTV C60 scaling and 4 matched baselines

Same stored 20% multilevel Hadamard acquisition and NPL-default noise | UTV C60, 512 PDHG iterations


Ground truth




Zero-fill
PSNR 27.19 dB | SSIM 0.606
HaarPSI 0.616




SPGL1-BPDN
PSNR 29.82 dB | SSIM 0.751
HaarPSI 0.685




PnP-ADMM-tuned-5
PSNR 33.00 dB | SSIM 0.849
HaarPSI 0.789




GS-PnP-tuned-5
PSNR 29.68 dB | SSIM 0.652
HaarPSI 0.662




UTV C60 rho=0.01
PSNR 27.09 dB | SSIM 0.622
HaarPSI 0.706




UTV C60 rho=0.05
PSNR 27.41 dB | SSIM 0.653
HaarPSI 0.724




UTV C60 rho=0.1
PSNR 28.46 dB | SSIM 0.694
HaarPSI 0.737




UTV C60 rho=0.3
PSNR 30.92 dB | SSIM 0.780
HaarPSI 0.729




UTV C60 rho=0.4
PSNR 31.14 dB | SSIM 0.791
HaarPSI 0.708




UTV C60 rho=0.45
PSNR 31.15 dB | SSIM 0.793
HaarPSI 0.695




UTV C60 rho=0.5
PSNR 31.12 dB | SSIM 0.794
HaarPSI 0.685




UTV C60 rho=0.55
PSNR 31.08 dB | SSIM 0.794
HaarPSI 0.678




UTV C60 rho=0.7
PSNR 30.90 dB | SSIM 0.790
HaarPSI 0.657




UTV C60 rho=0.9
PSNR 30.60 dB | SSIM 0.783
HaarPSI 0.628



UTV C60 rho=0.95
PSNR 30.52 dB | SSIM 0.782
HaarPSI 0.621



UTV C60 rho=1
PSNR 30.46 dB | SSIM 0.780
HaarPSI 0.615



Best UTV PSNR: rho=0.45
Best overall PSNR:
PnP-ADMM-tuned-5

All panels display [0,1]. PSNR, SSIM and HaarPSI use raw unclipped reconstructions.

PnP parameters: fixed tuned-5 selections; UTV scaling is a single-image post-hoc experiment.