

# Applied Computational Methods in Mechanical Sciences

(ME466)

## Assignment 7

Himanshu Kumar

16ME234

October 14, 2019

### Problem Statement:

Obtain the variation of  $\phi$  vs  $x$ , given the governing differential equation as:

$$\Gamma \frac{d^2 \phi}{dx^2} + \frac{d\phi}{dx} - \phi = 0$$

1. Use central difference scheme with  $\Gamma = 0.1$ , where  $\Delta x = 0.1$  and  $\Delta x = 0.01$ .
2. Use forward difference scheme with  $\Gamma = 0.1$ , where  $\Delta x = 0.01$ .
3. Use backward difference scheme with  $\Gamma = 0.1$ , where  $\Delta x = 0.01$ .

The boundary conditions are:

1. At  $x = 0$ ;  $\phi = 1.0$
2. At  $x = 1.0$ ;  $\phi = 0$

### Python Code:

```
import time
import matplotlib.pyplot as plt

# formulate tridiagonal matrix
def solve_plot(delx,scheme):
    def matrix_form(delx,scheme):
        rng = 1.0
        n = int((rng/delx) -1)
        #print (n)
```

```

a = [[0 for i in range(n)] for i in range(n)]
t = 0.1

xm = [0 for i in range(n+1)]
for i in range(n):
    xm[i+1] = xm[i]+delx
#print (x)
if(scheme is "cds"):
    alpha = 1+ (delx/2*t)
    beta = -2-(delx*delx/t)
    gamma = 1- (delx/2*t)
elif(scheme is "bds"):
    alpha = 1
    beta = -2-(delx*delx/t) +(delx/t)
    gamma = 1- (delx/t)
elif(scheme is "fds"):
    alpha = 1+ (delx/t)
    beta = -2-(delx*delx/t) -(delx/t)
    gamma = 1

for i in range(1,n-1):
    a[i][i-1] = alpha
    a[i][i] = beta
    a[i][i+1] = gamma

#row 0
a[0][0]=beta
a[0][1] = gamma

#row n-1
a[n-1][n-1]=beta
a[n-1][n-1]=alpha

```

```

#rhs vector
b = [0 for i in range(n)]

b[0] = -gamma
b[n-1] = 0

return(a,b,xm,n)

def thomas(a,b):
    n= len(b)

    for i in range(1,n):
        a[i][i-1]=a[i][i-1]/a[i-1][i-1]

        a[i][i] = a[i][i]-a[i][i-1]*a[i-1][i];

        b[i]= b[i]-a[i][i-1]*b[i-1]

        a[i][i-1]=0

    #backward substitution
    x=[0 for i in range(n)]
    x[n-1]= b[n-1]/a[n-1][n-1]
    for k in range(n-1):
        i=n-2-k

        x[i] = ( b[i] + x[i+1] )/ a[i][i]

    #print(x)
    return(x)

#display matrices and check
a,b,xm,n = matrix_form(delx,scheme)

# for i in range(n):
#     print(a[i])
# for i in range(n):
#     print(b[i])

```

```

phi=thomas(a,b)

mod_phi = [0 for i in range(n+1)]
for i in range(len(phi)):
    mod_phi[i+1] = phi[i]
mod_phi[0] = 1
mod_phi[n]= 0
print(mod_phi)
print(xm)
print ("\n CPU time: ", time.process_time(),'s')

#plotting
plt.plot(mod_phi, xm)
plt.xlabel('x')
plt.ylabel('phi')
meta = str(dx)
meta = "phi vs. x : dx = " + meta
plt.title(meta)
plt.show()

solve_plot(0.1,"cds")
# solve_plot(0.01,"cds")

# solve_plot(0.01,"fds")


#solve_plot(0.01,"bds")

```

## Results:


### 1. With CDS and $\Delta x = 0.1$ :

2. CPU time: 0.390625 s




### 2. With CDS and $\Delta x = 0.01$ :

3. CPU time: 0.734375 s



### 3. With FDS and $\Delta x = 0.01$ :

3. CPU time: 0.4375 s



### 4. With BDS and $\Delta x = 0.01$ :

5. CPU time: 0.828125 s

