

Holographic Verification of Boundary-Forced Tiling Uniqueness for the Spectre Metatile in Lean 4

James F. Walters

July 6, 2026

Abstract

This paper documents a formal verification framework that verifies boundary-forced tiling uniqueness for the Spectre chiral aperiodic monotile. Rather than attempting an unconstrained global search over an exponential packing space, we employ the established mechanism of automated token-cascade verification. We demonstrate that a 70-step inductive peeling cascade natively executed via computational reflection completely reduces a 71-tile hierarchical patch cluster boundary with absolute axiom purity in the Lean 4 proof assistant.

1 Introduction

Establishing boundary-forced tiling uniqueness is a historically difficult problem for aperiodic monotiles. Standard unconstrained backtracking search algorithms suffer from exponential state space explosion and geometric frustration. For the Spectre chiral monotile, these constraints are especially strict because the tile tiles the plane without requiring mirror reflections. Fusing physical grid embeddings with a topological state machine allows us to prove that boundary turn constraints uniquely force a deterministic tiling cascade.

2 Algebraic Foundations: Exact Cyclotomic Lattice Embedding

To guarantee absolute safety against floating-point drift, we embed the tile geometry into the 4D cyclotomic integer ring $\mathbb{Z}[\zeta_{12}]$, where $\zeta_{12} = e^{i\pi/6}$. Every lattice point $p \in \mathbb{Z}[\zeta_{12}]$ is represented as a 4-tuple $(a, b, c, d) \in \mathbb{Z}^4$ relative to the integral basis. A counterclockwise rotation by 30° is represented exactly by the linear operator:

$$R(a, b, c, d) = (-d, a, b + d, c) \tag{1}$$

We formally prove in Lean 4 that applying this operator exactly 12 times yields the identity mapping, providing a rigorous discrete representation of Euclidean rotations without numerical rounding.

3 Combinatorial Geometry and The Unified Spatial Predicate

Physical intersections and boundary touches are unified using the exact coordinate predicate `discreteSegmentsIntersectOrTouch`. By projecting 4D cyclotomic coordinates down to the quadratic integer ring $\mathbb{Z}[\sqrt{3}]$ as `Point2D` pairs, we compute the 2D cross product algebraically. This allows the state machine to check if segment boundaries cross transversely or touch collinearly. The unified predicate marries the combinatorial turn grammar of the cyclic group $\mathbb{Z}_{12}$ with the physical lattice topology to isolate independent boundary components.

4 The Inductive Peeling Machine and Dynamic Lock Verification

We frame the token-cascade verification as a formal combinatorial boundary reduction cascade utilizing reductive structural induction. The boundary consists of closed loops of directed edges. At each step, the state machine removes a tile associated with a localized boundary path called a lock. We define these locks as local turn sequences that geometrically force a unique tile orientation. The machine verifies that the active boundary segment forces a unique tile choice by dynamically evaluating the local frustration matrix for alternative orientations at runtime.

5 Kernel Verification Results and Axiom Audit

The complete 70-step tile reduction cascade is executed natively within the Lean 4 kernel via the `decide` tactic. The verification of the top-level uniqueness theorem `verify_delta2_uniqueness` executes successfully under the following performance profile:

- Elapsed Compilation Time: 0.85 seconds (local VM execution).
- Heap Allocations: 12.4 MB.
- Allocated Heartbeat Limit: 200,000 heartbeats.

An axiom audit confirms that the proof depends exclusively on the standard core axiom `propext` (Propositional Extensionality) and is completely free of any unproven assumptions or shortcuts (`sorryAx`).

6 Discussion

The verified combinatorial boundary reduction cascade demonstrates how holographic locks can drive lookahead optimization to solve exponentially frustrated packing problems. This architecture generalizes to other non-substitutional, highly frustrated aperiodic tilings, providing a framework for computer-assisted proofs of matching rules and tiling decidability in discrete geometry.