



شركة صناعات التبريد والتخزين والخدمات التعليلية
Refrigeration Industries & Storage and Oil Services Co. KSC

Product Technical Data Sheet

COOLEX

Model Series : PNG
Project Reference : KW26-007-00
Project Name : RE Request for Quotation

Prepared By : RODEL
Rev No. : 0
Date Printed : 22-Apr-26

TAG	MODEL	AIR FLOW [CFM]	AMBIENT [°F]	ON COIL		COOLING CAPACITY		POWER INPUT [kW]	QTY
				DB [°F]	WB [°F]	TOTAL [BTUH]	SENSIBLE [BTUH]		
	PNGC-090C2	3,227	118.4	80	67	86,700	63,737	10.09	1
	PNGC-175C2	6,381	118.4	80	67	160,920	117,596	20.02	1
	PNGC-240C2	7,998	118.4	80	67	199,680	163,139	25.03	2

AIR COOLED ROOFTOP PACKAGE UNITS STANDARD FEATURES

OUTDOOR SIDE

• Casing

- Galvanized Sheet metal fabricated from hot dipped G90 Zinc coating
- Zero spangle galvanised steel Painted Electro-static powder coat, oven baked

• Compressors

- High Efficiency, low noise Hermetic Scroll Compressor
- Cranck case heater
- Inherent thermal protection

• Controller

- Microprocessor based controller
- Designed to withstand high ambient temp.; up to 70 °C

• Control Panel

- Designed according to NEMA 4 (IP55)
- Control voltage is 240V-1Ph-50Hz

• Condenser coil

- 3/8" Dia. Copper tubes with Hydrophilic Aluminum Fins

• Condenser fan motor assembly

- Airo Dynamic design, Direct Driven Propeller
- Motors are totally enclosed air over type (TEAO), class "F" insulation
- Motors winding inherent thermal protection

• Refrigerant

- R407C, Fully charged

• Refrigerant line Accessories

- Filter dryer, sight glass (moisture indicator for Models PNGC-130 and above)



شركة صناعات التبريد والتخزين والخدمات النفطية
Refrigeration Industries & Storage and Oil Services Co. KSC

Product Technical Data Sheet

COOLEX

• Protection Controls

- Single phase preventer
- Compressors lockout function (through controller)
- Anti recycle 3 minutes timer delay

• Power Supply

- 415V- 3Ph- 50Hz

EVAPORATOR SIDE

• Casing

- Galvanized Sheet metal fabricated from hot dipped G90
- Zinc coating and zero spangle galvanised steel
- Painted Electro-static powder coat, oven baked
- Thermal & Acoustic insulation, Fiber glass insulation
- 15 mm thickness (48 kg/m³ Density)

• Supply Fan & Fan Motor

- Galvanized steel Centrifugal, DIDW Forward Curved
- Belt driven (For Models PNGC-76 & Above only)
- Single speed

• DX Cooling coil & Drain Pan

- 3/8" Dia. Copper tubes with Hydrophilic Aluminum Fins
- Thermostatic Expansion valve for refrigerant control (For Models PNGC-76 & Above only)
- Painted galvanized steel sheet metal
- Insulated with 8 mm Polyethylene insulation (Density 30 kg/m³)

• Filters Section

- Aluminum washable filter media

ADDITIONAL FEATURES

- Condenser & Evaporator Coils provided with anti-corrosion HERESITE coating

OUR OFFER EXCLUDES

- Any other requirements not mentioned specifically above