



شركة صناعات التبريد والتخزين والخدمات النفطية
Refrigeration Industries & Storage and Oil Services Co. KSC



PRODUCT SUBMITTAL

COOLEX Condensing Unit

Project Name :	-	Unit Model :	CCU-960
Reference No. :	-	Tag No. :	-
Revision No. :	<u>0</u>	Prepared by :	<u>0</u>
Date	19-Nov-25	Unit Qty :	<u>0</u>

PERFORMANCE DATA

Ambient Temp	95.0	°F	Refrigerant	R410A
Altitude	0	ft	Compressor KW Input	60.2
Capacity	918199	Btu/hr	Total Power Input (KW)	69.1

TECHNICAL DATA

Outdoor Specifications

Unit Model	CCU-960	Refrigerant	R410A
Compressor	Hermetic Scroll	Fan type	Direct driven Propeller fan
Coil Type	3/8" Ø IGT Copper	No. of fans	8
Fin Material	Aluminum	Condenser Motor HP	1.5
Coil Area (ft²)	19.8	<u>Compressor</u>	HP Qty
Rows / Fin Spacing	3 / 14	Model 1	20 4
Coil Qty	8	Model 2	- -
Refrigerant circuit	4		
Liquid Pipe Ø (in)	7/8	Unit Weight (kgs)	2500.0
Suction Pipe (in)	1 3/8	Unit Dimension (LxWxH) - mm	4767 x 2204 x 2132

ELECTRICAL DATA

Power Supply	400V/3Ø/50Hz		
		Qty	LRA RLA
Fan Motor FLA (each)	Amp 3.0	Compressor 1	4 229.0 34.3
Unit Ampacity (A)	169.8	Compressor 2	- - -
Max. Fuse Size (A)	200		

General Specification

Condenser

Casing	Painted Electro-static powder coat, oven baked
Compressor Type	Hermetic Scroll
Compressor protection	Provided with Inherent thermal protector, crankcase heater & external overload relay
Condenser Coil	3/8" Copper tubes mechanically bonded with Aluminum fins
Fan Type	Direct Driven Propeller fan
Fan Motor	TEAO with Class F motor insulation with inherent thermal protection
Refrigerant Line	filter drier, sight glass, manual shut off valve
Unit Controller	Microprocessor based control with multi function safety features

Additional Options



شركة صناعات التبريد والتخزين والخدمات النفطية
Refrigeration Industries & Storage and Oil Services Co. KSC



UNIT LAYOUT

Model : CCU-960

