

PRODUCT SUBMITTAL

Fresh Air Package Unit

Project Name :	<u>0-Jan-00</u>	Unit Model :	<u>FAPU-480F2T</u>
Reference No. :	<u>0</u>	Tag No. :	<u>0</u>
Revision No. :	<u>0</u>	Sales Engineer :	<u>Ronny Bittar</u>
Date	<u>19-Nov-25</u>	Prepared by :	<u>0</u>

PERFORMANCE DATA

<u>Unit Model</u>	<u>FAPU-480F2T</u>	Qty	1
Entering Air Temp (DB)	118.4 °F	Power Supply	400V/3Ø/50Hz
Entering Air Temp (WB)	80.0 °F	Refrigerant	R410A
Altitude	0 Ft	ESP	2.5 In WG
Total Cooling Capacity	414,086 Btu/hr	Electric Heater	30.0 KW
Sensible Capacity	351,257 Btu/hr	Total Power Input	49.6 KW
Air Flow	6100 CFM	Unit MCA	100.2 A
Face Velocity	381.3 FPM	Unit MOCP	125.0 A
Leaving Air DB	65.1 °F	EER	8.4
Leaving Air WB	63.0 °F		

TECHNICAL DATA

Compressor

Type	Hermetic Scroll	Refrigerant circuit	4
Qty (Comp1)/(Comp2)	4 -	Capacity Step	0-50-100
Size-HP (Comp1)/(Comp2)	10.2 -		

Condenser & Fan Motor Assy.

Rows	3	No. of Condenser Coil	4
Fins per inch	14	Condenser Motor (HP)	1.50
Face Area (ft²)	79.2	No. of fans	4
Coil Type	3/8" Ø IGT Copper		
Fin Type	Aluminum		
Fan type	Direct driven Propeller fan		
Fan Motor	TEAO with Class F motor insulation with inherent thermal protection		

Evaporator

Rows	5	Blower Motor (KW)	5.50
Fins per inch	12	No. of fans	1
Face Area (ft²)	16		
Coil Type	3/8" Ø IGT Copper		
Fin Type	Aluminum		
Blower type	DWDI Backward curve centrifugal fan		
Blower Motor	Totally Enclosed Fan Cooled (TEFC) type, IP 55 Protected, 2 Pole class F insulation		
Drive type	Belt driven with adjustable motor pulley		
Casing	Single skin construction with 15 mm thick fiberglass insulation		
Pre Filter	2" Aluminum washable		
Final Filter	High efficiency synthetic bag filter		

ADDITIONAL OPTIONS

- Electric Heater

UNIT LAYOUT

Model : FAPU-480F2T

