



شركة صناعات التبريد والتخزين والخدمات النفطية
Refrigeration Industries & Storage and Oil Services Co. KSC



PRODUCT SUBMITTAL

Special Package Unit - R410A

Project Name :	<u>0-Jan-00</u>	Unit Model :	<u>SPU-840F24T</u>
Reference No. :	<u>0</u>	Tag No. :	<u>0</u>
Revision No. :	<u>0</u>	Qty :	<u>1</u>
Date :	<u>19-Nov-25</u>	Sales Engineer :	<u>Ronny Bittar</u>
		Prepared by :	<u>0</u>

PERFORMANCE DATA

PERFORMANCE RATING

Air Flow Rate	21000	CFM	Power Supply	400V/3Ø/50Hz
On Coil Temp (DB/WB)	86/72	°F	Ambient Temp	118.4 °F
Altitude	0	°F	Refrigerant	R410A
Total Cooling Capacity	784,044	Btu/hr	ESP	1.50 In WG
Sensible Capacity	539,721	Btu/hr	Electric Heater	10.0 KW
Face Velocity	403	FPM	Total Power Input	92.9 KW
Leaving Air DB	62.2	°F	Unit MCA	177.7 A
Leaving Air WB	61.5	°F	Unit MOCP	200 A
EER	8.4			

TECHNICAL DATA

Compressor

Type	Hermetic Scroll	Refrigerant circuit	4
Qty (Comp1)/(Comp2)	2 2	Capacity Step	0-50-100
Size-HP (Comp1)/(Comp2)	19.7 15.2		

Condenser & Fan Motor Assy.

Rows	3	No. of Condenser Coil	8
Fins per inch	14		
Face Area (ft²)	158.3	Condenser Motor (HP)	1.50
Coil Type	3/8" Ø IGT Copper	No. of fans	8
Fin Type	Aluminum Fins		
Fan type	Direct driven Propeller fan		
Fan Motor	TEAO with Class F motor insulation with inherent thermal protection		

Evaporator & Blower Motor Assy.

Rows	4	No. of Evaporator Coil	2
Fins per inch	12		
Face Area (ft²)	52.1	Blower Motor (KW)	11.0
Coil Type	3/8" Ø IGT Copper	No. of blower	1
Fin Type	Copper Fins		
Blower type	DWDI Forward curve centrifugal fan		
Blower Motor	Totally Enclosed Fan Cooled (TEFC) type, IP 55 Protected, class F insulation		
Drive type	Belt driven		
Casing	Double skin construction with 25 mm thick fiberglass insulation		
Pre Filter	2" Aluminum washable		



شركة صناعات التبريد والتخزين والخدمات النفطية
Refrigeration Industries & Storage and Oil Services Co. KSC



Additional Options

- Condenser coil Protective coating
- Evaporator coil Protective coating
- Copper fins evaporator
- Electric Heater

UNIT LAYOUT

Model : SPU-840F24T

