

Changes made in v1.1

- Use `read_spss()` as single data source; derive `data_labels` via `as_factor()` for descriptive tables
- Re-sync `data_labels` after computing new variables (line 157)
- Fix `Materialsused:exclude TOP_4Materials_8 ("None")` from denominator
- Handle RQ3 long SPSS labels via `dplyr::recode()` with `.default` fallback (replaces manual `method_labels` lookup)
- Use `data_labels` for `CrossTable()`, `data_raw` for `chisq.test()` / `cramersV()`
- Fix typo: "Transparancy" → "Transparency" in axis labels
- Remove redundant `c()` wrappers in single-row summary table
- Add `library(haven)`

Questions

T-test

I have not checked every data with the manuscript yet, but I compared v1.1 (the latest one) to the original one you had. The only difference is the t-test comparing qualitative vs. quantitative studies. The groupings are the same (n = 93, 343, df = 434), but the means, SDs, t-value, and p-value are all different:

- Original: M_qual = 0.72, M_quant = 1.32, t = -3.30, p = .001
- v1.1: M_qual = 0.30, M_quant = 1.46, t = -6.44, p < .001

The possible cause: in your original script, `Method_qualVSquan` is created from `data_rawnum` (original row order) but assigned into `data_raw` (which was reordered by `merge()`). This might have caused the grouping variable to be misaligned with the composite scores (each study's qual/quant label may be attached to the wrong study's composite score). In v1.1 we used the same .sav file throughout so it should be legit.

The manuscript currently reports the original (bugged?) values.

TOP_4Materials_8

`TOP_4Materials_8` means the study used "None" of the materials (i.e., no materials apply). Including it in the denominator inflates `Materialsused`, which deflates the `TOP4_Transparancy` (now `TOP4_Transparency`) ratio.

So maybe we just leave it out?