

# Results - Lab10

```
[root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f "./import.sql"
```

```
INSERT 0 1
```

```
INSERT 0 1
```

```
INSERT 0 1
```

```
CREATE TABLE
```

```
INSERT 0 14
```

| id | name | salary   | deptid |
|----|------|----------|--------|
| 1  | 张三   | 15000.00 | 1      |
| 2  | 李四   | 25000.00 | 1      |
| 3  | 王五   | 10000.00 | 2      |
| 4  | 赵六   | 6000.00  | 6      |
| 5  | 庄七   | 5000.00  | 6      |
| 6  | 郝八   | 12000.00 | 3      |
| 7  | 段九   | 7500.00  | 3      |
| 8  | 殷十   | 15000.00 | 4      |
| 9  | 周一   | 15000.00 | 4      |
| 10 | 范二   | 25000.00 | 5      |
| 11 | 何玲   | 15000.00 | 5      |
| 12 | 李雷   | 7000.00  | 6      |
| 13 | 刘小毛  | 4500.00  | 6      |
| 14 | 张大壮  | 6000.00  | 6      |

(14 rows)

```
[root@iZwz989thjg5p4g6ibyphsZ Lab10]#
```

(14 rows)

```
• [root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f "./test1.sql"
```

```
psql:test1.sql:1: NOTICE: function emp_stamp() does not exist, skipping
```

```
DROP FUNCTION
```

```
CREATE FUNCTION
```

```
psql:test1.sql:27: NOTICE: trigger "emp_stamp_before" for relation "emp" does not exist, skipping
```

```
DROP TRIGGER
```

```
CREATE TRIGGER
```

```
[root@iZwz989thjg5p4g6ibyphsZ Lab10]#
```

```

lab10=# INSERT INTO emp (id, name, salary, deptId)
lab10=# VALUES (015, NULL, 8000, 1);
ERROR:  emp_name cannot be null
CONTEXT:  PL/pgSQL function emp_stamp() line 5 at RAISE
lab10=# INSERT INTO emp (id, name, salary, deptId)
lab10=# VALUES (017, 'test', -1000, 1);
ERROR:  test cannot have a negative salary
CONTEXT:  PL/pgSQL function emp_stamp() line 15 at RAISE
lab10=# INSERT INTO emp (id, name, salary, deptId)
lab10=# VALUES (017, 'test2', 7000, 1);
INSERT 0 1
lab10=#

```

```

[root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f ./test2.sql
psql:test2.sql:1: NOTICE:  table "emp_log" does not exist, skipping
DROP TABLE
CREATE TABLE
psql:test2.sql:13: NOTICE:  function process_emp_check() does not exist, skipping
DROP FUNCTION
CREATE FUNCTION
[root@iZwz989thjg5p4g6ibyphsZ Lab10]#

```

```

CREATE FUNCTION
[root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f ./test3.sql
psql:test3.sql:1: NOTICE:  trigger "check_after" for relation "emp" does not exist, skipping
DROP TRIGGER
CREATE TRIGGER
DROP TRIGGER
CREATE TRIGGER
TRUNCATE TABLE
INSERT 0 1
UPDATE 1
DELETE 1

```

| operation | stamp                      | userid   | level | when_trigger | id | name | salary  |
|-----------|----------------------------|----------|-------|--------------|----|------|---------|
| I         | 2025-11-14 14:37:52.512336 | postgres | ROW   | AFTER        | 18 | 贺小山  | 7000.00 |
| U         | 2025-11-14 14:37:52.515495 | postgres | ROW   | AFTER        | 18 | 贺小山  | 8000.00 |
| D         | 2025-11-14 14:37:52.516817 | postgres | ROW   | AFTER        | 18 | 贺小山  | 8000.00 |

```

(3 rows)
[root@iZwz989thjg5p4g6ibyphsZ Lab10]#

```

```
[root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f ./test4.sql"
DROP TRIGGER
CREATE TRIGGER
TRUNCATE TABLE
INSERT 0 0
UPDATE 0
DELETE 0
 operation |          stamp          | userid | level | when_trigger | id | name | salary
-----+-----+-----+-----+-----+----+-----+-----
 I         | 2025-11-14 14:39:58.671907 | postgres | ROW   | BEFORE       | 18 | 贺小山 | 7000.00
(1 row)

[root@iZwz989thjg5p4g6ibyphsZ Lab10]#
```

```
[root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f ./test5.sql"
TRUNCATE TABLE
DROP TRIGGER
psql:test5.sql:3: NOTICE: trigger "check_update_col" for relation "emp" does not exist, skipping
DROP TRIGGER
CREATE TRIGGER
UPDATE 1
UPDATE 1
 operation |          stamp          | userid | level | when_trigger | id | name | salary
-----+-----+-----+-----+-----+----+-----+-----
 U         | 2025-11-14 14:41:12.285935 | postgres | ROW   | AFTER        | 13 | 刘小毛 | 5400.00
(1 row)

[root@iZwz989thjg5p4g6ibyphsZ Lab10]#
```

```
[root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f ./test6.sql"
TRUNCATE TABLE
DROP TRIGGER
psql:test6.sql:3: NOTICE: trigger "check_update_col_when" for relation "emp" does not exist, skipping
DROP TRIGGER
CREATE TRIGGER
UPDATE 1
UPDATE 1
 operation |          stamp          | userid | level | when_trigger | id | name | salary
-----+-----+-----+-----+-----+----+-----+-----
 U         | 2025-11-14 14:41:46.10251 | postgres | ROW   | AFTER        | 13 | 刘小毛 | 4860.00
(1 row)

[root@iZwz989thjg5p4g6ibyphsZ Lab10]#
```

```
[root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f ./test7.sql"
TRUNCATE TABLE
DROP TRIGGER
psql:test7.sql:3: NOTICE: trigger "check_update_row_when" for relation "emp" does not exist, skipping
DROP TRIGGER
CREATE TRIGGER
UPDATE 1
UPDATE 1
 operation |          stamp          | userid | level | when_trigger | id | name | salary
-----+-----+-----+-----+-----+----+-----+-----
 U         | 2025-11-14 14:42:37.017453 | postgres | ROW   | AFTER        | 13 | 刘小毛 | 5346.00
(1 row)

[root@iZwz989thjg5p4g6ibyphsZ Lab10]#
```

```
[root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f ./test8.sql"
TRUNCATE TABLE
DROP TRIGGER
psql:test8.sql:3: NOTICE: trigger "check_after_statement" for relation "emp" does not exist, skip
ping
DROP TRIGGER
CREATE TRIGGER
UPDATE 15
  operation |          stamp          | userid | level | when_trigger | id | name | salary
-----+-----+-----+-----+-----+-----+-----+-----
-
U          | 2025-11-14 14:43:11.545292 | postgres | STATEMENT | AFTER          |    |    |
(1 row)
```

```
[root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f ./test9.sql"
TRUNCATE TABLE
DROP TRIGGER
psql:test9.sql:3: NOTICE: trigger "check_before_statement" for relation "emp" does not exist, skip
ping
DROP TRIGGER
CREATE TRIGGER
INSERT 0 1
UPDATE 16
DELETE 1
  operation |          stamp          | userid | level | when_trigger | id | name | salary
-----+-----+-----+-----+-----+-----+-----+-----
-
I          | 2025-11-14 14:44:12.440283 | postgres | STATEMENT | BEFORE         |    |    |
U          | 2025-11-14 14:44:12.443263 | postgres | STATEMENT | BEFORE         |    |    |
D          | 2025-11-14 14:44:12.444523 | postgres | STATEMENT | BEFORE         |    |    |
(3 rows)

[root@iZwz989thjg5p4g6ibyphsZ Lab10]#
```

```
^[[A[root@iZwz989thjg5p4g6ibyphsZ Lab10]# psql "postgresql://postgres:postgres@127.0.0.1:5432/lab10" -f ./test10.sql"
psql:test10.sql:1: NOTICE: Operation here: ddl_command_start DROP FUNCTION
psql:test10.sql:1: NOTICE: drop cascades to event trigger tr_fun_event
DROP FUNCTION
CREATE FUNCTION
psql:test10.sql:13: NOTICE: event trigger "tr_fun_event" does not exist, skipping
DROP EVENT TRIGGER
CREATE EVENT TRIGGER
psql:test10.sql:23: NOTICE: Operation here: ddl_command_start CREATE TABLE
CREATE TABLE
psql:test10.sql:25: NOTICE: Operation here: ddl_command_start DROP TABLE
DROP TABLE
  oid | tgrelid | tgparentid |          tgname          | tgfoid | tgtype | tgenabled | tgisinternal | tgconstrrelid | tgconstrindid | tgconstraint | tgdeferrable | tginitdeferred | tgnargs | tgattr | tgargs | tgqual | tgoldtable | tgnewtable
-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----
17468 | 17455 | 0 | RI_ConstraintTrigger_a_17468 | 1654 | 9 | 0 | t |  | 17459 | 17467 | f | f |  |  |  |  |  |  |  |
| \x | 17461 | 17459 | 17467 | f | f |  | 0 |
```