

Contents

3	Rayleigh-Bénard convection	1
3.1	Governing equations	1
3.2	Nondimensionalisation and scale analysis	2
3.3	Large-eddy simulation	3
3.4	Model configuration	3
3.5	Choice of resolution: literature	3
3.5.1	Definitions	4
3.5.2	Resolution guidelines	4
3.5.3	Consequences of insufficient resolution	5
3.6	Choice of resolution: experiment	6

This page intentionally left blank

Talia flammato secum dea corde volutans
nimborum in patriam, loca feta furentibus austris,
Aeoliam venit. Hic vasto rex Aeolus antro
luctantes ventos tempestatesque sonoras
imperio premit ac vinclis et carcere frenat.
Illi indignantes magno cum murmure montis
circum claustra fremunt; celsa sedet Aeolus arce
sceptrum tenens, mollitque animos et temperat iras.
Ni faciat, maria ac terras caelumque profundum
quippe ferant rapidi secum verrantque per auras.
Sed pater omnipotens speluncis abdidit atris,
hoc metuens, molemque et montis insuper altos
imposuit, regemque dedit, qui foedere certo
et premere et laxas sciret dare iussus habenas.

Thus inwardly brooding with heart inflamed,
the goddess came to Aeolia, motherland of
storm clouds, tracts teeming with furious
blasts. Here in his vast cavern, Aeolus, their
king, keeps under his sway and with prison
bonds curbs the struggling winds and the roar-
ing gales. They, to the mountain's mighty
moans, chafe blustering around the barriers.
In his lofty citadel sits Aeolus, sceptre in hand,
taming their passions and soothing their rage;
did he not so, they would surely bear off with
them in wild flight seas and lands and the
vault of heaven, sweeping them through space.
But, fearful of this, the father omnipotent hid
them in gloomy caverns, and over them piled
high mountain masses and gave them a king
who, under fixed covenant, should be skilled
to tighten and loosen the reins at command.

Virgil, *Aeneid* I, ll. 50–63
trans. H. R. Fairclough

Chapter 3

Rayleigh-Bénard convection

TODO: introductory paragraph

3.1 Governing equations

Rayleigh-Bénard convection is the overturning motion of a fluid confined between two horizontal isothermal plates, the bottom plate being warmer than the top plate. The fluid is traditionally assumed to be incompressible, with density ρ related to temperature T by the linear equation of state

$$\rho = \rho_0[1 - \alpha(T - T_0)],$$

α being the volume coefficient of thermal expansion and ρ_0 and T_0 a reference density and temperature. Provided that the density variations are small ($\alpha(T - T_0) \ll 1$), one may employ the *Boussinesq approximation*, neglecting density variations everywhere except in their contribution to the weight force. This leads to the Boussinesq equations

$$\frac{\partial \mathbf{u}}{\partial t} + \mathbf{u} \cdot \nabla \mathbf{u} = -\frac{1}{\rho_0} \nabla p' + \alpha(T - T_0)g\hat{\mathbf{z}} + \nu \nabla^2 \mathbf{u}, \quad (3.1.1)$$

$$\frac{\partial T}{\partial t} + \mathbf{u} \cdot \nabla T = \kappa \nabla^2 T, \quad \text{and} \quad (3.1.2)$$

$$\nabla \cdot \mathbf{u} = 0, \quad (3.1.3)$$

which represent the momentum balance, the conservation of energy and the assumption of incompressibility, respectively. The prognostic variables are the fluid velocity \mathbf{u} and the temperature T (the pressure perturbation p' is implicitly determined by (3.1.3)). The parameters of the model are the kinematic viscosity ν and thermal diffusivity κ . $\hat{\mathbf{z}}$ is the upward unit vector. The Boussinesq approximation has led to the appearance of a buoyant force (per unit mass)

$$\alpha(T - T_0)g = \frac{\rho_0 - \rho}{\rho_0}g$$

in the momentum equation, in agreement with Archimedes' principle. The reader is referred to Chandrasekhar (1961) for a detailed derivation of the Boussinesq equations; I have merely summarised the main assumptions and approximations involved.

In this work, I consider solutions of (3.1.1)–(3.1.3) in a two-dimensional domain $[0, d] \times [0, L]$ with Cartesian coordinates x and z , subject to no-slip, isothermal boundary conditions

$$\mathbf{u} = \mathbf{0}, \quad T = T_0 + \frac{\delta T}{2} \quad \text{at } z = 0 \text{ and} \quad (3.1.4)$$

$$\mathbf{u} = \mathbf{0}, \quad T = T_0 - \frac{\delta T}{2} \quad \text{at } z = d \quad (3.1.5)$$

on the top and bottom plates, and periodic boundary conditions

$$\mathbf{u}(x=0) = \mathbf{u}(x=L) \quad \text{and} \quad T(x=0) = T(x=L) \quad (3.1.6)$$

in the horizontal. δT is the constant temperature difference between the plates.

3.2 Nondimensionalisation and scale analysis

It is helpful to nondimensionalise the governing equations (3.1.1)–(3.1.6); this is not only useful for numerical work but also gives insight into the different flow regimes that are possible. A range of nondimensionalisations are used in fluid dynamics literature; I adopt a common one (see, e.g., Grötzbach 1983; Ouertatani et al. 2008; Stevens, Verzicco, and Lohse 2010) which is suitable for the turbulent convective regime.

The first step is to choose representative time, length and temperature scales. For low-viscosity, turbulent flow, a suitable time scale is the *free-fall time* t_0 , which is the time for a fluid element with constant temperature $T = T_0 - \delta T$ to fall from the top plate to the bottom plate under the influence of buoyancy ($-\alpha g \delta T$) alone. It is simple to show that

$$t_0 \sim \left(\frac{d}{g \alpha \delta T} \right)^{1/2},$$

ignoring a factor of $\sqrt{2}$. The obvious length and temperature scales are the plate separation d and temperature difference δT , respectively.

Making the substitutions $p'/\rho_0 \rightarrow \pi$ and $T - T_0 \rightarrow \theta$ in (3.1.1)–(3.1.6) and expressing all variables in units of t_0 , d and δT leads to the dimensionless equations

$$\frac{\partial \mathbf{u}}{\partial t} + \mathbf{u} \cdot \nabla \mathbf{u} = -\nabla \pi + \left(\frac{\text{Pr}}{\text{Ra}} \right)^{1/2} \nabla^2 \mathbf{u} + \theta \hat{\mathbf{z}}, \quad (3.2.1)$$

$$\frac{\partial \theta}{\partial t} + \mathbf{u} \cdot \nabla \theta = (\text{Ra Pr})^{-1/2} \nabla^2 \theta, \quad \text{and} \quad (3.2.2)$$

$$\nabla \cdot \mathbf{u} = 0, \quad (3.2.3)$$

which are solved in the domain $[0, \Gamma] \times [0, 1]$ with boundary conditions

$$\mathbf{u} = \mathbf{0}, \quad \theta = +\frac{1}{2} \quad \text{at } z = 0, \quad (3.2.4)$$

$$\mathbf{u} = \mathbf{0}, \quad \theta = -\frac{1}{2} \quad \text{at } z = 1, \quad (3.2.5)$$

$$\mathbf{u}(x=0) = \mathbf{u}(x=\Gamma) \quad \text{and} \quad \theta(x=0) = \theta(x=\Gamma). \quad (3.2.6)$$

There are three dimensionless parameters: the aspect ratio of the domain

$$\Gamma \equiv \frac{L}{d},$$

the *Prandtl number*

$$\text{Pr} \equiv \frac{\nu}{\kappa}$$

which measures the relative importance of viscosity (momentum diffusivity) and thermal diffusivity, and the *Rayleigh number*

$$\text{Ra} \equiv \frac{g\alpha d^3 \delta T}{\kappa \nu}.$$

The Rayleigh number can be interpreted as the ratio of the time scale for thermal transport by conduction to the time scale for thermal transport by convection. It determines the importance of diffusion for the evolution of \mathbf{u} and θ ; inspection of (3.2.1) and (3.2.2) indicates that low Ra implies strong diffusion and high Ra weak diffusion. Stability analysis (see, e.g., Chandrasekhar (1961) and the seminal work by Lord Rayleigh (1916)) reveals that there exists a critical Rayleigh number (dependent on boundary conditions but of order 10^3), below which the equations have a stable equilibrium with the fluid at rest and a linear conductive temperature profile. Above the critical Rayleigh number, the equilibrium is unstable and small perturbations lead to the formation of a regular series of steady convection cells. If the Rayleigh number is increased much further (Le Quéré (1991) cites $\text{Ra} \approx 2 \times 10^8$), the solution becomes unsteady and increasingly turbulent. This work is concerned with the turbulent regime, since Rayleigh numbers for atmospheric deep moist convection can be as large as 10^{22} (Chillà and Schumacher 2012).

3.3 Large-eddy simulation

TODO: Describe Smagorinsky scheme

3.4 Model configuration

The nondimensionalised Boussinesq equations (3.1.1)–(3.2.6) are solved numerically using Dedalus, a spectral code built in Python (Burns et al. 2020). Spectral methods represent the solution of a partial differential equation as a linear combination of linearly independent basis functions, solving for the coefficients of the basis function expansion rather than the values of the solution in real space. The resolution of the model is thus set by choosing the number of basis functions used. This work uses a Fourier (sine/cosine) basis in the horizontal direction and a basis of Chebyshev polynomials (of the first kind) in the vertical direction. The Fourier basis has the special property that all linear combinations respect the periodic boundary conditions. Timestepping is performed using a second-order Runge-Kutta scheme. The complete model source code is publicly available [TODO: data availability](#).

The Rayleigh number was set to 10^9 , a value at which the flow was found to be unsteady and feature transient eddies. The aspect ratio of the domain was $\Gamma = 8$ and the Prandtl number was set to 1 for simplicity.

TODO: link to animations

3.5 Choice of resolution: literature

TODO: fix introductory paragraph

TODO: s.sherwood: Might be important to further explain here that you will regard this as the ("warts and all") dynamical system you want to emulate at a coarser representation. This avoids the issue of whether this hig-res is a perfect solution of the fluid equations or not (it doesn't have to be, although for robustness we want it to be relatively insensitive to small changes in dx).

The first basic requirement for a parametrisation testbed is a reasonably accurate high-resolution model to treat as truth. The next requirement is a truncated coarse model which possesses systematic biases relative to truth that might reasonably be improved by parametrising the unresolved subgrid-scale dynamics. In this section, I review relevant literature on numerical solutions of the Rayleigh-Bénard problem with the aim of establishing the nature of the biases that might be expected. Practically, the following questions must be answered:

- What resolution is necessary for a converged solution?
- Which quantities are most sensitive to insufficient resolution?

3.5.1 Definitions

Two more definitions are necessary before proceeding. First, the Nusselt number measures the rate of (vertical) heat transport across a horizontal plane at height z , normalised by the purely conductive rate that would exist if the fluid were at rest (Verzicco and Camussi 1999). Following Chillà and Schumacher (2012), I use the definition (before nondimensionalisation)

$$\text{Nu}(z, t) \equiv \frac{\langle wT \rangle_{A,t} - \kappa \partial \langle T \rangle_{A,t} / \partial z}{\kappa \delta T / d} \quad (3.5.1)$$

where $\langle \cdot \rangle_{A,t}$ denotes averaging over time and the horizontal plane at height z , and $w = \mathbf{u} \cdot \hat{\mathbf{z}}$ is the vertical velocity. The rate of heat transport in the numerator has two terms: advection $\langle wT \rangle_{A,t}$ and conduction $-\kappa \partial \langle T \rangle_{A,t} / \partial z$. The denominator $\kappa \delta T / d$ is the rate of heat transport for a linear conductive temperature profile with the fluid at rest.

Another important quantity is the thickness δ_T of the *thermal boundary layer* at each plate where large temperature gradients exist. Chillà and Schumacher (2012) define δ_T as follows: if, on average, the fluid temperature changes with height from $+\delta T/2$ at the lower plate to 0 (the mean value in the well-mixed interior) over a distance δ_T , then

$$\left. \frac{\partial \langle T \rangle_{A,t}}{\partial z} \right|_{z=0} \approx -\frac{\delta T}{2\delta_T}.$$

But if one considers the definition of the Nusselt number (3.5.1) at $z = 0$, the advection term $\langle wT \rangle_{A,t}$ vanishes due to the $\mathbf{u} = \mathbf{0}$ boundary condition and

$$\text{Nu}(z = 0) = -\frac{d}{\delta T} \left. \frac{\partial \langle T \rangle_{A,t}}{\partial z} \right|_{z=0}.$$

Thus,

$$\delta_T = \frac{d}{2 \text{Nu}(z = 0)}. \quad (3.5.2)$$

3.5.2 Resolution guidelines

Grötzbach (1983) is recognised as the first to formulate resolution requirements for accurate simulations of Rayleigh-Bénard convection (Chillà and Schumacher 2012; Scheel, Emran, and Schumacher 2013). He identified separate constraints on the mean (i.e., averaged in each spatial direction) grid spacing and the vertical spacing near the plates; I first discuss the former. Grötzbach reasoned that a numerical model that neglects subgrid-scale effects must have a geometric mean grid spacing $h = (\Delta x \Delta y \Delta z)^{1/3}$ such that

$$h \leq \pi \eta = \pi \left(\frac{\nu^3}{\langle \epsilon \rangle} \right)^{1/4} \quad (3.5.3)$$

where $\eta \equiv (\nu^3/\langle\epsilon\rangle)^{1/4}$ is the *Kolmogorov length*, the universal smallest relevant length scale for general turbulent flow, and $\langle\epsilon\rangle$ is the spatial and temporal average of the kinetic energy dissipation rate defined by

$$\epsilon(\mathbf{x}, t) \equiv \frac{\nu}{2} \sum_{ij} \left(\frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} \right)^2 \quad (3.5.4)$$

(Chillà and Schumacher 2012). The inequality (3.5.3) between h and η can be understood using the Nyquist-Shannon theorem, which states that a sampling frequency $f \geq k/\pi$ is needed to unambiguously reconstruct a signal with maximum wavenumber k ; substituting $f = 1/h$, $k = 1/\eta$ leads to the claimed relation.

Grötzbach recognised that the above reasoning was only valid for the mean grid spacing; large gradients in temperature and velocity near the top and bottom plates require finer resolution in those regions. The notion of nearness can be formalised using the thermal boundary layer thickness (3.5.2), and one asks how many grid points are necessary in this layer. Grötzbach did not give a theoretical argument to derive this number but claimed that 3 points are sufficient for turbulent flows. Shishkina et al. (2010) presented a theoretical argument based on the (experimentally and numerically justified) assumption of laminar *Prandtl-Blasius* flow conditions in the boundary layer and were able to calculate the minimum number of grid points (e.g., 9 for $Ra = 2 \times 10^9$ and $Pr = 0.7$). The results agreed with criteria derived in previous numerical experiments. Importantly, the results of Shishkina et al. allow *a priori* determination of vertical resolution requirements, potentially bypassing the time-consuming and expensive process of iteratively running simulations, checking their convergence and updating the resolution.

3.5.3 Consequences of insufficient resolution

TODO: note double purpose of this section: verifying fine resolution and choosing coarse resolution. Also provides good evaluation metrics

Performing numerical experiments for a 3D fluid layer, Grötzbach found that RMS velocity and Nusselt number were the most sensitive quantities to insufficient mean grid spacing, but even they increased “only slightly” above the values obtained from well-resolved simulations.

Later work also supports the finding that the Nusselt number is sensitive to under-resolution. Even studying only steady-state convective solutions at moderate Rayleigh number, Le Quéré (1991) found that the maximum and minimum Nusselt numbers were most sensitive to changes in resolution and had the largest uncertainty among existing benchmark solutions. Other studies have used the convergence of the Nusselt number as an indicator that the spatial resolution is sufficient to produce an accurate solution (Quertatani et al. 2008).

Stevens, Verzicco, and Lohse (2010) performed 3D simulations in a finite cylindrical cavity with the aim of reconciling the apparent disagreement between the Nusselt numbers in previous numerical studies and experimental observations. They found that agreement with experiment could be achieved, but only by using a much higher resolution than the previous studies. They offered the physical explanation that horizontally under-resolved simulations produce insufficient thermal diffusion, leading to systematic overestimation of the buoyancy of convective plumes near the side-walls of the cylinder; this results in Nusselt numbers that exceed experimentally observed values. This led them to conclude that the two criteria of Grötzbach (1983)—for mean grid spacing and for the vertical spacing near the upper and lower plates—are not independent; the definition $h = (\Delta x \Delta y \Delta z)^{1/3}$ in (3.5.3) allows the horizontal spacing to remain relatively coarse near the plates, provided the vertical spacing is small. Since fine horizontal resolution is also necessary to accurately capture the dynamics of the thin plumes, they proposed that (3.5.3) be applied with $h = \max(\Delta x, \Delta y, \Delta z)$ instead.

Some more recent work, however, casts doubt on the notion that the Nusselt number is sensitive to under-resolution and that its convergence is a good indicator that the flow is well-resolved. In assessing the performance of several published computational fluid dynamics codes on the Rayleigh-Bénard problem in a cylindrical cavity, Kooij et al. (2018) identified one higher-order code that reproduced the theoretically

predicted scaling of Nu as a function of Ra even when the flow was deliberately under-resolved. On the other hand, the presence of numerical artefacts in the instantaneous temperature field near the bottom plate was a clear indicator of insufficient resolution.

Scheel, Emran, and Schumacher (2013) performed similar high-resolution simulations for a cylindrical cavity and also found that the Nusselt number, among other global transport properties, were “fairly insensitive to insufficient resolution, as long as the mean Kolmogorov length [was] resolved” (i.e., (3.5.3) was satisfied). However, they found that the horizontally averaged or local kinetic energy dissipation rate (3.5.4) and the corresponding thermal dissipation rate

$$\epsilon_T(\mathbf{x}, t) \equiv \kappa \sum_i \left(\frac{\partial T}{\partial x_i} \right)^2 \quad (3.5.5)$$

were much more sensitive, with their convergence requiring even stricter conditions than (3.5.3).

In summary, conditions on the mean grid spacing and number of grid points in the thermal boundary layer exist to guide high-resolution simulations. It is known that the Nusselt number and kinetic and thermal dissipation rates are sensitive to under-resolution, so the statistics of these quantities could serve as metrics for evaluating parametrisation performance. **TODO: fix concluding paragraph**

3.6 Choice of resolution: experiment

Bibliography

- Burns, K. J., G. M. Vasil, J. S. Oishi, D. Lecoanet, and B. P. Brown (2020). “Dedalus: a flexible framework for numerical simulations with spectral methods”. *Phys. Rev. Res.* **2**(2). DOI: [10.1103/PhysRevResearch.2.023068](https://doi.org/10.1103/PhysRevResearch.2.023068).
- Chandrasekhar, S. (1961). *Hydrodynamic and hydromagnetic stability*. Oxford: Clarendon Press. ISBN: 9780486319209.
- Chillà, F. and J. Schumacher (2012). “New perspectives in turbulent Rayleigh-Bénard convection”. *Eur. Phys. J. E* **35**(7). DOI: [10.1140/epje/i2012-12058-1](https://doi.org/10.1140/epje/i2012-12058-1).
- Grötzbach, G. (1983). “Spatial resolution requirements for direct numerical simulation of the Rayleigh-Bénard convection”. *J. Comput. Phys.* **49**(2). DOI: [10.1016/0021-9991\(83\)90125-0](https://doi.org/10.1016/0021-9991(83)90125-0).
- Kooij, G. L., M. A. Botchev, E. M. A. Frederix, B. J. Geurts, S. Horn, D. Lohse, E. P. van der Poel, O. Shishkina, R. J. A. M. Stevens, and R. Verzicco (2018). “Comparison of computational codes for direct numerical simulations of turbulent Rayleigh-Bénard convection”. *Comput. Fluids* **166**. DOI: [10.1016/j.compfluid.2018.01.010](https://doi.org/10.1016/j.compfluid.2018.01.010).
- Le Quéré, P. (1991). “Accurate solutions to the square thermally driven cavity at high Rayleigh number”. *Comput. Fluids* **20**(1). DOI: [10.1016/0045-7930\(91\)90025-D](https://doi.org/10.1016/0045-7930(91)90025-D).
- Lord Rayleigh (1916). “On convection currents in a horizontal layer of fluid, when the higher temperature is on the under side”. *Philos. Mag.* **32**(192). DOI: [10.1080/14786441608635602](https://doi.org/10.1080/14786441608635602).
- Ouertatani, N., N. Ben Cheikh, B. Ben Beya, and T. Lili (2008). “Numerical simulation of two-dimensional Rayleigh-Bénard convection in an enclosure”. *C.R. Mec.* **336**(5). DOI: [10.1016/j.crme.2008.02.004](https://doi.org/10.1016/j.crme.2008.02.004).
- Scheel, J. D., M. S. Emran, and J. Schumacher (2013). “Resolving the fine-scale structure in turbulent Rayleigh-Bénard convection”. *New J. Phys.* **15**(11). DOI: [10.1088/1367-2630/15/11/113063](https://doi.org/10.1088/1367-2630/15/11/113063).
- Shishkina, O., R. J. A. M. Stevens, S. Grossmann, and D. Lohse (2010). “Boundary layer structure in turbulent thermal convection and its consequences for the required numerical resolution”. *New J. Phys.* **12**(7). DOI: [10.1088/1367-2630/12/7/075022](https://doi.org/10.1088/1367-2630/12/7/075022).
- Stevens, R. J. A. M., R. Verzicco, and D. Lohse (2010). “Radial boundary layer structure and Nusselt number in Rayleigh-Bénard convection”. *J. Fluid Mech.* **643**. DOI: [10.1017/S0022112009992461](https://doi.org/10.1017/S0022112009992461).
- Verzicco, R. and R. Camussi (1999). “Prandtl number effects in convective turbulence”. *J. Fluid Mech.* **383**. DOI: [10.1017/S0022112098003619](https://doi.org/10.1017/S0022112098003619).