

HW3_tdolkar

Due Wednesday Sep 30

Tsering Dolkar

9/24/2020

Problem 1

I did primer on Rstudio cloud.

Problem 2

Created the Rmd file

Problem 3

Problem 4

Problem 5

#dplyr + summarize + group_by

```
summarise_data <- function(our_data){  
  #function to calculate summary of a dataframe, returns a vector of the summary  
  observer_summary <- double(length = 5)  
  for(i in 1:5){  
    if(i == 1)  
      observer_summary[i] <- mean(our_data[,1])  
    if(i == 2)  
      observer_summary[i] <- mean(our_data[,2])  
    if(i == 3)  
      observer_summary[i] <- sd(our_data[,1])  
    if(i == 4)  
      observer_summary[i] <- sd(our_data[,2])  
    if(i == 5)  
      observer_summary[i] <- cor(our_data[,1], our_data[,2])  
  }  
  return(observer_summary)  
}
```

```

# We'll find the summary for each observer:
# We will be returned a vector of length 5 for each of 13 observers from the function
# summarise_data such that
# 1. mean of dev 1
# 2. mean of dev 2
# 3. standard dev of dev 1
# 4. standard dev of dev 2
# 5. correlation between dev 1 and 2
# are the values respectively in a row.

#separate the data into vectors to make it less confusing to work with first
observer <- observations$Observer
dev1 <- observations$dev1
dev2 <- observations$dev2

#initialize vectors we will need:
dev1_by_observer <- double(0)
dev2_by_observer <- double(0)
summary_statistics <- data.frame()
colnames(summary_statistics) <-

#we have a nested for loop here. The outer for loop keeps track of observer 1 to 13 and
#the inside for loop looks for all the data by the said observer in the dataset from top to bottom
#once.
for(i in 1:13){
  track_observer <- i
  for(j in 1:length(observer)){
    if(track_observer == observer[j]){
      dev1_by_observer <- c(dev1_by_observer, dev1[j])
      dev2_by_observer <- c(dev2_by_observer, dev2[j])
    }
  }
  raw_data <- data.frame(dev1_by_observer, dev2_by_observer)
  colnames(raw_data) <- c("dev1", "dev2")
  summary_statistics_each_observer <- cbind(rep(i, 5), summarise_data(raw_data))
  summary_statistics <- rbind(summary_statistics, summary_statistics_each_observer)
}
summary_statistics <- data.frame(rep(c("Mean_dev1", "Mean_dev2", "SD_dev1", "SD_dev2",
                                     "Cor_dev1_dev2"), 13), summary_statistics)
colnames(summary_statistics) <- c('V1', 'Observer', 'V3')
new_summary_statistics <- summary_statistics %>%
  spread(key = V1, value = V3)
# reorder by column name
new_summary_statistics <- new_summary_statistics[c("Observer", "Mean_dev1", "Mean_dev2",
                                                  "SD_dev1", "SD_dev2", "Cor_dev1_dev2")]
new_summary_statistics <- kable(new_summary_statistics)

## [1] "boxplot summary of devices"

```

boxplot summary of devices







