Test Plan for Serial Console

LINEO
Solutions

@ for
Ubiquitous,
Ultimate,
Universal

Test Plan for Serial Console

1 Outline

This document is for the Serial Console driver in Linux kernel of MVF TOWER BOARD (XTWR-VF600) with VF6XX SoC, and describes test plan for each API/feature of such unit.

Serial Console indicates the portion specialized for the following functions in UART.

 - Kernel message at boot
 - Command input/output on serial terminal

2 Test Environment

Toolchain: The latest Linaro toolchain
Bootloader: u-boot 2011.12
Kernel: Freescale i.MX Linux 3.0.15 kernel
Rootfs: rootfs on NFS

3 Target Module of the Test

Serial Console Input/Output

4 Test Plan

Verify kernel boot output and shell command input/output.

5 Conditions

Flow control, modem control and such will be tested at a time of release as UART driver.

Baud rate will be tested at 115200 (to be the same as u-boot). Change of baud rate will be tested at a time of release as UART driver.

Specify "console=ttymvf1,115200n8" in kernel command line.

Test plan for Serial Console
Datails

No.	Head	Item	Procedure	Points to be checked	Judge	Note
1	Kernel Message	Kernel Output	Boot kernel from u-boot.	Kernel boot message appears properly without character corruption.		
2	Comamnd Prompt	Login	Type "root" in login prompt on serial terminal.	Login prompt appears on serial console.		
3			Continue from the test above. Press Enter on serial terminal.	Login properly.		
4		Command Execute	Enter the following command in command prompt of serial tierminal. # ls /	/ directory list of rootfs on NFS appears properly without character corruption.		
5			Enter the following command in command prompt of serial tierminal. # echo "Hello world" > /dev/ttymvf1	"Hello world" appears on serial terminal.		
6			Enter other commands (such as below) in command prompt. # cat /proc/interrupts # ls -lR / etc..	Each output of executed commands appears properly.		