

# The `abbrev` package\*

Thai Son Hoang  
ECS, University of Southampton  
<T dot S dot Hoang at ecs dot soton dot ac dot uk>

May 16, 2017

## Abstract

This package provides macros for typesetting abbreviations. It was developed initially at the Swiss Federal Institute of Technology Zurich (ETH-Zurich) and subsequently at the University of Southampton.

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Usage</b>	<b>1</b>
2.1	Creating Abbreviations . . . . .	1
2.2	Resetting Abbreviations . . . . .	2
2.3	Creating a List of Abbreviations . . . . .	2
<b>3</b>	<b>Implementation</b>	<b>2</b>

## 1 Introduction

This package was developed in order to ease the typesetting of abbreviations in L<sup>A</sup>T<sub>E</sub>X. Each abbreviation is associated with a set of macros for typesetting. Abbreviations are collected and can be displayed in list of abbreviations by making use of package `nomenc1`.

## 2 Usage

Just like any other package, you need to request this package with a `\usepackage` command in the preamble.

So in the simpler case, one just types

`\usepackage{abbrev}`

to load the package

The rest of this section is to give descriptions of the main (meta-)macro for creating abbreviation macros and their expected behaviour.

---

\*This document corresponds to `abbrev` v1.1, dated 2017/05/16.

## 2.1 Creating Abbreviations

`\newabbrev` Macro `\newabbrev` is a meta-macro that creating several abbreviation macros. The signature of `\newabbrev` is as follows.

```
\newabbrev[csname]{abbreviation}{expansion string}  
             {plural-csname}{plural-abbreviation}{plural-expansion-string}
```

The first optional argument `csname` is the *control sequence* name that will be use to create the abbreviation macro, i.e., the marco will be `\csname`. If the first optional argument is omitted, the second argument representing the `abbreviation` will be used as the control sequence. The third argument is the *full expansion string* of for the abbreviation. A plural macro for the abbreviation is also created. By default, the plural control sequence name, the plural abbreviation and the plural expansion string correspond to singular version with an additional `s`. In the case where it should be defined differently, it can be declared as the additional argument `plural-csname`, `plural-abbreviation`, `plural-expansion-string`.

An invocation of the above `\newabbrev` with control sequence `csname` will create the following macros:

- `\csname`: Singular version of the abbreviation macro.
- `\csnames`: Plural version of the abbreviation macro (with an additional `s`).

First time usage of `\csname` will be replaced by “full string (abbreviation)”. Subsequent uses of `\csname` will be replaced by “abbreviation”. Macro `\csnames` is the plural version macro.

## 2.2 Resetting Abbreviations

`\resetabbrev` The above expansion behaviour can be reset by calling `\resetallabbrev`. Afterwards, `\csname` and `\csnames` will be expanded the first time that they are used. Individual abbreviation `\csname` can be reset by `\resetabbrev{csname}` (Here `csname` is the control sequence corresponding to the singular version of the macro.

More information can be found in the accompanying sample document.

## 2.3 Creating a List of Abbreviations

The list of abbreviations can be created by making use of package `nomenc1`. Typically, one includes the following in the document preamble.

```
\usepackage{nomenc1}  
\renewcommand{\nomname}{List of Abbreviations}  
\makenomenclature
```

The following command from `nomenc1` is used print the list of abbreviations.

```
\printnomenclature
```

Finally, use `makeindex` to compile and generate the list of abbreviations appropriately.

```
makeindex filename.nlo -s nomenc1.ist -o filename.nls  
where filename is the name of the main .tex file.
```

### 3 Implementation

The implementation is quite straightforward. We first request the `etoolbox` package for implementation purpose, `xspace` for utilising the spacing, and `nomenc1` for creating list of abbreviations.

```
\RequirePackage{etoolbox}
\RequirePackage{xspace}
\RequirePackage{nomenc1}
```

`\newabbrev` The `\newabbrev` makes use of the worker macro `\newfullabbrev` for creating abbreviations macros.

```
\newcommand{\newabbrev}[3][{}]{%
  \newfullabbrev[#1]{#2}{#3}{-}{-}{-}
}
```

`\newfullabbrev` The `\newfullabbrev` makes use of the worker macro `\abbrev@create` for creating abbreviations macros.

```
\newcommand{\newfullabbrev}[6][{}]{%
  \expandafter\ifstrequal\expandafter{#1}{-}{
    \def\abbrev@sgcsname{#2}
  }{
    \def\abbrev@sgcsname{#1}
  }
  \def\abbrev@sgabbrev{#2}
  \def\abbrev@sgexpn{#3}

  \expandafter\ifstrequal\expandafter{#4}{-}{
    \edef\abbrev@plcsname{\abbrev@sgcsname s}
  }{
    \def\abbrev@plcsname{#4}
  }

  \expandafter\ifstrequal\expandafter{#5}{-}{
    \edef\abbrev@plabbrev{\abbrev@sgabbrev s}
  }{
    \def\abbrev@plabbrev{#5}
  }

  \expandafter\ifstrequal\expandafter{#6}{-}{
    \edef\abbrev@plexpn{\abbrev@sgexpn s}
  }{
    \def\abbrev@plexpn{#6}
  }

  % This code ensure that the arguments are expanded properly
  \begingroup\edef\z{\endgroup\noexpand\abbrev@create
    {\abbrev@sgcsname}{\abbrev@sgabbrev}{\abbrev@sgexpn}
    {\abbrev@plcsname}{\abbrev@plabbrev}{\abbrev@plexpn}}\z
}
```

**\abbrev@create** The main worker meta-macro for creating the abbreviation macros is implemented as follows. It create a private toggle variable to be used to distinguish the first time usage of the abbreviation. The abbreviation is add to **abbrev@list** (for resetting abbreviation macros later). It then call **abbrev@init** to create the initialisation macro, then call the initialisation macro afterward.

```
\newcommand{\abbrev@create}[6]{%
  \newtoggle{#1@toggle}
  \listadd{\abbrev@list}{#1}
  \abbrev@init{#1}{#2}{#3}{#4}{#5}{#6}
  \csuse{#1@init}
}
```

**\abbrev@init** This macro create the initialisation meta-macro for creating the abbreviation macros.

```
\newcommand{\abbrev@init}[6]{%
  \expandafter\def\csname#1@init\endcsname{%
    \togglefalse{#1@toggle}
    \expandafter\def\csname#1\endcsname{%
      \iftoggle{#1@toggle}{%
        #2%
      }{%
        \nomenclature{#2}{#3}%
        \toggletrue{#1@toggle}%
        #3 (#2)%
      }%
      \expandafter\def\csname#1\endcsname{#2\hspace}%
      \hspace%
    }%

    \expandafter\def\csname#4\endcsname{%
      \iftoggle{#1@toggle}{%
        #5%
      }{%
        \nomenclature{#2}{#3}%
        \toggletrue{#1@toggle}%
        #6 (#5)%
      }%
      \expandafter\def\csname#4\endcsname{#5\hspace}%
      \hspace%
    }%
  }%
}
```

**\resetabbrev** Reset the all abbreviation macros to full expansion mode by going through **abbrev@list** and call the initialisation macro for each abbreviation. In the case where the optional argument is non-empty only the corresponding abbreviation is reset.

```
\newcommand{\resetabbrev}[1][]{%
  \expandafter\ifstrequal\expandafter{#1}{%
    \renewcommand*{\do}[1]{%
      \csuse{##1@init}
    }
  }
```

```

\doalistloop{\abbrev@list}
}{
\csuse{#1@init}
}
}

```

## Change History

v1.0		newfullabbrev . . . . . 3
\newabbrev: Macro created . . . . . 3		\newfullabbrev: Macro created . . 3
General: Initial version . . . . . 1		\resetabbrev: Added optional
v1.1		argument to reset individual
\abbrev@create: Allow explicit		abbreviation . . . . . 4
declaration of plural version . . . 3		General: Added command to
\newabbrev: Change the		address plural version of
implement to use		abbreviations . . . . . 1

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in *roman* refer to the pages where the entry is used.

<b>A</b>	\abbrev@sgexpn . . . . . 3	<b>N</b>
\abbrev@create . . . 3, <u>3</u>		\newabbrev . . . . . 1, <u>3</u>
\abbrev@init . . . . . 3, <u>4</u>	<b>B</b>	\newfullabbrev . . . 3, <u>3</u>
\abbrev@list . . . . . 3, 4	\begingroup . . . . . 3	\noexpand . . . . . 3
\abbrev@plabbrev . . . 3		<b>R</b>
\abbrev@plcsname . . . 3	<b>E</b>	\resetabbrev . . . . . 2, <u>4</u>
\abbrev@plexpn . . . . . 3	\edef . . . . . 3	<b>Z</b>
\abbrev@sghabbrev . . . 3	\endgroup . . . . . 3	\z . . . . . 3
\abbrev@sgcsname . . . 3		