UGAIYA BIO-SCIENCES

H1650 Benchtop High Speed Micro Centrifuge

H1650 Benchtop High Speed Centrifuge

H1650 Benchtop High Speed Centrifuge provides multiple protection against over-speed, door lid and misoperation, etc. 7 types of rotors are available for users to choose from, with powerful functions and safe operation, which can meet various centrifugal experiments.

Product Advantages

- 5 inch HD touch screen, simple interface, setting parameters and running parameters can be displayed simultaneously.
- Directly input the setting value for fast and convenient operation without adjusting the parameters back and forth many times (compared to traditional keypad and knob control products).
- Multiple user-defined programs can be saved.
- Microprocessor control, DC brushless motor for stable and low noise operation.
- Parameters can be set freely during a run.
- Door lid interlock to improve the safety performance.
- Compact with great performance.
- 10 Acceleration and 11 Deceleration rates, to achieve the best centrifugation result.

Specification

- Max Speed : 16500/min
- Max RCF : 18360×g
- Max Capacity : 12 x 5 ml
- Speed Accuracy : ± 30 rpm
- Time Setting Range : 1 s to 99 min 59 s
- Noise : ≤ 65 dB(A)
- Power Supply : AC 220±22V 50Hz
- Power Consumption : 250W
- Dimension (External) : 320×370×235 mm
- Packing Dimension (W×D×H) : 530×410×290 mm
- Net Weight : 11 kg

Exclusive Distributor : PT Gravia Citra Lestari
GC Aesthetics Clinic Building 3rd & 4th Floor
Jl. Wolter Monginsidi No. 84 HH, Petogogan Kebayoran Baru, Jakarta Selatan, Indonesia – 12170
Website : www.graviacitralestari.id
Phone : (021) 7398967 | Email : sales@graviacitralestari.id

CDAKB ISO 9001:2015

UGAIYA BIO-SCIENCES

H1650 Benchtop High Speed Micro Centrifuge

Rotor Parameters

Rotor Type: Angle rotor Max Capacity: 12×1.5 ml Max Speed: 16500 rpm Max RCF: 18360×g Adapter: 0.5 ml, 0.2 ml	Rotor Type: Angle rotor Max Speed: 16500 rpm Max RCF: 18360×g Max Capacity: 18×0.5 ml
Rotor Type: Angle rotor Max Speed: 12000 rpm Max RCF: 10142×g Max Capacity: 12×5 ml Adapter: 0.5 ml, 1.5 ml	Rotor Type: Angle rotor Max Speed: 13000 rpm Max RCF: 16170×g Max Capacity: 24×1.5 ml Adapter: 0.5 ml , 0.2ml
Rotor Type: Angle rotor Max Speed: 15000 rpm Max RCF: 13800×g Max Capacity: 3x8x0.2 ml PCR Tube	Rotor Type: Angle rotor Max Speed: 12000 rpm Max RCF: 14800×g Max Capacity: 12 Capillaries
Rotor Type: Angle rotor Max Speed: 12000 rpm Max RCF: 14800×g Max Capacity: 24 Capillaries	

Exclusive Distributor : PT Gravia Citra Lestari
GC Aesthetics Clinic Building 3rd & 4th Floor
Jl. Wolter Monginsidi No. 84 HH, Petogogan Kebayoran Baru, Jakarta Selatan, Indonesia – 12170
Website : www.graviacitralestari.id
Phone : (021) 7398967 | Email : sales@graviacitralestari.id

CDAKB ISO 9001:2015