

Netcat GET request

1. Objective

The objective of this test was to verify that the OWASP Juice Shop web application was accessible over HTTP by manually sending a GET request using Netcat and the printf command.

2. Target

- **Target application:** OWASP Juice Shop
- **Target IP:** 192.168.18.81
- **Target port:** 3000/TCP
- **Protocol:** HTTP
- **Method:** GET

3. Command line used:

```
printf 'GET / HTTP/1.1\r\nHost: 192.168.18.81:80\r\nConnection: close\r\n\r\n' | nc 192.168.18.81 3000
```

4. Test procedure:

A raw HTTP GET request was constructed using printf. The request was piped to Netcat (nc), which established a TCP connection to the Juice Shop server on port 3000.

5. Conclusion

The Netcat test was successful. A manually constructed HTTP GET request generated using printf was transmitted to the OWASP Juice Shop application, and the server returned an HTTP response.

The test confirms that the Juice Shop HTTP service was accessible on:

192.168.18.65:80/TCP

The screenshot below depicts all the information that was obtained from the terminal:

```
kali@kali: ~  
Session Actions Edit View Help  
  
(kali@kali)-[~]  
$ printf "GET / HTTP/1.1\r\nHost: 192.168.18.81:80\r\nConnection: close\r\n\r\n" | nc 192.168.18.81 3000  
  
HTTP/1.1 200 OK  
Access-Control-Allow-Origin: *  
X-Content-Type-Options: nosniff  
X-Frame-Options: SAMEORIGIN  
Feature-Policy: payment 'self'  
X-Recruiting: /#/jobs  
Accept-Ranges: bytes  
Cache-Control: public, max-age=0  
Last-Modified: Tue, 18 Aug 2026 16:35:48 GMT  
ETag: W/"26d0-1a015baa605"  
Content-Type: text/html; charset=UTF-8  
Content-Length: 9936  
Vary: Accept-Encoding  
Date: Tue, 18 Aug 2026 17:17:46 GMT  
Connection: close  
  
~ Copyright (c) 2014-2026 Bjoern Kimminich & the OWASP Juice Shop contributors.  
~ SPDX-License-Identifier: MIT  
→  
  
<!doctype html>  
<html lang="en" data-beasties-container>  
<head>  
  <meta charset="utf-8">  
  <title>OWASP Juice Shop</title>  
  <meta name="description" content="Probably the most modern and sophisticated insecure web application">  
  <meta name="viewport" content="width=device-width, initial-scale=1">  
  <link rel="preconnect" href="https://fonts.googleapis.com">  
  <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
```