

# Creating a Program from Start to Finish

Brandon Reyes

Colorado School of Mines

# Outline

## Introduction

## Coding the Matrix-Vector Product

- Creating a Module

- Coding the A vector

- Coding the B matrix

- Serial Matrix-Vector Multiplication

- Vectorized Matrix-Vector Multiplication

## Organizing our code

- Creating the main file

- Creating the makefile

- The readme file

## Running our Program

## Turning in Assignments

# Introduction

- ▶ Objective: Create a program that computes a matrix vector product.
- ▶ To begin, we will first establish the "theory" of the problem.

$$\begin{bmatrix} b_{11} & b_{12} & b_{13} & b_{14} \\ b_{21} & b_{22} & b_{23} & b_{24} \\ b_{31} & b_{32} & b_{33} & b_{34} \\ b_{41} & b_{42} & b_{43} & b_{44} \end{bmatrix} \begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ a_4 \end{bmatrix} = \begin{bmatrix} c_1 \\ c_2 \\ c_3 \\ c_4 \end{bmatrix}$$

- ▶ Where the  $i - j^{th}$  entry of matrix B is  $1.5*i*j$  and the  $i^{th}$  entry of vector A is  $.5*i$ .

# Creating a Module

```
module matrix_module
contains

    !Constructs an N by 1 vector A
    subroutine A_vec(N,A)
        .
        .
        .
    end subroutine A_vec

    !Constructs the B matrix for a given N and M
    function B_mat(M,N)
        .
        .
        .
    end function B_mat

    !computes the vector C serially
    subroutine serial_mult(A,B,C)
        .
        .
        .
    end subroutine serial_mult

    !Vectorized form of matrix vector multiplication
    subroutine vec_mult(A,B,C)
        .
        .
        .
    end subroutine vec_mult

end module matrix_module
```

## Coding the A vector

```
!Constructs an N by 1 vector A
subroutine A_vec(N,A)
  Implicit none
  !Declaring Variables
  integer, parameter :: mykind = selected_real_kind(16,300)
  real(kind=mykind), allocatable, dimension(:), intent(out) :: A
  integer, intent(in) :: N
  integer :: i

  !Allocating our vector of length N
  Allocate(A(N))

  !Filling in the A matrix, where the i th entry is .5*i
  do i = 1,N
    A(i) = real(.5,mykind)*real(i,mykind)
  end do

end subroutine A_vec
```

# Coding the B matrix

```
!Constructs the B matrix for a given N
function B_mat(M,N)
  implicit none
  !Declaring Variables
  integer, parameter :: mykind = selected_real_kind(16,300)
  real(kind=mykind), allocatable, dimension(:,:) :: B_mat
  integer,intent(in) :: M,N
  integer :: i,j

  !Allocating our N by N matrix
  Allocate(B_mat(M,N))

  !Filling in the B matrix, where the i-j th entry is 1.5*i*j
  do i = 1,M
    do j=1,N
      B_mat(i,j) = real(1.5,mykind)*real(i,mykind)*real(j,mykind)
    end do
  end do

end function B_mat
```

# Serial Matrix-Vector Multiplication

```
!computes the vector C serially
subroutine serial_mult(A,B,C)
  implicit none
  !Declaring our Variables
  integer, parameter :: mykind = selected_real_kind(16,300)
  real(kind=mykind), allocatable, dimension(:,,:), intent(in) :: B
  real(kind=mykind), allocatable, dimension(:), intent(in) :: A
  real(kind=mykind), allocatable, dimension(:), intent(out) :: C
  real(kind=mykind) :: vec_sum
  integer :: i,j,A_row,B_row,B_col

  !Obtaining the dimensions of A
  A_row = size(A)

  !Obtaining the dimensions of B
  B_row = size(B(:,1))
  B_col = size(B(1,:))

  !Allocating our C vector which is the matrix B times the vector A
  ALLOCATE(C(A_row))

  !computing the vector C in a serial manner
  do i= 1,B_row
    vec_sum = 0
    do j = 1,B_col
      vec_sum = vec_sum + B(i,j)*A(j)
    end do
    C(i) = vec_sum
  end do

end subroutine serial_mult
```

# Vectorized Matrix-Vector Multiplication

```
!Vectorized form of matrix vector multiplication
subroutine vec_mult(A,B,C)
  implicit none
  !Declaring our Variables
  integer, parameter :: mykind = selected_real_kind(16,300)
  real(kind=mykind),allocatable, dimension(:,,:),intent(in) :: B
  real(kind=mykind),allocatable, dimension(:,), intent(in) :: A
  real(kind=mykind),allocatable, dimension(:,), intent(out) :: C
  integer :: i,A_row,B_row,B_col

  !Obtaining the dimensions of A
  A_row = size(A)

  !Obtaining the dimensions of B
  B_row = size(B(:,1))
  B_col = size(B(1,:))

  !Allocating our C vector which is the matrix B times the vector A
  ALLOCATE(C(A_row))

  !computing the vectorx C using vectors
  do i = 1,B_row
    C(i) = sum(B(i,:)*A)
  end do

end subroutine vec_mult
```



# Outline of the Main File

- ▶ Read in values  $M$  and  $N$  from input.txt file to specify the  $M$  by  $N$  matrix  $B$  and  $N$  by  $1$  vector  $A$ .
- ▶ Call and time the serial matrix vector product .
- ▶ Call and time the vectorized version of the matrix vector product.
- ▶ Print the matrix  $B$  and vector  $A$  if  $N$  is less than  $5$  for the serial version of the product.
- ▶ Print the vector  $C$  if  $N$  is less than  $5$  for both versions of the product.

# Creating the main file

```
program main
  use matrix_module    !allows us to use the module we created
  implicit none

  !Declaring our variables
  integer, parameter :: mykind = selected_real_kind(16,300)
  real(kind=mykind), allocatable, dimension(:,:) :: B
  real(kind=mykind), allocatable, dimension(:) :: A,C
  integer :: N,M,i
  real :: time1,time2

  !opening our input file
  OPEN(UNIT=13,file='input.txt')

  !Reading in the number of rows of our matrix
  READ(13,*) M

  !setting the number of columns of our matrix and the number of rows of vector A
  READ(13,*) N

  !closing the file because it is not needed anymore
  close(13)

  !constructing the N by 1 A vector
  call A_vec(N,A)

  !constructing the M by N B matrix
  B = B_mat(M,N)
```

# Creating the main file

```
!printing the vector A and matrix B if N < 5
if(N < 5)then
  print *, ''
  print *, 'Matrix B : '
  print *, ''
  do i = 1,M
    print *, B(i,:)
  end do
  print *, ''
  print *, 'Vector A : '
  print *, ''
  do i = 1,N
    print *, A(i)
  end do
  print *, ''
end if

!Computing C serially
call CPU_TIME(time1)
call serial_mult(A,B,C)
call CPU_TIME(time2)

!creating a space for asthetics
if(N > 4)then
  print *, ''
end if

print *, 'Elapsed time for serial version : ', time2 - time1
print *, ''
```

# Creating the main file

```
if(N < 5)then
  !printing out C from the serial matrix multiplication
  print *, 'Vector C from serial version : '
  print *, ''
  do i = 1,N
    print *, C(i)
  end do
  print *, ''
end if

!Deallocating C so we can use it again for vector matrix multiplication
DEALLOCATE(C)

!Computing C using vectors
call CPU_TIME(time1)
call vec_mult(A,B,C)
call CPU_TIME(time2)
print*, 'Elapsed time for vectorized version : ', time2 - time1
print*, ''

if(N < 5)then
  !printing out C from the vector matrix multiplication
  print *, 'Vector C from vector version : '
  print *, ''
  do i = 1,N
    print *, C(i)
  end do
  print *, ''
end if

!Freeing the memory for all allocatables
DEALLOCATE(C,A,B)

end program main
```

## Creating the makefile

```
FC90 = gfortran
vector_files = matrix_module.f90 main.f90

all:main_exe

main_exe:$(vector_files)
    $(FC90) $(vector_files) -o      $@

clean:
    rm      *_exe    *.mod *~
```

# The readme.txt file

This program creates an  $M$  by  $N$  matrix  $B$  (where the  $i$ - $j$  th entry is  $1.5*i*j$ ) and multiplies it by a  $N$  by 1 vector  $A$  (where the  $i$  th entry is  $.5*i$ ). The result is then stored in a vector  $C$ . Note that this program computes this matrix vector multiplication by first doing it in a serial manner and then in a vectorized way.

To compile the program :

type :

```
make main_exe
```

then press enter to create our executable

To run the program :

```
./main_exe
```

To run the program and save to a.out :

```
./main_exe > a.out
```

# Results

Now that we have coded everything, let's compile and run our code.

# Turning in Assignments

- ▶ Make sure you have all of your essential files
  - ▶ For our program the essential files are: input.txt , main.f90, makefile, matrix\_module.f90, and readme.txt .
- ▶ Do not leave executable files (\_exe) or compiled modules (.mod).
- ▶ Create a zip file of your final turn in folder
  - ▶ If all of our files are in the directory all\_mult, we can create a zip file using the following command:  
tar -czvf all\_mult.tar.gz all\_mult
- ▶ Report
  - ▶ The report must be very well written, assume that your audience is someone who has little to no experience with coding or the assignment at hand.
  - ▶ Make sure all your code is well commented. I will go through the code, so make it readable.
  - ▶ At the end of your report, cite who helped you.
  - ▶ If you would like to see an example report come visit me during my office hours (4-5pm everyday).