

The schl package^{*}

Tassos Tsesmetzis

ttsesmetzis@gmail.com

July, 2019

Abstract

schl is a \LaTeX package that provides commands and environments suitable for document types that appear in a classroom environment. It's development is based on the Greek school system, but it may be useful in other contexts as well.

1 Introduction

Worksheets and tests are common document types in a classroom. schl package comes with macros that facilitate the creation of these documents. It has list environments for questions, exercises and tasks. Other environments of the package can be used for tickable or multiple choice answers. There are also commands for typesetting solutions, hints and answers to exercises.

Furthermore, you can set the name of the teacher, subject, grade, headmaster, school, date, school year and use these to print school's logo or information about an exam. schl has commands to typeset headers for each document type, a macro for typing the points of an exercise and two commands for blank space. There is also a macro for typesetting a wish for good luck!

schl is based on the Greek school practice. It redefines in Greek the common math macros \sin , \cos , \tan , \cot and \gcd . Also, it provides the math operator lcm for the least common multiple of integers. Another characteristic of Greek school mathematics, is that \lim operator appears in display mode. schl offers a macro for this.

By default, schl prints all macros in Greek but this can be changed to any other language. This can be done by redefining package's internal macros.

schl loads the packages fontspec, enumitem, mdframed and amsmath. It is written for \LaTeX , but can be used by any system that supports fontspec.

^{*}This document corresponds to schl v0.1, dated 2019/06/15.

2 Macros

2.1 Mathematics

`\sin` These macros redefine in Greek the corresponding trigonometric operators `\sin`, `\cos`, `\tan`
`\cos` and `\cot`.
`\tan`
`\cot`

```

1 \renewcommand{\sin}{\mathop{%
2   \mathgroup\symgropoperators \eta\mu}\nolimits}
3 \renewcommand{\cos}{\mathop{%
4   \mathgroup\symgropoperators \sigma\upsilon\pi\alpha\nu}\nolimits}
5 \renewcommand{\tan}{\mathop{%
6   \mathgroup\symgropoperators \varphi}\nolimits}
7 \renewcommand{\cot}{\mathop{%
8   \mathgroup\symgropoperators \sigma\phi}\nolimits}

```

`gropoperators` is the font used to typeset the functions.

`\gcd` `\gcd` and `\lcm` provide the arithmetic operators for greatest common divisor and
`\lcm` least common multiple in Greek. `\gcd` is redefined as

```

9 \renewcommand{\gcd}{\mathop{%
10  \mathgroup\symgropoperators \text{MK}\Delta}\nolimits}

```

On the other hand, for `\lcm` we have

```

11 \DeclareMathOperator{\lcm}{\text{EK}\Pi}

```

`\limdisplay` Command `\limdisplay {<text>}` prints `<text>` under `\lim`

```

12 \newcommand{\limdisplay}[1]{\displaystyle\lim_{#1}}

```

2.2 Blank space

`\lowerdots` Usually, we need to designate blank space in a document. `schl` package has two
`\blankspace` commands for this. The first one `\lowerdots [<length>]{<number>}`, prints `<number>`
dotted. Optional argument `<length>` sets the deviation from base line. It's default value is
`-0.3ex`.

```

13 \newcommand\lowerdots[2][-0.3ex]{%
14   \begingroup
15   \lccode`m=`.\relax
16   \raisebox{#1}{\lowercase\expandafter{\romannumeral\number\number#2 000}}%
17   \endgroup
18 }

```

`\blankspace [<length>]{<linelength>}` prints a line with length `<linelength>`. The
optional argument is the deviation from the base line and it's default value is `-0.3ex`.
`\schl@rulethickness` is the default thickness for all `\blankspace` lines.

```

19 \newcommand\blankspace[2][-0.3ex]{%
20   \raisebox{#1}{\rule{#2}{\schl@rulethickness}}
21 }

```

2.3 Lists

schl package defines six types of lists. These are question, exercise, schltask, multichoice, tickchoice and truefalse. tickchoice comes also with a starred version tickchoice*. All of them depend on the package enumitem.

question These environments are enumerate-like lists. List's \item is of the form $\langle type \rangle$
exercise $\langle counter \rangle$, where type is \question@term for question, \exercise@term for exercise
schltask and \task@term for schltask. $\langle counter \rangle$ is the internal counter of the environment.

```

22 \newlist{question}{enumerate}{1}
23 \setlist*[question]{%
24   align=left,
25   label=\normalsize\bf \question@term\ \arabic*,
26   wide,
27   leftmargin=0pt,
28   labelindent=0pt
29 }

30 \newlist{exercise}{enumerate}{1}
31 \setlist*[exercise]{%
32   align=left,
33   label=\normalsize\bf \exercise@term\ \arabic*,
34   wide,
35   leftmargin=0pt,
36   labelindent=0pt
37 }

38 \newlist{schltask}{enumerate}{1}
39 \setlist*[schltask]{%
40   align=left,
41   label=\normalsize\bf\letterspace{\defaultletterspace}\task@term\ \Alph*,
42   wide,
43   leftmargin=0pt,
44   labelindent=0pt
45 }
```

\letterspace The macro \letterspace{ $\langle number \rangle$ } is used to set the horizontal space of adjacent characters in a word. It is based on the \addfontfeature macro from the package fontspec. The argument $\langle number \rangle$ is a percentage of the font size.

```

46 \def\letterspace#1{\addfontfeature{LetterSpace=#1}}
```

multichoice The multichoice environment is used to typeset multiple choice answers.

```

47 \newlist{multichoice}{enumerate*}{1}
48 \setlist*[multichoice]{
49   labelindent=\parindent,
50   label=\Alph*,
51   itemjoin=\hspace{\fill},
52   before=\hspace{\fill},
53   after=\hspace{\fill}
54 }
```

tickchoice The environments tickchoice and tickchoice* are variants of the itemize list.
tickchoice*

For both cases, each item is preceded by a square. tickchoice stacks items vertically,

```
55 \newlist{tickchoice}{itemize}{1}
56 \setlist[tickchoice]{labelindent=\parindent,label={\large$\square$}}
```

while tickchoice* stacks them horizontally.

```
57 \newlist{tickchoice*}{itemize*}{1}
58 \setlist*[tickchoice*]{
59   labelindent=\parindent,
60   label={\large$\square$},
61   itemjoin=\hspace{\fill},
62   before=\hspace{\fill},
63   after=\hspace{\fill}
64 }
```

truefalse truefalse is a variant of the enumerate environment. Each \item is divided in two parts. The first part is the text that follows the \item macro. The second part is a \parbox that prints \trueabbr@term and \falseabbr@term.

```
65 \newlist{truefalse}{enumerate}{1}
66 \setlist[truefalse]{label={\bf \arabic*},%
67   before*=%
68     \let\defaultitem\item%      Save the standard definition of \item in a macro.
69     \toggletrue{first}%        Set the first toggle with initial value true.
70     \def\item{%
71       \iftoggle{first}{%
72         \togglefalse{first}%    Set the first toggle to take the value false.
73         \defaultitem\begin{minipage}[t]{0.8\linewidth minus \truefalselength}%
74       }{%
75         \end{minipage}\hfill\truefalselabel\defaultitem\begin{minipage}[t]{0.8\linewidth minus
76       }
77     }% new, temporary definition of \item
78   },
79   after*=%    This takes care of adding the fill for the final item on
80   %          the list and just makes sure that \item is reset to its standard definition
81   \end{minipage}\hfill\truefalselabel% fill for final item in list
82   \let\item\defaultitem% restore standard definition of \item
83 }%
84 }
```

matchingque The macro \matchingque{<CSV>}{<CSV>} is used to typeset matching questions. <CSV> are comma separated values. The <CSV>s of the first argument are the parts of the matching questions that will be print in the left column. Similarly, the <CSV> of the second argument are going to be printed on the right column of the matching questions.

```
85 \newcommand\matchingque[3][300pt]{%
86   \begin{center}
87     \parbox[c]{#1}{
88       \parbox[c]{\leftmatchwidth}{%
89         \begin{leftmatching}
90           \@for\tmp:=#2%
91           \do{%
92             \item \tmp
```

```

93         }
94         \end{leftmatching}
95     }\hfill%
96     \parbox[c]{\rightmatchwidth}{%
97         \begin{rightmatching}
98             \@for\tmp:=#3%
99             \do{%
100                 \item \tmp
101             }
102         \end{rightmatching}
103     }
104 }
105 \end{center}
106 }

```

`leftmatching` Environments `leftmatching` and `rightmatching` are used to typeset each column
`rightmatching` in `\matchingque`.

```

107 \newlist{leftmatching}{enumerate}{1}
108 \newlist{rightmatching}{enumerate}{1}
109 \setlist*[leftmatching]{label=\bf\Alph*.}
110 \setlist*[rightmatching]{label=\bf\arabic*.}

```

2.4 Answers, solutions and hints

`\answer` Macro `\answer{<text>}` prints (`\answerabbr@term \meta{text}`) at the right end of the current line.

```

111 \newcommand\answer[1]{%
112   \hfill{\footnotesize (\answerabbr@term: #1)}
113 }

```

`\solution` Macro `\solution{<text>}` is used to typeset the solution of an exercise.

```

114 \newcommand\solution[1]{%
115   \par\noindent\phantom{.}\hfill\textbf{\solution@term}\hfill\phantom{.}\par%
116   \noindent #1
117 }

```

`\hint` `schl` provides the macro `\hint{<text>}` for typesetting exercise hints.

```

118 \newcommand\hint[1]{%
119   \par{\scriptsize\noindent\textbf{\hint@term:} #1}%
120 }

```

`\deadline` A feature of homework assignments is a deadline date. `\deadline{<date>}` prints `\deadline@term` followed by argument `<date>`.

```

121 \newcommand\deadline[1]{%
122   \noindent{\bf\normalsize\deadline@term}: #1}
123 }

```

2.5 Titles and headers

`\heading` Common document types in a school environment are the worksheet, various tests

and final written exams. The macro `\heading{<text>}` gives a generic header for all these documents.

```

124 \newcommand\heading[1]{%
125   \begin{center}
126     {\bf\large #1}
127   \end{center}
128 }

\worksheettitle      Macro \worksheettitle{<text>} sets the title of a worksheet. It appends <text> to
\worksheet@term.

129 \newcommand\worksheettitle[1]{%
130   \heading{\worksheet@term\ #1}
131 }

\examtitle           \examtitle[<text>]{<text>} is used to set the title of tests. the optional argument
has the default value \termtest@term.

132 \newcommand\examtitle[2][\termtest@term]{%
133   \heading{#1 #2}
134 }

\finalexamheader     Titles for end year exams have a standardized form in Greek schools. \exams@term
is followed by information about the exam, then comes \period@term with the exam
period after it. \finalexamheader{<info>}{<period>} is used for these cases.

135 \newcommand\finalexamheader[2]{%
136   \heading{\letterspace{\defaultletterspace} #1 \exams@term\[\[0.5ex] \period@term\ #2}
137 }

\schl@framedbox      \schl@framedbox{<text>} prints <text> in a centered frame box. It is used by
\theorypart and \exercisepart.

138 \newcommand\schl@framedbox[1]{%
139   \begin{center}
140     \fbox{\large{\bf\letterspace{\defaultletterspace} #1} }%
141   \end{center}
142 }

\theorypart          Sometimes theory and exercise sections constitute a written test. Macros \theorypart
\exercisepart        and \exercisepart print headers for those parts.

143 \newcommand\theorypart{%
144   \schl@framedbox{\theoryheader@term\!}
145 }

and

146 \newcommand\exercisepart{%
147   \schl@framedbox{\exercisepart@term\!}
148 }

```

2.6 School information

The macros `\school{<text>}`, `\headmaster{<name>}`, `\teacher{<name>}`, `\subject{<text>}`, `\grade{<text>}`, `\schoolyear{<year>}` and `\schldate{<date>}` define and set the value of internal macros.

```

\school
\headmaster
\teacher
\subject
\grade
\schoolyear
\schldate

```

```

149 \newcommand\school[1]{\def\schl@school{#1}}
150 \newcommand\headmaster[1]{\def\schl@headmaster{#1}}
151 \newcommand\teacher[1]{\def\schl@teacher{#1}}
152 \newcommand\subject[1]{\def\schl@subject{#1}}
153 \newcommand\grade[1]{\def\schl@grade{#1}}
154 \newcommand\schoolyear[1]{\def\schl@schoolyear{#1}}
155 \newcommand\schldate[1]{\def\schl@schldate{#1}}

\authorityi      In a similar vein, \authorityi{<text>}, \authorityii{<text>} and \authorityiii{<text>}
\authorityii     define the internal macros \schl@authorityi, \schl@authorityii and \schl@authorityiii.
\authorityiii    156 \newcommand\authorityi[1]{\def\schl@authorityi{#1}}
                  157 \newcommand\authorityii[1]{\def\schl@authorityii{#1}}
                  158 \newcommand\authorityiii[1]{\def\schl@authorityiii{#1}}

```

2.7 Other macros for tests

\points `\points{<number>}` is used to designate the points of an exercise. `{<number>}` is the number of points for the current exercise.

```

159 \newcommand\points[1]{%
160 \phantom{.}\hfill\textbf{\footnotesize \points@term{#1}\ #1}}
161 }

```

\textfield `\textfield{<text>}{<number>}` prints `<text>` followed by `<number>` dots.

```

162 \newcommand\textfield[2]{%
163 \noindent\normalsize #2:\lowerdots{#1}
164 }

```

\fullname Macro `\textfield` is used by `\fullname{<number>}`. It prints `\fullname@term` with `<number>` dots after it.

```

165 \newcommand\fullname[1][0]{%
166 \textfield{#1}{\fullname@term}
167 }

```

\datefield Similarly, `\datefield{<number>}` prints `\date@term` followed by `<number>` dots.

```

168 \newcommand\datefield[1][0]{%
169 \textfield{#1}{\date@term}
170 }

```

\schoollogo `\schoollogo{<width>}` prints `\schl@school`, `\schl@grade`, `\schl@subject` and `\schl@teacher`. `<width>` is the length of the `\parbox`.

```

171 \def\schoollogo#1{%
172 \parbox[t]{#1}{%
173 \schl@school\\%
174 \schl@grade\\%
175 \schl@subject\\%
176 \schl@teacher
177 }
178 }

```

\authoritylogo `\authoritylogo{<path>}` prints `\sch@authorityi`, `\sch@authorityii`, `\sch@authorityiii` and `\schl@school`. Argument `<path>` is a path to a picture.

```

179 \newcommand\authoritylogo[1]{%
180   \noindent\parbox[t]{40ex}{%
181     \centering%
182
183     \vspace{1ex}
184
185     \includegraphics{#1}
186
187     \vspace{\lineskip}
188
189     {\bf\letterspace{\defaultletterspace}\schl@authorityi}
190
191     \vspace{8\lineskip}
192
193     {\scriptsize\letterspace{\defaultletterspace}\schl@authorityii}
194
195     \vspace{2\lineskip}
196
197     {\footnotesize\letterspace{\defaultletterspace}\schl@authorityiii}
198
199     \vspace{8\lineskip}
200
201     {\small\letterspace{\defaultletterspace}\schl@school}
202   }
203 }

\examdetails Written exam documents contain information about the period of the exam, subject,
\examdetailsii grade, writer of the test, supervisors of the exam and date. schl package has the macros
\examdetails{<text>} and \examdetailsii for printing this information. Argument
<text> of \examdetails is the exam period.

204 \newcommand\examdetails[2][3pt]{%
205   \parbox[t]{20em}{
206     \begin{mdframed}[linewidth=#1]
207       \normalsize%
208       {%
209         \bf\letterspace{\defaultletterspace}%
210         \schoolyearabbr@term:\hspace{3pt}\schl@schoolyear\\[1ex]
211         \examperiod@term #2\\[1.0ex]
212         \textbf{\grade@term:}\hspace{3pt}\schl@grade\\[1.0ex]
213         \textbf{\subject@term:}\hspace{3pt}\schl@subject \\[1.0ex]
214         \textbf{\testwriter@term:}\hspace{3pt}\schl@teacher\\[1.0ex]
215         \textbf{\testsupervisor@term:}\hspace{3pt}\schl@teacher\\[1.0ex]
216         \textbf{\date@term:}\hspace{3pt}\schl@schldate
217       }
218     }
219   }

and

220 \newcommand\examdetailsii{%
221   \parbox[t]{330pt}{%

```



```

222 \begin{center}\underline{\bf\letterspace{\defaultletterspace}\schoolyear@term\ \schl@schoo
223 \begin{tabular}{|c|p{60pt}|p{40pt}|p{60pt}|}
224 \hline
225 {\bf\letterspace{\defaultletterspace}\lastname@term:} & \multicolumn{3}{|c|}{ } \\
226 \hline
227 {\bf\letterspace{\defaultletterspace}\name@term:} & \multicolumn{3}{|c|}{ } \\
228 \hline
229 {\bf\letterspace{\defaultletterspace}\examnoabbr@term:} & & {\bf\letterspace{\defaultlett
230 & \schl@grade \\
231 \hline
232 {\bf\letterspace{\defaultletterspace}\MakeUppercase{\subject@term:} & \multicolumn{3}{|c|
233 \hline
234 {\bf\letterspace{\defaultletterspace}\MakeUppercase{\date@term:} & \schl@schldate
235 & {\bf\letterspace{\defaultletterspace}\time@term:} & \schl@
236 \hline
237 \end{tabular}
238 }
239 }

```

\signatures Some types of written tests end with the names of the headmaster and the teacher(s) followed by handwritten signatures. Macro `\signer{⟨name⟩}` accepts the name of a signer. `\signatures[⟨role⟩]{⟨signer(s)⟩}` prints the name(s) of the *⟨signer(s)⟩* under a line with the *⟨role⟩* of the signer(s). `\signatureslength` is the length of the `\signatures` block.

```

240 \newcommand\signer[1]{\par #1}
241 \newcommand\signatures[2][\headmaster@term]{%
242 \parbox[t]{\signatureslength}{%
243 \setlength \baselineskip{\signaturelineskip}
244 \begin{center}
245 #1 #2
246 \end{center}
247 }
248 }

```

\wish `\wish` prints `\schl@wish`, a default wish for tests.

```

249 \newcommand\wish{%
250 \begin{center}
251 {\LARGE\bf \schl@wish}
252 \end{center}
253 }

```