

Subcortical brain structure segmentation using FCNNs

Stavros Tsogkas¹, Mahsa Shakeri^{2,3}, Enzo Ferrante¹, Sarah Lippe^{3,4}, Samuel Kadoury^{2,3}, Nikos Paragios¹, Iasonas Kokkinos¹



CentraleSupélec

1

POLYTECHNIQUE
MONTRÉAL



2




CHU Sainte-Justine

3


Université de Montréal 

4


Diseases and their relation to subcortical structures



Alzheimer's:
structure degeneration




Schizophrenia: volume abnormalities
[Shenton M.E. et al., Psychiatry Res. 2002]



Tumors: avoid radiation on sensitive regions
[Hoehn D. et al., Journal of Medical Cases, 2012]


3D Segmentation



Our results

Groundtruth

Why automatic segmentation?



Visualization and inspection




*No need for manual annotation
(time consuming, need experts,
limited reproducibility)*

Non-invasive diagnosis and treatment

Segmentation using MRI



- Intensity is not enough
- Spatial arrangement patterns




Goal


- Classify *every pixel* as one of L possible structures.
- Exploit context.
- Enforce volumetric homogeneity.

Fully convolutional neural networks (FCNNs)
+ Graphical models (MRFs)

Outline




Semantic segmentation of MRI slices




[1] Long et al., CVPR 2015

Our CNN architecture



- 16 layers including max-pooling and dropout.
- Compact architecture ($\sim 4\text{GB GPU RAM}$).

MRF for volume homogeneity



$$\mathcal{S}^* = \operatorname{argmin} E(\mathcal{S}) = \sum_{i \in \mathcal{V}} V_i(l_i) + \lambda \sum_{(i,j) \in \mathcal{E}} V_{ij}(l_i, l_j)$$

↓

$f(P_i^{\text{CNN}}(l_i))$


↓

$d(I_i, I_j)[l_i \neq l_j]$

Experiments

- Two datasets:
 - Internet Brain Segmentation Repository (IBSR).
 - Roland Epilepsy (RE).
- Train CNN on 2D slices from *axial* view.
- Data augmentation: ~100K training images.

Results (Dice coefficient)



Dice: 1 = perfect overlap with ground truth.

Average Dice (IBSR)

- Thalamus: 0.87
- Putamen: 0.83
- Caudate: 0.78
- Pallidum: 0.75

Comparison with other methods

Dice coefficient


	Freesurfer ¹	FSL ²	Ours
IBSR - Thalamus	0.86	0.85	0.87
IBSR - Caudate	0.82	0.68	0.78
IBSR - Putamen	0.81	0.81	0.83
IBSR - Pallidum	0.71	0.73	0.75
RE - Putamen	0.74	0.88	0.89
Running time (1 vol.)	~hours	~minutes	~1 minute

[1] Fischl et al., Neuron 2002.

[2] Patenaude et al., NeuroImage 2011.


The type of unaries matters

Dice coefficient (IBSR dataset)




1. Thalamus left
2. Caudate left
3. Putamen left
4. Pallidum left
5. Thalamus right
6. Caudate right
7. Putamen right
8. Pallidum right


The type of unaries matters



MRF removes spurious responses




CNN




CNN+MRF


Limitations and future directions



Left hemisphere Right hemisphere



Does not work for sagittal view
because of symmetry




3D CNNs

Summary

- FCNNs + MRFs:
 - accurate, *dense* labelling using 2D image data.
 - volumetric homogeneity
- Efficient segmentation of 3D volumes: (*~1 min*)
- No need for expensive GPUs (*~4GB GPU RAM*)

Code, CNN probability maps:
<https://github.com/tsogkas/brainseg>

IBSR dataset: Hausdorff distance



1. Thalamus left
2. Caudate left
3. Putamen left
4. Pallidum left
5. Thalamus right
6. Caudate right
7. Putamen right
8. Pallidum right




Random forest unaries



CNN unaries

IBSR dataset: contour mean distance



1. Thalamus left
2. Caudate left
3. Putamen left
4. Pallidum left
5. Thalamus right
6. Caudate right
7. Putamen right
8. Pallidum right




Random forest unaries




CNN unaries

RE dataset: HD and CMD

Hausdorff distance



Contour mean distance



Random forest unaries



CNN unaries