

Курсор, който изпраща на променливи полетата си

```
CREATE OR REPLACE PROCEDURE Res_Empl(v_IME VARCHAR2)
IS
CURSOR CUR_SELECT -- CUR_SELECT име на курсор
IS
SELECT R.REZ_DATE,S.IME_SLUJITEL,R.PRESTOI, R1.ROOM_NUM,
C.CL_NAME
FROM REZERVACIQ R
JOIN SLUJITEL S ON R.SLUJITEL_SLUJITEL_ID=S.SLUJITEL_ID
JOIN ROOMS R1 ON R.ROOMS_ROOM_ID=R1.ROOM_ID
JOIN CLIENT C ON R.CLIENT_CL_ID=C.CL_ID
WHERE S.IME_SLUJITEL = v_IME;

C_R_DATE DATE; -- декларация на променливи
C_S_IME VARCHAR2(50);
C_PR NUMBER;
C_ROOM ROOMS.ROOM_NUM%TYPE;
C_CL_NAME CLIENT.CL_NAME%TYPE;

BEGIN -- начало на процедурата
OPEN CUR_SELECT;
LOOP FETCH CUR_SELECT INTO C_R_DATE, C_S_IME, C_PR, C_ROOM,
C_CL_NAME
EXIT WHEN CUR_SELECT%NOTFOUND;
    DBMS_OUTPUT.PUT_LINE('RESERVATION Date=>' || ' ' ||
    C_R_DATE || ' ' || 'NAME EMPLOYEE=>' || ' ' || C_S_IME || ' ' ||
    'PERIOD=>' || ' ' || C_PR || ' ' || 'Room number=>' || ' ' || C_ROOM || ' ' ||
    'Client=>' || ' ' || C_CL_NAME);
END LOOP;
CLOSE CUR_SELECT; -- затваряне на курсора
END Res_Empl;
```

Пример за извикване - EXEC Res_Empl ('&Employee_name');

```

create or replace PROCEDURE BOOK_AUTHOR
    (V_NAME_A AUTHOR.NAME_OF_THE_AUTHOR%TYPE)
IS
BEGIN --начало процедура
DECLARE
CURSOR BK_AUT IS --cursor name
select b.NAME_OF_THE_BOOK from BOOK b
join AUTHOR a on (b.ID_AUTHOR_OF_THE_BOOK=a.AUTH_ID)
where a.NAME_OF_THE_AUTHOR = V_NAME_A;

BEGIN
FOR AUT_RECORD IN BK_AUT --recordname
LOOP
DBMS_OUTPUT.PUT_LINE(AUT_RECORD.NAME_OF_THE_BOOK);
END LOOP;
END;
END; --на процедурата

```

Пример за извикване:

```
EXEC BOOK_AUTHOR('&Book_author');
```

Процедура с курсор към търсене на книги по ключови думи:

```
create or replace PROCEDURE BOOK_KEYWORDS(v_KEYWORDS varchar2)
IS
KEYWORDS_new varchar2(500);
BEGIN -- наало процедура
KEYWORDS_new:='%'||v_KEYWORDS||'%';
DECLARE
CURSOR BK_KEY IS
select b.NAME_OF_THE_BOOK
from BOOK b
where b.NAME_OF_THE_BOOK LIKE KEYWORDS_new;
BEGIN
FOR BK_RECORD IN BK_KEY
LOOP
DBMS_OUTPUT.PUT_LINE(BK_RECORD.NAME_OF_THE_BOOK);
END LOOP;
END;
END; --процедура
```

Пример за извикване:

```
EXEC BOOK_KEYWORDS('&Keywords');
```