CTF Agent Benchmarking: Assignment 4 Report

Team Members: Parker Cummins, Lalit Lakamsani, Jenessa Lu, Vamsee Vusuwandla

1. Benchmark and Challenge Selection

We used CTFTiny and selected three file-based reversing challenges: rev-checker, rev-baby-mult, and rev-whataxor. We chose file-based reversing because these challenges need no network service, so we could test the agent loop and sandbox without Compose setup. They also form a difficulty ladder: Python source, then raw machine code, then an ELF binary with an obfuscated flag. We thought this would be a good way of gradually testing the agent.

During development we used challenges from NYU CTF Bench: 2016q-rev-rock and 2015q-cry-bricks_of_gold. Those records are kept separate from the scored results (evidence/development/). No team member had solved the selected challenges before.

2. Architecture

We built a new multi-step CTF-solving agent rather than reusing Assignment 3. The Python agent sends an observation and function schemas to Ollama Cloud, receives a tool request, dispatches it, appends the returned observation, continues until a flag is verified, the agent requests to stop, or an execution budget is exhausted.

We used gpt-oss:120b through Ollama's hosted API. The Duke AI Gateway unfortunately did not work, and the HTTP requests kept running out of time and never got back. This happened when using the VPN, and when on-campus using the Duke wifi. All scored attempts used one frozen configuration: 15 steps and 300 seconds per attempt, enforced in code.

Component	Role
`benchmark_runner.py`	Local runner. Loads each challenge with nyuctf, stages only contestant files into a fresh workspace, starts a new solver container per attempt, and writes one record per attempt.
`agent_core.py`	Agent loop. Sends the conversation to the model, runs the chosen tool, appends the result, and repeats until the agent solves, stops, or hits a limit. Logs every event to a JSONL trace.
`controller.py`	Dispatches tool requests, applies argument and path validation to supported file tools, and returns structured execution results.
`solver_runtime.py`	Docker sandbox with no network, a read-only root, all capabilities dropped, no-new-privileges, a non-root user, and 64 PIDs / 512 MB / 1 CPU limits. Files are read-only at /challenge; /work is the executable scratch space.
`flag_verifier.py`	Holds the expected flag on the host and compares candidates with hmac.compare_digest. The model sees only {verified: true/false}, and every submission is logged.

The frozen evaluation configuration exposed five tools: run_command, read_file, write_file, submit_flag, and finish. The post-evaluation configuration added inspect_binary and disassemble_binary after observing inefficient binary analysis, excessive disassembly output, and repeated tool errors during development testing. Most tool errors return to the model as structured results. In the scored configuration, unsupported tool names caused the run to terminate.

We checked the controls inside the container: DNS lookups fail, the Docker socket is absent, and id shows the unprivileged user (evidence/isolation_test.md). challenge.json, flags, and the benchmark repository are never mounted into the solver, and the API key stays in the host environment.

3. Problems Encountered

1. **Model availability**
   A 402 Payment Required ended our first CTFTiny attempt (395149e7). This is because Ollama changed their free model policy on November 9th, 2025 at 5:40pm EST. HTTP 500 errors from Ollama ended 4 of the 9 scored attempts, even after three retries each.
2. **Sandbox rules the agent couldn't see**
   In Rock run 0c6139eb, the agent attempted to execute /challenge/rock, modify its permissions on the read-only challenge mount, and execute a copy from the non-executable /tmp directory. It used all 8 steps without ever running the binary.
3. **Workspace permissions**
   The temporary workspace was initially created with 0700 permissions, preventing the unprivileged solver from accessing the mounted challenge files. We corrected this by changing the permissions to 0755. During the affected development run (Bricks, 8a436499), the agent made 11 unsuccessful tool calls before searching for SUID binaries using find / -perm -4000. Although the sandbox restricted the impact, this demonstrated how the agent could pursue unrelated environment-discovery actions rather than solving the challenge.
4. **Invented tool names**
   In whataxor attempt 1 (a27358aa), the model called a nonexistent file tool, and the runner ended the attempt after 1 second.

Before freezing, we added retry logging, an execution-environment section to the prompt, and a 0755 workspace, and we raised the step limit in the development testing from 8 to 15 in accordance with the implementation guidelines.

4. Results (frozen config 7a39bf0, 3 fresh attempts per challenge)

Challenge	Outcomes (1/2/3)	Solves	Success rate	Sample SD	Mean tokens (in / out / total)	Mean time (s)
rev-checker	0 / 1 / 0	1/3	33.3%	57.7 pp	5,022 / 752 / 5,774	15.3
rev-baby-mult	0 / 0 / 0	0/3	0%	0 pp	22,389 / 766 / 23,154	15.6
rev-whataxor	0 / 0 / 0	0/3	0%	0 pp	49,480 / 861 / 50,342	8.3

Attempt status	Count	Attempts
Solved	1	rev-checker 2
Budget exhausted (15 steps)	3	baby-mult 2, whataxor 2 and 3
Model error (HTTP 500 after retries)	4	rev-checker 1 and 3, baby-mult 1 and 3
Invalid tool call	1	whataxor 1

Totals across all 9 attempts:

- 117.5 seconds of wall-clock time
- 62 model calls (77 requests including retries)
- 62 tool calls

- 230,673 input and 7,136 output tokens

Estimated cost: The Ollama dashboard reported $0.03 for 169 requests across development and evaluation activity using gpt-oss:120b. The nine official benchmark attempts accounted for 77 request attempts and 237,809 known tokens. Because the dashboard aggregates usage across runs, the exact cost attributable to the scored evaluation could not be isolated. Our script provides a separate token-based estimate, which should not be interpreted as the measured billing charge.


Models Keys

Model	Requests	Input	Output	Cost
gpt-oss:120b	169	446.2K	18K	$0.03


Last updated 23:02:08 UTC

Pass@k (order-independent): 11.1% at k=1, 22.2% at k=2, and 33.3% at k=3. Solve rate by run was 0%, 33.3%, and 0%.

Overall success rate: 1/9 = 11.1%. We mark the evaluation as “incomplete” because four attempts ended with model API errors and one ended after an invalid tool request. The latter was an agent tool-selection failure rather than an external infrastructure outage. We retained all five attempts in the denominator instead of rerunning them. The latter was an agent tool-selection failure, not an external infrastructure outage. Four were model outages and one was an invalid tool call. We kept them in the denominator rather than rerunning them. Three attempts per challenge is limited evidence, and the SD describes outcome variation, not a confidence interval.



Recorded attempts include model/tool incidents; estimates are descriptive.



5. Trace Analysis

Success: rev-checker (9f1877c1). The agent read checker.py and worked out its four encoding steps. It measured the encoded string (184 bits, so 23 characters), wrote a Python decoder that inverts each step, and submitted a correct flag on its first submission.

Failure: rev-whataxor (dd2c9584). This attempt used 111,183 input tokens, the most of any attempt, and did not solve.

Step	Tool call	Result	Issue
2	`read_file readme.txt`	Hint that the flag is embedded in the binary	Useful
6	`objdump -d … | head -n 200`	200 lines, mostly startup boilerplate	Untargeted dump
8	`objdump -d … | sed -n '200,320p'`	Shows movb $0xc4… byte stores	Key evidence not acted on
11	`grep "<xor_transform>"`	Finds the XOR routine	Good
12–14	`grep "movb" | grep "-0x"`	grep usage error, twice	Repeats a failing command
15	Corrected `grep`	Lists every encoded byte	Out of steps before decoding

The agent found everything it needed but spent its budget on large untargeted output and a repeated error. Input tokens grew quickly because the whole history, including each dump, is re–sent on every call. Attempt 3 (0862ce91) showed the same pattern: it called hexdump and less (neither installed) and never reached main.

rev-baby-mult (5bba734b). The agent turned the byte list into a raw file and disassembled it correctly. Then it tried to execute the raw machine code as a program (Exec format error) and ran out of steps.

6. Changes and Follow-up Checks

Hypothesis. The agent wastes its step budget on untargeted disassembly, repeated failing commands, and invented tool names. The following three changes should get it to the core logic in fewer steps and tokens:

1. Prompt rules for targeted analysis and for not repeating failed commands
2. A recoverable error listing the valid tools, instead of ending the run
3. inspect_binary and disassemble_binary tools

We tested these on development challenges only, kept separate from the scored attempts.

Check	Run	Result
Prompt change, Rock (before)	`2be47e5d`	8 tool calls, 11,615 input tokens; dumped strings and tried inputs blindly
Prompt change, Rock (after)	`a427f5f5`	15 tool calls, 64,265 input tokens; switched to --start-address/--stop-address ranges, but never found the check routine in the stripped binary
Offline mock test: an invalid tool call produced a recoverable error, and a scripted follow-up successfully invoked finish. No live model recovery was demonstrated.	`482d498a`	The model received the list of valid tools, then called finish instead of retrying

Because the two development runs used different step budgets, this comparison cannot isolate the effect of the prompt change. It provides qualitative evidence of changed tool behavior rather than a controlled performance measurement.

What we learned. The prompt change produced the behavior we targeted: targeted address ranges instead of full dumps. But on a stripped binary it didn't save steps, and its recorded input tokens were approximately 5.5× higher, although step budgets differed. An offline test with scripted model responses confirmed that an unsupported tool request no longer terminates the agent. However, this did not demonstrate that Ollama autonomously selects a valid replacement tool after receiving the error. We could not measure a solve-rate change from these Rock tests because the development runner had no flag verifier configured.

7. Next Steps and Competition Configuration

This agent is our foundation for the competition. We will carry forward the frozen agent with the post-evaluation prompt changes, recoverable tool errors, and the implemented inspect_binary and disassemble_binary tools. API retry handling was already part of the frozen evaluation configuration, rather than a new post-evaluation improvement. Further development will focus on reliable tool selection, appropriate execution of binaries, and reducing redundant analysis steps. The tradeoff is that these changes have not undergone a second full scored evaluation, and a longer tool list may introduce additional tool-selection errors. Our next test will evaluate rev-whataxor on a development run, measuring steps to the first decoding attempt and token usage.

8. Prior Exposure

The selected challenges are publicly available through CTFTiny, so model familiarity or recall of published solutions is possible. The successful trace derives the flag step by step from checker.py, which argues against recall. We didn't

consult evaluation flags or writeups. We did manually inspect Rock's strings output during development. The agent was not specifically trained on any of the information/tests beforehand.

9. Contributions

- Jenessa: Spearheaded agent creation/Ollama usage, which included establishing the benchmark testing and setup, and proctoring the model runs and recording the evaluation results.
- Parker: Created outline of the report, implemented two tools which contributed to the agent loop and model integration.
- Vamsee: Analyzed and looked over model execution, including examining errors and tool use, and helped write the report.
- Lalit: Contributed to Docker configuration, as well as workspace permissions and integration of controls to the resource limits.

10. Reused Code and AI Assistance

We used the NYU CTF Bench loader (nyuctf==1.1.1), CTFTiny (commit f1c9531), and the flag-check pattern from the course implementation guide. AI was used for parts of the code, and they are mentioned in the comments of the code.

We used ChatGPT (GPT-6 Thinking) to assist with agent architecture planning, code generation, debugging, trace interpretation, test-case development, and documentation review. Our team defined the agent's objectives, selected the architecture and tools, established evaluation constraints, and guided the development process. AI generated substantial portions of the implementation, which we reviewed, tested, and refined through iterative debugging. We conducted benchmark runs, examined execution traces, validated security controls and performance metrics, and used the findings to determine improvements to the agent.