In a Grove, Again: Optimizing over Feasible Event Histories for Incentive-Driven Testimony

Ruixin Song[1] **Jingjing Zheng**[1,2]
[1]GradientX Technologies Inc.
[2]Department of Mathematics, University of British Columbia
ruixinsong21@gmail.com jjzheng233@gmail.com

Abstract

We formulate narrative agency in testimony as a computational problem for Creative AI. Rather than generating different texts, agents select feasible histories from shared evidence. A deterministic simulator constructs $\mathrm{Feasible}(F)$, the set of histories consistent with public facts F. Each witness selects the feasible history that maximizes a transparent self-interest utility U_i. We study the framework's computational feasibility across three exactly enumerated domains: an agent-operations incident, an adaptation of Akutagawa's *In a Grove*, and an adaptation of Browning's *The Ring and the Book*. Enumeration provides ground truth. Q-learning recovers every reference optimum, while genetic search recovers all but the hardest Ring witness in $6/8$ seeds. This work provides a formal problem definition and feasibility framework for goal-driven history selection, rather than a new text-generation architecture.

1 Introduction

Narratives produced by agents are not merely linguistic artifacts: they are creative acts of selection among histories consistent with shared evidence. In creative testimony, legal reconstruction, and agent-incident analysis, the central problem is not generating a plausible account, but determining which causal histories remain compatible with the evidence and which history an agent has an incentive to endorse. Tool-using AI agents provide a concrete setting for this problem because their failures leave machine-readable execution traces. For example, a log may show that an executor process performed a destructive production write, while leaving open whether the planner requested the action, the executor escalated independently, or a monitor issued a hold that was later overridden.

Existing LLM workflows approach this task as text generation. Prompting, chain-of-thought reasoning, and retrieval can improve the plausibility of an explanation, but they do not enforce compatibility with the observed evidence. Even when prompts explicitly specify the physical and causal relationships that an explanation must satisfy, language models may still fail to recover the optimal feasible explanation. We instead formulate explanation as constrained optimization. Given a public record, we first construct the histories whose replay is consistent with the observed evidence, and only then optimize over that feasible set according to an explicit objective. Explanation thus becomes a process of selecting among evidence-compatible histories rather than generating free-form text.


Let F denote the public record, and let $\mathrm{Feasible}(F)$ denote the set of event histories whose replay is consistent with F. If agent i has a utility function U_i over histories, then a report is simply a selection from $\mathrm{Feasible}(F)$. This setup also formalizes the central insight of *In a Grove*: a single factual record may support multiple mutually incompatible but individually feasible accounts.

We instantiate this formulation as simulator-adjudicated optimization (Figure 1). Candidate histories are represented as structured action sequences and replayed from a common initial state. A history is considered feasible if the resulting terminal state is consistent with the public record F.

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.

candidate history $\tau \xrightarrow{\text{replay}}$ terminal state $s_T \xrightarrow{\text{compare}}$ public record F

feasible iff s_T matches the observed evidence in F



(a) Public record F (b) Enumeration counts

Figure 1: Replay turns evidence into a feasible set in the three domains.

Our contribution is a problem formulation and computational framework for treating narrative agency as goal-driven selection over evidence-compatible histories. We define narrative agency as $\arg\max_{\tau \in \text{Feasible}(F)} J(\tau)$: evidence determines which histories are admissible, while an agent's objective determines which admissible history it endorses. We validate the formulation across three exactly enumerated domains, including a non-literary agent-operations incident, and extend it to interactive testimony. In that setting, corroboration may eliminate the simulator's reference history, while accountability preserves alternatives.

Related work and novelty. We build on abduction and plan recognition [1–4], formal story-and-evidence accounts [5], multi-agent narrative worlds [6–12], strategic communication [13–18], and LLM deception and faithfulness studies [19–24].

To our knowledge, existing approaches rank hypotheses, construct intentional plots, or assess messages and prose. They do not treat the replay-admissible history set as an objective-invariant computational object. In *In a Grove*, for example, the same evidence can rule out Tajomaru's preferred duel while still admitting incompatible accounts of the killing. Changing his objective therefore changes which feasible account he selects, but not which histories the evidence permits. Likewise, corroboration can change the reports selected by witnesses without changing physical feasibility. This separation makes narrative plurality a controllable creative material rather than an inference failure. **The full positioning comparison is provided in Supplementary Table S1.**

2 Reasoning under Evidence as Constrained Optimization

Reasoning under evidence is formulated as constrained optimization over feasible explanations:

$$\hat{\tau} = \arg\max_{\tau \in \text{Feasible}(F)} J(\tau), \tag{1}$$

where F denotes the public record, $\text{Feasible}(F)$ is the set of event histories whose replay is consistent with F, and J is the objective used for the final comparison over feasible histories. The objective does not determine which explanations are admissible. Evidence does.

2.1 Histories, feasibility, and assertions

A domain $\mathcal{D}$ specifies agents, objects, and STRIPS-style operators [25, 26]. A history τ is a grounded sequence of operator applications executed by named agents. Replay maps τ to a terminal state s_T, and a history is feasible if and only if s_T is consistent with the public record F (Figure 1).

Many feasible histories differ only in details that are irrelevant to the reporting objective. Replay therefore induces a *causal signature*, a representation of the report-relevant facts implied by a history, such as who acted, what action occurred, and under what conditions. An *assertion* is the projection of this signature visible to the objective function J.

2.2 Domains, objectives, and interaction

2.2.1 Three enumerated domains and their objectives

We evaluate the framework in three exactly enumerated domains, selected for identifiability rather than realism. The first is an agent-operations incident in which a planner, an executor with production access, and a monitor participate in an automated task that results in a destructive production write. The public record establishes that the write originated from the executor's process, but leaves unresolved who authorized it, whether access was granted or escalated, and whether the action was intentional. The remaining two domains formalize literary testimony. Akutagawa's *In a Grove* [27] specifies a dagger wound, an unbloodied longsword, a cut rope, the wife alive, and the bandit absent. Browning's *The Ring and the Book* [28] is instantiated from eleven establishable documents in the 1698 Roman prosecution of Count Guido Franceschini.

For incentive-driven testimony, each agent is associated with a utility function U_i. Replay computes domain-specific structural features from the causal outcome, including agency, clean hands, dignity, warrant, innocence, and efficacy. Let $d_{ik}(\tau)$ denote the selected feature values for agent i after replay. We use $U_i(\tau) = \frac{100}{K_i} \sum_{k=1}^{K_i} d_{ik}(\tau)$ with $K_i = 3$. **Complete feature definitions and scoring rules are provided in Supplementary Section S5 and the released code.**

These utilities encode general principles of self-presentation rather than domain-specific narratives. No scoring rule refers to concepts such as "duel", "suicide", or "honour-killing". Agents are given only the public record F and their own utility function U_i. They are never instructed to conceal information or deceive. Narrative divergence therefore arises from optimization within $\mathrm{Feasible}(F)$ rather than from prompt engineering or linguistic variation.

2.2.2 Interactive reporting under corroboration and accountability

For interactive testimony, we augment the individual objective with a symbolic interaction layer. Because U_i is reported on a scale from 0 to 100, let $\bar{U}_i = U_i/100 \in [0, 1]$ denote its normalized version:

$$J_i(\tau_i', \rho_{-i}, \tau_i^0) = (1 - \beta)\, \bar{U}_i(\tau_i') + \beta\, \mathrm{agr}_i(\tau_i', \rho_{-i})\, \mathrm{self}_i(\tau_i', \tau_i^0, \gamma)\, \mathrm{stand}_i, \tag{2}$$

where the first term is the normalized self-interest objective and the remaining terms model social interaction. Here, $\mathrm{agr}_i = (1 + \mathrm{corr})/(1 + \mathrm{corr} + \mathrm{contra}) \in [0, 1]$ rewards weighted agreement between assertion atoms across witnesses, $\mathrm{self}_i = \max(0, 1 - \gamma\, \mathrm{drift})$ penalizes deviations from the witness's initial testimony, and $\mathrm{stand}_i = \max(0, 1 - \delta r_i)$ reduces the influence of witnesses whose earlier accounts are contradicted by subsequent evidence. The parameter β controls the strength of the interaction layer. When $\beta = 0$, Equation 2 reduces to $\bar{U}_i$, which has the same argmax as the reported utility U_i.

The interaction objective is symbolic and ordinal: replay determines feasibility, while interaction operates only on witness assertion atoms. Agreement measures corroboration, L_1-style drift captures consistency with earlier testimony, and β controls social pressure. We do not use likelihood, KL divergence, entropy, or cross-entropy because we study how self-interest, corroboration, and accountability determine a witness's choice within the feasible set defined by the public record, rather than modeling a probability distribution over hidden histories or inferring a unique true history.

3 Exact and replay-based solvers

The solver target is

$$\hat{\tau}_i = \operatorname*{arg\,max}_{\tau_i \in \mathrm{Feasible}(F)} J_i(\tau_i, \rho_{-i}, \tau_i^0),$$

where J_i reduces to the normalized utility $\bar{U}_i$ for independent reports and to Equation 2 for interactive testimony. Normalization does not change any argmax. The formulation requires only a replay oracle. Enumeration constructs $\mathrm{Feasible}(F)$ and provides ground truth in the enumerated domains, but replay-based solvers never access $\mathrm{Feasible}(F)$ explicitly. Instead, genetic search and tabular Q-learning interact with the simulator solely through replay and objective evaluation. **The detailed pseudocode for both solvers is provided as Supplementary Algorithm S1.** We use tabular Q-learning because exact domains permit comparison with enumeration. In larger domains, the same

interface naturally extends to function approximation, Monte Carlo Tree Search (MCTS), beam search, or transformer-based policies.

In a hearing, ρ_{-i} and τ_i^0 are held fixed while witness i searches for a best response. After the response is selected, the profile is updated and the next witness solves a new replay-based problem. Enumeration provides exact optima in enumerated domains, while replay-based search demonstrates that the same objectives remain searchable without explicit construction of $\mathrm{Feasible}(F)$.

4 Results

We evaluate three questions. Does self-interest select distinct feasible accounts? Can prompting or constrained planning recover those optima? Do replay-based hearings change narrative plurality under corroboration? For these experiments, we call an account *infeasible* when replay rejects it. We call accounts *distinct* when their causal assertions differ. We call a claim *jointly incompatible* when it cannot coexist with the other reported causal claims under the joint record.

4.1 Objective selection and replay optimization

Distinct objectives select distinct, irreconcilable accounts. Optimizing three utilities over one feasible set selects different *causal assertions* in all domains (Table 1). In *In a Grove*, the bandit's unconstrained honour-maximizing assertion is ruled out by the unbloodied longsword, while the witnesses retain different feasible assertions about the fatal action. The table shows one representative history per optimum. Tied optima preserve the same cross-agent separation in 69 to 100% of cases. Binding dimensions vary across physical, legal, and procedural mechanisms. Independently perturbing each of the 19 normalized feature constants by a uniform offset in $[-0.4, 0.4]$ and clipping the result to $[0, 1]$, we recomputed each witness's feasible argmax. The full spread was retained in $4{,}040/5{,}000 = 80.8\%$ of trials (fixed seed, 95% Wilson CI $[79.7, 81.9]$). The exact protocol is in Supplementary Section S6.

Replay-based optimization avoids enumerating $\mathrm{Feasible}(F)$**.** Unlike prompting, replay solvers receive hard feasibility feedback. Enumeration supplies exact references. Replay search approaches them without constructing $\mathrm{Feasible}(F)$. Tabular Q-learning reaches every reference optimum, while genetic search misses only the hardest Ring witness in two of eight seeds (Table 1). Enumeration visits 3,631, 32,928, and 23,978 states, whereas representative Q-learning runs use 77, 1,337, and 29 episodes or calls. This preserves feasible-optimum search and agent separation without explicit enumeration. **Supplementary Figure S1 shows the corresponding Ring learning curves: Q-learning reaches the exact optimum in all eight seeds for all three witnesses, while genetic search is slower and more variable for Guido and Caponsacchi.**

Table 1: Objective selection and replay-based solver results. Panel (a) reports one representative history per utility optimum and its evidence status. Panel (b) reports replay-solver recovery of the exact optima.

(a) Objective selection

Domain	Agent	$\max U_i$	in $\mathrm{Feasible}(F)$?	$U_i(\hat{\tau}_i)$	binding dimension(s)
In a Grove	bandit	72	**no**	58	honour (unbloodied longsword)
$\lvert\mathrm{Feasible}(F)\rvert = 11$	wife	75	yes	75	none
	samurai	80	yes	80	none
The Ring and the Book	husband	100	**no**	30	warrant (he sued first), bearing, provocation
$\lvert\mathrm{Feasible}(F)\rvert = 36$	wife	100	yes	100	none
	priest	100	**no**	72	efficacy (never reached Rome)
An agent ops incident (not literary)	planner	100	yes	100	none
$\lvert\mathrm{Feasible}(F)\rvert = 48$	executor	87	**no**	72	clean hands (named as the actor)
	monitor	100	yes	100	none

(b) Replay solvers

domain	witness	exact U_i	exact cost	GA success	GA cost	Q-learning success	Q-learning cost
In a Grove	bandit	58	3,631	8/8	320	8/8	77
	wife	75		8/8	697	8/8	174
	samurai	80		8/8	1,738	8/8	845
The Ring	Guido	30	32,928	6/8	81,620	8/8	1,337
	Pompilia	100		8/8	2,438	8/8	357
	Caponsacchi	72		8/8	3,975	8/8	315
Ops incident	planner	100	23,978	8/8	265	8/8	29
	executor	72		8/8	262	8/8	10
	monitor	100		8/8	262	8/8	27

Table 2: Prompting ladder and deterministic baselines on *In a Grove*. GPT-5 and Claude Opus 4.8 are shown as separate per-model probes. Solver rows report their stated run or exact reference. †The account is excluded by F. ‡Distinct counts the three beam outputs.

	utility attained				
Solver / condition	bandit	wife	samurai	infeasible	distinct
Not enforced ($\arg\max$ over all assertions)	$72^{\dagger}$	75	80	23.2%	3.0
gpt-5 (instructed)	42	43	80	0%	3.0
+ consequence	42	43	80	0%	3.0
+ self-check	42	43	80	0%	3.0
+ self-revise	42	43	80	0%	3.0
Claude Opus 4.8 (instructed)	42	43	80	0%	3.0
+ consequence	42	43	80	0%	3.0
+ self-check	42	43	80	0%	3.0
+ self-revise	42	43	80	11%	3.0
Constrained beam planner ($w = 32, T = 7$)	58	75	73	0%	$1.0^{\ddagger}$
Genetic search (8 seeds)	58	75	80	0%	3.0
Tabular Q-learning (8 seeds)	58	75	80	0%	3.0
Simulator ($\arg\max$ over enumerated $\mathrm{Feasible}(F)$)	58	75	80	0%	3.0

4.2 Construction cannot be replaced by instruction

The main prompting ladder uses five generator models (zai-glm-4.7, gemma-4-31b, gpt-oss-120b, GPT-5, and Claude Opus 4.8), three samples for each model, witness, and condition, and four primary rungs: instructed, consequence, self-check, and self-revise. Table 2 reports per-model probe results for GPT-5 and Claude Opus 4.8, and **the complete primary-model results are in Supplementary Table S3.** The generators use temperature 0.85 and at most 900 tokens when supported. The separate JSON extractor uses temperature 0.1 and at most 200 tokens. The deterministic planning baseline is constrained beam search with width $w = 32$ and horizon $T = 7$, with illegal actions masked during decoding. Failed calls are marked unusable. Extracted claims are scored by the same simulator and objective as our method. We report mean utility, rejection by F, and modal-assertion counts. Raw generations and extraction records are released. **The replay-solver hyperparameters, seed policy, and stopping rules are given in Supplementary Section S5.**

Without the oracle, maximizing U_i over all assertions selects infeasible accounts in 23.2% of cases in the first domain and 66.7% in the second. Stronger prompts reduce rejection, but the primary-model results remain below the feasible optima and often collapse the three-way split (Supplementary Table S3). The GPT-5 and Claude probes retain three distinct assertions across their conditioned rungs, with only Claude's self-revise condition showing residual rejection (Table 2). The constrained beam planner reaches $(58, 75, 73)$, missing only the samurai optimum.

4.3 Corroboration can erase jointly incompatible claims




Figure 2: Panel (a) gives the minimum accountability $\gamma^{\star}$ that preserves the proof across β. Panel (b) shows that any tested $\beta > 0$ at $\gamma = 0$ reduces three accounts and two jointly incompatible claims to one account and no incompatible claims.

For the hearing experiment, we fix the "run-06" public record from *In a Grove*: Takehiro is dead from a dagger wound to the throat, Masago is alive and present, Tajomaru is absent, the dagger is bloodied, the longsword is unbloodied, and the rope is cut. We hold the simulator, utilities, and feasible pool fixed. Witnesses speak in the fixed order Tajomaru → Masago → Takehiro. At round 0, each witness opens with the deterministic $\arg\max_{\tau \in \mathrm{Feasible}(F)} U_i(\tau)$ before observing the other reports. In every later round, the designated speaker computes a best response to the current public profile under Eq. 2. A witness revises only if the selected account changes. Otherwise, the witness stands. The hearing

stops after a complete round with no revisions or after 24 rounds. Repeated profiles are reported as cycles. Ties use the simulator's stable account key rather than enumeration order. Solver comparisons are made at the report-relevant causal-profile level, so tied histories with different unscored actions count as the same outcome.

Enumeration provides the exact reference under this protocol, while the replay check tests whether Q-learning recovers the same causal profiles on the tested openings and revisions. With independent testimony ($\beta = 0$), the hearing retains three accounts and two jointly incompatible claims. Adding corroboration ($\beta = 0.5$) collapses the profile to a single account corresponding to the samurai's suicide, and removes both jointly incompatible claims, even though the simulator's reference history is no longer selected. Holding witnesses to their openings with accountability ($\gamma = 0.2$) restores the three-way outcome, as shown in Table 3. **The compact outcome summary for these three interaction settings is provided in Supplementary Table S2.**

Table 3: Round-by-round structured hearing trace on the same record and speaking order (Tajomaru $\rightarrow$ Masago $\rightarrow$ Takehiro). M, T, and S denote "Masago struck", "Tajomaru struck", and "Takehiro self-struck". Each profile transition shows the recorded profile before the action, the action, and the resulting profile. agr_i is a weighted agreement score, not truth.

round / turn	witness(es)	profile transition	$\Delta\bar{U}_i$	$\Delta\mathrm{agr}_i$ (pp)
opening profile	all three	$\emptyset \xrightarrow{\text{openings}} M, T, S$	n/a	n/a
		Corroborative hearing ($\beta = .5, \gamma = 0$)		
round 1	Tajomaru	$M, T, S \xrightarrow{M \to S} S, T, S$	0	+10
round 1	Masago	$S, T, S \xrightarrow{T \to S} S, S, S$	0	+47
round 1	Takehiro	$S, S, S \xrightarrow{\text{stand}} S, S, S$	0	0
round 2	all three	$S, S, S \xrightarrow{\text{all stand}} S, S, S$	0	0
		+ *accountability* ($\beta = .5, \gamma = .2$)		
round 1	all three	$M, T, S \xrightarrow{\text{stand}} M, T, S$	0	0

This collapse is objective-driven rather than physical: the two corroborating revisions leave $\bar{U}_i$ unchanged while increasing agr_i by 10 and 47 percentage points. Pressure therefore rewards consistency rather than truth. Accountability makes those revisions costly through self-consistency and preserves the opening profile. Figure 2 shows both the accountability curve and the collapse under corroboration pressure.

Interactive testimony realization. The *Magistrate* demo lets readers vary F, β, γ, and δ. Each change replays the simulator. Selected feasible claims are rendered as testimony ("The woman killed him", "The bandit struck him", "I ended my life"). Corroboration collapses these claims into the samurai's suicide account, whereas accountability restores their three-way divergence. Tied optima make the resulting narratives conventional. Adding live assertions shrinks the Ring assertion space from 576 to 36 feasible assertions and recovers the husband, priest, and wife accounts. The demo runs in the browser at `https://tsuzzy.github.io/2026-grove-again/`; its implementation is `demo/magistrate.html`. **The Ring filtration and sensitivity audit are reported in Supplementary Section S6.**

5 Discussion and limitations

These experiments support a narrow claim: evidence-constrained history selection is distinct from text generation, and corroboration can reduce rather than repair narrative plurality. The utilities are intentionally hand-specified and transparent. They encode generic desiderata rather than literary labels, so they are controlled interventions, not learned human preferences. The 19-constant sensitivity audit retains the full cross-agent spread in $4{,}040/5{,}000$ perturbation trials. The sampling rule and Wilson interval are given in Supplementary Section S6. We do not evaluate whether surface realizations are literary, persuasive, or faithful beyond the structured claims, and we use no human judges or human subjects. Replay still requires a simulator, and exhaustive ground truth is limited to enumerable domains. Generalization to larger open-world domains and learned utilities remains untested. Code and data are at `https://github.com/tsuzzy/2026-grove-again`; the interactive *Magistrate* demo runs at `https://tsuzzy.github.io/2026-grove-again/demo/magistrate.html`.

References

[1] Jerry R. Hobbs, Mark E. Stickel, Douglas E. Appelt, and Paul Martin. Interpretation as abduction. *Artificial Intelligence*, 63(1–2):69–142, 1993.

[2] Henry A. Kautz and James F. Allen. Generalized plan recognition. In *Proc. AAAI*, 1986.

[3] Miquel Ramírez and Hector Geffner. Probabilistic plan recognition using off-the-shelf classical planners. In *Proc. AAAI*, 2010.

[4] Chris L. Baker, Rebecca Saxe, and Joshua B. Tenenbaum. Action understanding as inverse planning. *Cognition*, 113(3):329–349, 2009.

[5] Floris J. Bex, Peter J. van Koppen, Henry Prakken, and Bart Verheij. A hybrid formal theory of arguments, stories and criminal evidence. *Artificial Intelligence and Law*, 18(2):123–152, 2010.

[6] Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proc. ACM UIST*, pages 1–22, 2023.

[7] Michael Mateas and Andrew Stern. Structuring content in the Façade interactive drama architecture. In *Proc. AIIDE*, pages 93–98, 2005.

[8] Mark O. Riedl and Robert Michael Young. Narrative planning: Balancing plot and character. *Journal of Artificial Intelligence Research*, 39:217–268, 2010.

[9] Stephen G. Ware and Robert Michael Young. Glaive: A state-space narrative planner supporting intentionality and conflict. In *Proc. AIIDE*, 2014.

[10] Parag K. Mital, Seth Rosetter, Arturo Castro Prieto, Jacobo Heredia Zurita, and Breanna Browning. Orchestrating emergent storytelling with embodied multi-agent systems. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems Creative AI Track: Humanity*, 2025.

[11] Meta Fundamental AI Research Diplomacy Team et al. Human-level play in the game of Diplomacy by combining language models with strategic reasoning. *Science*, 378(6624):1067–1074, 2022.

[12] Elif Akata, Lion Schulz, Julian Coda-Forno, Seong Joon Oh, Matthias Bethge, and Eric Schulz. Playing repeated games with large language models. *Nature Human Behaviour*, 9:1380–1390, 2025. doi: 10.1038/s41562-025-02172-y.

[13] Vincent P. Crawford and Joel Sobel. Strategic information transmission. *Econometrica*, 50(6):1431–1451, 1982.

[14] Navin Kartik. Strategic communication with lying costs. *Review of Economic Studies*, 76(4):1359–1395, 2009.

[15] Shuhui Zhu, Yue Lin, Shriya Kaistha, Wenhao Li, Baoxiang Wang, Hongyuan Zha, Gillian K. Hadfield, and Pascal Poupart. Talk, judge, cooperate: Gossip-driven indirect reciprocity in self-interested llm agents. In *Proceedings of the 43rd International Conference on Machine Learning (ICML)*, 2026.

[16] Emanuel Tewolde, Xiao Zhang, David Guzman Piedrahita, Vincent Conitzer, and Zhijing Jin. Coopeval: Benchmarking cooperation-sustaining mechanisms and llm agents in social dilemmas, 2026.

[17] Siyue Ren, Wanli Fu, Xinkun Zou, Chen Shen, Yi Cai, Chen Chu, Zhen Wang, and Shuyue Hu. Reputation as a solution to cooperation collapse in llm-based mass, 2025.

[18] Suveen Ellawela. Trust, lies, and long memories: Emergent social dynamics and reputation in multi-round avalon with llm agents, 2026.

[19] Ethan Perez et al. Discovering language model behaviors with model-written evaluations. In *Findings of ACL*, pages 13387–13434, 2023.

[20] Jérémy Scheurer, Mikita Balesni, and Marius Hobbhahn. Large language models can strategically deceive their users when put under pressure. arXiv:2311.07590, 2023.

[21] Lorenzo Pacchiardi, Alex J. Chan, Sören Mindermann, Ilan Moscovitz, Alexa Y. Pan, Yarin Gal, Owain Evans, and Jan Brauner. How to catch an AI liar: Lie detection in black-box LLMs by asking unrelated questions. In *ICLR*, 2024.

[22] Owain Evans, Owen Cotton-Barratt, Lukas Finnveden, et al. Truthful AI: Developing and governing AI that does not lie. arXiv:2110.06674, 2021.

[23] Stephanie Lin, Jacob Hilton, and Owain Evans. TruthfulQA: Measuring how models mimic human falsehoods. In *Proc. ACL*, pages 3214–3252, 2022.

[24] Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In *NeurIPS*, 2023.

[25] Richard E. Fikes and Nils J. Nilsson. STRIPS: A new approach to the application of theorem proving to problem solving. *Artificial Intelligence*, 2(3–4):189–208, 1971.

[26] Malik Ghallab, Dana Nau, and Paolo Traverso. *Automated Planning: Theory and Practice*. Morgan Kaufmann, 2004.

[27] Ryunosuke Akutagawa. Yabu no naka [in a grove], 1922.

[28] Robert Browning. *The Ring and the Book*. Smith, Elder and Co., 1869.