
Exploring Different Approaches to Improve Binary Classification Performance for Imbalanced Data Set

Yuan Sun

Department of Computer Engineering
University of British Columbia
Vancouver, BC
round.sun@alumni.ubc.ca

Yixuan Ji

Department of Computer Engineering
University of British Columbia
Vancouver, BC
jiyixuan@ece.ubc.ca

Jay Fu

Department of Computer Engineering
University of British Columbia
Vancouver, BC
jay.fu@alumni.ubc.ca

Abstract

This is a good abstract.

1 Introduction

This is instruction section.

1.1 sub

This is a good sub section.

1.2 sub

This is a good sub section.

2 Related Work

This is related work section.

3 Descriptions and Justifications

To boost up the accuracy of a model and minimize the effect of imbalanced data on the performance, there are several possible solutions, including undersampling, oversampling and class weighting. However, seldom have studied the difference in these approaches. The motivation of this experiment is to study how different machine learning techniques could have impact on the performance of models trained on imbalanced data set. The following sections discuss in detail the settings of the experiment and some of the approaches to tackle imbalanced problems.

3.1 Data Set Settings

The data set is drawn from the UCI Machine Learning Repository and is publicly known as the *Adult* data set. It contains general information of 48843 individuals and whether or

Table 1: Data Set Attributes

Name	Description
Age	Continuous
Workclass	Private, Self-emp-not-inc, Self-emp-inc, Federal-gov, Local-gov, State-gov, Without-pay, Never-worked
Final Weight	The number of people the census believes the entry represents; Continuous
Education	Bachelors, Some-college, 11th, HS-grad, Prof-school, Assoc-acdm, Assoc-voc, 9th, 7th-8th, 12th, Masters, 1st-4th, 10th, Doctorate, 5th-6th, Preschool
Education-Num	Continuous
Marital-Status	Married-civ-spouse, Divorced, Never-married, Separated, Widowed, Married-spouse-absent, Married-AF-spouse
Occupation	Tech-support, Craft-repair, Other-service, Sales, Exec-managerial, Prof-specialty, Handlers-cleaners, Machine-op-inspct, Adm-clerical, Farming-fishing, Transport-moving, Priv-house-serv, Protective-serv, Armed-Forces
Relationship	Wife, Own-child, Husband, Not-in-family, Other-relative, Unmarried
Race	White, Asian-Pac-Islander, Amer-Indian-Eskimo, Other, Black
Sex	Female, Male
Capital-Gain	Continuous
Capital-Loss	Continuous
Hours-per-Week	Continuous
Native-Country	United-States, Cambodia, England, Puerto-Rico, Canada, Germany, Outlying-US(Guam-USVI-etc), India, Japan, Greece, South, China, Cuba, Iran, Honduras, Philippines, Italy, Poland, Jamaica, Vietnam, Mexico, Portugal, Ireland, France, Dominican-Republic, Laos, Ecuador, Taiwan, Haiti, Columbia, Hungary, Guatemala, Nicaragua, Scotland, Thailand, Yugoslavia, El-Salvador, Trinidad& Tobago, Peru, Hong, Holand-Netherlands
Salary	>50K, <=50K

not they make more than 50K every year. The goal is to build a model that can accurately predict the annual income ($> 50K$ or $\leq 50K$) of a given person based on this data set. As shown in Table 1, the data set contains a mixture of categorical and numerical features for each entry. Therefore, data pre-processing techniques should be applied to enable further study on the data. Specifically, feature selection algorithms could help decide which features are relevant to the prediction. In addition, the label *salary* is a binary attribute of the individual's income being either $> 50K$ or $\leq 50K$, which makes it an ideal binary classification problems.

The major challenge for this data set is the imbalance of its binary label. There are only 11687 positive ($> 50K$) labels out of 48843 entries in total, which makes up 23.9% of the whole data set. Models trained on imbalanced data set tend to make prediction of the majority class. For example, consider a data set consisting 10000 entries of class *A* and 100 entries of class *B*. The model could get 90% of training accuracy by simply predicting everything as class *A*. The following sections discuss several methods to handle imbalanced data set, including previous efforts that has been made to study this data set, as well as other machine learning techniques that could also be applied.

3.2 Measure of Performance

In order to compare different algorithms, let us first define the measure of performance. In the sense of binary classification, predictions can be categorized into four different types: true positive (TP), false positive (FP), true negative (TN) and false negative (FN). In different applications, performance can be measured using different formulae. The following three are the most used formulae in binary classification:

$$Sensitivity(SEN) = \frac{TP}{TP+FP} \quad (1)$$

$$Specificity(SPE) = \frac{TN}{TN+FN} \quad (2)$$

$$PredictiveAccuracy(PA) = \frac{TP+TN}{TP+FP+TN+FN} \quad (3)$$

Sensitivity focuses on the model's accuracy on its positive predictions whereas *specificity* focuses on negative predictions. *Predictive accuracy* on the other hand, is used to measure the general accuracy of the model over both positive and negative predictions. In this experiments, we compare the performance of different algorithms using all three of the measures.

3.3 Undersampling

One of the most popular methods in handling imbalanced data sets is data undersampling, in which entries are randomly sampled from the majority class. Only a portion of the majority class are collected such that the size of the sampled majority class is the same as the minority class. Inouye (2018) has implemented such sampling method to the *Adult* data set. He randomly generated a subset of sample with income $\leq 50K$ and simply discarded the rest. This approach usually works relatively well, however, massive amount of data is discarded and the resulted model would not be able to reflect the complete data set. Next section introduces an alternative method that could potentially utilize every entry of the data set to build the model.

3.4 Oversampling

As an alternative to the undersampling method, oversampling "creates" new entries of the minority class to match the size of majority class. The simplest way to oversample is to duplicate the minority class multiple times. However, there are more sophisticated oversampling algorithms, such as SMOTE and ADASYN, that can create synthetic data points as oppose to duplicating original entries. The particular algorithm used in this experiment is ADASYN, which randomly generates a data point based on k nearest neighbors. In addition, ADASYN attributes more weights to data points that are harder to learn. Both undersampling and oversampling are types of data pre-processing methods to solve imbalance problems. Next section introduces another technique that could be applied in the training phase of model fitting.

3.5 Class Weighting

Class weighting is a method that assigns more weights on important classes so that the model focuses more on one class than the other during training. This method can also be applied to imbalanced data set so the model would focus more on the minority class. Lo, et al. (2008) applied class-balanced support vector machine (CB-SVM) to solve imbalanced problems. They assigned different weights to each class to prevent the model from favoring majority class. Similarly, class weighting is also conducted in this experiment using the *svm* module in *scikit-learn* package. The specific function used, *SVC*, allows users to specify weights for each class through the parameter *class_weight*.

3.6 Ensemble

Another approach that could potentially enhance the performance is model ensembling. In general it could help reduce the training error and/or approximation error of a variety of problems. However, seldom have applied ensemble method to the *adult* data set. In this experiment, we apply ensemble method to reduce false predictions of the model. Specifically, we gather the outputs of a series of heterogeneous machine learning models and train another logistic regression model based on these outputs. This is known as the stacking ensemble method. Section 4 discusses in detail how different techniques, including ensemble methods, would impact on the performance.

4 Experiments

We have done two experiments to study the effects of data balancing techniques and ensemble methods on performance. All hyper-parameters used in this section are determined using 10-fold

Table 2: Data Balancing Techniques

Algorithm	Undersampling			Oversampling			Class Weighting			None		
	SEN	SPE	PA	SEN	SPE	PA	SEN	SPE	PA	SEN	SPE	PA
Age	999	988	100	999	988888	100	999	988	100	999	988	100
Age	999	988	100	999	988888	100	999	988	100	999	988	100
Age	999	988	100	999	988888	100	999	988	100	999	988	100
Age	999	988	100	999	988888	100	999	988	100	999	988	100
Age	999	988	100	999	988888	100	999	988	100	999	988	100

Table 3: Ensemble vs. Single Models

Model	SEN	SPE	PA
Stacking Ensemble	9999	9999	8888
Model	SEN	SPE	PA
Model	SEN	SPE	PA
Model	SEN	SPE	PA
Model	SEN	SPE	PA
Model	SEN	SPE	PA
Model	SEN	SPE	PA
Model	SEN	SPE	PA

cross validation. After shuffling the raw data set, we divide it into training set and testing set by a ratio of 7 : 3. All algorithms use the same training set and test set for comparison purposes.

4.1 Data Balancing Techniques

The first experiment is to compare the performance of models after applying three different data balancing techniques as previously introduced: undersampling, oversampling and class weighting. In order to study only the effects of these techniques, we have controlled as many variables as possible. All three techniques use the same *adult* data set and same machine learning algorithms with the same hyper-parameters. In order to better observe how each technique influence the result, we conduct another control group in which no data balancing techniques are used. See Table 2 for the performance of each algorithms using different balancing techniques. As introduced in Section 3.2, binary classification models can be measured using SEN, SPE and PA. The corresponding scores are presented in the table.

As shown,

4.2 Ensemble Method

The second experiment explores how ensemble method can affect the model performance. From the result of Section 4.1, we determine that ??? performs the best in this binary data set. Therefore ??? is used in both groups of this experiment in order to control experimental factors. Similar to the previous part, models are compared in three different matrices SEN, SPE and PA.

5 Discussion

This is the conclusion.

One of the major contribution of this experiment is that our work has provided some insights to the performance of different balancing techniques.

In the ensemble experiment, we only used ??? in both groups to control experimental factors. However this might neglect the possibility that a different balancing technique might make a difference in the

ensemble results. If time permits, one possible improvement is to conduct ensembling to all balancing techniques and study their difference.

Another potential future improvement is to expand the experiment to more data sets that have different imbalance ratio. This could help explore how balancing techniques and ensemble methods would perform differently with different imbalance ratio.

References

References follow the acknowledgments. Use unnumbered first-level heading for the references. Any choice of citation style is acceptable as long as you are consistent. It is permissible to reduce the font size to small (9 point) when listing the references. **Remember that you can use more than eight pages as long as the additional pages contain *only* cited references.**

[1] Alexander, J.A. & Mozer, M.C. (1995) Template-based algorithms for connectionist rule extraction. In G. Tesauro, D.S. Touretzky and T.K. Leen (eds.), *Advances in Neural Information Processing Systems 7*, pp. 609–616. Cambridge, MA: MIT Press.

[2] Bower, J.M. & Beeman, D. (1995) *The Book of GENESIS: Exploring Realistic Neural Models with the GEneral NEural Simulation System*. New York: TELOS/Springer-Verlag.

[3] Hasselmo, M.E., Schnell, E. & Barkai, E. (1995) Dynamics of learning and recall at excitatory recurrent synapses and cholinergic modulation in rat hippocampal region CA3. *Journal of Neuroscience* **15**(7):5249-5262.