HW1 — Logic, SAT/SMT, and bounded reachability

CS 3892 / CS 5892 · Formal Methods: Safe and Trustworthy AI · Fall 2026

Out	Thursday, September 10
Due	**Thursday, September 24, 11:59 p.m. US Central**
Weight	4% of the course grade (100 points)
Tool	Z3 — Python API and SMT-LIB 2
Zero-install path	Google Colab, or GitHub Codespaces
Submit	Brightspace → Assignments → *HW1 — Logic; SAT-SMT; bounded reachability (Z3)*

Nothing to install. Every part of this runs in a browser tab.

Start here: github.com/ttj/cs3892-examples has a starter notebook for this homework with each part stubbed out, plus every worked example from sessions 5 onward in both SMT-LIB and Python.

What this is for

By the end you should be able to take an English requirement, write it down as a formula, decide it with a solver, and — the part that matters — **know whether the answer you got is the answer to the question you meant to ask.** A wrong encoding that returns `unsat` looks exactly like a correct one.

Part 1 — Logic warm-up *(20 points)*

Translate five English statements into propositional and, where they need it, first-order logic. For each one, **decide satisfiability and validity by hand first**, then confirm with Z3.

Doing it both ways is the point: you are calibrating your own judgement against a decision procedure. Where you and Z3 disagreed, say so and say who was right.

Recall the identity everything here rests on:

> φ is **valid** exactly when ¬φ is **unsatisfiable**.

A solver has no "is it valid?" button, so every validity question you ask becomes a satisfiability question about the negation.

Part 2 — Encoding *(30 points)*

Encode a combinatorial puzzle as an SMT query: pigeonhole, n-queens, sudoku, or KenKen. Starters are provided for each.

Then **report solve times as the size grows, and say where the wall is.** A table and one sentence of interpretation. "It got slow around n = 12" is not an answer; "it goes from milliseconds to minutes between n = 11 and n = 12, which is where the search stops fitting in the clause database" is closer.

Part 3 — Bounded reachability *(30 points)*

Write the bounded counter as a transition system and ask Z3 whether `x` can reach 11 within `N` steps.

Find the smallest `N` for which the answer changes, and explain precisely why that `N`. This is the running example for the whole semester — you will verify this same property four more times with four more tools, so it is worth understanding completely now.

Part 4 — AI component *(20 points)*

Ask an LLM to produce the SMT-LIB encoding for Part 3. Report what it got right, what it got wrong, and — critically — **how you knew.**

An encoding that is `unsat` for the wrong reason looks exactly like a correct one until you check it, so say what check you ran. Reading it over and finding it plausible does not count. Asserting the negation of a property you know should hold, and watching it come back `sat` with a model you can read, does.

What to submit

One archive or repository link containing:

1. Your `.py` and/or `.smt2` files, runnable as-is.
2. A short report — Markdown or PDF, roughly two pages — with the answers, the timing table, and your Part 4 write-up.
3. The AI-use disclosure (see below).

The mechanical part is checked automatically: do your files run, and do they produce the verdicts you claim? The interesting part — why the counterexample looks like that — is read by a human.

Late policy

Four late days for the semester, in whole-day units, no more than two on any one homework, no questions asked. Beyond that, 20% per day.

Collaboration and AI use

Discussion is encouraged; submitted work must be your own. **AI assistants are allowed and expected** — this is a course about the reliability of AI-produced artifacts. Two conditions:

1. **Disclose.** Say what you used and for what.
2. **Verify.** You are responsible for everything you submit, and "the model said so" does not transfer that responsibility. It carries less weight in this course than almost anywhere else, because every tool you will use is a decision procedure that can tell you whether the model was right — so use one.