

Search and filter behavior

Behavioral specification for query entry, facets, sorting, and state restoration.

Handoff anchor	Beacon Field Research / Study Alpha / 2026-07-13 / session UX-184 / n=24
----------------	--

Type query	→	Debounce	→	Results	→	Facet apply	→	Detail
------------	---	----------	---	---------	---	-------------	---	--------

Query behavior

Search begins after 2 characters with a 250 ms debounce. Results update in place; the query remains editable. Quoted strings are treated as ordinary text. Clear appears only when a query is present and returns focus to the field.

Input	System response	Edge case
0-1 characters	Show default list; no request.	Keep filters active.
2+ characters	Show loading row, then ranked results.	If request fails, keep prior results visible.
Whitespace only	Normalize to empty query.	Do not display an error.
No matches	Show empty state and adjacent suggestions.	Clear only query; preserve facets.

Facet model

Facets are Availability, Method, Topic, and Time window. Within a facet, choices use OR. Across facets, choices use AND. A chip labels every applied value and has a spoken removal name such as "Remove Method: diary study".

Control	Rule	Feedback
Facet drawer	Apply explicitly from sticky footer.	"3 filters applied" live update
Sort	One choice: Most relevant, Newest, A-Z.	Result order changes; scroll resets to top
Clear all	Clears facets, not query or sort.	Undo is offered for 5 seconds

Result card contract

A card exposes title, study tag, duration, and save status. Opening a card is distinct from saving it; the save control never navigates. Screen readers encounter result count before the list and card actions after the summary.