

Platform Integration Guide

Synthetic evaluation guide | Aster Loop K.K. | release 2026-07-13

Setup

Install only the invented, pinned SDK adapters: nimbus-control-sdk 3.4.1, orbit-ops-sdk 2.8.0, and harbor-portability-sdk 1.9.3. The application owns request identity, safe error mapping, and ADR-042 approval logic.

Lifecycle

A Product Alpha R7 request is validated, recorded as awaiting approval, and correlated with its request ID. After the ADR-042 approval transition, the async worker executes. Create and status control-plane calls target p95 184 ms; worker time is excluded.

Stage	Adapter responsibility	Result
Request	Assign request ID; validate replay safety	awaiting approval
Approval	Observe ADR-042 transition	approved
Execution	Start async worker	completed or failed
Review	Measure p95 control plane	rollout evidence

Error handling

Retry reads and replay-safe creates only. A timeout returns a safe, retryable error with the same request identity. Do not retry a changed create body. Duplicate events are deduplicated by event ID; missing approval remains a visible awaiting state.

Alpha R7 example

Example control flow: **POST /releases** records r7 as awaiting approval; the subsequent ADR-042 approval event starts the worker; **GET /releases/{id}** returns completed or failed. This is an internal synthetic guide and has no external vendor endpoint.

Portability boundary

Nimbus is the latency-first evaluation tier. Orbit informs operational practices. Harbor preserves a portable adapter boundary. No real vendor product, logo, endpoint, or credential is part of this package.