

Solar Based Electric Vehicle charging Station

D. Tirumala Tarun

Dept. of Electrical and Electronics
Engineering
Koneru Lakshmaiah Education
Foundation
Vaddeswaram, India.
daditirumalatarun@gmail.com

Prasanth Bokka

Dept. of Electrical and Electronics
Engineering
Koneru Lakshmaiah Education
Foundation
Vaddeswaram, India.
prasanthbokka9@gmail.com

G.G.Raja Sekhar

Dept. of Electrical and Electronics
Engineering
Koneru Lakshmaiah Education
Foundation
Vaddeswaram, India.
rsgg73@gmail.com

Katuri Rayudu

Dept. of Electrical and Electronics
Engineering
B V Raju Institute of Technology
Narsapur, Telangana, India.
rayudu.katuri@bvrit.ac.in

Sandeep Khantwal

Dept. of Electronics and
Communication Engineering
Tula's Institute
Dhoolkot, Dehradun, India.
sandeep.khantwal@tulas.edu.in

Vinay Negi

Dept. of Electronics and
Communication Engineering
Tula's Institute
Dhoolkot, Dehradun, India.
negi.graphicera@gmail.com

Abstract— This paper focuses on modeling a leading smart charging station for electric vehicles in the UK (EV), suitable for fast charging EVs with DC current while ensuring minimal pressure on the electrical network. The operation of the charging station managed by this type of method provides kilometers both by using photovoltaic (PV) electricity or from the grid, and the automatic grid (V2G) is also applied to improve stability. of the power grid. for the duration of the maximum load hours. PV Interface DC/DC Converters and Grid Interfaces The DC/AC bidirectional converter represents a DC bus. The clear transition from one walking mode to another demonstrates the effectiveness of the manipulation method used. Precision modeling and management of components are defined and applied in MATLAB Simulink. The simulations illustrate the possible behavior of the charging station in all operating modes in terms of the four-way interaction between PV, EV and the grid as well as V2G operation. It is recognized that electric vehicles offer new possibilities in terms of regulatory delivery and flexibility in consumption by varying the energy that recharges at a given time on site. The paper also discusses the financial incentives needed to encourage electric vehicle owners to actively participate in lieu of a response mechanism.

Keywords—Solar PV System, Electric Vehicle, charging station, Vehicle to Grid

I. INTRODUCTION

Because of its dependable results, the smart grid concept of integrating renewable energy resources (res) with grid software is becoming increasingly popular. e.g., the development of its energy gadget efficiency and the low strolling costs. that allows you to get extra sales, v2g (automobile to grid) technology also can be blended wherein EVs owners can benefit a balance of call for through charging/discharging modes i.e., charging during non-height hours and discharging during height hours. but this approach could motive a quick lifestyle of the EV battery and different unsolved issues. This paper focuses on an optimization set of rules of cs power to be allotted to charge EVs, the purpose is to use minimum power from the application via enforcing a subsystem accrued the res with the electricity garage unit.

Besides, immoderate charging prices result in excessive energy demand, which may not be supported by way of using one of the strength assets in a standalone mode. To comfortable the regulated dreams from a strong hybrid electrical tool, the intervention of grid is 3 paramount's in plenty of stages, as in compensation mode, even as a pressing immoderate power name for seems in the cs. so one can optimize the value and to benefit from solar irradiance, the injection of extra strength into the grid from pv-battery device is likewise carried out on this management approach.

To some extent, the organization gathering the PV array and the battery garage buffer (bsb) to charge EV batteries, is taken into consideration as a capability method for charging evs while ac load (residential, commercial, and business purchaser) is given high precedence to be power up from the electrical network.

II. BRIEF EXPLANATION AND DESIGNING OF CIRCUIT:

Conversion Of Solar Power The sun energy is the electricity acquired by using capturing warmth and light from the solar. The approach of acquiring power from daylight is daily the Photo everyday voltaic approach. this is performed the usage of a semiconductor day-to-day cloth. The alternative shape of acquiring solar energy is through the thermal era, which gives types of power tapping strategies. the primary is sun awareness, which focuses on solar electricity day by day power thermal mills. The second approach involves heating and cooling structures, which are used in solar water heating and air conditioning, respectively. The process of converting sun electricity in normal energy daily utilize its electricity in sports is given underneath Absorption of strength sporting particles in sun's rays day-to-day Pho every day voltaic conversion, within the solar cells. The mixture of cutting-edge from numerous cells. This step is vital considering that a unmarried cellular has a voltage of less than 0.5 V. Conversion of the ensuing DC day-to-day AC.




Fig. 1. PN Junction

The PN Junction become invented by way of Russell of Bell laboratory everyday inside the America. It refers to day-to-day a junction among semiconductors every day, this is, P-kind and N-type. Russell positioned that the two semiconductors all days have an exciting behavior on the junction that reasons conduction in a single route every day. Every day, holes (the absence of an electron) serve as the majority charge providers in a P-type semiconductor. Every day, electrons serve as the majority charge providers in an N-type semiconductor.

within the illustration offered above, at the junction –

- a larger diffuse charge over the period of the daily chance contacts such that a large fraction at the p component acquires negative charges and neutralizes them.
- In addition, the negatives on the n-side favor high costs and neutralize them. This office works with profit (m) at a time when prices are getting more and more depleting every day, let's make this place impartial and in a balanced country.

This location is day-to-day attenuation layer provides a capacitive barrier and thus uses external voltages daily. This device is known as the daily bias device.

- Behavior, upstream of bias, voltage is taken daily to pump electrons (terrible) from the daily junction to the p-component of the junction. Today's zero slip ensures consistent daily movement of electrons to fill holes, thus conduction throughout the depletion layer.
- The voltage inversion is done in the opposite way to the polarization per day, causing holes and electrons to drift aside each day, causing the depletion layer to grow.
- Every day an external load is installed a solar cell with a high-quality terminal connected daily with N facet panels and a terrible terminal every day with panels with surface P. A difference in power is produced by the photoelectric effect.
- The sharpness obtained by electrons displaced by photons is not always sufficient to make a large difference in power. The current date is therefore contained in the daily target in the same way as the collision and ejection of larger electrons.
- Photovoltaic effect

- A solar cell that uses the idea of a pn junction to collect solar energy. The following dedication suggests the Fermi degree of a semiconductor.




Fig. 2. SolarpanelDiagram

III. CIRCUIT DIAGRAM




Fig. 3. Simulation Overview




Fig. 4. Battery Charge Control Circuit




Fig. 5. Circuit diagram of CV solar Battery charging and charge control circuit

IV. RESULTS & DISCUSSIONS

The Figure 6 represents output power and state of charge output waveforms. In this case, the voltage can be controlled with respect to the state of charge, which is steady. The following output graph is for state of charge and voltage at EV Battery.




Fig. 6. Output of EV Battery

Figure 7 shows the output waveform of the voltage and charge status. Here, the voltage changes depending on the state of charge, and the state of charge is constant.

The following output graph is for state of charge and voltage at EV Charging Station.




Fig. 7. Output of EV Station Storage




Fig. 8. Output of Battery Charge Control

The Figure 8 represents the output of state of charge which is constant at 1. The graph shows constant at 1 when the state of percentage is less than 70. And it shows constant at 0 when the state of charge percentage is greater than 80.

The Figure 9 represents graph of Maximum power point tracking. Here we used voltage regulation method due to which the graph is increasing but at a point the charge is constant it is because we have used constant voltage technique.




Fig. 9. Output of Solar Panel PV MPPT

V. CONCLUSION

A solar-powered alternative power device has been quickly and effectively designed and tested in MATLAB Simulink. MATLAB model 2016a is used for layout. AC supply charger additionally designed, and it will assist each time solar faces electricity failure. Embedded primarily based characteristic calling automation is used right here for automobile switching manner (solar mode/AC supply Mode). This layout aid for 48V EV charging software.

REFERENCES

- [1] Patnaik, Lalit, A. V. J. S. Praneeth, and Sheldon S. Williamson. "A closed-loop constant-temperature constant-voltage charging technique to reduce charge time of lithium-ion batteries." *IEEE Transactions on Industrial Electronics* 66.2 (2018): 1059-1067.
- [2] Duru, Kamala Kumari, et al. "Critical Insights Into Fast Charging Techniques for Lithium-Ion Batteries in Electric Vehicles." *IEEE Transactions on Device and Materials Reliability* 21.1 (2021): 137-152.
- [3] Hannan, Mahammad A., "State-of-the-art and energy management system of lithium-ion batteries in electric vehicle applications: Issues and recommendations." *Ieee Access* 6 (2018): 19362-19378.
- [4] Gaglani, Mihir, Rashmi Rai, and Soumitra Das. "Implementation Of Multilevel Battery Charging Scheme For Lithium-ion Batteries." 2019 National Power Electronics Conference (NPEC). IEEE, 2019.
- [5] Kalla, U. K., & Shukla, T, "State of Art and Comprehensive Study on Charging Systems for Electric Vehicles".
- [6] Hickey, R., & Jahns, T. M, "Direct Comparison of State-of-Charge and State-of-Energy Metrics for Li-Ion Battery Energy Storage".
- [7] Ahn, J.-H., & Lee, B. K, "High Efficiency Adaptive-Current Charging Strategy for Electric-Vehicles Considering Variation of Internal Resistance of Lithium-ion Battery".
- [8] Ouyang Q, Zhang D, Wang Z, & Duan C, "User-Involved Optimal Charging Control for Lithium-Ion Batteries".
- [9] Chen, Wu, Shieh, D-T, & Chen, T-R, "Sinusoidal-Ripple-Current Charging Strategy and Optimal Charging Frequency Study for Li-Ion Batteries".
- [10] Muni, T. V., & Lalitha, S. V. N. L. (2020). Implementation of control strategies for optimum utilization of solar photovoltaic systems with energy storage systems. *International Journal of Renewable Energy*

- [11] Research, 10(2), 716–726. Rahimi-Eichi, H.; Ojha, U.; Baronti, F.; Chow, M.Y. Battery management system: An overview of its application in the smart grid and electric vehicles. *IEEE Ind. Electron. Mag.* 2013.
- [12] Yu, H.; Duan, J.; Du, W.; Xue, S.; Sun, J. China's energy storage industry: Develop status, existing problems and countermeasures. *Renew. Sustain. Energy Rev.* 2017.
- [13] Chen, J.; Ouyang, Q.; Xu, C.; Su, H. Neural network-based state of charge observer design for lithium-ion batteries. *IEEE Trans. Control Syst. Technol.* 2017.
- [14] Ravi Kishore, D., Chandra Sekhar, G., Prakash, R. B. R., & Vijay Muni, T. (2020). A novel power management scheme for distributed generators in a DC microgrid IOP: Conference series. In *IOP Conference Series: Materials Science and Engineering* (Vol. 993). IOP Publishing Ltd. <https://doi.org/10.1088/1757-899X/993/1/012083>
- [15] Liu, G.; Lu, L.; Hong, F.; Hua, J.; Li, J.; Ouyang, M.; Wang, Y.; Xue, S.; Chen, P. A comparative study of equivalent circuit models and enhanced equivalent circuit models of lithium-ion batteries with different model structures. In *Proceedings of the 2014 IEEE Conference and Expo Transportation Electrification Asia-Pacific (ITEC Asia-Pacific)*, Beijing, China, 31 August–3 September 2014.
- [16] Chaoui, H.; Ibe-Ekeocha, C.C.; Gualous, H. Aging prediction and state of charge estimation of a lifepo4 battery using input time-delayed neural networks. *Electr. Power Syst. Res.* 2017.
- [17] Chen, Z.; Fu, Y.; Mi, C.C. State of charge estimation of lithium-ion batteries in electric drive vehicles using extended kalman filtering. *IEEE Trans. Veh. Technol.* 2013.
- [18] Shabnam, P., Priyanka, A. K., Vijay Muni, T., & Rajasekhar, S. (2020). PID controller based grid connected wind turbine energy system for power quality improvement. *Journal of Critical Reviews*, 7(7), 31–35. <https://doi.org/10.31838/jcr.07.07.06>
- [19] Zhang, Z.L.; Cheng, X.; Lu, Z.Y.; Gu, D.J. Soc estimation of lithium-ion batteries with aekf and wavelet transform matrix. *IEEE Trans. Power Electron.* 2017.
- [20] Cacciato, M.; Nobile, G.; Scarcella, G.; Scelba, G. Real-time model-based estimation of soc and soh for energy storage systems. *IEEE Trans. Power Electron.* 2017.
- [21] Karimulla Baig, K Prudhvi Raj, G G Raja Sekhar, T Vijay Muni, M Kiran Kumar, "Power Quality Enhancement With Active Power Control" in *JCR*, Vol-7, Issue-9, May 2020 (SCOPUS)
- [22] Mounika Muppavarapu, G G Rajasekhar, T Vijay Muni, R B R Prakash, "Enhancement Of Power Quality In A Grid Connected UDE Based PV Inverter" in *JCR*, Vol-7, Issue-2, Feb-2020 (SCOPUS)
- [23] R Bhargavi, P Ganesh, G G Rajasekhar, R B R Prakash, T Vijay Muni, "Design and Implementation of Novel Multilevel Inverter" in *JARDCS Vol-12, Issue-2, Feb 2020*(SCOPUS)
- [24] Sudha Dukkupati, AVGAMarthanda, G G Rajasekhar, Malligunta Kiran Kumar, "Design Analysis and Implementation of a Three Phase Seven Level PV & Wind based Microgrid" in *IJITEE Vol-8, Issue-10, Aug-2019*(SCOPUS)
- [25] Injam Harshith, Bathula Prudhvi Raj, G G Raja Sekhar, T. Vijay Muni "A Novel Methodology for Single Phase Transformerless Inverter with Leakage Current Elimination for PV Systems Application" in *IJRTE Vol-8, Issue-6, Jan-2019*(SCOPUS)
- [26] G.G.RajaSekhar, B.Basavaraja "Solar PV Fed Non-Isolated DC-DC Converter for BLDC Motor Drive with Speed Control" in *IJECS Vol-13, No:1, January-2019* (SCOPUS).
- [27] G.G.RajaSekhar, B.Basavaraja "Brushless DC Motor Drive with Single Current Sensor Fed from PV with Non-Isolated Interleaved Converter" in *JARDCS Vol-10, No:9, July-2018* (SCOPUS).
- [28] P.Swapnasai, G.G.Raja Sekhar, T.Vijaymuni, M.Saichand "Power quality and custom power improvement using UPQC" in *IJET(UAE) Vol-7, No:2.2, May-2018*(SCOPUS).
- [29] 29.B.Praveenkumar, K.S.Srikanth, M.Kiran Kumar, G.G.Raja Sekhar "ANN Control Based Variable Speed PMSG-Based Wind Energy Conversion System in *IJET(UAE) Vol-7, No:2.7, April-2018* (SCOPUS).
- [30] G.G.RajaSekhar, B.Basavaraja "Performance of Brushless DC Drive with Single Current Sensor Fed from PV with High Voltage Gain DC-DC Converter" in *IJPEDS Vol-9, No:1, March-2018* (SCOPUS).
- [31] G.G.RajaSekhar, B.Basavaraja "An Internal Current Controlled BLDC Motor Drive Supplied With PV Fed High Voltage Gain DC-DC Converter" in *IJECE Vol-8, No:2, April-2018* (SCOPUS).
- [32] G.G.RajaSekhar, B.Basavaraja "Photo-Voltaic System Fed High Voltage Gain DC-DC Converter Feeding BLDC Drive With Simplified Speed Control" in *ARNP Journal of Engineering and Applied Sciences Vol-12, No -24, December-2017* (SCOPUS).
- [33] P. L. Cochran, *Polyphase Induction Motors: Analysis, Design, and Applications*. New York: Marcel Dekker, 1989.
- [34] Baig, K., Prudhvi Raj, K., Raja Sekhar, G. G., Vijay Muni, T., & Kiran Kumar, M. (2020). Power quality enhancement with active power control. *Journal of Critical Reviews*, 7(9), 739–741. <https://doi.org/10.31838/jcr.07.09.143>
- [35] Ravi Kishore, D., Vijay Muni, T., & Srikanth, K. S. (2020). A novel power electronic-based maximum power point tracking technique for solar pv applications. In *Lecture Notes in Electrical Engineering* (Vol. 687, pp. 115–126). Springer Science and Business Media Deutschland GmbH. https://doi.org/10.1007/978-981-15-7245-6_10
- [36] G. S. Buja and M. P. Kazmierkowski, "Direct Torque Control of PWM Inverter-Fed AC Motors—A Survey," *IEEE Trans. Ind. Electron.*, vol. 51, no. 4, pp. 744–757, Aug. 2004.
- [37] A. Tripathi, A. M. Khambadkone, and S. K. Panda, "Torque Ripple Analysis and Dynamic Performance of a Space Vector Modulation Based Control Method for AC-Drives," *IEEE Trans. Power Electron.*, vol. 20, no. 2, pp. 485–492, 2005.
- [38] Vijay Muni, T., Srikanth, K. S., Venkatesh, N., & Sumedha, K. L. (2018). A high performance hybrid MPPT control scheme for a grid connected PV system based three level NPCMLI. *International Journal of Engineering and Technology(UAE)*, 7(2), 37–40. <https://doi.org/10.14419/ijet.v7i2.20.11741>
- [39] Muni, T. V., & Lalitha, S. V. N. L. (2020). Implementation of control strategies for optimum utilization of solar photovoltaic systems with energy storage systems. *International Journal of Renewable Energy Research*, 10(2), 716–726.
- [40] C. W. De Silva, *Intelligent Control: Fuzzy Logic Applications*. Boca Raton, FL: CRC Press, 1995.
- [41] A. Piegat, *Fuzzy Modeling and Control*. Heidelberg, Germany: Physica-Verlag, 2001.
- [42] Mounika Muppavarapu, G G Rajasekhar, T Vijay Muni, R B R Prakash, ENHANCEMENT OF POWER QUALITY IN A GRID CONNECTED UDE BASED PV INVERTER. *JCR*. 2020; 7(2): 340-343. doi:10.31838/jcr.07.02.65
- [43] Muni, T. V., Kishore, K. V., & Reddy, N. S. (2014). Voltage flicker mitigation by FACTS devices. In *2014 International Conference on Circuits, Power and Computing Technologies, ICCPCT 2014* (pp. 656–661). Institute of Electrical and Electronics Engineers Inc. <https://doi.org/10.1109/ICCPCT.2014.7054898>
- [44] M. N. Uddin, M. A. Abido, and M. A. Rahman, "Development and implementation of a hybrid intelligent controller for interior permanent magnet synchronous motor drive," *IEEE Trans. Ind. Appl.*, vol. 40, no. 1, pp. 68–76, Jan./Feb. 2004.
- [45] A. Consoli, E. Cerruto, A. Raciti, and A. Testa, "Adaptive vector control of induction motor drives based on a neuro-fuzzy approach," in *Proc. IEEE PESC*, 1994, pp. 225–232.
- [46] P. Z. Grabowski and F. Blaabjerg, "Direct torque neuro-fuzzy control of induction motor drive, DSP implementation," in *Proc. IEEE IECON*, 1998, pp. 657–662.
- [47] Bhargavi, R., Ganesh, P., Raja Sekhar, G. G., Prakash, R. B. R., & Muni, T. V. (2020). Design and implementation of novel multilevel inverter. *Journal of Advanced Research in Dynamical and Control Systems*, 12(2), 1322–1328. <https://doi.org/10.5373/JARDCS/V12I2/S20201169>
- [48] Tadvika, T., Srikanth, M., & Muni, T. V. (2015). THD reduction and voltage flicker mitigation in power system base on STATCOM. In *2014 International Conference on Information Communication and Embedded Systems, ICICES 2014*. Institute of Electrical and Electronics Engineers Inc. <https://doi.org/10.1109/ICICES.2014.7034161>
- [49] F. Blaschke, "The Principle of Field Orientation Applied to the new Transvector Closed Loop Control System for Rotating Field Machines", *Siemens Revue*, vol. 39, 1972, pp. 217 – 220.
- [50] J. Bocker, S. Mathapati, "State of the Art of Induction Motor Control", *IEEE International Conference on Electric Machines & Drives, IEMDC '07*, 3-5 May 2007, vol. 2, pp. 1459 – 1464.
- [51] Ravi Kishore, D., Chandra Sekhar, G., Prakash, R. B. R., & Vijay Muni, T. (2020). A novel power management scheme for distributed generators in a DC microgrid IOP: Conference series. In *IOP*

- [52] Shabnam, P., Priyanka, A. K., Vijay Muni, T., & Rajasekhar, S. (2020). PID controller based grid connected wind turbine energy system for power quality improvement. *Journal of Critical Reviews*, 7(7), 31–35. <https://doi.org/10.31838/jcr.07.07.06>
- [53] Moulali, S., Vijay Muni, T., Bala Subrahmanyam, Y., & Kesav, S. (2018). A flying capacitor multilevel topology for pv system with apod and pod pulse width modulation. *Journal of Advanced Research in Dynamical and Control Systems*, 10(2), 96–101.
- [54] Harshith, I., Raj, B. P., Raja Sekhar, G. G., & Muni, T. V. (2019). A novel methodology for single phase transformerless inverter with leakage current elimination for pv systems application. *International Journal of Innovative Technology and Exploring Engineering*, 8(6), 1017–1021.
- [55] Mounika Muppavarapu, G G Rajasekhar, T Vijay Muni, R B R Prakash. ENHANCEMENT OF POWER QUALITY IN A GRID CONNECTED UDE BASED PV INVERTER. *JCR*. 2020; 7(2): 340-343. doi:10.31838/jcr.07.02.65
- [56] Bhargavi, R., Ganesh, P., Raja Sekhar, G. G., Prakash, R. B. R., & Muni, T. V. (2020). Design and implementation of novel multilevel inverter. *Journal of Advanced Research in Dynamical and Control Systems*, 12(2), 1322–1328. <https://doi.org/10.5373/JARDCS/V12I2/S20201169>
- [57] J. Rodriguez, J.-S. Lai, and F. Z. Peng, “Multilevel inverters: A survey of topologies, controls, and applications,” *IEEE Trans. Ind. Electron.*, vol. 49, no. 4, pp. 724–738, Aug. 2002.
- [58] Baig, K., Prudhvi Raj, K., Raja Sekhar, G. G., Vijay Muni, T., & Kiran Kumar, M. (2020). Power quality enhancement with active power control. *Journal of Critical Reviews*, 7(9), 739–741. <https://doi.org/10.31838/jcr.07.09.143>
- [59] Ravi Kishore, D., Vijay Muni, T., & Srikanth, K. S. (2020). A novel power electronic-based maximum power point tracking technique for solar pv applications. In *Lecture Notes in Electrical Engineering* (Vol. 687, pp. 115–126). Springer Science and Business Media Deutschland GmbH. https://doi.org/10.1007/978-981-15-7245-6_10
- [60] M. N. Uddin and H. Wen, “Development of a self-tuned neuro-fuzzy controller for induction motor drives,” *IEEE Trans. Ind. Appl.*, vol. 43, no. 4, pp. 1108–1116, Jul./Aug. 2007.
- [61] A. Yamamoto, Y. Kitamura, and Y. Yamane, “Computational efficiencies of approximated exponential functions for transport calculations of the characteristics method,” *Ann. Nucl. Energy*, vol. 31, no. 9, pp. 1027–1037, Jun. 2004.