

# Paladim Compiler

Alexander Worm Olsen - bdj816

Chi Dan Pham - vqr853

Troels Thomsen - qvw203

Group Project

December 20 2013

Department of Computer Science

University of Copenhagen

# Contents

<b>Introduction</b>	<b>2</b>
<b>Task 1</b>	<b>2</b>
Parser.grm . . . . .	2
Terminals . . . . .	2
Precedence Rules . . . . .	2
Non-Terminals . . . . .	3
Grammar . . . . .	3
Program structure . . . . .	4
Statements, Values and Expressions . . . . .	4
Parameters and Procedures . . . . .	4
Driver.sml . . . . .	4
Lexer.lex . . . . .	5
<b>Task 2</b>	<b>5</b>
TpAbSyn.sml . . . . .	5
TpInterpret.sml . . . . .	5
Type.sml . . . . .	5
Compiler.sml . . . . .	6
<b>Task 3</b>	<b>6</b>
Type.sml . . . . .	6
<b>Task 4</b>	<b>6</b>
<b>Task 5</b>	<b>6</b>
TpInterpreter.sml . . . . .	7
Compiler.sml . . . . .	7
<b>Testing</b>	<b>8</b>
<b>Appendix A. Parser.grm</b>	<b>9</b>
<b>Appendix B. Driver.sml</b>	<b>10</b>
<b>Appendix C. TpAbSyn.sml</b>	<b>11</b>
<b>Appendix D. TpInterpret.sml</b>	<b>12</b>
<b>Appendix E. Type.sml</b>	<b>13</b>

**Appendix F. Compiler.sml**

**14**

## Introduction

The goal of the group assignment is to implement a compiler for the Paladim language using a bottom-up grammar. The language we use for this implementation is Standard ML. The majority of the compiler has already been implemented, and the changes we made are described in the individual tasks below. The first two tasks of the assignment were completed as a milestone assignment. We have made slight changes since the milestone, which improves the work done in these two tasks. A full description of these tasks and all the changes we made, are also included here.

## Task 1

We were asked to implement the grammar production rules for the paladim language, which is described in the group project description document.

In order to implement the grammar, we have edited the empty file *Parser.grm*, which was already included in the source code handout. We also edited the *Driver.sml* and the *Lexer.lex* source code file, to use our new parser structure instead of the LL1Parser which was included in the handout.

For inspirational purposes we used the file *example.pdf* which we found on absalon, and the groupproject description document. In these documents we found examples for creating type precedence, how to construct terminals and non-terminals, and how to use them correctly in the grammar.

The following sections describe the changes made to each file respectively.

### Parser.grm

#### Terminals

The first definition in the parser, is the definition of terminals, which in mosmlyac is called tokens. Here we use the abstract syntax type definitions to define the types of our tokens. The tokens themselves are defined in the *Lexer.lex* file. We simply found all tokens in the lexer, and defined tokens for them.<sup>1</sup>

#### Precedence Rules

Next we define our precedence rules, to prevent shift / reduce conflicts. The rules at the bottom take the highest precedence. We use left associative precedence for

---

<sup>1</sup>See Appendix A. Parser.grm figure 1.

arithmetic operations, ranking *TTimes* and *TSlash* higher than *TPlus* and *TMinus*.

We define comparison operations *TLess* and *TEq* as non-associative, since it is not specified whether comparison is associative in Paladim in the project description.

The logical operation *TNot* is defined as non-associative because it is unary. We define the other logical operations *TAnd* and *TOr* as left-associative (they can be either left- or right-associative, but should not be non-associative). Here *TNot* takes precedence over *TAnd* which takes precedence over *TOr*.

The last two precedence rules are defined to resolve the shift / reduce conflict, which occurs when trying to write productions for If-Then-Else and If-Then. This conflict occurs in the following scenario.

```
if a > b then
  if c = d then
    return a
  else
    return b
```

In this scenario the parser does not know whether to match the production for If-Then-Else, or the production for If-Then. If it shifts, the else belongs to the inner if-statement, but if it reduces, the else belongs to the outer if-statement. In this scenario, we actually always wants to shift, because the else should belong to the closest previous if-then-statement. In order to accomplish this, we define TElse to take precedence over "LowPrec". We later assign "LowPrec" to the If-Then production grammar, and thus resolve the shift / reduce conflict.<sup>2</sup>

## Non-Terminals

In this section we define our start symbol, and the non-terminals for our productions. The types used for the non-terminals are defined in *AbSyn.sml*. The actual non-terminals are defined in figure 3 in the group project definition document. The start symbol "Program" was defined by us, in order to handle end of file.<sup>3</sup>

## Grammar

In this section we define the grammar<sup>4</sup> used by the parser. For easier analysis we have divided the grammar into sections. In general we built the grammar by looking

<sup>2</sup>See Appendix A. Parser.grm figure 1.

<sup>3</sup>See Appendix A. Parser.grm, figure 2

<sup>4</sup>See Appendix A. Parser.grm figure 2-5

at the production definitions in figure 3 in the group project definition. The type we return in the productions, are defined in the *AbSyn.sml*.

### Program structure

The most important change in this section, is the Block production. To begin with we had a DBlock production, as described in figure 3 in the group project definition. This caused a shift / reduce conflict, which we resolved by combining the DBlock with the Block production.<sup>5</sup>

### Statements, Values and Expressions

The most important change in this section, is the *TIf Exp TThen Block %prec LowPrec* production. As described in the non-terminal definitions, we need to assign lower precedence to the If-Then production. This is done by adding *%prec LowPrec* at the end of the production.<sup>6</sup>

**The Exp LVal production** in this section might be problematic. This production needs to return an *AbSyn.LValue(LVal, Pos)*. However this is not possible, because we call another production which only returns an LVal without a position. To solve this issue, we changed the non-terminal definition from *<AbSyn.LVAL>* to *<AbSyn.LVAL\*AbSyn.Pos>*<sup>7</sup>. This allows us to give our LValue the correct position, without modifying the syntax definition in *AbSyn.sml*.

### Parameters and Procedures

At the end we have our simple definitions for parameters and declarations.<sup>8</sup>

### Driver.sml

In the driver file we have uncommented the two lines which was meant for the LL1 parser and instead inserted the appropriate ones for our parser (line 57 and 69). Furthermore we have uncommented the *Parser.ParseError*, because this error message will be caught by the *Parsing.ParseError*, and instead only created compile errors.<sup>9</sup>

---

<sup>5</sup>See Appendix A. Parser.grm figure 3.

<sup>6</sup>See Appendix A. Parser.grm figure 3.

<sup>7</sup>See Appendix A. Parser.grm figure 2.

<sup>8</sup>See Appendix A. Parser.grm figure 5.

<sup>9</sup>See appendix B. Driver.sml figure 6.

### **Lexer.lex**

In the *Lexer.lex* we have changed all instances of LL1parser to Parser, thereby including our newly created Parser.grm instead of the handout. Please note that this code is left out.

## **Task 2**

In this task we were to implement the functionality of multiplication, division, or and not in Paladim. To do this we had to go through several source code files and implement the functionality of each of them. The files we've changed include; *Compiler.sml*, *TpInterpret.sml*, *Type.sml* and *TpAbSyn.sml*. Furthermore we were to make sure our precedence for boolean operators and arithmetic operations were correct, please note that this was done already in task 1<sup>10</sup>

### **TpAbSyn.sml**

In order to implement the functionality of the four operations we started in *TpAbSyn.sml*, where we first uncommented the four of them in the datatype for *exp*, afterwards we made pretty printing for the four of the functions with inspiration from the ones already implemented, then a function that was able to find the position of each of the operations and at last we implemented the functionality to find the type of the operations.<sup>11</sup>

### **TpInterpret.sml**

In this file we implemented the functionality of the four functions for the Interpreter, this was done with inspiration from the ones already implemented, this was done in *evalExp*. In order to implement the to logical operations we had needed the a helper function for each of them. These changes made the functionality of our four functions work in the interpreter.<sup>12</sup>

### **Type.sml**

In order to implement the functions for our compiler aswell we had to include them in the *type.sml*. These were aswell inspired by the ones already there. Please note that the types stated weren't added until task 3, and that the one for multiplication is left out because it's very similar to the one for division.<sup>13</sup>

---

<sup>10</sup>See Appendix A. Parser.grm figure 1.

<sup>11</sup>See Appendix C. TpAbSyn.sml figure 7.

<sup>12</sup>See Appendix D. TpInterpret.sml figure 8.

<sup>13</sup>See Appendix E. Type.sml figure 9

### Compiler.sml

The last step for the full implementation of multiplication, division, or and not were to implement them in *compiler.sml*. The functionality of the four operations were straight forward and inspired by the ones already implemented. For the functionality of not in mips code we used the mips instruction *XORI*. This is due to the fact that there doesn't exist a *NOT* instruction in mips. *XOR* returns 1 (true) if one of the arguments is different from 1. In order to use this in the not scenario we pass the value to be negated, together with 1 as the second argument. *XORI* then returns true if the input argument is 0 and false if the argument is 1, as we would expect of not.

## Task 3

In this task we were to implement typechecking for Paladims library functions *Read()* and *New()*

### Type.sml

The major change in the task, was changing the *typeCheckExp* function, to correctly typecheck the functions *read* and *new*. In order to accomplish this, the typechecker needs to determine the expected type of the argument calling context. In the majority of the cases we changed from *UnknownType* to *KnownType* (<expected type>).

The actual changes can be found in figure 9, 10 and 11 in appendix E. Two operations differ from this; *Less* and *Equal*, these two still holds *UnknownType* for *argument1* but here the second argument is the same as what the 1. argument turns out to be. This is due to the fact that they are polymorphic. Even tho they are polymorphic, the types of both arguments needs to be equal. We cannot infer exactly what types, but only that they must be equal.

The major reason we do not inherit the expected type, is due to the fact that not all of our operators are polymorphic.<sup>14</sup>

## Task 4

## Task 5

In this task we were to change the way Paladims procedures passes their arguments from call-by-value to call-by-value-result.

---

<sup>14</sup>Appendix E. *Type.sml* figure 10, 11 and 12.



**TpInterpreter.sml**

In order to make Paladim procedures use call-by-value-result we change the *TpInterpreter.sml*. We use the references from our innerVtable and swap them with the references for the according arguments in the outerVtable.<sup>15</sup> To do this we used the already implemented arguments *fargs* and *aexps*.

**Compiler.sml**

---

<sup>15</sup>See appendix D. TpInterpreter.sml figure 9

## Testing

We have made two test examples; one that covers the problem with nested *if then else* and another one that tests precedence with multiplication and addition. We ran the compiled programs in Mars and they returned the expected results ("If-then-else virker!!!" and "det virker jo").

## Appendix A. Parser.grm

## Appendix B. Driver.sml

## Appendix C. TpAbSyn.sml

## Appendix D. TpInterpret.sml

## Appendix E. Type.sml

## Appendix F. Compiler.sml



```

%{

%}

/* Token type definitions (will often be used in the Lexer)
 * Tokens use position attribute for demonstration
 * (see below for Lexer)
 * As mentioned, the SML code above ends up after
 * this data declaration,
 * so we cannot use any types defined above
 * at this point of the file.
 * tokens needs to be of sml types
 * through the rules the should be converted to an absyn syntaxtree */

%token <AbSyn.Pos> TProgram TFunction TProcedure TVar TBegin TEnd
          TIf TThen TElse TWhile TDo TReturn TArray TOf
          TInt TBool TChar TAnd TOr TNot TAssign TPlus TMinus
          TTimes TSlash TEq TLess TLParen TRParen TLBracket
          TRBracket TLCurly TRCurly TComma TSemi TColon TEOF

%token <bool*AbSyn.Pos> TBLit
%token <int*AbSyn.Pos> TNLit
%token <char*AbSyn.Pos> TCLit
%token <string*AbSyn.Pos> TSLit TId

%nonassoc LowPrec
%nonassoc TElse
%right TOr
%right TAnd
%nonassoc TNot
%nonassoc TEq TLess
%left TPlus TMinus
%left TTimes TSlash

/* start symbol */
%start Program

```

Figure 1: The tokens and precedence rules for our grammar in Parser.grm.

```

/* types returned by rules below */
%type <AbSyn.Prog> Program
%type <AbSyn.Prog> Prog
%type <AbSyn.Prog> FunDecs
%type <AbSyn.FunDec> FunDec
%type <AbSyn.StmtBlock> Block
%type <AbSyn.Stmt list> SBlock
%type <AbSyn.Stmt list> StmtSeq
%type <AbSyn.Stmt> Stmt
%type <AbSyn.LVAL*AbSyn.Pos> LVal
%type <AbSyn.Exp option> Ret
%type <AbSyn.Exp> Exp
%type <AbSyn.Dec list> PDecl Params
%type <AbSyn.Dec> Dec
%type <AbSyn.Dec list> Decs
%type <AbSyn.Type> Type
%type <AbSyn.Exp list> CallParams Exps

%%

/* rules — a separate start rule is added automatically */

/* PROGRAM STRUCTURE*/
Program: Prog TEOF { $1 }
;

Prog :
    TProgram TId TSemi FunDecs { $4 }
;

FunDecs :
    FunDecs FunDec { $1 @ [$2] }
    | FunDec { [$1] }
;

```

Figure 2: The types and some of the grammar for the Parser.grm.

```

FunDec :
    TFunction TId TLParen PDecl TRParen TColon Type Block TSemi
        { AbSyn.Func($7, #1 $2, $4, $8, $1) }
    | TProcedure TId TLParen PDecl TRParen Block TSemi
        { AbSyn.Proc(#1 $2, $4, $6, $1) }
;

Block :
    SBlock { AbSyn.Block ([], $1) }
    | TVar Decs SBlock { AbSyn.Block ($2, $3) }
;

SBlock :
    TBegin StmtSeq TSemi TEnd { $2 }
    | Stmt { [$1] }
;

StmtSeq :
    StmtSeq TSemi Stmt { $1 @ [$3] }
    | Stmt { [$1] }
;

/* STATEMENTS */
Stmt :
    TId TLParen CallParams TRParen { AbSyn.ProcCall (#1 $1, $3, #2 $1) }
    | TIf Exp TThen Block TElse Block { AbSyn.IfThEl ($2, $4, $6, $1) }
    | TIf Exp TThen Block %prec LowPrec
        { AbSyn.IfThEl ($2, $4,
                        AbSyn.Block ([], []),
                        $1) }

/* prec gives precedence as LowPrec */
    | TWhile Exp TDo Block { AbSyn.While ($2, $4, $1) }
    | TReturn Ret { AbSyn.Return ($2, $1) }
    | LVal TAssign Exp { AbSyn.Assign ($1, $3, $2) }
;

```

Figure 3: More of the grammar for our Parser.grm.

```

/* L-VALUES AND EXPRESSIONS */
LVal :
    TId                                     { AbSyn.Var (#1 $1) }
    | TId TLBracket Exps TRBracket        { AbSyn.Index (#1 $1, $3) }
    ;

Ret :
    Exp                                     { SOME $1 }
    |                                     { NONE }
    ;

Exp :
    TNLit                                  { AbSyn.Literal (AbSyn.BVal(
    |                                     AbSyn.Num(#1 $1)), #2 $1) }
    | TBLit                                { AbSyn.Literal (AbSyn.BVal(
    |                                     AbSyn.Log(#1 $1)), #2 $1) }
    | TCLit                                { AbSyn.Literal (AbSyn.BVal(
    |                                     AbSyn.Chr(#1 $1)), #2 $1) }
    | TSLit                                { AbSyn.StrLit (#1 $1, #2 $1) }
    | TLCurly Exps TRCurly                 { AbSyn.ArrLit ($2,$1) }
    | LVal                                  { AbSyn.LValue (#1 $1, #2 $1) }
    | TNot Exp                             { AbSyn.Not ($2, $1) }
    | Exp TPlus Exp                        { AbSyn.Plus ($1, $3, $2) }
    | Exp TMinus Exp                       { AbSyn.Minus ($1, $3, $2) }
    | Exp TTimes Exp                       { AbSyn.Times ($1, $3, $2) }
    | Exp TSlash Exp                       { AbSyn.Div ($1, $3, $2) }
    | Exp TEq Exp                          { AbSyn.Equal ($1, $3, $2) }
    | Exp TLess Exp                        { AbSyn.Less ($1, $3, $2) }
    | Exp TAnd Exp                         { AbSyn.And ($1, $3, $2) }
    | Exp TOr Exp                          { AbSyn.Or ($1, $3, $2) }
    | TLParen Exp TRParen                  { $2 }
    | TId TLParen CallParams TRParen      { AbSyn.FunApp (#1 $1, $3, # 2$1) }
    ;

/* VARIABLE AND PARAMETER DECLARATIONS, TYPES */
PDecl :
    Params                                 { $1 }
    |                                     { [] }
    ;

```

Figure 4: More of the grammar for our Parser.grm.

```

Params :
    Params TSemi Dec          { $1 @ [$3] }
    | Dec                     { [$1] }
;

Dec :
    TId TColon Type          { AbSyn.Dec (#1 $1, $3, #2 $1) }
;

Decs :
    Decs Dec TSemi           { $1 @ [$2] }
    | Dec TSemi              { [$1] }
;

Type :
    TInt                     { AbSyn.Int ($1) }
    | TChar                  { AbSyn.Char ($1) }
    | TBool                  { AbSyn.Bool ($1) }
    | TArray TOf Type        { AbSyn.Array ($3,$1) }
;

/* FUNCTION AND PROCEDURE PARAMETERS AND INDEX LISTS */
CallParams :
    Exps                     { $1 }
    |                        { [] }
;

Exps :
    Exp TComma Exps          { $1 :: $3 }
    | Exp                    { [$1] }
%%

(* SML trailer *)

```

Figure 5: The last of the grammar for our Parser.grm.

```
fun compile arg path =
  let
    val inpath = path
    val outpath = Path.base path ^ ".asm"
    val lexbuf = createLexerStream (BasicIO.open_in inpath)
  in
    let
      (* val pgm = LL1Parser.parse Lexer.Token lexbuf *)
      (* COMMENT LINE ABOVE AND UNCOMMENT *)
      (* THE LINE BELOW TO USE YOUR PARSER *)
      val pgm = Parser.Program Lexer.Token lexbuf
    in case arg of
      "-ti" => typedInterpret (typeCheck pgm)
    | "-c"  => compileNormal pgm outpath
    | other => print ("'" ^ other ^ "': Unknown mode of operation.\n")
    end
    handle
      Parsing.yyexit ob => errorMsg "Parser-exit\n"
    | Parsing.ParseError ob =>
      (* errorMsgAt "Parsing error" (Lexer.getPos lexbuf) *)
      (* COMMENT LINE ABOVE AND UNCOMMENT *)
      (* THE LINE BELOW TO USE YOUR PARSER *)
      errorMsgAt "Parsing error" (Lexer.getPos lexbuf)

    (* | Parser.ParseError s =>
      errorMsgAt ("Parse error: " ^ s) (Lexer.getPos lexbuf) *)
```

Figure 6: The Driver.sml changes for our parser.grm.

```

| Times    of Exp * Exp      * Pos      (* e.g., x * 3 *)
| Div      of Exp * Exp      * Pos      (* e.g., x / 3 *)
| Or       of Exp * Exp      * Pos (* e.g., (x=5) or y *)
| Not      of Exp            * Pos (* e.g., not (x>3) *)

| pp_exp (Or      (e1, e2, _)) = "( " ^ pp_exp e1 ^ " | " ^
                                   pp_exp e2 ^ " )"
| pp_exp (Not     (e1,      _)) = "( not " ^ pp_exp e1 ^ " )"
| pp_exp (Times   (e1, e2, _)) = "( " ^ pp_exp e1 ^ " * " ^
                                   pp_exp e2 ^ " )"
| pp_exp (Div     (e1, e2, _)) = "( " ^ pp_exp e1 ^ " / " ^
                                   pp_exp e2 ^ " )"

| typeOfExp ( Or      (_,_,_) ) = BType Bool
| typeOfExp ( Not     (_,  _ ) ) = BType Bool
| typeOfExp ( Times   (a,b,_) ) = typeOfExp a
| typeOfExp ( Div     (a,b,_) ) = typeOfExp a

| posOfExp ( Or      (_,_,p) ) = p
| posOfExp ( Not     (_,  p) ) = p
| posOfExp ( Times   (_,_,p) ) = p
| posOfExp ( Div     (_,_,p) ) = p

```

Figure 7: TpAbSyn.sml with the functionality of the four operations implemented for task 2.

```

fun evalOr (BVal (Log b1), BVal (Log b2), pos) =
    BVal (Log (b1 orelse b2))
| evalOr (v1, v2, pos) =
    raise Error( "Or: argument types do not match. Arg1: " ^
        pp_val v1 ^ ", arg2: " ^ pp_val v2, pos )

fun evalNot (BVal (Log b1), pos) = BVal (Log (not b1))
| evalNot (v1, pos) =
    raise Error( "Not: argument types do not match. Arg1: " ^
        pp_val v1, pos )

| evalExp ( Div(e1, e2, pos), vtab, ftab ) =
    let val res1 = evalExp(e1, vtab, ftab)
        val res2 = evalExp(e2, vtab, ftab)
    in evalBinop(op div, res1, res2, pos)
    end

| evalExp ( Times(e1, e2, pos), vtab, ftab ) =
    let val res1 = evalExp(e1, vtab, ftab)
        val res2 = evalExp(e2, vtab, ftab)
    in evalBinop(op *, res1, res2, pos)
    end

| evalExp ( Or(e1, e2, pos), vtab, ftab ) =
    let val r1 = evalExp(e1, vtab, ftab)
        val r2 = evalExp(e2, vtab, ftab)
    in evalOr(r1, r2, pos)
    end

| evalExp ( Not(e1, pos), vtab, ftab ) =
    let val r1 = evalExp(e1, vtab, ftab)
    in evalNot(r1, pos)
    end
end

```

Figure 8: TpInterpret.sml changes for task 2



```

let val new_vtab = bindTypeIds(fargs, aargs, fid, pdcl, pcall)
    val res = execBlock( body, new_vtab, ftab )
in ( case (rtp, res) of
    (NONE, _) =>
        let
            fun call_args [] [] = NONE
              | call_args (x::xs) (y::ys) =
                  let
                      val hitler = updateOuterVtable vtab new_vtab (x, y)
                  in
                      call_args xs ys
                  end
              | call_args _ _ = raise Error("Number of functions args" ^
                                             " does not match " ^
                                             "declaration, at ", pdcl)
        in
            call_args aexps fargs
        end
    and updateOuterVtable vtabOuter vtabInner (TpAbSyn.LValue (lval1, pos1),
                                                TpAbSyn.Dec ((id2, tp), pos2))
        =
            let val lenin = (case lval1 of
                Var(id, tp) => id
              | Index((id, tp), e) => id)
            in
                case (SymTab.lookup lenin vtabOuter,
                     SymTab.lookup id2 vtabInner) of
                    (SOME x, SOME y) => x := !y
                  | _ => raise Error("Procedure argument " ^
                                     "not in caller", pos1)
            end
        | updateOuterVtable _ _ _ = ()

```

Figure 9: TpInterpreter task 5

```

(* Must be modified to complete task 3 *)
| typeCheckExp( vtab, AbSyn.Div (e1, e2, pos), _ ) =
  let val e1_new = typeCheckExp(vtab, e1, KnownType (BType Int) )
      val e2_new = typeCheckExp(vtab, e2, KnownType (BType Int) )
      val (tp1, tp2) = (typeOfExp e1_new, typeOfExp e2_new)
  in if typesEqual(BType Int, tp1) andalso
      typesEqual(BType Int, tp2)
    then Div(e1_new, e2_new, pos)
    else raise Error("in type check minus exp, one argument " ^
                     "is not of int type " ^ pp_type tp1 ^
                     " and " ^ pp_type tp2 ^ " at ", pos)
  end

(* Must be modified to complete task 3 *)
| typeCheckExp ( vtab, AbSyn.Or (e1, e2, pos), _ ) =
  let val e1_new = typeCheckExp(vtab, e1, KnownType (BType Bool) )
      val e2_new = typeCheckExp(vtab, e2, KnownType (BType Bool) )
      val (tp1, tp2) = (typeOfExp e1_new, typeOfExp e2_new)
  in if typesEqual(BType Bool, tp1) andalso
      typesEqual(BType Bool, tp2)
    then Or(e1_new, e2_new, pos)
    else raise Error("in type check and exp, one argument is " ^
                     "not of bool type " ^
                     pp_type tp1 ^ " and " ^ pp_type tp2 ^ " at ", pos)
  end

(* Must be modified to complete task 3 *)
| typeCheckExp ( vtab, AbSyn.Not (e1, pos), _ ) =
  let val e1_new = typeCheckExp(vtab, e1, KnownType (BType Bool) )
      val (tp1) = (typeOfExp e1_new)
  in if typesEqual(BType Bool, tp1)
    then Not(e1_new, pos)
    else raise Error("in type check and exp, one argument is not " ^
                     "of bool type " ^
                     pp_type tp1 ^ " at ", pos)
  end

```

Figure 10: Changes made in type.sml for task 2 and task 3

```

(* Must be modified to complete task 3 *)
| typeCheckExp ( vtab, AbSyn.Less (e1, e2, pos), _ ) =
    let val e1_new = typeCheckExp(vtab, e1, UnknownType )
        val e2_new = typeCheckExp(vtab, e2, KnownType (typeOfExp e1_new))
        val (tp1, tp2) = (typeOfExp e1_new, typeOfExp e2_new)
        (* check that tp1 is not an array type *)
        val () = case tp1 of
            Array _ => raise Error("in type check less, " ^
                                   "first expression " ^
                                   pp_exp e1_new ^
                                   "is an array (of type) " ^
                                   pp_type tp1 ^ " at ", pos)
            | _ => ()
    in if typesEqual(tp1, tp2)
        then Less(e1_new, e2_new, pos)
        else raise Error("in type check less exp, argument types " ^
                        " do not match " ^
                        pp_type tp1 ^ " <> " ^ pp_type tp2 ^ " at ", pos)
    end

(* Must be modified to complete task 3 *)
| typeCheckExp ( vtab, AbSyn.Equal(e1, e2, pos), _ ) =
    let val e1_new = typeCheckExp(vtab, e1, UnknownType)
        val e2_new = typeCheckExp(vtab, e2,
                                   KnownType (typeOfExp e1_new) )
        val (tp1, tp2) = (typeOfExp e1_new, typeOfExp e2_new)
        (* check that tp1 is not an array type *)
        val () = case tp1 of
            Array _ => raise Error("in type check equal, " ^
                                   "first expression " ^
                                   pp_exp e1_new ^
                                   "is an array (of type) " ^
                                   pp_type tp1 ^ " at ", pos)
            | _ => ()
    in if typesEqual(tp1, tp2)
        then Equal(e1_new, e2_new, pos)
        else raise Error("in type check equal exp, " ^
                        " argument types do not match " ^
                        pp_type tp1 ^ " <> " ^ pp_type tp2 ^ " at ", pos)
    end

```

Figure 11: Changes in type.sml for task 3

```

(* function call to 'new' uses expected type to infer
   the to-be-read result *)
| typeCheckExp ( vtab, AbSyn.FunApp ("new", args, pos), etp ) =
  ( case expectedBasicType etp of
    SOME btp =>
      let
        val typedargs = map (fn n =>
          typeCheckExp(vtab, n, KnownType (BType Int))) args
        val types = map typeOfExp typedargs
        val rtp = Array ( length args, btp)
      in
        if List.all (fn n => typesEqual(BType Int, n)) types
        then
          FunApp(("new", (types, SOME rtp)), typedargs, pos)
        else
          raise Error("declared array dimensions are not " ^
            "integers, at ", pos)
      end
    end

| typeCheckExp( vtab, AbSyn.LValue( AbSyn.Index(id, inds), pos ), _ ) =
  let
    val indices = length inds
    val newinds = map (fn n=>
      typeCheckExp(vtab, n, KnownType (BType Int))) inds
    val correctinds = List.all (fn n =>
      typesEqual(BType Int, typeOfExp n)) newinds
  in
    case SymTab.lookup id vtab of
      SOME (Array(r, t)) =>
        if indices > 0 andalso r = length inds andalso correctinds
        then
          LValue(Index((id, Array(r, t)), newinds), pos)
        else
          raise Error("ill-formed array indexing at ", pos)
      | _ => raise Error("in type check variable, var "
        ^ id ^ "not in VTab, at", pos)
  end
end

```

Figure 12: changes in type.sml for task 3 and 4

```

| compileExp( vtable, Times (e1, e2, _), place ) =
    let val t1 = "times1_" ^ newName()
        val c1 = compileExp(vtable, e1, t1)
        val t2 = "times2_" ^ newName()
        val c2 = compileExp(vtable, e2, t2)
    in c1 @ c2 @ [Mips.MUL (place, t1, t2)]
    end

| compileExp( vtable, Div (e1, e2, _), place ) =
    let val t1 = "div1_" ^ newName()
        val c1 = compileExp(vtable, e1, t1)
        val t2 = "div2_" ^ newName()
        val c2 = compileExp(vtable, e2, t2)
    in c1 @ c2 @ [Mips.DIV (place, t1, t2)]
    end

| compileExp( vtable, Or(e1, e2, _), place ) =
    let val t1 = "or1_" ^ newName()
        val c1 = compileExp(vtable, e1, t1)
        val t2 = "or2_" ^ newName()
        val c2 = compileExp(vtable, e2, t2)
        val lA = "_or_" ^ newName()
    in
        c1 @ c2 @ [Mips.OR (place, t1, t2)]
    end

| compileExp( vtable, Not(e1, _), place ) =
    let val t1 = "not1_" ^ newName()
        val c1 = compileExp(vtable, e1, t1)
        val lA = "_not_" ^ newName()
    in
        c1 @ [Mips.XORI (place, t1, "1")]
    end

```

Figure 13: The compiler.sml changes for task 2

```

| compileLVal( vtab : VTab, Index ((n,t),inds) : LVAL, pos : Pos ) =
  ( case SymTab.lookup n vtab of
    SOME mem =>
      let
        val rank = length inds
        val strides = 4 * (rank - 1)

        (* Variables for generated MIPS code *)
        val arrptr = "_arrptr_" ^ newName()
          (* pointer to a *)
        val ind_reg = "_indx_" ^ newName()
          (* current index i_k *)
        val dim_reg = "_dimx_" ^ newName()
          (* current dimension d_k *)
        val flat = "_flatIndx_" ^ newName()
          (* flat index value *)
        val ctr = "_ctr_" ^ newName()
          (* loop counter (init to rank) *)
        val tmp = "_tmp_" ^ newName()
          (* tmp register to check bounds *)
        val calc_name = "_calc_and_check_" ^ newName()
          (* label name for loop *)
        val str_sz = "_strides_" ^ newName()
          (* Number of strides (to skip) *)

        (* Generates code for adding the indices to the stack *)
        fun copy_to_stack ([], code, n, l) =
          ( Mips.ADDI(SP, SP, makeConst(~4*l)) ) :: code
        | copy_to_stack (i :: inds, code, n, l) =
          let
            val temp = "_temp_" ^ newName()
          in
            copy_to_stack(inds,
              code @ (compileExp(vtab, i, temp)) @
              [ Mips.ADD (ind_reg, "0", temp),
                Mips.SW (ind_reg, SP, makeConst n) ],
              n+4, l)
          end

        (* If basic type size is k, returns log2(k) (easier to calc l
        fun element_size w = (case w of
          (Array(a, Int)) => "2"
        | (Array(a, Bool)) => "0"
        | (Array(a, Char)) => "0"
        | _ => raise Error("Impossible!!!", pos))

```

Figure 14: Compiler.sml for Task 4

```

(* Initiates variables *)
val init_code =
  [ Mips.ADDI (arrptr, mem, "0"),
    Mips.ADDI (ind_reg, "0", "0"),
    Mips.ADDI (flat, "0", "0"),
    Mips.ADDI (ctr, "0", makeConst rank),
    Mips.ADDI (str_sz, "0", makeConst strides)]

(* Checks if array index is out of bounds *)
val calc_out_of_bounds =
  [ Mips.SUB (tmp, dim_reg, ind_reg),
    Mips.SLT (dim_reg, dim_reg, tmp),
    Mips.SLTI (tmp, tmp, "1"),
    Mips.OR (tmp, tmp, dim_reg),
    Mips.BNE (tmp, "0", "_IllegalArrIndexError_")]

(* Loop: checks if each index is within bounds
   and calculates flat index *)
val calc_and_check =
  [ Mips.LABEL (calc_name),
    Mips.LW (dim_reg, arrptr, "0"),
    (* loads current dim *)
    Mips.MUL (flat, flat, dim_reg),
    Mips.LW (ind_reg, SP, "0")]
  (* loads current index *)
  @ calc_out_of_bounds @
  [ Mips.ADD (flat, flat, ind_reg),
    Mips.ADDI (arrptr, arrptr, "4"),
    (* points to next index *)
    Mips.ADDI (SP, SP, "4"),
    (* points to next dim *)
    Mips.ADDI (ctr, ctr, "-1"),
    Mips.BNE (ctr, "0", calc_name)]

```

Figure 15: Compiler.sml task 4

```
(* Calculates the address of the array index *)
val get_address =
  [ Mips.ADD(arrptr, arrptr, str_sz),
    (* skip the strides *)
    Mips.LW(arrptr, arrptr, "0"),
    Mips.SLL (flat, flat, element_size t),
    Mips.ADD (arrptr, arrptr, flat)]
in
  (copy_to_stack(inds, [], 0, rank) @
   init_code @
   calc_and_check @
   get_address,
  Mem arrptr)
end
```

Figure 16: Compiler.sml task 4



```

(* Swap temporary registers with caller registers, after
   the procedure has finished *)
and popArgs (TpAbSyn.LValue(lval, pos)::es) vtable
            reg ((Mips.ORI(rd, rs, v))::ts) =
    let
        val code = popArgs es vtable (reg+1) ts
    in
        code @ [Mips.MOVE (rs, makeConst reg)]
    end
| popArgs (e::es) vtable reg (t::ts) = popArgs (e::es) vtable reg ts
(* if expression has more than 1 mips command, we want to pass the same
   expression along again. *)
| popArgs _ vtable reg [] = []
| popArgs [] vtable reg _ = []

| ProcCall ((n,_), es, p) =>
    let
        val (mvcode, maxreg) = putArgs es vtable minReg
        val prod_codes = popArgs es vtable minReg mvcode
        val new_mvcode = mvcode
            @ [Mips.JAL (n, List.tabulate (maxreg, fn reg => makeConst reg))]
            @ prod_codes
    in
        new_mvcode
    end
end

val new_argcode =
    if isProc andalso (not (fname = "main"))
    then map (fn (vname, reg) => Mips.MOVE (reg, vname)) movePairs
    else []
val body = compileStmts block vtable (fname ^ "_exit")
val (body1, _, maxr, spilled) = (* call register allocator *)
    RegAlloc.registerAlloc ( argcode @ body @ new_argcode )

```

Figure 17: Compiler.sml task 5