

# Race Data Analysis

Goal: Develop graphs of WR statistics of certain tracks over time

Test the hypothesis: World Record Times have been cut down as new technology in racing becomes better

## Import Data and Modules

```
from seaborn import FacetGrid

from DataFrameImport import get_schema_info, list_schemas, schema

import pandas as pd
import seaborn as sns

path = 'resources/pickled_tables/'
extension = '.plk'

race_data_table = 'race_data'
race_table = 'race'
circuit_table = 'circuit'

race_data_file = path + race_data_table + extension
race_file = path + race_table + extension
circuit_file = path + circuit_table + extension

race_data = pd.read_pickle(race_data_file)
race = pd.read_pickle(race_file)
circuit = pd.read_pickle(circuit_file)

race_data
```

	race_id	type	position_display_order	\
0	290	PRE_QUALIFYING_RESULT	1	
1	290	PRE_QUALIFYING_RESULT	2	
2	290	PRE_QUALIFYING_RESULT	3	
3	290	PRE_QUALIFYING_RESULT	4	
4	290	PRE_QUALIFYING_RESULT	5	
...	...	...	...	...
183627	1143	DRIVER_OF_THE_DAY_RESULT	1	
183628	1143	DRIVER_OF_THE_DAY_RESULT	2	
183629	1143	DRIVER_OF_THE_DAY_RESULT	3	
183630	1143	DRIVER_OF_THE_DAY_RESULT	4	
183631	1143	DRIVER_OF_THE_DAY_RESULT	5	

	position_number	position_text	driver_number
driver_id \			
0	1.0	1	40 gilles-

villeneuve				
1	2.0	2	23	patrick-
tambay				
2	3.0	3	34	jean-pierre-
jarier				
3	4.0	4	30	brett-
lunger				
4	5.0	5	38	brian-
henton				
...	...	...	...	..
.				
183627	1.0	1	14	fernando-
alonso				
183628	2.0	2	63	george-
russell				
183629	3.0	3	1	max-
verstappen				
183630	4.0	4	4	lando-
norris				
183631	5.0	5	44	lewis-
hamilton				

	constructor_id	engine_manufacturer_id	tyre_manufacturer_id	...
\				
0	mclaren	ford	goodyear	...
1	ensign	ford	goodyear	...
2	penske	ford	goodyear	...
3	mclaren	ford	goodyear	...
4	march	ford	goodyear	...
...	...	...	...	...
183627	aston-martin	mercedes	pirelli	...
183628	mercedes	mercedes	pirelli	...
183629	red-bull	honda-rbpt	pirelli	...
183630	mclaren	mercedes	pirelli	...
183631	ferrari	ferrari	pirelli	...

	fastest_lap_time_millis	fastest_lap_gap	fastest_lap_gap_millis
\			
0	NaN	None	NaN

1	NaN	None	NaN
2	NaN	None	NaN
3	NaN	None	NaN
4	NaN	None	NaN
...	...	...	...
183627	NaN	None	NaN
183628	NaN	None	NaN
183629	NaN	None	NaN
183630	NaN	None	NaN
183631	NaN	None	NaN
fastest_lap_interval fastest_lap_interval_millis			
pit_stop_stop \			
0	None	NaN	
NaN			
1	None	NaN	
NaN			
2	None	NaN	
NaN			
3	None	NaN	
NaN			
4	None	NaN	
NaN			
...	...	...	..
.			
183627	None	NaN	
NaN			
183628	None	NaN	
NaN			
183629	None	NaN	
NaN			
183630	None	NaN	
NaN			
183631	None	NaN	
NaN			
pit_stop_lap pit_stop_time pit_stop_time_millis \			
0	NaN	None	NaN
1	NaN	None	NaN
2	NaN	None	NaN

3	NaN	None	NaN
4	NaN	None	NaN
...	...	...	...
183627	NaN	None	NaN
183628	NaN	None	NaN
183629	NaN	None	NaN
183630	NaN	None	NaN
183631	NaN	None	NaN

driver_of_the_day_percentage	
0	NaN
1	NaN
2	NaN
3	NaN
4	NaN
...	...
183627	22.5
183628	16.4
183629	14.5
183630	8.7
183631	7.6

[183632 rows x 71 columns]

race

	id	year	round	date	time	grand_prix_id \
0	1	1950	1	1950-05-13	None	great-britain
1	2	1950	2	1950-05-21	None	monaco
2	3	1950	3	1950-05-30	None	indianapolis
3	4	1950	4	1950-06-04	None	switzerland
4	5	1950	5	1950-06-18	None	belgium
...	...	...	...	...	...	...
1144	1145	2025	20	2025-10-26	20:00	mexico
1145	1146	2025	21	2025-11-09	17:00	sao-paulo
1146	1147	2025	22	2025-11-23	04:00	las-vegas
1147	1148	2025	23	2025-11-30	16:00	qatar
1148	1149	2025	24	2025-12-07	13:00	abu-dhabi

	official_name
qualifying_format \	
0	1950 RAC British Grand Prix
TWO_SESSION	
1	Grand Prix de Monaco 1950
TWO_SESSION	
2	1950 Indianapolis 500
FOUR_LAPS	
3	Grosser Preis der Schweiz 1950
TWO_SESSION	
4	1950 Belgian Grand Prix

TWO\_SESSION

```
...
...
1144 Formula 1 Gran Premio de la Ciudad de México 2025
KNOCKOUT
1145 Formula 1 MSC Cruises Grande Prêmio de São Pau...
KNOCKOUT
1146 Formula 1 Heineken Las Vegas Grand Prix 2025
KNOCKOUT
1147 Formula 1 Qatar Airways Qatar Grand Prix 2025
KNOCKOUT
1148 Formula 1 Etihad Airways Abu Dhabi Grand Prix ...
KNOCKOUT
```

	sprint_qualifying_format	circuit_id	...
qualifying_2_date \			
0	None	silverstone	...
None			
1	None	monaco	...
None			
2	None	indianapolis	...
None			
3	None	bremgarten	...
None			
4	None	spa-francorchamps	...
None			
...	...	...	...
.			
1144	None	mexico-city	...
None			
1145	SPRINT_SHOOTOUT	interlagos	...
None			
1146	None	las-vegas	...
None			
1147	SPRINT_SHOOTOUT	lusail	...
None			
1148	None	yas-marina	...
None			

	qualifying_2_time	qualifying_date	qualifying_time \
0	None	None	None
1	None	None	None
2	None	None	None
3	None	None	None
4	None	None	None
...	...	...	...
1144	None	2025-10-25	21:00
1145	None	2025-11-08	18:00
1146	None	2025-11-22	04:00

1147	None	2025-11-29	18:00
1148	None	2025-12-06	14:00
	sprint_qualifying_date	sprint_qualifying_time	sprint_race_date
\			
0	None	None	None
1	None	None	None
2	None	None	None
3	None	None	None
4	None	None	None
...	...	...	...
1144	None	None	None
1145	2025-11-07	18:30	2025-11-08
1146	None	None	None
1147	2025-11-28	17:30	2025-11-29
1148	None	None	None
	sprint_race_time	warming_up_date	warming_up_time
0	None	None	None
1	None	None	None
2	None	None	None
3	None	None	None
4	None	None	None
...	...	...	...
1144	None	None	None
1145	14:00	None	None
1146	None	None	None
1147	14:00	None	None
1148	None	None	None
[1149 rows x 42 columns]			
circuit			
	id	name	full_name \
0	adelaide	Adelaide	Adelaide Street Circuit
1	aida	Aida	Okayama International Circuit
2	ain-diab	Ain-Diab	Ain-Diab Circuit
3	aintree	Aintree	Aintree Motor Racing Circuit
4	anderstorp	Anderstorp Raceway	Anderstorp Raceway

72	yas-marina	Yas Marina	Yas Marina Circuit
73	yeongam	Korea	Korea International Circuit
74	zandvoort	Zandvoort	Circuit Park Zandvoort
75	zeltweg	Zeltweg	Zeltweg
76	zolder	Zolder	Circuit Zolder

	previous_names	type	direction	place_name \
0	None	STREET	CLOCKWISE	Adelaide
1	TI Circuit Aida	RACE	CLOCKWISE	Aida
2	None	ROAD	CLOCKWISE	Casablanca
3	None	ROAD	CLOCKWISE	Aintree
4	Scandinavian Raceway	RACE	CLOCKWISE	Anderstorp
72	None	RACE	ANTI_CLOCKWISE	Abu Dhabi
73	None	RACE	ANTI_CLOCKWISE	Yeongam
74	None	RACE	CLOCKWISE	Zandvoort
75	None	ROAD	CLOCKWISE	Zeltweg
76	None	RACE	CLOCKWISE	Heusden-Zolder

	country_id	latitude	longitude	length	turns \
0	australia	-34.927222	138.617222	3.780	16
1	japan	34.915000	134.221111	3.703	13
2	morocco	33.578611	-7.687500	7.618	18
3	united-kingdom	53.476944	-2.940556	4.828	8
4	sweden	57.264167	13.601389	4.031	8
72	united-arab-emirates	24.467222	54.603056	5.281	16
73	south-korea	34.733333	126.416667	5.615	18
74	netherlands	52.388819	4.540922	4.259	14
75	austria	47.202222	14.742222	3.186	4
76	belgium	50.988889	5.255556	4.262	15

	total_races_held
0	11
1	2
2	1
3	5
4	6
72	16
73	4
74	35
75	1
76	10

[77 rows x 13 columns]

# Clean Data

## Data Documentation Look-up

Display helper tools that describe the information contained in the table

```
get_schema_info('races')
```

races

The list of races, each representing detailed information about individual races, including results, participants, and statistics.

```
get_schema_info('circuits')
```

circuits

The list of circuits, each representing a specific racing track, including geographical location and race history.

```
print(schema.Race)
```

id = type = integer

description = The unique identifier of the race.

year = type = integer

description = The year of the season.

round = type = integer

description = The round number of the race in the season.

date = type = string

description = The date of the race in UTC.

time = type = ['string', 'null']

description = The start time of the race in UTC.

grandPrixId = type = string

description = The identifier of the Grand Prix associated with the race.

officialName = type = string

description = The official name of the race.

qualifyingFormat = description = The qualifying format of the race.

sprintQualifyingFormat = description = The sprint qualifying format of the race.

circuitId = type = string

description = The identifier of the circuit where the race takes



place.

circuitType = description = The type of the circuit.

direction = description = The direction of the circuit.

courseLength = type = number  
description = The length of the circuit (race course) in kilometers.

turns = type = integer  
description = The number of turns (corners) in the configuration of the circuit.

laps = type = integer  
description = The total number of laps of the race.

distance = type = number  
description = The total distance of the race in kilometers.

scheduledLaps = type = ['integer', 'null']  
description = The scheduled number of laps of the race.

scheduledDistance = type = ['number', 'null']  
description = The scheduled distance of the race in kilometers.

driversChampionshipDecider = type = boolean  
description = Whether this race was the decider of the World Drivers' Championship.

constructorsChampionshipDecider = type = boolean  
description = Whether this race was the decider of the World Constructors' Championship.

preQualifyingDate = type = ['string', 'null']  
description = The date of the pre-qualifying session in UTC.

preQualifyingTime = type = ['string', 'null']  
description = The start time of the pre-qualifying session in UTC.

preQualifyingResults = type = ['array', 'null']  
description = The results of the pre-qualifying session.

freePractice1Date = type = ['string', 'null']  
description = The date of the 1st free practice session in UTC.

freePractice1Time = type = ['string', 'null']  
description = The start time of the 1st free practice session in UTC.

freePractice1Results = type = ['array', 'null']  
description = The results of the 1st free practice session.

freePractice2Date = type = ['string', 'null']  
description = The date of the 2nd free practice session in UTC.

freePractice2Time = type = ['string', 'null']  
description = The start time of the 2nd free practice session in UTC.

freePractice2Results = type = ['array', 'null']  
description = The results of the 2nd free practice session.

freePractice3Date = type = ['string', 'null']  
description = The date of the 3rd free practice session in UTC.

freePractice3Time = type = ['string', 'null']  
description = The start time of the 3rd free practice session in UTC.

freePractice3Results = type = ['array', 'null']  
description = The results of the 3rd free practice session.

freePractice4Date = type = ['string', 'null']  
description = The date of the 4th free practice session UTC.

freePractice4Time = type = ['string', 'null']  
description = The start time of the 4th free practice session in UTC.

freePractice4Results = type = ['array', 'null']  
description = The results of the 4th free practice session.

qualifying1Date = type = ['string', 'null']  
description = The date of the 1st qualifying session in UTC.

qualifying1Time = type = ['string', 'null']  
description = The start time of the 1st qualifying session in UTC.

qualifying1Results = type = ['array', 'null']  
description = The results of the 1st qualifying session.

qualifying2Date = type = ['string', 'null']  
description = The date of the 2nd qualifying session UTC.

qualifying2Time = type = ['string', 'null']  
description = The start time of the 2nd qualifying session UTC.

qualifying2Results = type = ['array', 'null']  
description = The results of the 2nd qualifying session.

qualifyingDate = type = ['string', 'null']  
description = The date of the qualifying session UTC.

qualifyingTime = type = ['string', 'null']  
description = The start time of the qualifying session UTC.

```
qualifyingResults = type = ['array', 'null']
description = The results of the qualifying session.

sprintQualifyingDate = type = ['string', 'null']
description = The date of the sprint qualifying session in UTC.

sprintQualifyingTime = type = ['string', 'null']
description = The start time of the sprint qualifying session in UTC.

sprintQualifyingResults = type = ['array', 'null']
description = The results of the sprint qualifying session.

sprintStartingGridPositions = type = ['array', 'null']
description = The starting grid positions for the sprint race.

sprintRaceDate = type = ['string', 'null']
description = The date of the sprint race in UTC.

sprintRaceTime = type = ['string', 'null']
description = The start time of the sprint race in UTC.

sprintRaceResults = type = ['array', 'null']
description = The results of the sprint race.

warmingUpDate = type = ['string', 'null']
description = The date of the warming-up session in UTC.

warmingUpTime = type = ['string', 'null']
description = The start time of the warming-up session in UTC.

warmingUpResults = type = ['array', 'null']
description = The results of the warming-up session.

startingGridPositions = type = ['array', 'null']
description = The starting grid positions for the race.

raceResults = type = ['array', 'null']
description = The results of the race.

fastestLaps = type = ['array', 'null']
description = The fastest laps recorded during the race..

pitStops = type = ['array', 'null']
description = The pit stops made during the race.

driverOfTheDayResults = type = ['array', 'null']
description = The results of the Driver of the Day vote.

driverStandings = type = ['array', 'null']
description = The driver standings after the race.
```

```
constructorStandings = type = ['array', 'null']  
description = The constructor standings after the race.
```

## Initial Analysis

```
print(schema)
```

```
Continent = id = type = string  
description = The unique identifier for the continent.
```

```
code = type = string  
description = The unique code of the continent.
```

```
name = type = string  
description = The name of the continent.
```

```
demonym = type = string  
description = The demonym used for people from the continent.
```

```
Country = id = type = string  
description = The unique identifier for the country.
```

```
alpha2Code = type = string  
description = The unique ISO 3166-1 alpha-2 code of the country.
```

```
alpha3Code = type = string  
description = The unique ISO 3166-1 alpha-3 code of the country.
```

```
iocCode = type = ['string', 'null']  
description = The unique International Olympic Committee (IOC) code of  
the country.
```

```
name = type = string  
description = The name of the country.
```

```
demonym = type = ['string', 'null']  
description = The demonym for citizens of the country.
```

```
continentId = type = string  
description = The identifier for the continent where the country is  
located.
```

```
Driver = id = type = string  
description = The unique identifier of the driver.
```

```
name = type = string  
description = The name of the driver, typically used for display
```

purposes.

firstName = type = string  
description = The given name or first name of the driver.

lastName = type = string  
description = The family name or last name of the driver.

fullName = type = string  
description = The full name of the driver, usually a combination of first, middle and last names.

abbreviation = type = string  
description = The three-letter abbreviation for the driver, consisting of uppercase letters (e.g., 'SEN' for Ayrton Senna).

permanentNumber = type = ['string', 'null']  
description = The permanent racing number chosen by the driver.

gender = description = The gender of the driver.

dateOfBirth = type = string  
description = The birth date of the driver.

dateOfDeath = type = ['string', 'null']  
description = The death date of the driver, if applicable.

placeOfBirth = type = string  
description = The place of birth of the driver.

countryOfBirthCountryId = type = string  
description = The identifier of the country where the driver was born.

nationalityCountryId = type = string  
description = The identifier of the nationality of the driver.

secondNationalityCountryId = type = ['string', 'null']  
description = The identifier of the second nationality of the driver, if applicable.

familyRelationships = type = ['array', 'null']  
description = The family relationships involving the driver, such as parent or sibling relationships.

bestChampionshipPosition = type = ['integer', 'null']  
description = The best finishing position achieved by the driver in a World Drivers' Championship.

bestStartingGridPosition = type = ['integer', 'null']  
description = The best starting grid position achieved by the driver in a race.

bestRaceResult = type = ['integer', 'null']  
description = The best finishing position achieved by the driver in a race.

totalChampionshipWins = type = integer  
description = The total number of World Drivers' Championship titles won by the driver.

totalRaceEntries = type = integer  
description = The total number of races entered by the driver.

totalRaceStarts = type = integer  
description = The total number of races started by the driver.

totalRaceWins = type = integer  
description = The total number of races won by the driver.

totalRaceLaps = type = integer  
description = The total number of laps completed by the driver.

totalPodiums = type = integer  
description = The total number of podium finishes achieved by the driver.

totalPoints = type = number  
description = The total number of points accumulated by the driver.

totalChampionshipPoints = type = number  
description = The total number of World Drivers' Championship points accumulated by the driver.

totalPolePositions = type = integer  
description = The total number of pole positions achieved by the driver.

totalFastestLaps = type = integer  
description = The total number of fastest laps set by the driver.

totalDriverOfTheDay = type = integer  
description = The total number of Driver of the Day awards received by the driver.

totalGrandSlams = type = integer  
description = The total number of Grand Slams achieved by the driver, defined as pole position, fastest lap, and leading every lap of the race.

DriverFamilyRelationship = positionDisplayOrder = type = integer  
description = The display order of the family relationship relative to

other relationships of the parent driver.

driverId = type = string

description = The identifier of the related driver.

type = description = The type of the family relationship.

Constructor = id = type = string

description = The unique identifier of the constructor.

name = type = string

description = The name of the constructor, typically used for display purposes.

fullName = type = string

description = The full name of the constructor.

countryId = type = string

description = The identifier of the country of origin of the constructor.

chronology = type = ['array', 'null']

description = The chronology of the constructor.

bestChampionshipPosition = type = ['integer', 'null']

description = The best finishing position achieved by the constructor in a World Constructors' Championship.

bestStartingGridPosition = type = ['integer', 'null']

description = The best starting grid position achieved by the constructor in a race.

bestRaceResult = type = ['integer', 'null']

description = The best finishing position achieved by the constructor in a race.

totalChampionshipWins = type = integer

description = The total number of World Constructors' Championship titles won by the constructor.

totalRaceEntries = type = integer

description = The total number of races entered by the constructor.

totalRaceStarts = type = integer

description = The total number of races started by the constructor.

totalRaceWins = type = integer

description = The total number of races won by the constructor.

total1And2Finishes = type = integer

description = The total number of races in which the constructor finished in both 1st and 2nd place.

totalRaceLaps = type = integer

description = The total number of laps completed by the constructor.

totalPodiums = type = integer

description = The total number of podium finishes achieved by the constructor.

totalPodiumRaces = type = integer

description = The total number of races in which the constructor finished on the podium.

totalPoints = type = number

description = The total number of points accumulated by the constructor.

totalChampionshipPoints = type = number

description = The total number of World Constructors' Championship points accumulated by the constructor.

totalPolePositions = type = integer

description = The total number of pole positions achieved by the constructor.

totalFastestLaps = type = integer

description = The total number of fastest laps set by the constructor.

ConstructorChronology = positionDisplayOrder = type = integer

description = The display order of the constructor within the chronological sequence of the parent constructor.

constructorId = type = string

description = The identifier of the constructor.

yearFrom = type = integer

description = The year from.

yearTo = type = ['integer', 'null']

description = The year to, or null if it is still active.

Chassis = id = type = string

description = The unique identifier of the chassis.

constructorId = type = string

description = The identifier of the constructor associated with the chassis.



name = type = string  
description = The name of the chassis.

fullName = type = string  
description = The full name of the chassis.

EngineManufacturer = id = type = string  
description = The unique identifier of the engine manufacturer.

name = type = string  
description = The name of the engine manufacturer.

countryId = type = string  
description = The identifier of the country of origin of the engine manufacturer.

bestChampionshipPosition = type = ['integer', 'null']  
description = The best finishing position achieved by the engine manufacturer in a World Constructors' Championship.

bestStartingGridPosition = type = ['integer', 'null']  
description = The best starting grid position achieved by the engine manufacturer in a race.

bestRaceResult = type = ['integer', 'null']  
description = The best finishing position achieved by the engine manufacturer in a race.

totalChampionshipWins = type = integer  
description = The total number of World Constructors' Championship titles won by the engine manufacturer.

totalRaceEntries = type = integer  
description = The total number of races entered by the engine manufacturer.

totalRaceStarts = type = integer  
description = The total number of races started by the engine manufacturer.

totalRaceWins = type = integer  
description = The total number of races won by the engine manufacturer.

totalRaceLaps = type = integer  
description = The total number of laps completed by the engine manufacturer.

totalPodiums = type = integer  
description = The total number of podium finishes achieved by the

engine manufacturer.

totalPodiumRaces = type = integer  
description = The total number of races in which the engine manufacturer finished on the podium.

totalPoints = type = number  
description = The total number of points accumulated by the engine manufacturer.

totalChampionshipPoints = type = number  
description = The total number of World Constructors' Championship points accumulated by the engine manufacturer.

totalPolePositions = type = integer  
description = The total number of pole positions achieved by the engine manufacturer.

totalFastestLaps = type = integer  
description = The total number of fastest laps set by the engine manufacturer.

Engine = id = type = string  
description = The unique identifier of the engine.

engineManufacturerId = type = string  
description = The identifier of the engine manufacturer associated with the engine.

name = type = string  
description = The name of the engine.

fullName = type = string  
description = The full name of the engine.

capacity = type = ['number', 'null']  
description = The capacity of the engine, measured in liters.

configuration = description = The configuration of the engine, such as V6, V8, etc.

aspiration = description = The aspiration of the engine, such as naturally aspirated or turbocharged.

TyreManufacturer = id = type = string  
description = The unique identifier of the tyre manufacturer.

name = type = string  
description = The name of the tyre manufacturer.

```
countryId = type = string
description = The identifier of the country of origin of the tyre
manufacturer.

bestStartingGridPosition = type = ['integer', 'null']
description = The best starting grid position achieved by the tyre
manufacturer in a race.

bestRaceResult = type = ['integer', 'null']
description = The best finishing position achieved by the tyre
manufacturer in a race.

totalRaceEntries = type = integer
description = The total number of races entered by the tyre
manufacturer.

totalRaceStarts = type = integer
description = The total number of races started by the tyre
manufacturer.

totalRaceWins = type = integer
description = The total number of races won by the tyre manufacturer.

totalRaceLaps = type = integer
description = The total number of laps completed by the tyre
manufacturer.

totalPodiums = type = integer
description = The total number of podium finishes achieved by the tyre
manufacturer.

totalPodiumRaces = type = integer
description = The total number of races in which the tyre manufacturer
finished on the podium.

totalPolePositions = type = integer
description = The total number of pole positions achieved by the tyre
manufacturer.

totalFastestLaps = type = integer
description = The total number of fastest laps set by the tyre
manufacturer.

Circuit = id = type = string
description = The unique identifier of the circuit.

name = type = string
description = The name of the circuit, typically used for display
purposes.
```

```
fullName = type = string
description = The full official name of the circuit.

previousNames = type = ['array', 'null']
description = The previous names used for the circuit.

type = description = The type of the circuit.

direction = description = The direction of the current or most
recently used configuration of the circuit.

placeName = type = string
description = The place name where the circuit is located.

countryId = type = string
description = The identifier of the country where the circuit is
located.

latitude = type = number
description = The latitude coordinate where the circuit is located.

longitude = type = number
description = The longitude coordinate where the circuit is located.

length = type = number
description = The length of the current or most recently used
configuration of the circuit in kilometers.

turns = type = integer
description = The number of turns (corners) in the current or most
recently used configuration of the circuit.

totalRacesHeld = type = integer
description = The total number of races held at the circuit.

GrandPrix = id = type = string
description = The unique identifier of the Grand Prix.

name = type = string
description = The name of the Grand Prix, typically used for display
purposes.

fullName = type = string
description = The full name of the Grand Prix.

shortName = type = string
description = The short name of the Grand Prix.

abbreviation = type = string
```

description = The three-character abbreviation of the Grand Prix.

countryId = type = ['string', 'null']  
description = The identifier of the country where the Grand Prix is held.

totalRacesHeld = type = integer  
description = The total number of races held for this Grand Prix.

SeasonEntrant = entrantId = type = string  
description = The identifier of the entrant.

countryId = type = string  
description = The identifier of the country of the entrant.

constructors = type = array  
description = The constructors associated with the entrant.

Entrant = id = type = string  
description = The unique identifier of the entrant.

name = type = string  
description = The name of the entrant.

Season = year = type = integer  
description = The year of the season.

entrants = type = ['array', 'null']  
description = The entrants competing in the season.

constructors = type = ['array', 'null']  
description = The constructors competing in the season.

engineManufacturers = type = ['array', 'null']  
description = The engine manufacturers competing in the season.

tyreManufacturers = type = ['array', 'null']  
description = The tyre manufacturers competing in the season.

drivers = type = ['array', 'null']  
description = The drivers competing in the season.

driverStandings = type = ['array', 'null']  
description = The driver standings of the season.

constructorStandings = type = ['array', 'null']  
description = The constructor standings of the season.

SeasonEntrantConstructor = constructorId = type = string  
description = The identifier of the constructor.

engineManufacturerId = type = string  
description = The identifier of the engine manufacturer.

chassis = type = array  
description = The chassis used by the constructor.

engines = type = array  
description = The engines used by the constructor.

tyreManufacturers = type = array  
description = The tyre manufacturers used by the constructor.

drivers = type = ['array', 'null']  
description = The drivers who drove for the constructor.

SeasonEntrantChassis = chassisId = type = string  
description = The identifier of the chassis.

SeasonEntrantEngine = engineId = type = string  
description = The identifier of the engine.

SeasonEntrantTyreManufacturer = tyreManufacturerId = type = string  
description = The identifier of the tyre manufacturer.

SeasonEntrantDriver = driverId = type = string  
description = The identifier of the driver.

rounds = type = ['array', 'null']  
description = The rounds in which the driver participated.

roundsText = type = ['string', 'null']  
description = The textual representation of the rounds in which the driver participated.

testDriver = type = boolean  
description = Whether the driver was a test / free practice driver.

SeasonConstructor = year = type = integer  
description = The year of the season.

constructorId = type = string  
description = The identifier of the constructor.

positionNumber = type = ['integer', 'null']  
description = The numerical position of the constructor in the season standings.

positionText = type = ['string', 'null']  
description = The textual representation of the constructor's position in the season standings, including special statuses.

bestStartingGridPosition = type = ['integer', 'null']  
description = The best starting grid position achieved by the constructor during the season.

bestRaceResult = type = ['integer', 'null']  
description = The best finishing position achieved by the constructor during the season.

totalRaceEntries = type = integer  
description = The total number of races entered by the constructor during the season.

totalRaceStarts = type = integer  
description = The total number of races started by the constructor during the season.

totalRaceWins = type = integer  
description = The total number of races won by the constructor during the season.

total1And2Finishes = type = integer  
description = The total number of races in which the constructor finished in both 1st and 2nd place during the season.

totalRaceLaps = type = integer  
description = The total number of laps completed by the constructor during the season.

totalPodiums = type = integer  
description = The total number of podium finishes achieved by the constructor during the season.

totalPodiumRaces = type = integer  
description = The total number of races in which the constructor finished on the podium during the season.

totalPoints = type = number  
description = The total number of points accumulated by the constructor during the season.

totalPolePositions = type = integer  
description = The total number of pole positions achieved by the

constructor during the season.

totalFastestLaps = type = integer  
description = The total number of fastest laps set by the constructor during the season.

SeasonEngineManufacturer = year = type = integer  
description = The year of the season.

engineManufacturerId = type = string  
description = The identifier of the engine manufacturer.

positionNumber = type = ['integer', 'null']  
description = The numerical position of the engine manufacturer in the season standings.

positionText = type = ['string', 'null']  
description = The textual representation of the engine manufacturer's position in the season standings, including special statuses.

bestStartingGridPosition = type = ['integer', 'null']  
description = The best starting grid position achieved by the engine manufacturer during the season.

bestRaceResult = type = ['integer', 'null']  
description = The best finishing position achieved by the engine manufacturer during the season.

totalRaceEntries = type = integer  
description = The total number of races entered by the engine manufacturer during the season.

totalRaceStarts = type = integer  
description = The total number of races started by the engine manufacturer during the season.

totalRaceWins = type = integer  
description = The total number of races won by the engine manufacturer during the season.

totalRaceLaps = type = integer  
description = The total number of laps completed by the engine manufacturer during the season.

totalPodiums = type = integer  
description = The total number of podium finishes achieved by the engine manufacturer during the season.

totalPodiumRaces = type = integer  
description = The total number of races in which the engine



manufacturer finished on the podium during the season.

totalPoints = type = number  
description = The total number of points accumulated by the engine manufacturer during the season.

totalPolePositions = type = integer  
description = The total number of pole positions achieved by the engine manufacturer during the season.

totalFastestLaps = type = integer  
description = The total number of fastest laps set by the engine manufacturer during the season.

SeasonTyreManufacturer = year = type = integer  
description = The year of the season.

tyreManufacturerId = type = string  
description = The identifier of the tyre manufacturer.

bestStartingGridPosition = type = ['integer', 'null']  
description = The best starting grid position achieved by the tyre manufacturer during the season.

bestRaceResult = type = ['integer', 'null']  
description = The best finishing position achieved by the tyre manufacturer during the season.

totalRaceEntries = type = integer  
description = The total number of races entered by the tyre manufacturer during the season.

totalRaceStarts = type = integer  
description = The total number of races started by the tyre manufacturer during the season.

totalRaceWins = type = integer  
description = The total number of races won by the tyre manufacturer during the season.

totalRaceLaps = type = integer  
description = The total number of laps completed by the tyre manufacturer during the season.

totalPodiums = type = integer  
description = The total number of podium finishes achieved by the tyre manufacturer during the season.

totalPodiumRaces = type = integer  
description = The total number of races in which the tyre manufacturer

finished on the podium during the season.

totalPolePositions = type = integer  
description = The total number of pole positions achieved by the tyre manufacturer during the season.

totalFastestLaps = type = integer  
description = The total number of fastest laps set by the tyre manufacturer during the season.

SeasonDriver = year = type = integer  
description = The year of the season.

driverId = type = string  
description = The identifier of the driver.

positionNumber = type = ['integer', 'null']  
description = The numerical position of the driver in the season standings.

positionText = type = ['string', 'null']  
description = The textual representation of the driver's position in the season standings, including special statuses.

bestStartingGridPosition = type = ['integer', 'null']  
description = The best starting grid position achieved by the driver during the season.

bestRaceResult = type = ['integer', 'null']  
description = The best finishing position achieved by the driver during the season.

totalRaceEntries = type = integer  
description = The total number of races entered by the driver during the season.

totalRaceStarts = type = integer  
description = The total number of races started by the driver during the season.

totalRaceWins = type = integer  
description = The total number of races won by the driver during the season.

totalRaceLaps = type = integer  
description = The total number of laps completed by the driver during the season.

totalPodiums = type = integer  
description = The total number of podium finishes achieved by the

driver during the season.

totalPoints = type = number

description = The total number of points accumulated by the driver during the season.

totalPolePositions = type = integer

description = The total number of pole positions achieved by the driver during the season.

totalFastestLaps = type = integer

description = The total number of fastest laps set by the driver during the season.

totalDriverOfTheDay = type = integer

description = The total number of Driver of the Day awards received by the driver during the season.

totalGrandSlams = type = integer

description = The total number of Grand Slams achieved by the driver during the season, defined as pole position, fastest lap, and leading every lap of the race.

SeasonDriverStanding = positionDisplayOrder = type = integer

description = The display order of the driver's position in the standings.

positionNumber = type = ['integer', 'null']

description = The numerical position of the driver in the standings.

positionText = type = string

description = The textual representation of the driver's position in the standings, including special statuses.

driverId = type = string

description = The identifier of the driver.

points = type = number

description = The total number of points determining the driver's position in the standings.

SeasonConstructorStanding = positionDisplayOrder = type = integer

description = The display order for the constructor's position in the standings.

positionNumber = type = ['integer', 'null']

description = The numerical position of the constructor in the standings.

positionText = type = string  
description = The textual representation of the constructor's position in the standings, including special statuses.

constructorId = type = string  
description = The identifier of the constructor.

engineManufacturerId = type = string  
description = The identifier of the engine manufacturer.

points = type = number  
description = The total number of points determining the constructor's position in the standings.

Race = id = type = integer  
description = The unique identifier of the race.

year = type = integer  
description = The year of the season.

round = type = integer  
description = The round number of the race in the season.

date = type = string  
description = The date of the race in UTC.

time = type = ['string', 'null']  
description = The start time of the race in UTC.

grandPrixId = type = string  
description = The identifier of the Grand Prix associated with the race.

officialName = type = string  
description = The official name of the race.

qualifyingFormat = description = The qualifying format of the race.

sprintQualifyingFormat = description = The sprint qualifying format of the race.

circuitId = type = string  
description = The identifier of the circuit where the race takes place.

circuitType = description = The type of the circuit.

direction = description = The direction of the circuit.

courseLength = type = number

description = The length of the circuit (race course) in kilometers.

turns = type = integer

description = The number of turns (corners) in the configuration of the circuit.

laps = type = integer

description = The total number of laps of the race.

distance = type = number

description = The total distance of the race in kilometers.

scheduledLaps = type = ['integer', 'null']

description = The scheduled number of laps of the race.

scheduledDistance = type = ['number', 'null']

description = The scheduled distance of the race in kilometers.

driversChampionshipDecider = type = boolean

description = Whether this race was the decider of the World Drivers' Championship.

constructorsChampionshipDecider = type = boolean

description = Whether this race was the decider of the World Constructors' Championship.

preQualifyingDate = type = ['string', 'null']

description = The date of the pre-qualifying session in UTC.

preQualifyingTime = type = ['string', 'null']

description = The start time of the pre-qualifying session in UTC.

preQualifyingResults = type = ['array', 'null']

description = The results of the pre-qualifying session.

freePractice1Date = type = ['string', 'null']

description = The date of the 1st free practice session in UTC.

freePractice1Time = type = ['string', 'null']

description = The start time of the 1st free practice session in UTC.

freePractice1Results = type = ['array', 'null']

description = The results of the 1st free practice session.

freePractice2Date = type = ['string', 'null']

description = The date of the 2nd free practice session in UTC.

freePractice2Time = type = ['string', 'null']

description = The start time of the 2nd free practice session in UTC.

freePractice2Results = type = ['array', 'null']

description = The results of the 2nd free practice session.

freePractice3Date = type = ['string', 'null']  
description = The date of the 3rd free practice session in UTC.

freePractice3Time = type = ['string', 'null']  
description = The start time of the 3rd free practice session in UTC.

freePractice3Results = type = ['array', 'null']  
description = The results of the 3rd free practice session.

freePractice4Date = type = ['string', 'null']  
description = The date of the 4th free practice session UTC.

freePractice4Time = type = ['string', 'null']  
description = The start time of the 4th free practice session in UTC.

freePractice4Results = type = ['array', 'null']  
description = The results of the 4th free practice session.

qualifying1Date = type = ['string', 'null']  
description = The date of the 1st qualifying session in UTC.

qualifying1Time = type = ['string', 'null']  
description = The start time of the 1st qualifying session in UTC.

qualifying1Results = type = ['array', 'null']  
description = The results of the 1st qualifying session.

qualifying2Date = type = ['string', 'null']  
description = The date of the 2nd qualifying session UTC.

qualifying2Time = type = ['string', 'null']  
description = The start time of the 2nd qualifying session UTC.

qualifying2Results = type = ['array', 'null']  
description = The results of the 2nd qualifying session.

qualifyingDate = type = ['string', 'null']  
description = The date of the qualifying session UTC.

qualifyingTime = type = ['string', 'null']  
description = The start time of the qualifying session UTC.

qualifyingResults = type = ['array', 'null']  
description = The results of the qualifying session.

sprintQualifyingDate = type = ['string', 'null']  
description = The date of the sprint qualifying session in UTC.

sprintQualifyingTime = type = ['string', 'null']

description = The start time of the sprint qualifying session in UTC.

sprintQualifyingResults = type = ['array', 'null']

description = The results of the sprint qualifying session.

sprintStartingGridPositions = type = ['array', 'null']

description = The starting grid positions for the sprint race.

sprintRaceDate = type = ['string', 'null']

description = The date of the sprint race in UTC.

sprintRaceTime = type = ['string', 'null']

description = The start time of the sprint race in UTC.

sprintRaceResults = type = ['array', 'null']

description = The results of the sprint race.

warmingUpDate = type = ['string', 'null']

description = The date of the warming-up session in UTC.

warmingUpTime = type = ['string', 'null']

description = The start time of the warming-up session in UTC.

warmingUpResults = type = ['array', 'null']

description = The results of the warming-up session.

startingGridPositions = type = ['array', 'null']

description = The starting grid positions for the race.

raceResults = type = ['array', 'null']

description = The results of the race.

fastestLaps = type = ['array', 'null']

description = The fastest laps recorded during the race..

pitStops = type = ['array', 'null']

description = The pit stops made during the race.

driverOfTheDayResults = type = ['array', 'null']

description = The results of the Driver of the Day vote.

driverStandings = type = ['array', 'null']

description = The driver standings after the race.

constructorStandings = type = ['array', 'null']

description = The constructor standings after the race.

RaceDriverStanding = positionDisplayOrder = type = integer

description = The display order of the driver's position in the standings.

```
positionNumber = type = ['integer', 'null']
description = The numerical position of the driver in the standings.

positionText = type = string
description = The textual representation of the driver's position in
the standings, including special statuses.

driverId = type = string
description = The identifier of the driver.

points = type = number
description = The total number of points determining the driver's
position in the standings.

positionsGained = type = ['integer', 'null']
description = The positions gained in the standings since the previous
race.

RaceConstructorStanding = positionDisplayOrder = type = integer
description = The display order for the constructor's position in the
standings.

positionNumber = type = ['integer', 'null']
description = The numerical position of the constructor in the
standings.

positionText = type = string
description = The textual representation of the constructor's position
in the standings, including special statuses.

constructorId = type = string
description = The identifier of the constructor.

engineManufacturerId = type = string
description = The identifier of the engine manufacturer.

points = type = number
description = The points.

positionsGained = type = ['integer', 'null']
description = The total number of points determining the constructor's
position in the standings.

race.info(verbose=True, memory_usage='deep', show_counts=True)
```



```
<class 'pandas.core.frame.DataFrame'>
```

```
RangeIndex: 1149 entries, 0 to 1148
```

```
Data columns (total 42 columns):
```

#	Column	Non-Null Count	Dtype
0	id	1149 non-null	int64
1	year	1149 non-null	int64
2	round	1149 non-null	int64
3	date	1149 non-null	object
4	time	48 non-null	object
5	grand_prix_id	1149 non-null	object
6	official_name	1149 non-null	object
7	qualifying_format	1149 non-null	object
8	sprint_qualifying_format	18 non-null	object
9	circuit_id	1149 non-null	object
10	circuit_type	1149 non-null	object
11	direction	1149 non-null	object
12	course_length	1149 non-null	float64
13	turns	1149 non-null	int64
14	laps	1149 non-null	int64
15	distance	1149 non-null	float64
16	scheduled_laps	80 non-null	float64
17	scheduled_distance	80 non-null	float64
18	drivers_championship_decider	1149 non-null	bool
19	constructors_championship_decider	1149 non-null	bool
20	pre_qualifying_date	0 non-null	object
21	pre_qualifying_time	0 non-null	object
22	free_practice_1_date	48 non-null	object
23	free_practice_1_time	48 non-null	object
24	free_practice_2_date	36 non-null	object
25	free_practice_2_time	36 non-null	object
26	free_practice_3_date	36 non-null	object
27	free_practice_3_time	36 non-null	object
28	free_practice_4_date	0 non-null	object
29	free_practice_4_time	0 non-null	object
30	qualifying_1_date	0 non-null	object
31	qualifying_1_time	0 non-null	object
32	qualifying_2_date	0 non-null	object
33	qualifying_2_time	0 non-null	object
34	qualifying_date	48 non-null	object
35	qualifying_time	48 non-null	object
36	sprint_qualifying_date	12 non-null	object
37	sprint_qualifying_time	12 non-null	object
38	sprint_race_date	12 non-null	object
39	sprint_race_time	12 non-null	object
40	warming_up_date	0 non-null	object
41	warming_up_time	0 non-null	object

```
dtypes: bool(2), float64(4), int64(5), object(31)
```

```
memory usage: 1.2 MB
```

```
race_data.info(verbose=True, memory_usage='deep', show_counts=True)
```

```
<class 'pandas.core.frame.DataFrame'>
```

```
RangeIndex: 183632 entries, 0 to 183631
```

```
Data columns (total 71 columns):
```

#	Column	Count	Dtype	Non-Null
0	race_id	183632	int64	non-null
1	type	183632	object	non-null
2	position_display_order	183632	int64	non-null
3	position_number	172468	float64	non-null
4	position_text	183632	object	non-null
5	driver_number	183632	object	non-null
6	driver_id	183632	object	non-null
7	constructor_id	183632	object	non-null
8	engine_manufacturer_id	183632	object	non-null
9	tyre_manufacturer_id	183632	object	non-null
10	practice_time	47260	object	non-null
11	practice_time_millis	47260	float64	non-null
12	practice_gap	45124	object	non-null
13	practice_gap_millis	45124	float64	non-null
14	practice_interval	45124	object	non-null
15	practice_interval_millis	45124	float64	non-null
16	practice_laps	38322	float64	non-null
17	qualifying_time	33926	object	non-null
18	qualifying_time_millis	33926	float64	non-null
19	qualifying_q1	8470	object	non-null
20	qualifying_q1_millis	8470	float64	non-null

null	float64	
21	qualifying_q2	6216 non-
null	object	
22	qualifying_q2_millis	6216 non-
null	float64	
23	qualifying_q3	3952 non-
null	object	
24	qualifying_q3_millis	3952 non-
null	float64	
25	qualifying_gap	36049 non-
null	object	
26	qualifying_gap_millis	36049 non-
null	float64	
27	qualifying_interval	36036 non-
null	object	
28	qualifying_interval_millis	36036 non-
null	float64	
29	qualifying_laps	17016 non-
null	float64	
30	starting_grid_position_qualification_position_number	25680 non-
null	float64	
31	starting_grid_position_qualification_position_text	25809 non-
null	object	
32	starting_grid_position_grid_penalty	573 non-
null	object	
33	starting_grid_position_grid_penalty_positions	500 non-
null	float64	
34	starting_grid_position_time	25258 non-
null	object	
35	starting_grid_position_time_millis	25258 non-
null	float64	
36	race_shared_car	27591 non-
null	object	
37	race_laps	25664 non-
null	float64	
38	race_time	8318 non-
null	object	
39	race_time_millis	8318 non-
null	float64	
40	race_time_penalty	274 non-
null	object	
41	race_time_penalty_millis	274 non-
null	float64	
42	race_gap	14822 non-
null	object	
43	race_gap_millis	7154 non-
null	float64	
44	race_gap_laps	7668 non-
null	float64	

45	race_interval	7136	non-
null	object		
46	race_interval_millis	7136	non-
null	float64		
47	race_reason_retired	9998	non-
null	object		
48	race_points	8505	non-
null	float64		
49	race_pole_position	27591	non-
null	object		
50	race_qualification_position_number	26872	non-
null	float64		
51	race_qualification_position_text	27009	non-
null	object		
52	race_grid_position_number	25584	non-
null	float64		
53	race_grid_position_text	25815	non-
null	object		
54	race_positions_gained	16626	non-
null	float64		
55	race_pit_stops	12676	non-
null	float64		
56	race_fastest_lap	27571	non-
null	object		
57	race_driver_of_the_day	4601	non-
null	object		
58	race_grand_slam	27591	non-
null	object		
59	fastest_lap_lap	16689	non-
null	float64		
60	fastest_lap_time	16736	non-
null	object		
61	fastest_lap_time_millis	16736	non-
null	float64		
62	fastest_lap_gap	15593	non-
null	object		
63	fastest_lap_gap_millis	15593	non-
null	float64		
64	fastest_lap_interval	15593	non-
null	object		
65	fastest_lap_interval_millis	15593	non-
null	float64		
66	pit_stop_stop	21889	non-
null	float64		
67	pit_stop_lap	21889	non-
null	float64		
68	pit_stop_time	21888	non-
null	object		
69	pit_stop_time_millis	21888	non-

```
null    float64
70  driver_of_the_day_percentage          720 non-
null    float64
dtypes: float64(34), int64(2), object(35)
memory usage: 253.4 MB
```

```
circuit.info(verbose=True, memory_usage='deep', show_counts=True)
```

```
<class 'pandas.core.frame.DataFrame'>
```

```
RangeIndex: 77 entries, 0 to 76
```

```
Data columns (total 13 columns):
```

#	Column	Non-Null Count	Dtype
0	id	77 non-null	object
1	name	77 non-null	object
2	full_name	77 non-null	object
3	previous_names	15 non-null	object
4	type	77 non-null	object
5	direction	77 non-null	object
6	place_name	77 non-null	object
7	country_id	77 non-null	object
8	latitude	77 non-null	float64
9	longitude	77 non-null	float64
10	length	77 non-null	float64
11	turns	77 non-null	int64
12	total_races_held	77 non-null	int64

```
dtypes: float64(3), int64(2), object(8)
```

```
memory usage: 37.4 KB
```

```
circuit.id.unique()
```

```
array(['adelaide', 'aida', 'ain-diab', 'aintree', 'anderstorp',
      'austin',
      'avus', 'bahrain', 'baku', 'brands-hatch', 'bremgarten',
      'buddh',
      'buenos-aires', 'bugatti', 'caesars-palace', 'catalunya',
      'clermont-ferrand', 'dallas', 'detroit', 'dijon', 'donington',
      'east-london', 'estoril', 'fuji', 'hockenheimring',
      'hungaroring',
      'imola', 'indianapolis', 'interlagos', 'istanbul',
      'jacarepagua',
      'jarama', 'jeddah', 'jerez', 'kyalami', 'las-vegas', 'long-
      beach',
      'lusail', 'magny-cours', 'marina-bay', 'melbourne', 'mexico-
      city',
      'miami', 'monaco', 'monsanto', 'mont-tremblant', 'montjuic',
      'montreal', 'monza', 'mosport', 'mugello', 'niveilles',
      'nurburgring', 'paul-ricard', 'pedralbes', 'pescara',
      'phoenix',
      'portimao', 'porto', 'reims', 'riverside', 'rouen', 'sebring',
```

```

        'sepang', 'shanghai', 'silverstone', 'sochi', 'spa-
francorchamps',
        'spielberg', 'suzuka', 'valencia', 'watkins-glen', 'yas-
marina',
        'yeongam', 'zandvoort', 'zeltweg', 'zolder'], dtype=object)

circuit.sort_values(by='total_races_held', ascending=False)
[['id', 'total_races_held']].head()

# Circuits that have been repetitively raced on will show the most
conclusive results

```

	id	total_races_held
48	monza	75
43	monaco	71
65	silverstone	60
67	spa-francorchamps	58
47	montreal	44

### Initial Notes:

- constructors\_championship\_decider is used for postgres functionality, and therefore can be dropped from the dataframe for analysis

Circuit.previous\_name is arbitrary info and can be dropped from the dataframe Circuit.name and index are the same values, names can be dropped Circuit.total\_races\_held can be simplified to be called 'races\_count'

```

circuit =
circuit.drop(columns=['name', 'previous_names', 'direction', 'latitude', '
longitude'])
circuit = circuit.rename(columns = {
    'total_races_held' : 'race_count'
})

```

## Preparing the Data

```

tracks = ['monza', 'monaco', 'silverstone', 'spa-francorchamps',
'montreal'] # Circuits of interest; have the most amount of racing
data to analyze

race[['date']] = race[['date']].apply(pd.to_datetime, format="%Y-%m-
%d")

def query_circuit(circuit_name: str, agg_method : str = 'min') ->
pd.DataFrame:

    selected_data = (race.query(f'circuit_id == "{circuit_name}"')
        .rename(columns={'id' : 'race_id'}))

```

```

# Change id name to match with race_data for merge

selected_data = (
    selected_data
    .drop(columns=['time', 'grand_prix_id',
'circuit_id', 'circuit_type', 'direction']) # Remove redundant
information (same for all rows)
    .dropna(axis=1, how='all')
# Remove non-applicable information (null for all rows)

    .merge(right=race_data, on='race_id', how='left')
# Merge selected data and race_data to obtain lap time data
    .rename(columns={'fastest_lap_time_millis' :
'fastest_time'})

    .groupby('race_id')[['fastest_time']]
    .agg(agg_method)
# apply aggregation

    .merge(right=selected_data[['race_id', 'date',
'circuit_id']].copy(), on='race_id', how='left' ) # Merge
selected data back to maintain date column
    .drop(columns='race_id')
)

selected_data['fastest_time'] = selected_data['fastest_time'] /
60000 # Convert to minutes
selected_data = selected_data.sort_values(by='date')
# selected_data =
selected_data.set_index('date').resample('YE').agg(agg_method).reset_i
ndex()
selected_data['record'] =
selected_data['fastest_time'].expanding().min()
# Calculate running minimum

selected_data = selected_data.melt(id_vars=['circuit_id', 'date'],
value_vars=['fastest_time', 'record']) # melt data for plotting

return selected_data

lap_data_min = pd.concat([query_circuit(table) for table in tracks])
# lap_data_avg = pd.concat([query_circuit(table, 'mean') for table in
tracks])

lap_data_min.head()

```

	circuit_id	date	variable	value
0	monza	1950-09-03	fastest_time	2.000000
1	monza	1951-09-16	fastest_time	1.941667
2	monza	1952-09-07	fastest_time	2.101667

```

3      monza 1953-09-13  fastest_time  2.075000
4      monza 1954-09-05  fastest_time  2.013333

# lap_data_avg.head()

data_percent_change = (
    lap_data_min
    .query('variable == "record"')
    .set_index(['circuit_id', 'date'])
    .groupby(level=0)['value']
    .pct_change()
    .apply(lambda x: -1 * x)
    .to_frame()
    .reset_index()
    .set_index('date',)
)

# Apply percentage
# Reverse so all data is
positive

data_percent_change.head()

df = []

# Downsize data to yearly for clarity

for track in tracks:
    temp = data_percent_change.query(f'circuit_id == "{track}"')
    temp = temp.value.resample('YS').mean().to_frame()
    temp['circuit_id'] = track
    temp = temp.reset_index()
    df.append(temp)

data_percent_change = pd.concat(df) # Recompile into a single
DataFrame (so graphing functions can be used)
data_percent_change.head()

```

	date	value	circuit_id
0	1950-01-01	NaN	monza
1	1951-01-01	0.029167	monza
2	1952-01-01	0.000000	monza
3	1953-01-01	0.000000	monza
4	1954-01-01	0.000000	monza

## Plotting the data

```

def create_plot ( data_set : pd.DataFrame, super_title : str ) ->
sns.FacetGrid:
    # Create single figure with multiple plots
    g = sns.relplot(data=data_set,
                    kind="line", x='date', y='value', hue='variable',
                    col='circuit_id', facet_kws={ 'sharex' : False,

```



```

'sharey' : False }
    )
    g.set_axis_labels('Year', 'Lap Time (in minutes)')
    g.figure.suptitle(super_title, y = 1.02)

    for ax in g.axes.flat:
        ax.set_title(ax.get_title()[13:].title())
    return g

path = 'charts/circuit_data/'
extension = '.png'

def save_plot (
    data_set : pd.DataFrame,
    super_title : str,
    subfolder : str = '',
    x_label : str = "Lap Time (in Minutes)",
    y_label : str = "Year",
    y_lim : float = None,
):
    # Save individual plots to directory

    sns.set_style('whitegrid')

    for cir in lap_data_min.circuit_id.unique().tolist():

        g = sns.relplot(
            data=data_set.query(f'circuit_id == "{cir}"'),
            kind='line',
            x='date',
            y='value',
            hue= 'variable' if 'variable' in data_set.columns else
None,
            # legend=False          # Used for presentation
        )

        g.figure.suptitle(f'{super_title} - {cir.title()}', y = 1.02)

        g.set_axis_labels(
            x_label,
            y_label
        )


        for ax in g.axes.flat:
            ax.set(ylim = (0, y_lim) if y_lim is not None else None)

        file = path + subfolder + cir + extension
        g.savefig(file)


save_plot(lap_data_min, "Fastest Lap Time over Year")

```


Fastest Lap Time over Year - Monza





Fastest Lap Time over Year - Monaco




Fastest Lap Time over Year - Silverstone









```
create_plot(lap_data_min, "Fastest Lap Time over Year")
<seaborn.axisgrid.FacetGrid at 0x16b3a3750>
```




```
save_plot(
    data_set=data_percent_change,
    super_title="Percent Decrease in Record over Time",
    subfolder='pct_change/',
    y_label='Percent Change in Record',
    y_lim = .5
)
```









Percent Decrease in Record over Time - Spa-Francorchamps

