

Building the Cross-Compilation Toolchain

Pieter P

To compile software for the Raspberry Pi, you need a cross-compilation toolchain. A cross-compilation toolchain is a collection of development files and programs that you can run on your computer or workstation, that produce binaries that can be executed on a different system with a possibly different architecture, such as a Raspberry Pi.

Downloading a pre-built toolchain

If you need the cross-compiled programs and libraries like Python and OpenCV, the toolchain will be included in the next step.

If, on the other hand, you just want the toolchain, without any of the additional programs and libraries, you can install the toolchain separately. The easiest way is to just download and extract the pre-built toolchains from GitHub. Pick the one for the Raspberry Pi you need:

```
$ mkdir -p ~/opt
$ wget -qO- https://github.com/tttapa/docker-arm-cross-toolchain/releases/latest/download/x-tools-armv6-rpi-linux-gnueabihf.tar.bz2 | tar xJ -C ~/opt
```

```
$ mkdir -p ~/opt
$ wget -qO- https://github.com/tttapa/docker-arm-cross-toolchain/releases/latest/download/x-tools-armv8-rpi3-linux-gnueabihf.tar.bz2 | tar xJ -C ~/opt
```

```
$ mkdir -p ~/opt
$ wget -qO- https://github.com/tttapa/docker-arm-cross-toolchain/releases/latest/download/x-tools-aarch64-rpi3-linux-gnu.tar.bz2 | tar xJ -C ~/opt
```

For more details on how to select the correct one, and instructions for adding it to your PATH, see [tttapa/docker-arm-cross-toolchain](https://github.com/tttapa/docker-arm-cross-toolchain).

Building the toolchain yourself

If you want full control over the toolchain, customizing the compiler, debugger and other tools, the libc version, Linux version, etc., you can build the toolchain yourself, using [crosstool-NG](https://github.com/tttapa/crosstool-ng) and the config files provided by [tttapa/docker-arm-cross-toolchain](https://github.com/tttapa/docker-arm-cross-toolchain).

Docker

As explained on the previous page, building the toolchain happens inside of a Docker container. This allows you to experiment in a sandbox-like environment. Starting from scratch is really easy, and you don't have to worry about messing up your main Linux installation. When you're done building, you can just delete the Docker containers and images.

Dockerfiles

A Dockerfile describes how the Docker image is built. In this project, we'll start from a standard Ubuntu image, install some build tools, and then compile the toolchain and the dependencies. Each step of the build process creates a new layer in the image. This is handy, because it means that if a build fails in one of the last steps, you can just fix it in your Dockerfile, and build it again. It'll then start from the last layer that was successfully built before, you don't have to start from the beginning (which would take a while, since we'll be building many large projects.)

The actual Dockerfiles used for the build can be found on GitHub at [tttapa/docker-crosstool-ng-multiarch: Dockerfile](https://github.com/tttapa/docker-crosstool-ng-multiarch: Dockerfile) and [tttapa/docker-arm-cross-toolchain: Dockerfile](https://github.com/tttapa/docker-arm-cross-toolchain: Dockerfile). I'll briefly go over them on this page.

The following Dockerfile downloads, builds and installs crosstool-NG.

tttapa/docker-crosstool-ng-multiarch: Dockerfile

```

1 FROM ubuntu:focal as ct-ng
2
3 # Install dependencies to build toolchain
4 ENV DEBIAN_FRONTEND=noninteractive
5 RUN apt-get update && \
6     apt-get install -y gcc g++ gperf bison flex texinfo help2man make libncurses5-dev unzip \
7         python3-dev autoconf automake libtool libtool-bin gawk wget rsync git && \
8     apt-get clean autoclean && \
9     apt-get autoremove -y && \
10    rm -rf /var/lib/apt/lists/*
11
12 # Add a user called `develop` and add him to the sudo group
13 RUN useradd -m develop && \
14     echo "develop:develop" | chpasswd && \
15     adduser develop sudo
16
17 USER develop
18 WORKDIR /home/develop
19
20 # https://www.raspberrypi.org/forums/viewtopic.php?f=91&t=280707&p=1700861#p1700861
21 RUN wget https://ftp.debian.org/debian/pool/main/b/binutils/binutils-source_2.31.1-16_all.deb && \
22     mkdir binutils && cd binutils && \
23     ar x ../binutils-source_2.31.1-16_all.deb && \
24     tar xf data.tar.xz && \
25     cp usr/src/binutils/patches/129_multiarch_libpath.patch /home/develop
26
27 # Download and install the latest version of crosstool-ng
28 RUN git clone -b master --single-branch --depth 1 \
29     https://github.com/crosstool-ng/crosstool-ng.git
30 WORKDIR /home/develop/crosstool-ng
31 RUN git show --summary && \
32     ./bootstrap && \
33     mkdir build && cd build && \
34     ../configure --prefix=/home/develop/.local && \
35     make -j$((nproc * 2)) && \
36     make install && \
37     cd .. && rm -rf build
38 ENV PATH=/home/develop/.local/bin:$PATH
39 WORKDIR /home/develop

```

You'll notice that the Dockerfile downloads a patch for the binutils package. This is done in order to support [Debian Multiarch](#). Raspberry Pi OS and Ubuntu are both configured for Multiarch by default, so the toolchains we build must support this. To this end, we need to patch binutils. For more details, see [this forum post](#).

Next, we build another Docker image, which actually builds the toolchain, using the crosstool-NG installation from the previous step.

tttapa/docker-arm-cross-toolchain:Dockerfile

```

1 FROM ghcr.io/tttapa/docker-crosstool-ng-multiarch:master
2
3 ARG HOST_TRIPLE
4
5 WORKDIR /home/develop
6 RUN mkdir /home/develop/host-config && mkdir /home/develop/src
7 WORKDIR /home/develop/host-config
8 COPY ${HOST_TRIPLE}.config .config
9 COPY ${HOST_TRIPLE}.env .env
10 RUN mkdir -p patches/binutils/2.31.1 && \
11     cp /home/develop/129_multiarch_libpath.patch patches/binutils/2.31.1
12 RUN ls -lah
13
14 # https://www.raspberrypi.org/forums/viewtopic.php?f=91&t=280707&p=1700861#p1700861
15 RUN . ../.env; export DEB_TARGET_MULTIARCH="${HOST_TRIPLE_LIB_DIR}"; \
16     V=1 ct-ng build || { cat build.log && false; } && rm -rf .build
17
18 ENV TOOLCHAIN_PATH=/home/develop/x-tools/${HOST_TRIPLE}
19 ENV PATH=${TOOLCHAIN_PATH}/bin:$PATH
20 WORKDIR /home/develop

```

Different variants of the Raspberry Pi use different configuration files. These files have names that contain the full [target triplet](#). They can be found on GitHub in [same folder](#) as the Dockerfile.

Building the crosstool-NG base image

This step is optional. It can be useful to build it yourself if you want the very latest version of crosstool-NG.

```

$ cd docker-crosstool-ng-multiarch
$ docker build . -t ghcr.io/tttapa/docker-crosstool-ng-multiarch:master

```

If you skip this step, pull the image from [GitHub](#):

```

$ docker pull ghcr.io/tttapa/docker-crosstool-ng-multiarch:master

```

Upgrading and customizing the configurations

Next, we'll use crosstool-NG to update the configuration files and interactively customize the configuration. Here you can choose versions of the compiler and other tools, Linux and libc versions, and so on.

First, start a shell in the crosstool-NG container you built or pulled in the previous step. Mount the **docker-arm-cross-toolchain** folder containing the config files, so you can access them inside of the container.

```
$ cd ../docker-arm-cross-toolchain
$ docker run -it -v"$PWD:/mnt" ghcr.io/tttapa/docker-crosstool-ng-multiarch:master
```

Now copy the configuration you need to a file named **.config**, update the configuration, make your changes, save the changes, and then overwrite the previous configuration with the new one. Here I'll use the **aarch64-rpi3-linux-gnu** configuration, but you should use the correct one for your specific setup.

```
[docker] $ # Rename the old configuration
[docker] $ cp /mnt/aarch64-rpi3-linux-gnu.config .config
[docker] $ # Upgrade the configuration
[docker] $ ct-ng upgradeconfig
[docker] $ # Customize the configuration
[docker] $ ct-ng menuconfig
[docker] $ # Overwrite the old configuration
[docker] $ cp .config /mnt/aarch64-rpi3-linux-gnu.config
[docker] $ exit
```

Building the toolchain

Finally, build the toolchain with the new config. Use the host triple that matches the configuration file name.

```
$ docker build . --build-arg=HOST_TRIPLE=aarch64-rpi3-linux-gnu -t ghcr.io/tttapa/docker-arm-cross-toolchain:aarch64-rpi3-linux-gnu
```

Packaging and extracting the toolchain

Finally, create a tar archive of the toolchain, and copy it out of the Docker container so you can use it.

```
$ container=$(docker run -d ghcr.io/tttapa/docker-arm-cross-toolchain:aarch64-rpi3-linux-gnu bash -c "tar cJf x-tools.tar.bz2 x-tools")
$ docker wait $container
$ docker cp $container:/home/develop/x-tools.tar.bz2 x-tools-aarch64-rpi3-linux-gnu.tar.bz2
$ docker rm $container
```

Installing the toolchain

You can now simply extract the toolchain and install it somewhere on your system, e.g. in **~/opt**:

```
$ mkdir -p ~/opt
$ tar xJf x-tools-aarch64-rpi3-linux-gnu.tar.bz2 -C ~/opt
```

For more details on how to select the correct one, and instructions for adding it to your PATH, see [tttapa/docker-arm-cross-toolchain](https://github.com/tttapa/docker-arm-cross-toolchain).