

# Building the Cross-Compilation Toolchain

Pieter P

To compile software for the Raspberry Pi, you need a cross-compilation toolchain. It's a collection of files and programs that you can run on your computer, and that produce a binary that can be executed on the Raspberry Pi.

If you want to do development on the Pi itself, you'll need a native toolchain as well. This is a toolchain that runs on the Pi, and produces binaries for the Pi.

## Docker

---

As explained on the previous page, building the toolchain happens inside of a Docker container. This allows you to experiment in a sandbox-like environment. Starting from scratch is really easy, and you don't have to worry about messing up your main Linux installation.

You can compare a Docker container with a virtual machine, but without the virtualization. Programs that run inside of the container use the same kernel as your main Linux OS, and there's almost no performance overhead.

It's very easy to share Docker images, so you don't have to build everything from scratch yourself, you can just pull it from Docker Hub.

## Dockerfiles

A Dockerfile describes how the Docker image is built. In this project, we'll start from a standard Ubuntu image, install some build tools, and then compile the toolchain and the dependencies. Each step of the build process creates a new layer in the image. This is handy, because it means that if a build fails in one of the last steps, you can just fix it in your Dockerfile, and build it again. It'll then start from the last layer that was successfully built before, you don't have to start from the beginning (which would take a while, since we'll be building many large projects.)

The actual Dockerfiles used for the build can be found [on my GitHub](#), I'll briefly go over them on this page.

## Pulling the toolchain from Docker Hub

---

If you just want to use the toolchain, without understanding how it works, and without changing anything to the configuration, you can just pull the toolchains I built from Docker Hub.

To pull and export the toolchain, you can use:

```
$ ./toolchain/toolchain.sh <board> --export-toolchain
```

Where **<board>** is one of the following:

- **rpi**: Raspberry Pi 1 or Zero, cross-compilation toolchain
- **rpi-dev**: Raspberry Pi 1 or Zero, cross-compilation toolchain and native toolchain
- **rpi3-armv8**: Raspberry Pi 3, 32-bit, cross-compilation toolchain
- **rpi3-armv8-dev**: Raspberry Pi 3, 32-bit, cross-compilation toolchain and native toolchain
- **rpi3-aarch64**: Raspberry Pi 3, 64-bit, cross-compilation toolchain
- **rpi3-aarch64-dev**: Raspberry Pi 3, 64-bit, cross-compilation toolchain and native toolchain

## Building the toolchain using the provided shell scripts

---

Instead of pulling from Docker Hub, you can build the toolchain locally instead. I would only recommend this if you made changes to the toolchain configuration files, or if you have a really fast computer with a slow internet connection.

Building one toolchain took around 25 minutes on a 2018 Dell XPS i7-8750H, and 40 minutes on a 2017 Dell XPS i7-7700HQ.

```
$ ./toolchain/toolchain.sh <board> --build-toolchain --export-toolchain
```

The cross-compilation toolchain will be located in **toolchain/x-tools/<arch>-rpi\*-linux-<abi>**, and the native toolchain will be in **toolchain/x-tools/HOST-<arch>-linux-<abi>/<arch>-rpi\*-linux-<abi>**.

## Deleting the toolchains

The toolchains are read-only, to prevent you from accidentally breaking them during a build. If you try to delete them using the usual methods, you'll get **Permission denied**. The solution is to make them writable first, using **chmod**.

The **toolchain/clean.sh** script will do this for you, and deletes all toolchains in the **toolchain** folder:

```
$ ./toolchain/clean.sh
```

The toolchains will still be available in the Docker images used to build them. This means that next time you run the **build-and-export-toolchain.sh** script, it will finish in just a couple of seconds, as it just has to export the toolchain, it doesn't build it from scratch.

If you want to delete these Docker images as well (to save disk space, for instance), you can use **docker image ls** to inspect all images on your system, and then you can delete them using **docker image rm <image>**.

## Detailed information about configuring and building toolchains

---

As mentioned before, you don't need to read or understand the sections below if you just want to use the toolchain.

If you're interested in how the toolchains are actually configured and built, or if you want to customize the configuration, you'll find the necessary information below.

### Crosstool-NG

---

The toolchain is built using [Crosstool-NG](#).

The following Dockerfile downloads, builds and installs Crosstool-NG to the `~/local` directory of the container.

#### Dockerfile

```
1 FROM ubuntu:focal as ct-ng
2
3 # Install dependencies to build toolchain
4 ENV DEBIAN_FRONTEND=noninteractive
5 RUN apt-get update && \
6     apt-get install -y gcc g++ gperf bison flex texinfo help2man make libncurses5-dev unzip \
7         python3-dev autoconf automake libtool libtool-bin gawk wget rsync git && \
8     apt-get clean autoclean && \
9     apt-get autoremove -y && \
10    rm -rf /var/lib/apt/lists/*
11
12 # Add a user called `develop` and add him to the sudo group
13 RUN useradd -m develop && \
14     echo "develop:develop" | chpasswd && \
15     adduser develop sudo
16
17 USER develop
18 WORKDIR /home/develop
19
20 RUN wget https://ftp.debian.org/debian/pool/main/b/binutils/binutils-source_2.31.1-16_all.deb && \
21     mkdir binutils && cd binutils && \
22     ar x ../binutils-source_2.31.1-16_all.deb && \
23     tar xf data.tar.xz && \
24     cp usr/src/binutils/patches/129_multiarch_libpath.patch /home/develop
25
26 # Download and install the latest version of crosstool-ng
27 RUN git clone -b master --single-branch --depth 1 \
28     https://github.com/crosstool-ng/crosstool-ng.git
29 WORKDIR /home/develop/crosstool-ng
30 RUN git show --summary && \
31     ./bootstrap && \
32     mkdir build && cd build && \
33     ../configure --prefix=/home/develop/.local && \
34     make -j$(($(nproc) * 2)) && \
35     make install && \
36     cd .. && rm -rf build
37 ENV PATH=/home/develop/.local/bin:$PATH
38 WORKDIR /home/develop
```

The list of dependencies can be found on Crosstool-NG's GitHub: <https://github.com/crosstool-ng/crosstool-ng/blob/master/testing/docker/ubuntu19.10/Dockerfile>

### Cross-Compilation Toolchain

---

The following Dockerfile builds the toolchain:

#### Dockerfile

```

1 FROM ttapa/crosstool-ng-master as cross-toolchain
2
3 ARG HOST_TRIPLE
4 ARG HOST_TRIPLE_LIB_DIR
5
6 WORKDIR /home/develop
7 RUN mkdir /home/develop/RPi && mkdir /home/develop/src
8 WORKDIR /home/develop/RPi
9 COPY ${HOST_TRIPLE}.config .config
10 RUN mkdir -p patches/binutils/2.31.1 && \
11     cp /home/develop/129_multiarch_libpath.patch patches/binutils/2.31.1
12
13 # https://www.raspberrypi.org/forums/viewtopic.php?f=91&t=280707&p=1700861#p1700861
14 ENV DEB_TARGET_MULTIARCH=${HOST_TRIPLE_LIB_DIR}
15 RUN ct-ng build || { cat build.log && false; } && rm -rf .build
16
17 ENV TOOLCHAIN_PATH=/home/develop/x-tools/${HOST_TRIPLE}
18 ENV PATH=${TOOLCHAIN_PATH}/bin:$PATH
19 WORKDIR /home/develop

```

The different configuration files have names that contain the full target triplet. They can be found in same folder as the Dockerfile.

## Raspberry Pi 3, 64-bit (AArch64)

This configuration is based on the `aarch64-rpi3-linux-gnu` sample that comes with Crosstool-NG: <https://github.com/crosstool-ng/crosstool-ng/tree/master/samples/aarch64-rpi3-linux-gnu>

I changed the GCC version to the latest stable one, and the Linux kernel and glibc versions to match the versions that the Ubuntu Server 18.04 image ships with.

## Raspberry Pi 3, 32-bit (ARMv8)

This configuration is based on the `armv8-rpi3-linux-gnueabi` sample that comes with Crosstool-NG: <https://github.com/crosstool-ng/crosstool-ng/tree/master/samples/armv8-rpi3-linux-gnueabi>

Even though the CPU will be running in 32-bit mode, you can still use the ARMv8 NEON instructions, so I changed the compiler's default FPU flag to `neon-fp-armv8`. I haven't tested if it actually makes any difference.

I changed the GCC version to the latest stable one, and the Linux kernel and glibc versions to match the versions that the Ubuntu Server 18.04 image ships with. These are also supported on Raspbian Buster.

## Raspberry Pi 1 & Zero, 32-bit (ARMv6)

This configuration is based on the `armv6-rpi-linux-gnueabi` sample that comes with Crosstool-NG: <https://github.com/crosstool-ng/crosstool-ng/tree/master/samples/armv6-rpi-linux-gnueabi>

## Native toolchain

Building the native toolchain for the Raspberry Pi is very similar.

### Dockerfile

```

1 FROM ttapa/crosstool-ng-master as cross-native-toolchain
2
3 ARG HOST_TRIPLE
4 ARG HOST_TRIPLE_LIB_DIR
5
6 WORKDIR /home/develop
7 RUN mkdir /home/develop/RPi && mkdir /home/develop/src
8 WORKDIR /home/develop/RPi
9 COPY ${HOST_TRIPLE}.config .config
10 RUN mkdir -p patches/binutils/2.31.1 && \
11     cp /home/develop/129_multiarch_libpath.patch $_
12
13 # https://www.raspberrypi.org/forums/viewtopic.php?f=91&t=280707&p=1700861#p1700861
14 ENV DEB_TARGET_MULTIARCH=${HOST_TRIPLE_LIB_DIR}
15 RUN ct-ng build || { cat build.log && false; } && rm -rf .build
16
17 WORKDIR /home/develop

```

The toolchain type is "Cross-Native", and is implemented as a special case of the "Canadian Cross" toolchain. It uses the cross-compilation toolchain that was built earlier. More information can be found in the [Crosstool-NG documentation](#).

## Customizing the toolchain

You can customize all previously mentioned toolchains by running `ct-ng menuconfig` on the corresponding configuration file. The easiest way to do this is by running it inside of the `crosstool-ng-master` Docker container.

```
$ cd RPi-Cpp-Toolchain/  
$ ./toolchain/docker/crosstool-ng-master/build.sh  
$ docker run -it --rm --volume "$PWD/toolchain/docker:/mnt" ttapa/crosstool-ng-master
```

```
[docker] $ cd /mnt/merged/cross-toolchain/  
[docker] $ cp aarch64-rpi3-linux-gnu.config .config # Choose RPi model and architecture  
[docker] $ ct-ng menuconfig
```

Now make your changes and save the result to **.config**.

```
[docker] $ # Rename the old configuration  
[docker] $ mv aarch64-rpi3-linux-gnu.config aarch64-rpi3-linux-gnu.config.old  
[docker] $ # Replace with new configuration  
[docker] $ mv .config aarch64-rpi3-linux-gnu.config  
[docker] $ exit
```

Now you can build the toolchain again using the **./toolchain.sh** script, as explained earlier:

```
$ ./toolchain/toolchain.sh <board> --build-toolchain --export-toolchain
```