

DSLs as Harnesses:

Declarative Applications-as-Data as a Reliability Substrate for LLM Agents

Satoshi Nakajima

The Singularity Society

satoshi.nakajima@gmail.com

June 14, 2026

Abstract

A recurring lesson of applied agent engineering is that the *harness*—the designed environment an agent operates in—governs reliability more than the underlying model. We argue that a *domain-specific language* (DSL) is one of the most effective harnesses available for autonomous, long-horizon agents, precisely because it gives up the unbounded expressiveness of general-purpose code in exchange for a small, legible, checkable surface. We make this concrete by describing **Collections**, a declarative *applications-as-data* system implemented in Mulmo-Claude, an open-source LLM-agent application. In Collections, a single JSON schema defines an application’s data model, relationships, computed values, recurrence, user interface, external-data acquisition, and workflows; record files are the database; and the language model is the runtime that operates inside the schema rather than writing imperative code. We show how four well-known harness properties—schema-as-system-of-record, a validator as a free feedback loop, a grammar as a forcing function, and a unit of the language as a unit of context—fall out of this single design decision, and how a deliberate *reliability dial* divides what the host guarantees deterministically (schema validity, derived-value computation, recurrence math, sandboxed rendering, scheduled ingestion) from what the model supplies (judgment, language, domain modeling). We report a longitudinal single-user deployment in which 26 applications, 6 bespoke sandboxed UI views, and 3 external feeds accreted over roughly two months without any host code being written per application. We discuss the design’s principal hazard—the escape hatch from the declarative surface to arbitrary code—and its limitations, including non-replayable execution and the single-user, single-system scope of our evidence.

Keywords: LLM agents; agent harness; domain-specific languages; end-user software engineering; low-code; applications as data; declarative systems.

1 Introduction

The prevailing lesson of applied AI engineering in 2024–2026 is that the *harness*—the designed environment an agent operates inside: the tools it can call, the format of the information it receives, the feedback that catches its mistakes, and the scaffolding that lets it hand work to its future self—matters more than the model alone [9, 10]. The same model, given a better harness, produces dramatically better work. For a language model, the interface is not a convenience layer wrapped around the intelligence; it is the cognitive architecture.

This paper argues a narrower and, we believe, more actionable point: **a domain-specific language (DSL) is one of the most powerful harnesses one can give an agent, precisely because it gives up power.** A general-purpose programming language is Turing-complete; that

is its glory and, for an autonomous agent, its hazard. There are infinitely many ways to express any behavior, no two codebases agree on conventions, and nothing in the language tells the agent whether a given program is *correct for this domain*. Freedom under uncertainty is where agents thrash: they explore broadly, drift toward locally plausible patterns, and accumulate subtle errors that surface much later. A DSL inverts every one of those properties—it expresses a bounded set of things, in a bounded number of ways, and typically ships with a parser and validator that can decide well-formedness before anything executes.

We ground the argument in a working system. **Collections** is a feature of MulmoClaude,¹ an open-source agent application built on the Claude Agent SDK whose founding philosophy is *the workspace is the database; files are the source of truth; the model is the intelligent interface*. A collection is defined by a single JSON *schema* that simultaneously specifies a data model, inter-record relationships, spreadsheet-like derived computations, completion and notification rules, host-driven recurrence, a rendered user interface, optional bespoke HTML views, and optional scheduled ingestion of external data. The records are plain JSON files on disk. The host platform contains *zero* domain knowledge; it understands only generic concepts (fields, relationships, derived values, views, actions, ingestion). Everything domain-specific lives in the schema, and the language model operates the application by reading and writing records under the schema’s constraints.

The significance for reliability is that a self-built, model-operated application need not be “flaky chat with extra steps.” The DSL is a contract that pins down what must be deterministic while the model supplies flexibility and judgment, and the two live on opposite sides of a deliberate line we call the *reliability dial* (§5). A schema *validator* makes the boundary self-enforcing: a structurally incoherent application is rejected at load, with an actionable message, before it can run.

Contributions.

1. We articulate **DSL-as-harness**: a mapping from a single design decision (constrain the agent’s authoring surface to a validated DSL) to four established harness properties, and an argument for why the case strengthens, rather than weakens, as models improve (§3).
2. We describe **Collections**, a concrete declarative applications-as-data system, including its schema DSL, relationships, derived formulas, host-driven recurrence, sandboxed custom views, and declarative feed ingestion (§4).
3. We formalize the **host/model responsibility split** and the *reliability dial*, and explain the validator and escape-hatch mechanisms that keep the surface both safe and expressive (§5, §6).
4. We report a **longitudinal single-user deployment**: 26 applications, 6 bespoke sandboxed views, and 3 external feeds accreted over ~2 months with no per-application host code (§7).
5. We give an **honest account of the limitations**: the escape-hatch hazard, non-replayable execution, and the scope of our evidence (§8).

2 Background and Related Work

Agent harnesses and agent–computer interfaces. Yang et al. [9] showed that a purpose-built agent–computer interface (ACI)—structured tools, capped and guided search, and a linter that rejects syntactically broken edits at the moment of introduction—improves software-engineering

¹<https://github.com/receptron/mulmoclaude>

agent performance substantially with a fixed model. Yao et al. [10] interleave reasoning and acting; Schick et al. [7] teach models to call external tools. These works establish the empirical primacy of the surrounding environment. Our contribution is to identify the *DSL* as a particularly sharp instance of such an environment and to instantiate it as an applications-as-data substrate.

Self-improving and memory-augmented agents. Voyager [8] accretes a reusable skill library, and Generative Agents [6] maintain a memory stream they reflect over. Both let an agent extend itself over time. Collections differ in substrate: the agent’s accreted capabilities are *declarative DSL artifacts on disk*, not learned weights or imperative code, which makes them inspectable, diffable, and validated. A complementary line of work makes the event log the primary artifact—Nakajima [4] prioritizes an append-only log to obtain deterministic replay and cheap forking. We deliberately forgo byte-for-byte replay (the model step is nondeterministic) in exchange for an agent whose configuration is plain, readable, validated files; §8 returns to this trade.

Domain-specific languages. The software-engineering literature has long studied when and how a deliberately limited language pays off [1, 3]: a DSL trades general expressiveness for analyzability, a smaller error surface, and tooling (parsers, validators) that come “for free.” We apply this classical argument to a new consumer—an autonomous language-model agent—and observe that the properties DSLs were always praised for map directly onto modern harness-engineering guidance.

End-user software engineering and low-code. End-user programming has sought for decades to let non-programmers build software, from the spreadsheet onward [2, 5]; commercial low-code/no-code platforms (Airtable, Notion, Retool, PowerApps) continue this lineage. The persistent constraint in that tradition is that the user must work inside a constrained authoring surface *and* perform the assembly. Collections keeps the constrained, validated surface but moves authorship to the agent: the user expresses intent in natural language and the agent emits the DSL. We position this as a shift from *no-code* (a human composes blocks) to *intent-driven* (an agent composes the DSL program from intent).

3 A DSL Is a Harness

When you hand an agent a DSL you are not merely giving it a tool; you are reshaping the space it must search. That reshaping makes four classic harness patterns fall out of a single design decision.

(1) The schema is the system of record. Harness engineering insists that anything the agent cannot read in context effectively does not exist; intent must live in a machine-readable artifact. A DSL satisfies this by construction: its schema *is* the specification. When the agent writes a DSL document, the user’s intent is captured as a structured, inspectable object rather than dissolved into the incidental details of imperative code. It can be diffed, versioned, validated, and reasoned about without running it.

(2) The validator is a free feedback loop. The highest-leverage component in the SWE-agent study was a linter that rejected broken edits at the moment of introduction, before the error could propagate through later steps [9]. Every DSL ships with this loop: the instant the agent emits a malformed structure, a parser or schema checker rejects it with a localized, actionable message. The feedback loop came bundled with the language.

(3) The grammar is a forcing function. Because the vocabulary is finite, the room to hallucinate is structurally smaller. The agent cannot invent an option absent from the grammar; it can only compose the primitives the language provides. Constraint, here, is a feature.

(4) The unit of the language is the unit of context. A well-designed DSL has a natural decomposition—a field, a record, a rule—which becomes the agent’s editing unit. It can work on one piece without holding the whole document in mind, and the language’s structure, not an ad-hoc heuristic, defines the seams (progressive disclosure).

Why this matters more as models improve. A tempting intuition holds that DSLs are a crutch for weak models. We argue the opposite. The case for a constrained, validated surface is strongest exactly where we want to delegate *autonomously and over long horizons*: where no human reviews each step, where output must be verifiable, and where execution must be deterministic and reversible. A stronger model inside a DSL harness is not wasted capability; it is capability aimed at the part of the problem that genuinely requires judgment—what to model, what to express—while the language guarantees the rest.

4 The Collections System

Collections applies the DSL-as-harness idea to software itself. A collection is:

`schema.json + records/*.json + model = application.`

There is no database server, no migration framework, and no application-specific backend. The host understands only generic capabilities; everything domain-specific lives in the collection.

4.1 The schema DSL

A schema declares typed *fields*. The current implementation supports 17 field types, including `string`, `text`, `number`, `date`, `datetime`, `boolean`, `markdown`, `enum`, `money`, `image`, `file`, a nested `table` of sub-records, two relationship types (`ref`, `embed`), a computed `derived` field, and a `toggle` that projects an enum. Relationships are first-class: a `ref` stores a foreign key and the host renders pickers, links, and navigation generically; an `embed` pulls a fixed record from another collection for display.

4.2 Computation without code

A `derived` field behaves like a spreadsheet formula, but formulas may follow references into other collections:

```
"total": {
  "type": "derived", "display": "money", "currencyField": "currency",
  "formula": "sum(lineItems[].quantity * lineItems[].rate) * (1 + taxRate)"
}
```

The host evaluates derived fields, and crucially returns them *to the model* as well as to the screen, so the agent reasons over the same numbers the user sees. A portfolio can revalue itself when a quote changes elsewhere, with no synchronization code.

4.3 Completion, notification, and host-driven recurrence

A schema can mark which field and values count as “done” (`completionField` / `completionDoneValues`), gate notifications on a date (`triggerField` / `triggerLeadDays`), and—via a `spawn` block—provision the next instance of a recurring obligation on a civil-date cadence when the current one closes:

```
"triggerField": "dueOn", "triggerLeadDays": 3,
"spawn": {
  "every": { "unit": "month", "interval": 1, "dayOfMonth": 10 },
  "carry": ["payee", "amount"], "set": { "status": "pending" }
}
```

The author declares *what recurs and when to nudge*; the host’s reconciler owns the deterministic half—raising and clearing reminders and advancing each cycle with create-if-absent (idempotent) semantics. No timer, cron expression, or notification code is written.

4.4 Custom views: bespoke UI as data

Host-rendered field types give every collection a list, a detail form, and—when declared—calendar and Kanban layouts for free. When field types cannot present the data well (a portfolio as an allocation chart, a set of places as a map, a word list as flashcards), a collection may carry a *custom view*: an HTML file the agent authors and the host serves.

```
"views": [
  { "id": "allocation", "label": "Allocation",
    "file": "views/allocation.html", "capabilities": ["read", "write"] }
]
```

A view is an ordinary web page (it may load a charting library from a curated CDN allow-list) but it is rendered inside a sandboxed `iframe` under a strict Content-Security-Policy: an opaque origin, `default-src 'none'`, and network access only back to the host. It receives its records through a capability-scoped, time-limited token rather than ambient access; the declared `capabilities` (`read`, `write`) bound what that token permits. A custom view is thus not a hole in the harness but the same bargain as the rest of the system: the model supplies the bespoke surface, the host supplies the deterministic, sandboxed boundary, and the presentation layer too becomes inspectable, versioned data.

4.5 Feeds: acquisition as data

Some applications track an external source—a podcast’s episodes, a newspaper’s headlines, a JSON API. Such a collection declares an `ingest` block and becomes a *feed*:

```
"ingest": {
  "kind": "rss", "url": "https://lexfridman.com/feed/podcast/",
  "schedule": "daily", "idFrom": "guid",
  "map": { "headline": "title", "url": "link", "published": "pubDate" },
  "maxItems": 100
}
```

`kind` selects a retriever (`rss`, `atom`, `http-json`); `map` projects source fields onto collection fields; `schedule` (hourly/daily/weekly/on-demand) sets cadence; `maxItems` caps retention. The host owns fetching, parsing, field mapping, de-duplication by id, pruning, and cursor/failure tracking. Because

Host guarantees (deterministic)	Model owns (judgment)
Schema validity (load-time)	What to model
Path safety, record storage	What a record means
Derived-value computation	How a workflow should proceed
Recurrence / civil-date math	When to hand off to a human
Sandboxed view rendering (CSP)	How to present data (authoring the view)
Scheduled ingestion + de-dup	Which external source, mapped how

Table 1: The host/model responsibility split. Everything on the left runs identically every time; everything on the right is where the model’s flexibility is wanted.

a feed is still a collection, the user can layer their own fields onto the ingested ones—a rating, a note, a resume position—turning a passive mirror into a read-write application over an external source.

5 The Reliability Dial

The reason a self-built, model-operated application is reliable rather than flaky is a single principle: **the DSL is a contract that pins down what must be deterministic, while the model supplies flexibility, judgment, and language.** Table 1 summarizes the split.

A schema validator makes the boundary self-enforcing. A structurally incoherent application is rejected at load with an actionable reason—examples include a money field with neither a literal currency nor a per-record currency field, a `ref` pointing at a non-existent collection, a `triggerField` that does not name a real date field, and a `spawn` whose successor would be born already matching its own predicate (an unbounded respawn).

The craft is *where the dial sits*. Push everything into the DSL and you rebuild the brittle “can’t-express-this” cage that made no-code platforms frustrating; push everything to the model and you lose the durable contract that made it an application at all. The guiding rule is to *extend the declarative layer only when it outperforms the agent*.

6 The Escape Hatch

The same rigidity that makes a DSL a good harness is its failure mode: when the language cannot express what the user needs, an agent will either give up or contort the DSL into something it was never meant to hold. Every well-designed DSL answers this with a deliberate exit to a more expressive layer.

Collections provides two. First, a per-record or collection-level `action` hands off to a seeded chat—a full-tool agent—exactly when a task needs human judgment the form cannot capture (“generate the invoice PDF,” “what was the amount, and was it actually paid?”). This is business logic as prose, behind a declarative door. Second, the *custom view* (§4) is the escape for presentation: when host-rendered field types cannot express a layout, the schema drops to arbitrary HTML in a sandbox rather than distorting the field-type vocabulary. The art is not to maximize constraint but to choose *where* the constraint binds and to provide a clean, legible path out where it does not. A harness with no escape hatch eventually forces the agent to fail or to lie, and both are worse than a slightly leakier abstraction.

Collection	#rec	Collection	#rec	Collection	#rec
mag2-subscribers	466	engagements	22	recurring-bills	6
vocabulary	50	restaurants	20	videos	6
todos	23	lessons-biology	12	worklog	6
reading-list	10	baseball-scout	11	portfolio	4
stock-quotes	10	watchlist	10	html-apps	4
tax-payments	7	clients	3	(13 more)	≤ 2

Table 2: Representative collections by record count in the studied workspace (26 total). Sizes span from a single-record profile to 466 newsletter subscribers.

7 Case Study: A Longitudinal Single-User Deployment

We report on one author’s production workspace, which has accreted applications through ordinary use over roughly two months. No host code was written for any of these applications; each is a schema plus records, authored by the agent in response to natural-language requests.

Scale. The workspace contains 26 collections holding ~ 700 records. Their sizes vary by three orders of magnitude (Table 2), consistent with the claim that the marginal cost of a new application is low enough to justify even a single-record one.

Mechanisms exercised in practice. The deployment uses every major mechanism described in §4: relationships (an `invoice` references a `client` and embeds the issuer profile), derived computation (invoice totals from line items and tax), host-driven recurrence (monthly and annual obligations via `spawn`), and completion/notification gating (`todos`, tax payments).

Bespoke views. Six collections carry custom HTML views authored by the agent on request: a restaurant guide rendered as a transit-style map, a movie watchlist as a poster gallery, a vocabulary list as a flashcard drill, a portfolio as an allocation chart, a scouting collection as per-entity radar charts, and a subscriber collection as a trend line. Each is software with an addressable audience of one—software no vendor would build—produced for the cost of a request. The owner never wrote or read the HTML.

Feeds. Three collections are feeds: an hourly newspaper-technology feed (64 records at time of writing), and two daily podcast feeds (100 records each). One podcast feed is read-write: the schema layers the owner’s own rating, notes, and resume-position fields on top of the ingested episode metadata, and the host serves a custom gallery view over the combined record.

Observations. Two qualitative observations stand out. (i) *No per-application host code* was required for any of the 26 applications; the host’s generic capabilities sufficed, which is the load-bearing claim of applications-as-data. (ii) The applications *diverge sharply from any mass-market product*: a transit-map restaurant guide and a read-write podcast tracker with personal resume positions reflect one user’s specific needs, supporting the view that a near-zero marginal build cost shifts the natural unit of software from the mass-market product toward the individual.

8 Discussion and Limitations

The escape-hatch hazard. The expressiveness that escape hatches restore is also unconstrained: a custom view or a seeded-chat action runs outside the declarative guarantees. We mitigate this for views with sandboxing and capability-scoped tokens (§4), but the general tension—more expressiveness, fewer guarantees—is fundamental and must be managed per escape, not eliminated.

Non-replayable execution. Because the operating step is a nondeterministic model call, a run cannot be replayed byte-for-byte, and a self-modification’s effect cannot be A/B-replayed against the prior behavior on identical inputs. This is the deliberate trade against log-primary designs [4]. The mitigation is configuration-level rather than run-level: a git-backed workspace makes every schema and view edit auditable and revertable, which is the granularity that matters for an agent editing its own applications.

Correctness has no second audience. Mass software accumulates correctness through many users and years; an application with an audience of one does not. A wrong poster gallery is harmless, but a wrong financial or tax view is not, and only the model and the single user ever inspect it. The reliability dial is the relevant defense—push consequential computation into host-guaranteed derived fields rather than leaving it to a generated view—but the residual risk is real and is the price of building for one.

Threats to validity. Our empirical evidence is a single user, a single system, and an author-operated deployment; it demonstrates feasibility and the no-host-code property but does not establish generality, and it reports usage rather than a controlled comparison. Quantifying authoring effort, error rates, and how the reliability dial should be set across users and domains is future work.

9 Conclusion

A domain-specific language is a powerful harness for an autonomous agent precisely because it relinquishes expressiveness for a small, validated, inspectable surface. Collections applies that principle to applications themselves: a schema defines the application, record files are the database, the host runs the deterministic half, and the model operates inside the schema. The result is software an agent can author and refine on request, with the reliability of a declarative contract and the flexibility of a language model held apart by a deliberate dial. Building applications shifts from writing imperative code to declaring—and validating—harnesses; the records are data, the schema is the program, and the model is the runtime.

Availability

MulmoClaude and the Collections implementation are open source. The schema validator, derived-formula evaluator, recurrence reconciler, custom-view sandbox, and feed engine referenced above are part of that codebase, available at <https://github.com/receptron/mulmoclaude>.

References

- [1] Martin Fowler. *Domain-Specific Languages*. Addison-Wesley Professional, 2010.

- [2] Andrew J. Ko, Robin Abraham, Laura Beckwith, Alan Blackwell, Margaret Burnett, Martin Erwig, Christopher Scaffidi, Joseph Lawrance, Henry Lieberman, Brad Myers, Mary Beth Rosson, Gregg Rothermel, Mary Shaw, and Susan Wiedenbeck. The state of the art in end-user software engineering. *ACM Computing Surveys*, 43(3):1–44, 2011. doi: 10.1145/1922649.1922658. VERIFY pages/DOI.
- [3] Marjan Mernik, Jan Heering, and Anthony M. Sloane. When and how to develop domain-specific languages. *ACM Computing Surveys*, 37(4):316–344, 2005. doi: 10.1145/1118890.1118892. VERIFY pages/DOI.
- [4] Yohei Nakajima. The log is the agent: Event-sourced reactive graphs for auditable, forkable agentic systems. *arXiv preprint arXiv:2605.21997*, 2026. Primary category cs.AI; cross-list cs.MA. VERIFY id at publication.
- [5] Bonnie A. Nardi. *A Small Matter of Programming: Perspectives on End User Computing*. MIT Press, 1993.
- [6] Joon Sung Park, Joseph C. O’Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *ACM Symposium on User Interface Software and Technology (UIST)*, 2023. arXiv:2304.03442. VERIFY.
- [7] Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. arXiv:2302.04761. VERIFY.
- [8] Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. Voyager: An open-ended embodied agent with large language models. *arXiv preprint arXiv:2305.16291*, 2023. VERIFY arXiv id.
- [9] John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. SWE-agent: Agent–computer interfaces enable automated software engineering. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. arXiv:2405.15793. VERIFY arXiv id and venue.
- [10] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*, 2023. arXiv:2210.03629. VERIFY.