



# Accessing Two-Dimensional Arrays

Learn how to access the elements stored in a two-dimensional array.

We'll cover the following



- Array traversal
- Print all elements of a 2D array using for loop

## Array traversal#

To access elements in a two-dimensional array, we have to specify a row and column index.

**ArrayName** [ **RowIndex** ] [ **ColumnIndex** ] ;

Like a one-dimensional array, the index of rows and columns starts at **0**. For example, the first element of a two-dimensional array is at index **[0][0]**, the second element is stored at index **[0][1]**, and so on.

		Columns		
		Column0	Column1	Column2
Rows	Row0	arr[0][0]	arr[0][1]	arr[0][2]
	Row1	arr[1][0]	arr[1][1]	arr[1][2]
	Row2	arr[2][0]	arr[2][1]	arr[2][2]



# Print all elements of a 2D array using for loop#

Accessing each and every element in an array and then printing its value is a repetitive task. Instead, let's write a code that prints all the elements of the 2D array using the for loop. We will need two nested for loops, one to iterate through the rows of the 2D array and the other to iterate through the columns in each row.

Press the **RUN** button and see the output!

```
1  #include <iostream>
2
3  using namespace std;
4
5  int main() {
6  // Initialize row and column index
7   int row = 3 , column = 3;
8  // Initialize static 2D array
9   int Student[row][column] = {{100, 134, 234}, {34, 189, 221}, {109, 139, 56}};
10
11  //Print static 2D Array
12  for (int i = 0; i < row; i++) {
13   for (int j = 0; j < column; j++) {
14    // Access element at row index i and column index j
15    cout << Student[i][j] << " ";
16   }
17   cout << endl;
18  }
19
20 }
```



Output



1.2s



```
100 134 234
34 189 221
109 139 56
```

**Line No. 9:** We initialize the values of an array `Student` that can store  $3*3 = 9$  elements

**Line No. 12:** The outer `for` loop iterates through the rows of a 2D array from `0` to `row-1`.

**Line No. 13:** The inner `for` loop iterates through the columns of a 2D array from `0` to `column-1`.

**Line No. 15:** In the loop body, we are printing the array `Student` element at row index `i` and column index `j`.

Quiz



(/learn)



Q

What is the output of the following code?



```
int main() {  
    int row = 2 , column = 2;  
    int Student[row][column] = {{100, 134}, {34, 189}};  
    Student [1][1] = 67;  
  
    for (int i = 0; i < row; i++) {  
        for (int j = 0; j < column; j++) {  
            cout << Student[i][j] << " ";  
        }  
        cout << endl;  
    }  
}
```

☐ A) 100 134

34 189

Your Answer



B) 100 134

34 67

Explanation

We have updated the value at index **[1][1]** and then print the updated values in an array.

☐ C) 100 134

☐ D) Error

Submit Answer

Reset Quiz ↻



That wraps up our discussion of two-dimensional arrays. The next few lessons contain some coding exercises to test your understanding and help you practice.

← Back

Next →

Creating a Two-Dimensional Array

Challenge 1: Calculate the Average M...



Mark as Completed



Report an Issue