

Example 3: Newly added row has the description “Sum” and its ID is a UUID


BestRunJuice_SampleModel in Million USD 		
	Account	Gross_Margin Gross Margin
Location		
> SA1 California		173.48
> SA2 Nevada		13.25
> SA3 Oregon		48.30
Sum		235.04

Figure 37 Newly Added Row Has Description "Sum", ID Is a UUID

```

Table_1.getDataSource().getResultSet();

// ResultSet[]. Additional row is generated in table.
[ {
  "@MeasureDimension": {
    "id": "[Account_BestRunJ_sold].[parentId].&[Gross_Margin]",
    "description": "Gross Margin",
    "formattedValue": " 235.04",
    "rawValue": " 235036949.37"
  },
  "Location_4nm2e04531": {
    "id": "[Location_4nm2e04531].[State_47acc246_4m5x6u3k6s].&[SA1]",
    "description": "California"
  }
}, {
  ...
}, {
  "@MeasureDimension": {
    "id": "[Account_BestRunJ_sold].[parentId].&[Gross_Margin]",
    "description": "Gross Margin",
    "formattedValue": "48.30",
    "rawValue": "48301721.3"
  },
  "Location_4nm2e04531": {
    "id": "30835424-2216-4348-9273-946191519134", // generated in frontend
    "description": "Sum"
  }
}

```