

### 5.38.3 Smart Discovery

Class `SmartDiscoveryMeasureSettings` was deprecated and its functionality replaced by class `SmartDiscoveryStructureSettings`, which provides the following script API:

```
create(dataSource: DataSource, target: string | MemberInfo | MeasureInfo,
entityDimensions: string[] | DimensionInfo[], targetContext?: string | MemberInfo |
MeasureInfo) : SmartDiscoveryStructureSettings
copyDimensionFilterFrom(sourceDataSource: DataSource, dimension?: string |
DimensionInfo): void
setPageFilter(dimension: string | DimensionInfo, member: string | MemberInfo |
string[] | MemberInfo[]): void
setIncludedDataColumns(structureMembers: string[] | MemberInfo[] | MeasureInfo[]):
void
setIncludedDimensionColumns(includedDimensions: string[] | DimensionInfo[]): void
setSettingsPanelVisible(settingsPanelVisible: boolean): void
setVersion(version: string | MemberInfo): void
```

In class `SmartDiscoveryDimensionSettings` the following methods were deprecated and replaced:

Deprecated

```
setIncludedMeasures(includedMeasures: string[] | MeasureInfo[]): void
```

Replaced by

```
setIncludedDataColumns(structureMembers: string[] | MemberInfo[] | MeasureInfo[]):
void
```

Deprecated

```
setIncludedDimensions(includedDimensions: string[] | DimensionInfo[]): void
```

Replaced by

```
setIncludedDimensionColumns(includedDimensions: string[] | DimensionInfo[]): void
```

### 5.38.4 Smart Grouping

In class `SmartGouping` the following method was deprecated and replaced:

Deprecated

```
setTooltipMeasureIncluded(included: boolean): void
```

Replaced by

```
setTooltipFeedsIncluded(included: boolean): void
```

## 5.39 Open in New Story API

For each data-bound widget at runtime, such as a Table or Chart, end users can create a new story from the widget and start exploration based on it afterwards.