

```

ExportCsv.setExportFormattedValues(exportFormattedValues: boolean): void
ExportCsv.isExportFormattedValues(): boolean
ExportCsv.setHierarchyLevelsInIndividualCells(separate: boolean): void
ExportCsv.isHierarchyLevelsInIndividualCells(): boolean
ExportCsv.setScope(scope: ExportScope): void
ExportCsv.getScope(): ExportScope

```

Example:

In the following example, table `Table_1` is completely exported to CSV file *Export.csv*:

```

ExportToCsv_1.setFileName("Export.csv");
ExportToCsv_1.setWidget(Table_1);
ExportToCsv_1.setExportFormattedValues(false);
ExportToCsv_1.setHierarchyLevelsInIndividualCells(true);
ExportToCsv_1.setScope(ExportScope.All);
ExportToCsv_1.exportReport();

```

5.38 API for Models with Accounts and Measures

To support models with accounts and measures, some new script APIs were introduced that deprecate previous script APIs.

5.38.1 Chart

In class `Chart` the following methods were deprecated and replaced:

Deprecated

```
addMeasure(measure: string | MeasureInfo, feed: Feed, position?: integer): void
```

Replaced by

```
addMember(feed: Feed, structureMember: string | MeasureInfo | MemberInfo,
position?: integer): void
```

Deprecated

```
getMeasures(feed: Feed): string[]
```

Replaced by

```
getMembers(feed: Feed): string[]
```

Deprecated

```
removeMeasure(measure: string | MeasureInfo, feed: Feed): void
```

Replaced by

```
removeMember(feed: Feed, member: string | MeasureInfo | MemberInfo): void
```

5.38.2 Data Explorer

In class `DataExplorer` the following method was deprecated and replaced:

Deprecated

```
setAdditionalMeasures(additionalMeasures: string[] | MeasureInfo[]): void
```

Replaced by

```
setAdditionalStructureDimensionMembers(structureDimension: string | DimensionInfo,
structureDimensionMembers: string[] | MemberInfo[] | MeasureInfo[]): void
```