LuatCheck

A local, source-grounded assistant over Vietnamese regulations

Lê Trí Quyền (2470740) | Võ Phạm Tuấn Dũng (2570015) | Nguyễn Hoàng Phong (2570477)

CO5151 Advanced Agentic AI | D2 interim report

Application Track, Group 8 | Instructor: TS. Lê Xuân Bách

28 October 2026

What it is

A local assistant that answers only from the loaded regulations, cites the sections it used, checks those citations in code, and refuses (or asks) when the sources do not answer. Two evaluated collections: **HCMUT academic regulations** (10 documents, 143 sections; for students & advisers) and **Vietnamese labour law** (10 documents, 458 sections; 2019 Labour Code plus 9 later laws, decrees and circulars; for employees & HR). Not legal advice.


What changed since the proposal

Proposal commitment	**State**	What changed and why (no D1 pitch feedback received)
Agent loop, citation check	**Done**	Runs end to end; budgets unchanged
Qwen3 controllers, 32B	**Dropped**	Ternary Bonsai 2B and 4B: the same weights fit a 16 GiB Mac and a GPU
BM25 + Qdrant dense retrieval	**Dropped**	BM25 + TF-IDF; vector index built, *not evaluated*
$\geq$10 tasks, 3 configurations	**Done**	Two fixed 50-question benchmarks (HCMUT regulations, Labour law); 3 runs per configuration
Reranker (optional)	**Done**	Vietnamese cross-encoder, evaluated as "verifier + reranker"
Verifier audit (30 pairs)	**Done**	60-item blind judge audit: 96.7% agreement ($\kappa = 0.93$, HCMUT), 90.0% ($\kappa = 0.80$, labour)
HR walkthrough; attack tests	**Not started**	Walkthrough scheduled for W45 (Quyền, Phong); attack tests planned for W47

Two local controller options (Bonsai 4B default, Bonsai 2B lightweight)

Both ternary GGUF models run locally via `llama.cpp` on a 16 GiB Mac laptop. **Bonsai 4B** reaches **60.7% (HCMUT)** and **56.7% (labour)** strict success on the full system (~30 s median latency), while **Bonsai 2B** provides a 2× faster lightweight option (~14 s median, 28.0–28.7% strict success).

Architecture that runs end to end



■ used in every configuration ■ optional, switched on or off in the evaluation dashed: implemented, not used yet

One LLM agent + deterministic rule-based citation verifier (no multi-agent critic): permissions and budgets stay inspectable.

The loop on one real question (trace)

Question (HCMUT regulations): *Sinh viên vi phạm Nội quy học đường sẽ được xử lý theo căn cứ nào, và mức xử lý phụ thuộc vào yếu tố nào?*

1. search

query: *vi phạm nội quy học đường xử lý mức xử lý phụ thuộc*

20 candidates reranked, top 5 kept; Article 6 of the student code of conduct ranked first

1,509 tokens in, 117 out

→

2. read the document

Article 6, *Nội quy học đường* (decision 1924/QĐ-ĐHBK)

the full section text enters the model's context

2,905 tokens in, 171 out

→

3. answer

cites Article 6 with one exact quote

Citation verifier: accepted, 0 repairs (two soft warnings on one sentence, no rejection)

3,398 tokens in, 310 out

Outcome

Answered with 1 section cited: handling follows the student-affairs regulation and national law, depending on the severity of the violation. 3 model calls, 2 tool calls, 7,812 tokens in, 598 out. LLM judge (not a human): correctness 2/2, completeness 2/2.

Full configuration (verifier + reranker), Bonsai 4B controller. Illustrative clean run (0 repairs); end-to-end latency is reported from the Mac measurements on Slide 9.

Live demo: LuatCheck on a 16 GiB Mac

System: Bonsai 4B controller (2B also runs), BM25 + TF-IDF + reranker, citation verifier with repair, regex guardrails, `llama.cpp`, all on device.


Four queries:

1. HCMUT: answer with a citation
2. Labour law: same flow, second collection
3. Out of scope: refusal
4. Prompt injection: blocked before any model call

Point at: timeline, retrieved sections, highlighted quote, verifier verdict, tokens.


Backup

A backup video of real runs (Bonsai 4B controller, recorded 25 October) exists; used only if needed, and we say so.



Frame of a real run (Bonsai 4B controller): cited section and step timeline, verifier passed

Evaluation design and how correctness is decided




- **Strict success** (lower bound): run completes, valid judgment, appropriate behaviour, correctness 2/2, completeness 2/2, and all claims supported (errors/unknowns = fail).
- **Judge reliability** (blind human audit, 30 items/benchmark):
  - HCMUT: **96.7%** agreement ($\kappa = 0.93$)
  - Labour law: **90.0%** agreement ($\kappa = 0.80$)
- **Auxiliary metrics:** Recall@5 and citation F1 check section IDs only; the citation verifier checks word/quote overlap.

Honest limits

- Questions are AI-drafted and AI-verified; reviewed internally, no external legal review
- Retrieval is near-saturated; 15/45 HCMUT and 12/45 labour questions are guessable closed-book
- At $N = 50$ questions, differences under ~10 pp are within noise
- Full scores come from the audited LLM judge

Controller scaling: Bonsai 2B vs Bonsai 4B on the full system



Whiskers: 95% paired bootstrap CI. 50 questions × 3 runs per bar.

4B − 2B gain, pp (95% bootstrap CI)

Configuration	HCMUT	Labour
No verifier	+38.7	+30.7
31.3% → 70.0 / 62.0%	[+27.3, +50.0]	[+20.7, +40.7]
Verifier	+40.0	+24.7
24.0/28.0% → 64.0/52.7%	[+28.7, +51.3]	[+12.0, +37.3]
Verifier + reranker	**+32.0**	**+28.7**
28.7/28.0% → 60.7/56.7%	[+21.3, +42.0]	[+18.0, +39.3]

Key finding

Scaling the local controller from 2B to 4B adds **+25 to +40 pp** across all configurations; all six paired bootstrap intervals exclude zero.

Ablation study (Bonsai 4B): why the rule-based citation verifier matters

	HCMUT regulations				Labour law			
Configuration	judge %	**audited %**	**leak %**	cit. F1	judge %	**audited %**	**leak %**	cit. F1
No verifier	70.0	55.3	**25.6**	0.820	62.0	51.3	**28.0**	0.841
Verifier	64.0	**64.0**	**0.0**	0.704	52.7	52.7	**0.0**	0.728
Verifier + reranker (full)	60.7	**60.7**	**0.0**	0.714	56.7	**56.7**	**0.0**	0.691
Closed-book (no documents)	2.0	–	–	–	24.0	–	–	–
Oracle (correct section given)	82.2	–	–	–	75.6	–	–	–

judge % = LLM-judge strict success alone; **audited %** = passes LLM judge *and* deterministic L1 citation verification; **leak %** = share of emitted answers with fabricated/non-verbatim quotes, unretrieved IDs or wrong-clause numbers.

- **Without the L1 verifier (*No verifier*): 25.6% (31/121)** of HCMUT answers and **28.0% (37/132)** of labour answers (39.8% and 45.9% on 2B) leak unverifiable quotes or wrong-clause numbers that slip past the LLM judge.
- **With the L1 verifier (rule-based Python heuristic, < 2 ms, no LLM):** Eliminates unverified citation leakage to **0.0%**, rescues **17–20 flawed first drafts** via bounded 2-turn repair, and raises **citation-audited strict success** from **55.3% → 60.7–64.0% (+5.4 to +8.7 pp)** on HCMUT and **51.3% → 56.7% (+5.4 pp)** on labour law.

Cost, latency and runtime environment

Controller tokens per trial (local inference, USD 0 API cost)

	Configuration	in	out	calls
HCMUT	no verifier	10,233	666	3.13
	full system	12,070	763	3.37
Labour	no verifier	9,070	686	3.11
	full system	11,477	865	3.69

Offline evaluation judge cost:

- **USD 2.17 total** across both benchmarks (USD 1.06 HCMUT + 1.10 labour; ≈USD 0.002 per valid judgment).
- Reported by the API gateway (lower bound; timed-out or invalid attempts were automatically retried).

Mac end-to-end latency (Apple M4, 16 GiB)

Single-question sequential runs, median / p95:

Bonsai 4B (≈43 tok/s):
HCMUT: **33 s** / 86 s | Labour: **30 s** / 72 s

Bonsai 2B (≈92 tok/s):
HCMUT: **13 s** / 30 s | Labour: **15 s** / 28 s

Measurement environment:

- Accuracy tables come from batch runs on an H100 GPU; interactive latency is measured one query at a time on the Apple M4 Mac.
- All inference (controller + reranker) runs 100% locally with zero per-query API cost.

Threat model

Assets: faithful answers & citations; user data; corpus, config & weights; read-only tool boundary; availability.
Attacker: submits arbitrary questions or pasted text; cannot alter code, corpus files, weights, logs or host approvals.

Entry point	Mitigation (enforced in code)	Residual risk
Question, pasted text	Pre-model regex guardrails, input sanitising, untrusted-content tags; no write tool exposed	Paraphrase bypass; Vietnamese/English patterns only; not red-teamed yet
Retrieved sections	Wrapped as tool output; citation verifier checks section IDs, provenance and verbatim quotes	Tagged, not filtered: an adversarial instruction inside a source document reaches the model
Corpus, weights, config	Offline ingestion with URL, SHA-256 and page provenance; pinned weight hashes; localhost servers	No cryptographic signatures; third-party weights and `llama.cpp` fork unaudited
Memory, outbox	Long-term memory disabled in all runs; outbox requires host approval bound to payload SHA-256	Single-user local machine assumption
Judge gateway (offline)	Benchmark data only; API key in env; blind evaluation packets; strict JSON & quote checks	Candidate answer text could steer the LLM judge (untested)

No attack results yet. Mitigations define architectural boundaries; red-team attack tests are scheduled for W47.

Plan to the first final presentation, risks, status

Week	Deliverable
W45, 2–8 Nov	HR walkthrough; new benchmark of unseen questions with a harder slice (unnamed documents, paraphrases)
W46, 9–15 Nov	Failure analysis; verifier false accepts and rejects
W47, 16–22 Nov	Attack tests per entry point, permission and fault checks
W48, 23–29 Nov	Reproduction from frozen artifacts; demo hardening; final report (semantic check & vector index only if core is complete)
W49, 30 Nov–2 Dec	Tagged release; first final presentation on 2 Dec

Owners: Quyền, Phong (W45); Dũng, Quyền (W46); Phong, Dũng (W47); all (W48–W49)

Riskiest assumptions

- A 2–4B local controller answers accurately within step/time budgets
- Gains hold on unseen questions
- Harder benchmarks separate the configurations

Fallback scope: keep the loop, unseen benchmark, ablations and reproduction pipeline; cut vector index, semantic check and extra domains.

Self-assessment

On track, with one main risk: generalising to harder multi-clause questions on the unseen W45 benchmark.

Team, roles and what we ask you to challenge

Three takeaways

1. **Controller scale + loop design:** 60.7% (HCMUT) and 56.7% (labour) strict success with Bonsai 4B (vs 28.0–28.7% with 2B).
2. **The bottleneck was controller behaviour, not retrieval** (Recall@5 ≈ 0.99).
3. **Rule-based citation verifier eliminates unverified citation leakage** (26–28% → **0.0%**) and raises citation-audited strict success by **+5.4 to +8.7 pp**.

Please challenge: verifier over-refusal trade-off, benchmark difficulty, and multi-hop synthesis limits.

Repository:
`https://github.com/tuandung222/LuatCheck-D2`
Commit: `138128e804bf`

Member	%	Presents	Answers for
Lê Trí Quyền (Leader)	33%	Slides 1–2, 9, 11–12	Corpus ingestion, BM25 + TF-IDF index, RRF, reranker, local `llama.cpp` serving
Võ Phạm Tuấn Dũng (Tech Lead)	33%	Slides 3–4, 6–8	Idea & architecture/model selection, codebase refactoring, agent loop, verifier, benchmarks & evaluation
Nguyễn Hoàng Phong	33%	Slides 5 (Demo), 10	Tool permissions, guardrails, Web UI and outbox, audit log, threat model

Live demo: Nguyễn Hoàng Phong narrates; Võ Phạm Tuấn Dũng drives the keyboard.

Backup A: 60-item blind human audit of the LLM judge

Protocol: Stratified blind sample of 60 outputs from the Bonsai 4B runs (30 HCMUT + 30 Labour law; 8 strata per benchmark). Human auditor rated behaviour, correctness, completeness and claim faithfulness against the full source regulations without seeing the LLM judge (`deepseek/deepseek-v4-flash`) scores.

Benchmark	Sample	Strict-success agreement	κ / weighted κ_w	Behaviour match
HCMUT regulations	$n = 30$	**96.7%** (29/30)	0.933 / 0.974 (98.8%)	**100.0%** (30/30)
Vietnamese labour law	$n = 30$	**90.0%** (27/30)	0.800 / 0.948 (97.5%)	**93.3%** (28/30)

All 4 strict-success disagreements (1 HCMUT, 3 Labour law) are documented item-by-item:

- **HCMUT (`HV-004`):** Judge scored completeness 2/2 when the answer omitted 2 of 6 required bullet clauses in Article 11.4.
- **Labour law (`LVN-016`, `LVN-005`, `LVN-048`):** Two partial answers where the judge missed a secondary statutory condition (5-year renewal cap; job/workplace guarantee), and one verifier-exhaustion refusal where the judge treated a valid statutory quote as non-matching.

Backup B: strict success across controllers and configurations (%, 95% CI)


Benchmark	Configuration	Bonsai 2B	Bonsai 4B	4B − 2B (pp)
HCMUT regulations	no verifier	31.3 [22–41]	70.0 [61–79]	+38.7 [+27.3, +50.0]
	verifier	24.0 [15–33]	64.0 [53–75]	+40.0 [+28.7, +51.3]
	verifier + reranker	28.7 [20–37]	60.7 [50–71]	+32.0 [+21.3, +42.0]
Labour law	no verifier	31.3 [22–41]	62.0 [52–72]	+30.7 [+20.7, +40.7]
	verifier	28.0 [19–38]	52.7 [43–63]	+24.7 [+12.0, +37.3]
	verifier + reranker	28.0 [19–37]	56.7 [47–67]	+28.7 [+18.0, +39.3]

50 questions × 3 runs per cell, same questions for every configuration. Intervals: paired bootstrap over questions (5,000 draws), no correction for multiple comparisons.


Backup C: what the numbers do not show

- **Judge:** LLM estimates; on a 60-item blind human audit, strict-success agreement is 96.7% ($\kappa = 0.93$, HCMUT) and 90.0% ($\kappa = 0.80$, labour). Judge attempts invalid or timed out: 36% (HCMUT), 45% (labour); invalid or unjudged trials count as failures.
- **Benchmarks:** 50 questions each, AI-drafted and AI-verified; no expert review of documents or questions; about half the questions name their source document.
- **Guardrails:** regex patterns in Vietnamese and English; no red-team numbers yet.
- **Retrieval:** BM25 + TF-IDF with rank fusion; dense embedding retrieval is implemented but not evaluated.
- **Scope:** two document collections; labour-law results are not evidence for other domains. Not tried by real users.
- **Latency:** on the Mac the full system takes a median of about 30 s per question with the 4B controller and about 14 s with the 2B controller; GPU wall times are not reported.


Backup D: failure states in the demo UI (real recordings)



Guardrail block: 3 ms in the timeline, 0 model calls



Verifier rejected the first draft (quote not verbatim); after one repair the answer passes



Reranker server down: execution error, never an answer

Left and centre: 4B controller, showing pre-model regex guardrail refusal and bounded 1-step citation repair. Right: when a required local service (controller or reranker) is unreachable, the UI surfaces an explicit execution error state rather than a fabricated answer or silent fallback.