LuatCheck

A Local, Source-Grounded QA Agent for Vietnamese Regulations

Lê Trí Quyền (2470740) | Võ Phạm Tuấn Dũng (2570015) | Nguyễn Hoàng Phong (2570477)

CO5151 Advanced Agentic AI | D2 Interim Report

Application Track, Group 8 | Instructor: TS. Lê Xuân Bách

25 October 2026

System Overview

LuatCheck answers regulatory questions strictly from local document collections, verifies every cited section and quote in Python before returning an answer, and refuses or asks for clarification when the sources do not support a conclusion. Evaluated on **HCMUT academic regulations** (10 documents, 143 sections) and **Vietnamese labour law** (10 documents, 458 sections: 2019 Labour Code plus 9 implementing laws, decrees, and circulars). Research prototype; not legal advice.


Changes Since the D1 Proposal

Proposal commitment	State	Status and rationale (no D1 pitch feedback received)
Agent loop, citation check	**Done**	Runs end to end; step/tool/repair budgets unchanged
Qwen3 controllers, 32B	**Dropped**	Replaced by ternary Bonsai 2B and 4B (GGUF); runs on a 16 GiB Mac and GPU
BM25 + Qdrant dense retrieval	**Changed**	BM25 + TF-IDF + reranker; vector index built, scheduled for W46 ablation
$\geq$10 tasks, 3 configurations	**Done**	Two fixed 50-question benchmarks (HCMUT regulations, Labour law); 3 seeds
Reranker (optional)	**Done**	Vietnamese cross-encoder, evaluated in "verifier + reranker"
Verifier audit (30 pairs)	**Done**	60-item blind judge audit: 96.7% agreement ($\kappa = 0.93$, HCMUT), 90.0% ($\kappa = 0.80$, labour)
HR walkthrough; attack tests	**Not started**	Walkthrough scheduled for W45 (Quyền, Phong); attack tests planned for W47

Two local controller options (Bonsai 4B default, Bonsai 2B lightweight)

Both ternary GGUF models run locally via `llama.cpp` on a 16 GiB Mac laptop. **Bonsai 4B** reaches **60.7% (HCMUT)** and **56.7% (labour)** strict success on the full system (~30 s median latency), while **Bonsai 2B** provides a 2× faster lightweight option (~14 s median, 28.0–28.7% strict success).

System Architecture: Offline Indexing and Bounded Agent Loop



■ Core pipeline ■ Ablated modules (L1 verifier, reranker) Dashed: implemented, switched off in current D2 ablation

Single-agent ReAct loop with a deterministic Python citation verifier; dense vector index, L2 NLI check, and answer memory are switched off in D2 baseline runs.

Execution Trace on a Sample HCMUT Query

Question (HCMUT regulations): *Sinh viên vi phạm Nội quy học đường sẽ được xử lý theo căn cứ nào, và mức xử lý phụ thuộc vào yếu tố nào?*

1. search

query: *vi phạm nội quy học đường xử lý mức xử lý phụ thuộc*

20 candidates reranked, top 5 kept; Article 6 of the student code of conduct ranked first

1,509 tokens in, 117 out

→

2. read_document

Article 6, *Nội quy học đường* (decision 1924/QĐ-ĐHBK) loads the full text of Article 6 into the agent context

2,905 tokens in, 171 out

→

3. answer

cites Article 6 with one exact quote

Citation verifier: accepted, 0 repairs (two soft warnings on one sentence, no rejection)

3,398 tokens in, 310 out

Outcome

Verified answer citing Article 6: disciplinary action follows the student-affairs regulation and national law based on violation severity. Total cost: 3 model calls, 2 tool calls, 7,812 input tokens, 598 output tokens. Offline LLM judge score: correctness 2/2, completeness 2/2.

Full configuration (verifier + reranker), Bonsai 4B controller. End-to-end Mac latency measurements are reported on Slide 9.


Live Demo: LuatCheck on a 16 GiB Mac

System: Bonsai 4B controller (2B option available), BM25 + TF-IDF + reranker, rule-based citation verifier with repair, regex guardrails, `llama.cpp`, running locally.

Four queries:

1. HCMUT: verified answer with citation
2. Labour law: same pipeline, second corpus
3. Out of scope: explicit refusal
4. Prompt injection: blocked pre-model

UI elements shown: step timeline, retrieved sections, highlighted verbatim quote, verifier verdict, and token counts.




Web UI (Bonsai 4B): verified answer with highlighted source quote and step timeline.

Fallback recording

An unedited screen recording of the same 4B configuration (recorded 25 October) is available if a live local service fails.

Evaluation Protocol and Metrics




- **Strict success** (lower bound): run completes, valid judgment, appropriate behaviour, correctness 2/2, completeness 2/2, and all claims supported (errors/unknowns = fail).
- **Judge reliability** (blind human audit, 30 items/benchmark):
  - HCMUT: **96.7%** agreement ($\kappa = 0.93$).
  - Labour law: **90.0%** agreement ($\kappa = 0.80$).
- **Auxiliary metrics:** Recall@5 and citation F1 check section IDs only; the L1 citation verifier checks provenance, verbatim quotes, and local numbers.

D2 evaluation scope and limitations

- **D2 objective:** verify that the end-to-end pipeline and evaluation harness **run reliably and produce reproducible baseline metrics**; broader experiments follow in **D3**.
- Questions are LLM-drafted, cross-checked, and reviewed by the team (no external legal review).
- Lexical retrieval is near ceiling (Recall@5 ≈ 0.99); 15/45 HCMUT and 12/45 labour items are answerable closed-book.
- At $N = 50$ questions, differences under ~10 pp fall within bootstrap confidence intervals.

Controller Scaling: Bonsai 2B vs. Bonsai 4B on the Full System



Whiskers: 95% bootstrap CI (50 questions × 3 seeds).

4B − 2B gain, pp (95% paired bootstrap CI)

Configuration	HCMUT	Labour
No verifier	+38.7	+30.7
31.3/31.3% → 70.0/62.0%	[+27.3, +50.0]	[+20.7, +40.7]
Verifier	+40.0	+24.7
24.0/28.0% → 64.0/52.7%	[+28.7, +51.3]	[+12.0, +37.3]
Verifier + reranker	**+32.0**	**+28.7**
28.7/28.0% → 60.7/56.7%	[+21.3, +42.0]	[+18.0, +39.3]

Key finding

Scaling the local controller from 2B to 4B adds **+25 to +40 pp** across all configurations; all six paired bootstrap intervals exclude zero.

Component Ablation (Bonsai 4B): Impact of the Citation Verifier

	HCMUT regulations				Labour law			
Configuration	judge %	**audited %**	**leak %**	cit. F1	judge %	**audited %**	**leak %**	cit. F1
No verifier	70.0	55.3	**25.6**	0.820	62.0	51.3	**28.0**	0.841
Verifier	64.0	**64.0**	**0.0**	0.704	52.7	52.7	**0.0**	0.728
Verifier + reranker (full)	60.7	**60.7**	**0.0**	0.714	56.7	**56.7**	**0.0**	0.691
Closed-book (no documents)	2.0	–	–	–	24.0	–	–	–
Oracle (gold section given, 45 ans.)	82.2	–	–	–	75.6	–	–	–

judge % = LLM-judge strict success alone; **audited %** = passes LLM judge *and* deterministic L1 citation verification; **leak %** = share of emitted answers with non-verbatim quotes, unretrieved IDs, or wrong-clause numbers.

- **Without the L1 verifier (*No verifier*): 25.6% (31/121)** of HCMUT answers and **28.0% (37/132)** of labour answers (39.8% and 45.9% on 2B) contain non-verbatim quotes, unretrieved section IDs, or wrong-clause numbers undetected by the prose-only LLM judge.
- **With the L1 verifier (deterministic Python check, < 2 ms, no LLM):** Reduces unverified citation leakage to **0.0%**, corrects **17–20 initial drafts** via bounded 2-turn repair, and increases **citation-audited strict success** from **55.3%** → **60.7–64.0% (+5.4 to +8.7 pp)** on HCMUT and **51.3%** → **56.7% (+5.4 pp)** on labour law.

Cost, Latency, and Runtime Environment

Controller tokens per trial (local inference, USD 0 API cost)

	Configuration	in	out	calls
HCMUT	no verifier	10,233	666	3.13
	full system	12,070	763	3.37
Labour	no verifier	9,070	686	3.11
	full system	11,477	865	3.69

Offline evaluation judge cost:

- **USD 2.17 total** across both benchmarks (USD 1.06 HCMUT and USD 1.10 labour; ≈USD 0.002 per valid judgment).
- Reported by the API gateway (lower bound; timed-out or invalid attempts were automatically retried).

Mac end-to-end latency (Apple M4, 16 GiB)

Single-question sequential runs, median / p95:

Bonsai 4B (≈43 tok/s):
HCMUT: **33 s** / 86 s | Labour: **30 s** / 72 s

Bonsai 2B (≈92 tok/s):
HCMUT: **13 s** / 30 s | Labour: **15 s** / 28 s

Local RAM footprint & measurement environment:

- **Resident RAM (RSS):** ≈**4.8 GB** total for the 4B stack (3.4 GB 4B controller + 1.2 GB reranker + 0.2 GB web app & lexical index), or ≈**2.8 GB** for the 2B stack (1.4 GB 2B controller).
- Accuracy tables come from batch runs on an H100 GPU; interactive latency is measured one query at a time on the 16 GiB Apple M4 Mac.
- All inference (controller + reranker) runs 100% locally with zero per-query API cost.

Threat Model

Assets: faithful answers & citations; user data; corpus, config & weights; read-only tool boundary; availability.
Attacker: submits arbitrary questions or pasted text; cannot alter code, corpus files, weights, logs, or host approvals.

Entry point	Mitigation (enforced in code)	Residual risk
Question, pasted text	Pre-model regex guardrails, input sanitising, untrusted-content tags; no write tool exposed	Paraphrase bypass; Vietnamese/English patterns only; not red-teamed yet
Retrieved sections	Wrapped as tool output; citation verifier checks section IDs, provenance and verbatim quotes	Tagged, not filtered: an adversarial instruction inside a source document reaches the model
Corpus, weights, config	Offline ingestion with URL, SHA-256 and page provenance; pinned weight hashes; localhost servers	No cryptographic signatures; third-party weights and `llama.cpp` fork unaudited
Memory, outbox	Long-term memory disabled in all runs; outbox requires host approval bound to payload SHA-256	Single-user local machine assumption
Judge gateway (offline)	Benchmark data only; API key in env; blind evaluation packets; strict JSON & quote checks	Candidate answer text could steer the LLM judge (untested)

Evaluation status: Mitigations above are code-enforced boundaries; red-team attack tests are scheduled for W47.

D3 Roadmap, Key Risks, and Project Status

Week	Deliverable
W45, 2–8 Nov	HR walkthrough; design and freeze unseen harder benchmark (multi-hop, unnamed documents, paraphrases)
W46, 9–15 Nov	Run system & ablations on unseen benchmark; add dense-retrieval ablation; failure analysis
W47, 16–22 Nov	Entry-point attack tests; permission and fault checks
W48, 23–29 Nov	Reproduction from recorded runs; demo hardening; final report
W49, 30 Nov–2 Dec	Tagged release; Round 1 final presentation on 2 Dec

Owners: Quyền, Phong (W45); Dũng, Quyền (W46); Phong, Dũng (W47); all (W48–W49)

Riskiest assumptions

- A 2–4B local controller answers accurately within step/time budgets
- Gains hold on unseen questions
- Harder benchmarks separate the configurations

Fallback scope: keep the loop, unseen benchmark, ablations and reproduction pipeline; drop vector index, semantic check and extra domains.

D2 status & D3 roadmap

D2 proves the system runs and is measurable. Extensive improvements and experiments (unseen harder multi-hop benchmark, verifier refinement, attack tests) are scheduled for **D3**.

Key Takeaways and Team Contributions

Three takeaways

1. **Controller scale + loop design:** 60.7% (HCMUT) and 56.7% (labour) strict success with Bonsai 4B (vs. 28.0–28.7% with 2B).
2. **The bottleneck is controller synthesis, not lexical retrieval** (Recall@5 ≈ 0.99).
3. **Rule-based citation verifier reduces unverified citation leakage** (26–28% → **0.0%**) and raises citation-audited strict success by **+5.4 to +8.7 pp**.

Open questions for discussion: verifier over-refusal trade-off, benchmark difficulty, and multi-clause synthesis limits.

Repository:
`https://github.com/tuandung222/LuatCheck-D2`
Commit: `138128e804bf`

Member	%	Presents	Answers for
Lê Trí Quyền (Leader)	33%	Slides 1–2, 9, 11–12	Corpus ingestion, BM25 + TF-IDF index, RRF, reranker, local `llama.cpp` serving
Nguyễn Hoàng Phong	33%	Slides 5 (Demo), 10	Tool permissions, guardrails, Web UI and outbox, audit log, threat model
Võ Phạm Tuấn Dũng	33%	Slides 3–4, 6–8	System architecture & model selection, codebase refactoring, agent loop, verifier, benchmarks & evaluation

Live demo: Nguyễn Hoàng Phong narrates; Võ Phạm Tuấn Dũng drives the keyboard.

Backup A: 60-Item Blind Human Audit of the LLM Judge

Protocol: Stratified blind sample of 60 outputs from the Bonsai 4B runs (30 HCMUT + 30 Labour law; 8 strata per benchmark). Human auditor rated behaviour, correctness, completeness and claim faithfulness against the full source regulations without seeing the LLM judge (`deepseek/deepseek-v4-flash`) scores.

Benchmark	Sample	Strict-success agreement	κ / weighted κ_w	Behaviour match
HCMUT regulations	$n = 30$	**96.7%** (29/30)	0.933 / 0.974 (98.8%)	**100.0%** (30/30)
Vietnamese labour law	$n = 30$	**90.0%** (27/30)	0.800 / 0.948 (97.5%)	**93.3%** (28/30)

All 4 strict-success disagreements (1 HCMUT, 3 Labour law) are documented item-by-item:

- **HCMUT (`HV-004`):** Judge scored completeness 2/2 when the answer omitted 2 of 6 required bullet clauses in Article 11.4.
- **Labour law (`LVN-016`, `LVN-005`, `LVN-048`):** Two partial answers where the judge missed a secondary statutory condition (5-year renewal cap; job/workplace guarantee), and one verifier-exhaustion refusal where the judge treated a valid statutory quote as non-matching.

Backup B: Strict Success by Controller and Configuration (%, 95% CI)


Benchmark	Configuration	Bonsai 2B	Bonsai 4B	4B − 2B (pp)
HCMUT regulations	no verifier	31.3 [22–41]	70.0 [61–79]	+38.7 [+27.3, +50.0]
	verifier	24.0 [15–33]	64.0 [53–75]	+40.0 [+28.7, +51.3]
	verifier + reranker	28.7 [20–37]	60.7 [50–71]	+32.0 [+21.3, +42.0]
Labour law	no verifier	31.3 [22–41]	62.0 [52–72]	+30.7 [+20.7, +40.7]
	verifier	28.0 [19–38]	52.7 [43–63]	+24.7 [+12.0, +37.3]
	verifier + reranker	28.0 [19–37]	56.7 [47–67]	+28.7 [+18.0, +39.3]

50 questions × 3 runs per cell, same questions for every configuration. Intervals: paired bootstrap over questions (5,000 draws), no correction for multiple comparisons.


Backup C: Methodological Scope and Limitations

- **Judge:** LLM estimates; on a 60-item blind human audit, strict-success agreement is 96.7% ($\kappa = 0.93$, HCMUT) and 90.0% ($\kappa = 0.80$, labour). Judge attempts invalid or timed out: 36% (HCMUT), 45% (labour); invalid or unjudged trials count as failures.
- **Benchmarks:** 50 questions each, LLM-drafted and cross-checked, then reviewed by the team; no external legal review; about half the questions name their source document.
- **Guardrails:** regex patterns in Vietnamese and English; systematic red-team evaluation is scheduled for W47.
- **Retrieval:** BM25 + TF-IDF with rank fusion; dense embedding retrieval is implemented and scheduled for ablation in W46.
- **Domain scope:** evaluated on two regulatory collections; generalization to other domains and end-user testing (HR walkthrough in W45) remain future work.
- **Latency:** on the Mac the full system takes a median of about 30 s per question with the 4B controller and about 14 s with the 2B controller; GPU wall times are from batch runs on a shared server.


Backup D: Guardrail, Verifier Repair, and Error States in the Web UI



Guardrail block: 3 ms in the timeline, 0 model calls



Verifier rejected first draft (quote not verbatim); repaired and accepted



Reranker server unreachable: explicit execution error state

Left and centre: 4B controller, showing pre-model regex guardrail refusal and bounded 1-step citation repair. Right: when a required local service (controller or reranker) is unreachable, the UI surfaces an explicit execution error state rather than a fabricated answer or silent fallback.