LuatCheck

A local, source-grounded assistant over Vietnamese regulations

Lê Trí Quyền (2470740) | Võ Phạm Tuấn Dũng (2570015) | Nguyễn Hoàng Phong (2570477)

CO5151 Advanced Agentic AI | D2 interim report

Application Track, Group 8 | Instructor: TS. Lê Xuân Bách

28 October 2026

What it is

A local assistant that answers only from the loaded regulations, cites the sections it used, checks those citations in code, and refuses (or asks) when the sources do not answer. Two evaluated collections: HCMUT academic regulations and Vietnamese labour law (2019 Labour Code plus nine later laws, decrees and circulars). Not legal advice.


What changed since the proposal

Proposal commitment	**State**	What changed and why
Agent loop, citation check	**Done**	Runs end to end; budgets unchanged
Qwen3 controllers, 32B	**Dropped**	Ternary Bonsai 2B and 4B: the same weights fit a 16 GiB Mac and a GPU
BM25 + Qdrant dense retrieval	**Dropped**	BM25 + TF-IDF; vector index built, *not evaluated*
$\geq$10 tasks, 3 configurations	**Done**	Two fixed 50-question benchmarks (HCMUT regulations, Labour law); 3 runs per configuration
Reranker (optional)	**Done**	Vietnamese cross-encoder, evaluated as "verifier + reranker"; runtime parity measured
Verifier audit (30 pairs)	**Changed**	Human audit of the LLM judge, about 30 answers per benchmark: **[PENDING: result]**
HR walkthrough; attack tests	**Not started**	Walkthrough **[PENDING: new date]**; attack tests planned for week W47

How the system evolved, in plain words

The **initial system** (2B controller) reached 12–19% strict success (full system: 14.0% HCMUT, 18.7% labour). We built the **current system** (4B controller) from its failures. **The revision was designed after analysing the initial system's failures on these same questions, so gains may be optimistic; we confirm them on new questions for the final report.**

Architecture that runs end to end



■ used in every configuration ■ optional, switched on or off in the evaluation dashed: implemented, not used yet

One agent, not several: permissions and budgets stay inspectable. A backend failure is an **error**, never an answer or a refusal.

The loop on one real question (trace)

Question (HCMUT regulations): *Sinh viên vi phạm Nội quy học đường sẽ được xử lý theo căn cứ nào, và mức xử lý phụ thuộc vào yếu tố nào?*

1. search

query: *vi phạm nội quy học đường xử lý mức xử lý phụ thuộc*

20 candidates reranked, top 5 kept; Article 6 of the student code of conduct ranked first

1,509 tokens in, 117 out

→

2. read the document

Article 6, *Nội quy học đường* (decision 1924/QĐ-ĐHBK)

the full section text enters the model's context

2,905 tokens in, 171 out

→

3. answer

cites Article 6 with one exact quote

Citation verifier: accepted, 0 repairs (two soft warnings on one sentence, no rejection)

3,398 tokens in, 310 out

Outcome

Answered with 1 section cited: handling follows the student-affairs regulation and national law, depending on the severity of the violation. 3 model calls, 2 tool calls, 7,812 tokens in, 598 out. LLM judge (not a human): correctness 2/2, completeness 2/2.

Current system, full system (verifier + reranker), Bonsai 4B. Picked because the judge rated it correct with no repair: not a typical question. No times shown: latency comes from the Mac measurements.


Live demo: the current system on the Mac

System: Bonsai 4B controller (2B also runs), BM25 + TF-IDF + reranker, citation verifier with repair, regex guardrails, `llama.cpp`, all on device.

Four queries:

1. HCMUT: answer with a citation
2. Labour law: same flow, second collection
3. Out of scope: refusal
4. Prompt injection: blocked before any model call

Point at: timeline, retrieved sections, highlighted quote, verifier verdict, tokens.




Frame of a real run (current system, 4B controller, recorded 25 October): cited section and step timeline, verifier passed

Backup

A backup video of real runs (current system, 4B, recorded 25 October) exists; used only if needed, and we say so.

Evaluation design and how correctness is decided



Strict success (lower bound over all trials): the run completes, the judgment is valid, the behaviour is appropriate, correctness and completeness are 2/2, and every claim is supported. Errors and unknown judgments count as failures. 95% intervals: paired bootstrap over questions.


Judge reliability (human-labelled sample, about 30 answers per benchmark): agreement and κ
[PENDING: human audit]

Recall@5 and citation F1 compare section ids only: they are proxies, not answer correctness. The citation verifier is a word-overlap check.

Honest limits

- Questions are AI-drafted and AI-verified; no human review yet
- Retrieval is near-saturated; 15/45 HCMUT and 12/45 labour answerable questions are estimated to be guessable without the documents
- With 50 questions, differences under about 10 pp are not detectable
- Judge numbers are estimates, not human labels

First numbers: strict success of the full system (verifier + reranker)



Whiskers: 95% interval (bounds rounded to 1 pp). 50 questions × 3 runs per bar.

Paired differences, pp (95% interval)

	HCMUT	Labour
system change	+14.7	+9.3
current 2B − initial	[+6.0, +23.3]	[+0.7, +18.0]
model change	+32.0	+28.7
4B − 2B	[+21.3, +42.0]	[+18.0, +39.3]

Read with care

Gains may be optimistic (see slide 2). Judge lower bounds, not human labels. Small benchmarks.

Current system (Bonsai 4B): what the verifier and the reranker do

	HCMUT regulations			Labour law		
Configuration	strict %	faithful. %	cit. F1	strict %	faithful. %	cit. F1
No verifier	70.0	89.8	0.820	62.0	87.3	0.841
Verifier	64.0	90.3	0.704	52.7	86.3	0.728
Verifier + reranker (full)	60.7	89.3	0.714	56.7	85.6	0.691
Closed-book (no documents)	2.0	–	–	24.0	–	–
Oracle (correct section given)	82.2	–	–	75.6	–	–

strict = strict success (judge lower bound); faithful. = share of claims the judge found supported; cit. F1 = section-id proxy. Execution errors: 0.0–2.7% of trials. The last two rows use one run and are not configurations of the system.

- **Verifier vs no verifier, strict success:** -6.0 pp $[-16.0, +4.0]$ HCMUT, -9.3 pp $[-18.7, 0.0]$ labour: **no gain measured**. Faithfulness unchanged; citation F1 lower by 11.6 pp and 11.2 pp (intervals exclude 0).
- **Why:** after repeated rejections the model refuses. Answerable questions refused after the repair budget ran out: 10 (verifier) and 13 (full system) of 150 HCMUT trials; 14 and 18 on labour.
- **Reranker:** Recall@5 is already 0.98–0.99 without it, so no effect is detectable here. The verifier is a word-overlap check and can pass a wrong answer.

Cost, latency and reranker runtime parity

Controller tokens per trial (local, no API cost)

	Configuration	in	out	calls
HCMUT	no verifier	10,233	666	3.13
	full system	12,070	763	3.37
Labour	no verifier	9,070	686	3.11
	full system	11,477	865	3.69

Judge cost (reported by the API gateway, offline): USD 1.06 (HCMUT) + 1.10 (labour) = **USD 2.17**, about USD 0.002 per valid judgment. A lower bound: some attempts report no cost; 36% and 45% of judge attempts were invalid or timed out and were retried.

Mac latency, current system

Apple M4, one question at a time, median / 95th percentile per question:
4B controller: 33 s / 86 s (HCMUT), 30 s / 72 s (labour), ≈43 tokens/s
2B controller: 13 s / 30 s, 15 s / 28 s, ≈92 tokens/s

Reranker runtime parity against a torch fp32 CPU reference: 100 questions, 20 candidates each; rank agreement, not answer correctness

Runtime	Spearman	top-1	max Δ
Mac: GGUF f16	0.9994	99/100	0.094
GPU: H100 fp16	0.9943	100/100	0.034

Mean per-question Spearman (minimum 0.9955 and 0.9601). Accuracy numbers come from GPU runs, latency from the Mac; they are not pooled.

GPU wall times are not reported (shared server); GPU-active hours are not measured.

Threat model

Protect: faithful answers and citations; user data; document collections, settings and model weights; the tool boundary (no unreviewed write or egress); availability.
Attacker: sends any question or pasted document; cannot change code, documents, weights, the audit log or approval state.

Entry point	Mitigation (in code)	Residual risk
Question, pasted document	Regex guardrails before the model, input sanitising, untrusted-content tags; the model has no write action	Paraphrase bypass; Vietnamese and English patterns only; not attack-tested
Retrieved text	Tagged as tool output; citation verifier checks ids, provenance, quotes	Tagged, not filtered: an injected instruction inside a source would reach the model
Ingested documents, weights, settings	Offline ingestion; source URL, SHA-256 and pages per record; pinned hashes; local-only servers	No signatures; third-party weights and `llama.cpp` fork unaudited
Memory, outbox	Memory off in all runs; outbox needs host approval bound to the payload hash; no sender exists	Single-user assumption
Judge gateway (offline)	Benchmark data only; key from environment; blind packets; JSON and quote validation	Candidate text could steer the judge (untested)

No attack results yet. Mitigations are boundaries, not measured effectiveness; attack tests are planned for week W47.

Plan to the first final presentation, risks, status

Week	Deliverable
W45, 2–8 Nov	HR walkthrough; new benchmark of unseen questions with a harder slice (unnamed documents, paraphrases)
W46, 9–15 Nov	Failure analysis; verifier false accepts and rejects
W47, 16–22 Nov	Attack tests per entry point, permission and fault checks
W48, 23–29 Nov	Reproduction from frozen artifacts; demo hardening; final report. Semantic check and vector index only after the core evidence
W49, 30 Nov–2 Dec	Tagged release; first final presentation on 2 Dec

Owners per week: **[PENDING: team to confirm]**

Riskiest assumptions

- A 2–4B controller answers correctly within budget
- Gains hold on new questions
- Benchmarks separate the configurations

Fallback: keep the loop, benchmarks, configurations and pipeline; cut the vector index, semantic check and extra domains.

Done: loop, citation verifier, reranker, 2 collections, reproducible runs. **Measured:** strict success (judge estimate), cost. **Measured on the Mac:** latency. **Planned:** human audit, attack tests.

Self-assessment: **[PENDING: on track / at risk / narrow scope, after audit and latency results]**

Team, roles and what we ask you to challenge

Three takeaways

1. Initial system (2B): 12–19% strict success. Current system (4B): 57–61% for the full system (judge lower bound, may be optimistic).
2. The weak link was the controller's behaviour, not retrieval (Recall@5 about 0.99).
3. The citation verifier gives auditable citations; we measured no correctness gain from it.

Please challenge: judge reliability, benchmark difficulty, gains measured on the same questions.

Repository:
`https://github.com/tuandung222/LuatCheck-D2`
Commit: `1cd9226031f2`

Member	Presents	Answers for
Lê Trí Quyền	**[PENDING]**	**[PENDING]**
Võ Phạm Tuấn Dũng	**[PENDING]**	**[PENDING]**
Nguyễn Hoàng Phong	**[PENDING]**	**[PENDING]**

[PENDING: who presents which slides; who drives the demo keyboard; ownership of retrieval and reranker / loop, verifier and evaluation / tools, security and UI]

Backup A: why the current system differs from the initial one

What we found in the initial system's failures

- The model asked for clarification when the needed text was not in view: 57% (HCMUT) and 43% (labour) of such questions, against 17% and 13% when it was in view
- The model's own first search query kept only about a third of the question's informative words, and the loop silently returned 3 results
- After a repair message the model refused in 56% (HCMUT) and 53% (labour) of cases; the message itself ended with an instruction to refuse
- Five runaway reasoning notes hit the output limit
- Even with the correct section given (oracle), the 2B controller reached only 28.9% and 44.4%

What the current system does differently

- The first search uses the user's own question plus the model's query; 5 results by default
- A search is required before answering; clearer rules for when to ask or refuse
- Verifier feedback is phrased as a tool report, with no instruction to refuse
- The model's reasoning note is limited to 800 characters
- Fairer quote matching, numbers checked within the claim they belong to, sentence-level support reported as a warning
- A 4B controller added; the revised system is also run with 2B to separate system and model effects

All of this was decided after seeing the initial system's results (see slide 2). The plan was not to tune thresholds on the benchmark labels.

Backup B: strict success for every configuration (%, 95% interval)


Benchmark	Configuration	Initial (2B)	Current (2B)	Current (4B)
HCMUT regulations	no verifier	18.0 [11–26]	31.3 [22–41]	70.0 [61–79]
	verifier	12.0 [7–18]	24.0 [15–33]	64.0 [53–75]
	verifier + reranker	14.0 [8–21]	28.7 [20–37]	60.7 [50–71]
Labour law	no verifier	14.7 [7–23]	31.3 [22–41]	62.0 [52–72]
	verifier	14.7 [7–23]	28.0 [19–38]	52.7 [43–63]
	verifier + reranker	18.7 [11–27]	28.0 [19–37]	56.7 [47–67]

50 questions $\times$ 3 runs per cell, same questions for every system. Intervals: paired bootstrap over questions (5,000 draws), no correction for multiple comparisons. Gains of the current system may be optimistic (see slide 2).


Backup C: what the numbers do not show

- **Judge:** LLM estimates, no human labels yet (agreement and κ: **[PENDING: human audit]**). Judge attempts invalid or timed out: 36% (HCMUT), 45% (labour); invalid or unjudged trials count as failures.
- **Benchmarks:** 50 questions each, AI-drafted and AI-verified; no expert review of documents or questions; about half the questions name their source document.
- **Guardrails:** regex patterns in Vietnamese and English; no red-team numbers yet.
- **Retrieval:** BM25 + TF-IDF with rank fusion; dense embedding retrieval is implemented but not evaluated.
- **Scope:** two document collections; labour-law results are not evidence for other domains. Not tried by real users.
- **Latency:** on the Mac the full system takes a median of about 30 s per question with the 4B controller and about 14 s with the 2B controller; GPU wall times are not reported.


Backup D: failure states in the demo UI (real recordings)



Guardrail block: 3 ms in the timeline, 0 model calls



Verifier rejected the first draft (quote not verbatim); after one repair the answer passes



Reranker server down: execution error, never an answer

First two: current system, 4B controller, recorded 25 October. The repair clip is the one run of 6 tries on benchmark questions with frequent repairs that ended in an answer (5 of the 6 showed a repair; the other 4 of those ended in an L1-failure refusal). Third: recorded 24 October with the 2B controller on a separate instance whose reranker address was unreachable; the interface states are the same in the current system.