# LuatCheck

## A Local, Source-Grounded QA Agent for Vietnamese Regulations

Lê Trí Quyền (2470740) | Võ Phạm Tuấn Dũng (2570015) | Nguyễn Hoàng Phong (2570477)

**CO5151 Advanced Agentic AI | D2 Interim Report**

Application Track, Group 8 | Instructor: TS. Lê Xuân Bách

28 October 2026

## System Overview

LuatCheck answers regulatory questions strictly from local document collections, verifies every cited section and quote in Python before returning an answer, and refuses or asks for clarification when the sources do not support a conclusion. Evaluated on **HCMUT academic regulations** (10 documents, 143 sections) and **Vietnamese labour law** (10 documents, 458 sections: 2019 Labour Code plus 9 implementing laws, decrees, and circulars). Research prototype; not legal advice.


# Changes Since the D1 Proposal

| Proposal commitment | State | Status and rationale (no D1 pitch feedback received) |
|---|---|---|
| Agent loop, citation check | **Done** | Runs end to end; step/tool/repair budgets unchanged |
| Qwen3 controllers, 32B | **Dropped** | Replaced by ternary Bonsai 2B and 4B (GGUF); runs on a 16 GiB Mac and GPU |
| BM25 + Qdrant dense retrieval | **Changed** | BM25 + TF-IDF + reranker; vector index built, scheduled for W46 ablation |
| $\geq$10 tasks, 3 configurations | **Done** | Two fixed 50-question benchmarks (HCMUT regulations, Labour law); 3 seeds |
| Reranker (optional) | **Done** | Vietnamese cross-encoder, evaluated in "verifier + reranker" |
| Verifier audit (30 pairs) | **Done** | 60-item blind judge audit: 96.7% agreement ($\kappa = 0.93$, HCMUT), 90.0% ($\kappa = 0.80$, labour) |
| HR walkthrough; attack tests | **Not started** | Walkthrough scheduled for W45 (Quyền, Phong); attack tests planned for W47 |

## Two local controller options (Bonsai 4B default, Bonsai 2B lightweight)

Both ternary GGUF models run locally via `llama.cpp` on a 16 GiB Mac laptop. **Bonsai 4B** reaches **60.7% (HCMUT)** and **56.7% (labour)** strict success on the full system (~30 s median latency), while **Bonsai 2B** provides a 2× faster lightweight option (~14 s median, 28.0–28.7% strict success).

# System Architecture: Offline Indexing and Bounded Agent Loop




■ Core pipeline ■ Ablated modules (L1 verifier, reranker) Dashed: implemented, switched off in current D2 ablation

Single-agent ReAct loop with a deterministic Python citation verifier; dense vector index, L2 NLI check, and answer memory are switched off in D2 baseline runs.

# Execution Trace on a Sample HCMUT Query

**Question (HCMUT regulations):** *Sinh viên vi phạm Nội quy học đường sẽ được xử lý theo căn cứ nào, và mức xử lý phụ thuộc vào yếu tố nào?*

**1. search**

query: *vi phạm nội quy học đường xử lý mức xử lý phụ thuộc*

20 candidates reranked, top 5 kept; Article 6 of the student code of conduct ranked first

1,509 tokens in, 117 out

→

**2. read_document**

Article 6, *Nội quy học đường* (decision 1924/QĐ-ĐHBK) loads the full text of Article 6 into the agent context

2,905 tokens in, 171 out

→

**3. answer**

cites Article 6 with one exact quote

**Citation verifier: accepted, 0 repairs** (two soft warnings on one sentence, no rejection)

3,398 tokens in, 310 out

## Outcome

Verified answer citing Article 6: disciplinary action follows the student-affairs regulation and national law based on violation severity. Total cost: 3 model calls, 2 tool calls, 7,812 input tokens, 598 output tokens. Offline LLM judge score: correctness 2/2, completeness 2/2.

Full configuration (verifier + reranker), Bonsai 4B controller. End-to-end Mac latency measurements are reported on Slide 9.


# Live Demo: LuatCheck on a 16 GiB Mac

**System:** Bonsai 4B controller (2B option available), BM25 + TF-IDF + reranker, rule-based citation verifier with repair, regex guardrails, `llama.cpp`, running locally.

**Four queries:**

1. HCMUT: verified answer with citation
2. Labour law: same pipeline, second corpus
3. Out of scope: explicit refusal
4. Prompt injection: blocked pre-model

**UI elements shown:** step timeline, retrieved sections, highlighted verbatim quote, verifier verdict, and token counts.





Web UI (Bonsai 4B): verified answer with highlighted source quote and step timeline.

## Fallback recording

An unedited screen recording of the same 4B configuration (recorded 25 October) is available if a live local service fails.

# Evaluation Protocol and Metrics





- **Strict success** (lower bound): run completes, valid judgment, appropriate behaviour, correctness 2/2, completeness 2/2, and all claims supported (errors/unknowns = fail).
- **Judge reliability** (blind human audit, 30 items/benchmark):
  - HCMUT: **96.7%** agreement ($\kappa = 0.93$).
  - Labour law: **90.0%** agreement ($\kappa = 0.80$).
- **Auxiliary metrics:** Recall@5 and citation F1 check section IDs only; the L1 citation verifier checks provenance, verbatim quotes, and local numbers.

## D2 evaluation scope and limitations

- **D2 objective:** verify that the end-to-end pipeline and evaluation harness **run reliably and produce reproducible baseline metrics**; broader experiments follow in **D3**.
- Questions are LLM-drafted, cross-checked, and reviewed by the team (no external legal review).
- Lexical retrieval is near ceiling (Recall@5 $\approx 0.99$); 15/45 HCMUT and 12/45 labour items are answerable closed-book.
- At $N = 50$ questions, differences under ~10 pp fall within bootstrap confidence intervals.

# Controller Scaling: Bonsai 2B vs. Bonsai 4B on the Full System




Whiskers: 95% bootstrap CI (50 questions × 3 seeds).

**4B − 2B gain, pp** (95% paired bootstrap CI)

| Configuration | HCMUT | Labour |
|---|---|---|
| No verifier | +38.7 | +30.7 |
| 31.3/31.3% → 70.0/62.0% | [+27.3, +50.0] | [+20.7, +40.7] |
| Verifier | +40.0 | +24.7 |
| 24.0/28.0% → 64.0/52.7% | [+28.7, +51.3] | [+12.0, +37.3] |
| **Verifier + reranker** | **+32.0** | **+28.7** |
| 28.7/28.0% → 60.7/56.7% | [+21.3, +42.0] | [+18.0, +39.3] |

**Key finding**

Scaling the local controller from 2B to 4B adds **+25 to +40 pp** across all configurations; all six paired bootstrap intervals exclude zero.

# Component Ablation (Bonsai 4B): Impact of the Citation Verifier

| | HCMUT regulations | | | | Labour law | | | |
|---|---|---|---|---|---|---|---|---|
| Configuration | judge % | **audited %** | **leak %** | cit. F1 | judge % | **audited %** | **leak %** | cit. F1 |
| No verifier | 70.0 | 55.3 | **25.6** | 0.820 | 62.0 | 51.3 | **28.0** | 0.841 |
| Verifier | 64.0 | **64.0** | **0.0** | 0.704 | 52.7 | 52.7 | **0.0** | 0.728 |
| Verifier + reranker (full) | 60.7 | **60.7** | **0.0** | 0.714 | 56.7 | **56.7** | **0.0** | 0.691 |
| Closed-book (no documents) | 2.0 | – | – | – | 24.0 | – | – | – |
| Oracle (gold section given, 45 ans.) | 82.2 | – | – | – | 75.6 | – | – | – |

**judge %** = LLM-judge strict success alone; **audited %** = passes LLM judge *and* deterministic L1 citation verification;
**leak %** = share of emitted answers with non-verbatim quotes, unretrieved IDs, or wrong-clause numbers.

- **Without the L1 verifier (*No verifier*): 25.6% (31/121)** of HCMUT answers and **28.0% (37/132)** of labour answers (39.8% and 45.9% on 2B) contain non-verbatim quotes, unretrieved section IDs, or wrong-clause numbers undetected by the prose-only LLM judge.
- **With the L1 verifier (deterministic Python check, $< 2$ ms, no LLM):** Reduces unverified citation leakage to **0.0%**, corrects **17–20 initial drafts** via bounded 2-turn repair, and increases **citation-audited strict success** from **55.3%** $\rightarrow$ **60.7–64.0% (+5.4 to +8.7 pp)** on HCMUT and **51.3%** $\rightarrow$ **56.7% (+5.4 pp)** on labour law.

# Cost, Latency, and Runtime Environment

**Controller tokens per trial** (local inference, USD 0 API cost)

| | Configuration | in | out | calls |
|---|---|---|---|---|
| HCMUT | no verifier | 10,233 | 666 | 3.13 |
| | full system | 12,070 | 763 | 3.37 |
| Labour | no verifier | 9,070 | 686 | 3.11 |
| | full system | 11,477 | 865 | 3.69 |

**Offline evaluation judge cost:**

- **USD 2.17 total** across both benchmarks (USD 1.06 HCMUT and USD 1.10 labour; ≈USD 0.002 per valid judgment).
- Reported by the API gateway (lower bound; timed-out or invalid attempts were automatically retried).

**Mac end-to-end latency (Apple M4, 16 GiB)**

Single-question sequential runs, median / p95:

**Bonsai 4B (≈43 tok/s):**
HCMUT: **33 s** / 86 s | Labour: **30 s** / 72 s

**Bonsai 2B (≈92 tok/s):**
HCMUT: **13 s** / 30 s | Labour: **15 s** / 28 s

**Measurement environment:**

- Accuracy tables come from batch runs on an H100 GPU; interactive latency is measured one query at a time on the Apple M4 Mac.
- All inference (controller + reranker) runs 100% locally with zero per-query API cost.

# Threat Model

**Assets:** faithful answers & citations; user data; corpus, config & weights; read-only tool boundary; availability.
**Attacker:** submits arbitrary questions or pasted text; cannot alter code, corpus files, weights, logs, or host approvals.

| Entry point | Mitigation (enforced in code) | Residual risk |
|---|---|---|
| Question, pasted text | Pre-model regex guardrails, input sanitising, untrusted-content tags; no write tool exposed | Paraphrase bypass; Vietnamese/English patterns only; not red-teamed yet |
| Retrieved sections | Wrapped as tool output; citation verifier checks section IDs, provenance and verbatim quotes | Tagged, not filtered: an adversarial instruction inside a source document reaches the model |
| Corpus, weights, config | Offline ingestion with URL, SHA-256 and page provenance; pinned weight hashes; localhost servers | No cryptographic signatures; third-party weights and `llama.cpp` fork unaudited |
| Memory, outbox | Long-term memory disabled in all runs; outbox requires host approval bound to payload SHA-256 | Single-user local machine assumption |
| Judge gateway (offline) | Benchmark data only; API key in env; blind evaluation packets; strict JSON & quote checks | Candidate answer text could steer the LLM judge (untested) |

**Evaluation status:** Mitigations above are code-enforced boundaries; red-team attack tests are scheduled for W47.

# D3 Roadmap, Key Risks, and Project Status

| Week | Deliverable |
|---|---|
| W45, 2–8 Nov | HR walkthrough; design and freeze unseen harder benchmark (multi-hop, unnamed documents, paraphrases) |
| W46, 9–15 Nov | Run system & ablations on unseen benchmark; add dense-retrieval ablation; failure analysis |
| W47, 16–22 Nov | Entry-point attack tests; permission and fault checks |
| W48, 23–29 Nov | Reproduction from recorded runs; demo hardening; final report |
| W49, 30 Nov–2 Dec | Tagged release; Round 1 final presentation on 2 Dec |

**Owners:** Quyền, Phong (W45); Dũng, Quyền (W46); Phong, Dũng (W47); all (W48–W49)

**Riskiest assumptions**

- A 2–4B local controller answers accurately within step/time budgets
- Gains hold on unseen questions
- Harder benchmarks separate the configurations

**Fallback scope:** keep the loop, unseen benchmark, ablations and reproduction pipeline; drop vector index, semantic check and extra domains.

## D2 status & D3 roadmap

**D2 proves the system runs and is measurable.** Extensive improvements and experiments (unseen harder multi-hop benchmark, verifier refinement, attack tests) are scheduled for **D3**.

# Key Takeaways and Team Contributions

**Three takeaways**

1. **Controller scale + loop design:** 60.7% (HCMUT) and 56.7% (labour) strict success with Bonsai 4B (vs. 28.0–28.7% with 2B).
2. **The bottleneck is controller synthesis, not lexical retrieval** (Recall@5 ≈ 0.99).
3. **Rule-based citation verifier reduces unverified citation leakage** (26–28% → **0.0%**) and raises citation-audited strict success by **+5.4 to +8.7 pp**.

**Open questions for discussion:** verifier over-refusal trade-off, benchmark difficulty, and multi-clause synthesis limits.

Repository:
`https://github.com/tuandung222/LuatCheck-D2`
Commit: `138128e804bf`

| Member | % | Presents | Answers for |
|---|---|---|---|
| Lê Trí Quyền (Leader) | 33% | Slides 1–2, 9, 11–12 | Corpus ingestion, BM25 + TF-IDF index, RRF, reranker, local `llama.cpp` serving |
| Nguyễn Hoàng Phong | 33% | Slides 5 (Demo), 10 | Tool permissions, guardrails, Web UI and outbox, audit log, threat model |
| Võ Phạm Tuấn Dũng | 33% | Slides 3–4, 6–8 | System architecture & model selection, codebase refactoring, agent loop, verifier, benchmarks & evaluation |

Live demo: Nguyễn Hoàng Phong narrates; Võ Phạm Tuấn Dũng drives the keyboard.

# Backup A: 60-Item Blind Human Audit of the LLM Judge

**Protocol:** Stratified blind sample of 60 outputs from the Bonsai 4B runs (30 HCMUT + 30 Labour law; 8 strata per benchmark). Human auditor rated behaviour, correctness, completeness and claim faithfulness against the full source regulations without seeing the LLM judge (`deepseek/deepseek-v4-flash`) scores.

| Benchmark | Sample | Strict-success agreement | $\kappa$ / weighted $\kappa_w$ | Behaviour match |
|---|---|---|---|---|
| HCMUT regulations | $n = 30$ | **96.7%** (29/30) | $0.933$ / $0.974$ (98.8%) | **100.0%** (30/30) |
| Vietnamese labour law | $n = 30$ | **90.0%** (27/30) | $0.800$ / $0.948$ (97.5%) | **93.3%** (28/30) |

**All 4 strict-success disagreements (1 HCMUT, 3 Labour law) are documented item-by-item:**

- **HCMUT (`HV-004`):** Judge scored completeness 2/2 when the answer omitted 2 of 6 required bullet clauses in Article 11.4.
- **Labour law (`LVN-016`, `LVN-005`, `LVN-048`):** Two partial answers where the judge missed a secondary statutory condition (5-year renewal cap; job/workplace guarantee), and one verifier-exhaustion refusal where the judge treated a valid statutory quote as non-matching.

# Backup B: Strict Success by Controller and Configuration (%, 95% CI)


| Benchmark | Configuration | Bonsai 2B | Bonsai 4B | 4B − 2B (pp) |
|---|---|---|---|---|
| HCMUT regulations | no verifier | 31.3 [22–41] | 70.0 [61–79] | +38.7 [+27.3, +50.0] |
| | verifier | 24.0 [15–33] | 64.0 [53–75] | +40.0 [+28.7, +51.3] |
| | verifier + reranker | 28.7 [20–37] | 60.7 [50–71] | +32.0 [+21.3, +42.0] |
| Labour law | no verifier | 31.3 [22–41] | 62.0 [52–72] | +30.7 [+20.7, +40.7] |
| | verifier | 28.0 [19–38] | 52.7 [43–63] | +24.7 [+12.0, +37.3] |
| | verifier + reranker | 28.0 [19–37] | 56.7 [47–67] | +28.7 [+18.0, +39.3] |

50 questions × 3 runs per cell, same questions for every configuration. Intervals: paired bootstrap over questions (5,000 draws), no correction for multiple comparisons.


# Backup C: Methodological Scope and Limitations

- **Judge:** LLM estimates; on a 60-item blind human audit, strict-success agreement is 96.7% ($\kappa = 0.93$, HCMUT) and 90.0% ($\kappa = 0.80$, labour). Judge attempts invalid or timed out: 36% (HCMUT), 45% (labour); invalid or unjudged trials count as failures.
- **Benchmarks:** 50 questions each, LLM-drafted and cross-checked, then reviewed by the team; no external legal review; about half the questions name their source document.
- **Guardrails:** regex patterns in Vietnamese and English; systematic red-team evaluation is scheduled for W47.
- **Retrieval:** BM25 + TF-IDF with rank fusion; dense embedding retrieval is implemented and scheduled for ablation in W46.
- **Domain scope:** evaluated on two regulatory collections; generalization to other domains and end-user testing (HR walkthrough in W45) remain future work.
- **Latency:** on the Mac the full system takes a median of about 30 s per question with the 4B controller and about 14 s with the 2B controller; GPU wall times are from batch runs on a shared server.


# Backup D: Guardrail, Verifier Repair, and Error States in the Web UI



Guardrail block: 3 ms in the timeline, 0 model calls



Verifier rejected first draft (quote not verbatim); repaired and accepted



Reranker server unreachable: explicit execution error state

Left and centre: 4B controller, showing pre-model regex guardrail refusal and bounded 1-step citation repair. Right: when a required local service (controller or reranker) is unreachable, the UI surfaces an explicit execution error state rather than a fabricated answer or silent fallback.