

Ensemble Model

Bùi Tiến Lên

2022



KHOA CÔNG NGHỆ THÔNG TIN
TRƯỜNG ĐẠI HỌC KHOA HỌC TỰ NHIÊN

Contents



1. Ensemble Model

2. Bagging

3. Boosting



Notation

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

symbol	meaning
$a, b, c, N \dots$	scalar number
$\mathbf{w}, \mathbf{v}, \mathbf{x}, \mathbf{y} \dots$	column vector
$\mathbf{X}, \mathbf{Y} \dots$	matrix
\mathbb{R}	set of real numbers
\mathbb{Z}	set of integer numbers
\mathbb{N}	set of natural numbers
\mathbb{R}^D	set of vectors
$\mathcal{X}, \mathcal{Y}, \dots$	set
\mathcal{A}	algorithm

operator	meaning
\mathbf{w}^T	transpose
$\mathbf{X}\mathbf{Y}$	matrix multiplication
\mathbf{X}^{-1}	inverse

Big Picture





Ensemble Model



Bias vs. Variance

Bagging

Bootstrap

Algorithm


Random Forests

Boosting

AdaBoost

Face Detection

- Low-bias models tend to have high variance, and vice versa.





Basics of Ensembles

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

Concept 1

Instead of providing **one model**, an **ensemble** approach proposes **many models** to the same problem, and **combine** them

- The simplest ensemble H over models $\{h_i \in \mathcal{H}, i = 1 \dots T\}$

$$H(\mathbf{x}) = \sum_{i=1}^T \alpha_i h_i(\mathbf{x}) \text{ with } \sum_{i=1}^T \alpha_i = 1 \quad (1)$$

- Why should this be a good idea?
 - combine models \rightarrow reduce the variance \rightarrow enhance expected performance.
- However, increase the performance cost




Basics of Ensembles (cont.)

Bagging

Bootstrap
Algorithm
Random Forests

Boosting

AdaBoost
Face Detection





Why Does it Work?

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

It has been shown that the expected risk of the average of a set of models is better than the average of the expected risk of these models

- Let us consider the simplest ensemble H over models h_i

$$H(\mathbf{x}) = \sum_{i=1}^T \alpha_i h_i(\mathbf{x}) \text{ with } \sum_{i=1}^T \alpha_i = 1 \quad (2)$$

- The MSE risk of h_i at \mathbf{x} is

$$e_i(\mathbf{x}) = \mathbb{E}_y[(y - h_i(\mathbf{x}))^2] \quad (3)$$



Why Does it Work? (cont.)

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

- The average risk $\bar{e}(\mathbf{x})$ of a model is

$$\bar{e}(\mathbf{x}) = \sum_i \alpha_i e_i(\mathbf{x}) \quad (4)$$

- The average risk $e(\mathbf{x})$ of the ensemble is

$$e(\mathbf{x}) = \mathbb{E}_y[(y - H(\mathbf{x}))^2] \quad (5)$$

- Let us define diversity

$$d_i(\mathbf{x}) = (h_i(\mathbf{x}) - H(\mathbf{x}))^2 \quad (6)$$

- The average diversity is

$$\bar{d}(\mathbf{x}) = \sum_i \alpha_i d_i(\mathbf{x}) \quad (7)$$



Why Does it Work? (cont.)

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

- It can then be shown that

$$e(\mathbf{x}) = \bar{e}(\mathbf{x}) - \bar{d}(\mathbf{x}) \quad (8)$$

$$e(\mathbf{x}) < \bar{e}(\mathbf{x}) \quad (9)$$



Bagging

- Bootstrap
- Algorithm
- Random Forests



Bagging

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

Underlying idea

A part of the **variance** is due to the specific choice of the training data set

- Let us create many **similar** training data sets,
 - For each of them, let us train a new function f_i
 - The final function will be the *average* of each function outputs.
-
- How similar? using **bootstrap aggregating**



Bootstrap

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

Concept 2

Given a data set \mathcal{D}_n with n examples drawn from $p(\mathcal{Z}) = p(\mathcal{X}, \mathcal{Y})$, a bootstrap $\mathcal{B}_i, i = 1 \dots T$ of \mathcal{D}_n also contains n examples:

for $j = 1 \rightarrow n$

the j -th example of \mathcal{B}_i is drawn independently with replacement from \mathcal{D}_n

- Some examples from \mathcal{D}_n are in multiple copies in \mathcal{B}_i
- Some examples from \mathcal{D}_n are not in \mathcal{B}_i
- The examples were i.i.d. drawn from $p(\mathcal{Z}) \rightarrow$ the datasets \mathcal{B}_i are as plausible as \mathcal{D}_n , but drawn from \mathcal{D}_n instead of $p(\mathcal{Z})$.



Example

Bagging

Bootstrap


Algorithm

Random Forests

Boosting

AdaBoost

Face Detection





Diagram

Bagging

Bootstrap


Algorithm

Random Forests

Boosting

AdaBoost

Face Detection





Algorithm

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

Training:

- Given a training set \mathcal{D}_n , create T bootstraps \mathcal{B}_i of \mathcal{D}_n
- For each bootstrap \mathcal{B}_i , select

$$h_i = \arg \min_{h \in \mathcal{H}} E(h \mid \mathcal{B}_i) \quad (10)$$

Running:

- Given an input \mathbf{x} , the corresponding output \hat{y} is:

$$\hat{y} = H(\mathbf{x}) = \frac{1}{T} \sum_{i=1}^T h_i(\mathbf{x}) \quad (11)$$



Bias + Variance

Bagging

Bootstrap

Algorithm


Random Forests

Boosting

AdaBoost

Face Detection

- **Analysis:** if generalization error is decomposed into **bias** and **variance** terms then **bagging reduces variance**.





Random Forests

Concept 3

A **random forest** is an ensemble of decision trees.





Random Forests (cont.)

Each decision tree h_i is trained as follows:

- Create a **bootstrap** of the training set
- Select a subset $m \ll d$ input variables as **potential** split nodes (m is constant over all trees)
- No pruning of the trees

A decision is taken by **voting** amongst the trees

- Somehow, m controls the capacity.



Boosting

- AdaBoost
- Face Detection






Big Picture

Bagging

Bootstrap
Algorithm
Random Forests

Boosting

AdaBoost
Face Detection





Diagram

Bagging

Bootstrap


Algorithm

Random Forests

Boosting

AdaBoost

Face Detection





Weak vs. Strong Learning Model

Concept 4

A learning model is **strong** iff every hypothesis h has low error

Concept 5

A learning model is **weak** iff every hypothesis h has high error

Examples of weak classifiers:

- Simple decision trees such as **stumps**
- Simple neural networks such as **perceptrons**
- Haar-like features



Boosting

Bagging

Bootstrap
Algorithm
Random Forests

Boosting

AdaBoost
Face Detection

- Is there a **boosting** algorithm that turns a weak learner into a strong learner?



Robert Schapire



Yoav Freund

- Yes! There is boosting algorithm that uses simple (**weak**) classifiers h_t and combine them **iteratively** to a strong classifier.
- General combination classifier

$$H(x) = \sum_{t=1}^T \alpha_t h_t(x) \quad (12)$$



AdaBoost

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

Concept 6

AdaBoost, short for Adaptive Boosting, is the most popular algorithm in the family of **boosting** algorithms

- **Simplest framework:** binary classification $H(x)$
- **Simplest requirement:** each weak classifier $y = h_t(x)$, $y \in \{-1, +1\}$ should perform better than chance
- **Error function:**

$$\ell((H(x), y)) = e^{-yH(x)} \quad (13)$$



Concepts

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

- **Initialize** $H_0 \leftarrow \emptyset$
- At each time step t ,
 - **Select** h_t given the performance obtained by previous H_{t-1} .
 - **Modify** training sample distribution in order to favor difficult **examples**.
 - **Train** a new weak classifier
 - **Select** the new weight α_t by optimizing a global criterion

$$H_t \leftarrow H_{t-1} + \alpha_t h_t \quad (14)$$

- **Stop** when impossible to find a weak classifier satisfying the simplest condition (being better than chance)



Algorithm

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

Inputs: training data $\mathcal{D} = \{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_N, y_N)\}$ and a set of weak binary classifiers $\{h_i \in \mathcal{H}\}$

Initialize the weights' distribution of training data

$$(w_1^{(1)}, w_2^{(1)}, \dots, w_N^{(1)}) = \left(\frac{1}{N}, \frac{1}{N}, \dots, \frac{1}{N} \right) \quad (15)$$

Iterate over $t = 1, 2, \dots, T$, use training data with current weights' distribution

1. **Find** a weak classifier $h_t(\mathbf{x})$ that minimizes the error rate e_t of over the training data

$$e_t = P(h_t(\mathbf{x}_i) \neq y_i) = \sum_{i=1}^N w_i^{(t)} \mathbb{I}(h_t(\mathbf{x}_i) \neq y_i) \quad (16)$$



Algorithm (cont.)

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

2. **Compute** the coefficient of classifier $h_t(\mathbf{x})$

$$\alpha_t = \frac{1}{2} \log \frac{1 - e_t}{e_t} \quad (17)$$

3. **Update** the weights' distribution of training data

$$w_i^{(t+1)} = w_i^{(t)} \exp(-\alpha_t y_i h_t(\mathbf{x}_i)) \quad (18)$$

4. **Normalize** the weights

$$w_i = \frac{w_i}{\sum_i w_i} \quad (19)$$

Ensemble T weak classifiers

$$\text{sign} [H(\mathbf{x})] = \text{sign} \left[\sum_{t=1}^T \alpha_t h_t(\mathbf{x}) \right] \quad (20)$$



Example

Bagging

Bootstrap

Algorithm



Random Forests

Boosting

AdaBoost

Face Detection

- Given a training data set $\mathcal{D} = \{A, B, C, D, E, F, G, H, I, J\}$, find a strong classifier from weak classifiers (vertical or horizontal lines)






Round 1

Bagging

Bootstrap
Algorithm
Random Forests

Boosting

AdaBoost
Face Detection






Round 2

Bagging

Bootstrap
Algorithm
Random Forests

Boosting

AdaBoost
Face Detection








Round 3

Bagging

Bootstrap
Algorithm
Random Forests

Boosting

AdaBoost
Face Detection



$$\epsilon_3 = 0.14, \alpha_3 = 0.92$$



The combined classifier


Bagging

Bootstrap
Algorithm
Random Forests

Boosting

AdaBoost
Face Detection

$$H_{final} = \text{sign} \left[0.42 \begin{array}{|c|} \hline \text{Blue} \\ \hline \end{array} + 0.65 \begin{array}{|c|} \hline \text{Blue} \\ \hline \end{array} + 0.92 \begin{array}{|c|} \hline \text{Blue} \\ \hline \end{array} \right]$$





Analysis

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

- Selection of α_t comes from minimizing


$$\arg \min_{\alpha_t} \sum_{i=1}^N \exp(-y_i [H_{t-1}(\mathbf{x}_i) + \alpha_t h_t(\mathbf{x}_i)]) \quad (21)$$

- If each weak classifier is always better than chance, then AdaBoost can be proven to **converge to 0 training error**
- Even after training error is 0, generalization error continues to improve: the **margin** continues to grow
- **Sampling** can often be replaced by **weighting**



Cost Functions

- Comparison of various cost functions related to AdaBoost





Margin

Bagging

Bootstrap

Algorithm


Random Forests

Boosting

AdaBoost

Face Detection

- The AdaBoost margin is defined as the distribution of $y \cdot h(x)$





Extensions

Bagging

Bootstrap

Algorithm

Random Forests

Boosting

AdaBoost

Face Detection

- **Multi-class** classification
- **Single-class classification**: estimating quantiles
- **Regression**: transform the problem into a binary classification task
- **Localized Boosting**: similar to **mixtures of experts**



Face Detection

Bagging

Bootstrap

Algorithm

Random Forests


Boosting

AdaBoost

Face Detection

Face detection framework was proposed in 2001 by Paul Viola and Michael Jones using AdaBoost

- Some hypotheses h_{θ}



- Haar-like features for each hypothesis

$$h_{\theta} = \sum_{(x,y) \in \text{dark area}} \text{image}(x,y) - \sum_{(x,y) \in \text{white area}} \text{image}(x,y) \quad (22)$$



Important points to remember

- Bagging is predominantly a variance-reduction technique, while boosting is primarily a bias-reduction technique.
- This explains why bagging is often used in combination with high-variance models such as tree models, whereas boosting is typically used with high-bias models such as linear classifiers.

References



Goodfellow, I., Bengio, Y., and Courville, A. (2016).

Deep learning.

MIT press.



Lê, B. and Tô, V. (2014).

Cở sở trí tuệ nhân tạo.

Nhà xuất bản Khoa học và Kỹ thuật.



Russell, S. and Norvig, P. (2021).

Artificial intelligence: a modern approach.

Pearson Education Limited.