



Lecture 8: Hardware and Software

Last time

Optimization: SGD+Momentum,
Nesterov, RMSProp, Adam



Regularization: Dropout




Regularization: Add noise, then
marginalize out

$$\text{Train} \quad y = f_W(x, z)$$

$$\text{Test} \quad y = f(x) = E_z[f(x, z)]$$

**Transfer
Learning**



Today

- Deep learning hardware
 - CPU, GPU, TPU
- Deep learning software
 - PyTorch and TensorFlow
 - Static vs Dynamic computation graphs

Deep Learning Hardware

My computer




Spot the CPU!

(central processing unit)



[This image is licensed under CC-BY 2.0](#)




Spot the GPUs!

(graphics processing unit)



This image is in the public domain



NVIDIA

vs

AMD

NVIDIA

vs

AMD


CPU vs GPU

	Cores	Clock Speed	Memory	Price	Speed
CPU (Intel Core i7-7700k)	4 (8 threads with hyperthreading)	4.2 GHz	System RAM	\$339	~540 GFLOPs FP32
GPU (NVIDIA GTX 1080 Ti)	3584	1.6 GHz	11 GB GDDR5 X	\$699	~11.4 TFLOPs FP32

CPU: Fewer cores, but each core is much faster and much more capable; great at sequential tasks


GPU: More cores, but each core is much slower and “dumber”; great for parallel tasks

GigaFLOPs per Dollar



CPU vs GPU in practice


(CPU performance not well-optimized, a little unfair)



Data from <https://github.com/jcjohnson/cnn-benchmarks>

CPU vs GPU in practice

cuDNN much faster than
“unoptimized” CUDA



Data from <https://github.com/jcjohnson/cnn-benchmarks>

CPU vs GPU

	Cores	Clock Speed	Memory	Price	Speed
CPU (Intel Core i7-7700k)	4 (8 threads with hyperthreading)	4.2 GHz	System RAM	\$339	~540 GFLOPs FP32
GPU (NVIDIA GTX 1080 Ti)	3584	1.6 GHz	11 GB GDDR5 X	\$699	~11.4 TFLOPs FP32
TPU NVIDIA TITAN V	5120 CUDA, 640 Tensor	1.5 GHz	12GB HBM2	\$2999	~14 TFLOPs FP32 ~112 TFLOP FP16
TPU Google Cloud TPU	?	?	64 GB HBM	\$6.50 per hour	~180 TFLOP

CPU: Fewer cores, but each core is much faster and much more capable; great at sequential tasks

GPU: More cores, but each core is much slower and “dumber”; great for parallel tasks


TPU: Specialized hardware for deep learning

CPU vs GPU

	Cores	Clock Speed	Memory	Price	Speed
CPU (Intel Core i7-7700k)	4 (8 threads with hyperthreading)	4.2 GHz	System RAM	\$339	~540 GFLOPs FP32
GPU (NVIDIA GTX 1080 Ti)	3584	1.6 GHz	11 GB GDDR5 X	\$699	~11.4 TFLOPs FP32
TPU NVIDIA TITAN V	5120 CUDA, 640 Tensor	1.5 GHz	12GB HBM2	\$2999	~14 TFLOPs FP32 ~112 TFLOP FP16
TPU Google Cloud TPU	?	?	64 GB HBM	\$6.50 per hour	~180 TFLOP


NOTE: TITAN V isn't technically a "TPU" since that's a Google term, but both have hardware specialized for deep learning

GigaFLOPs per Dollar




Example: Matrix Multiplication


$A \times B$



$B \times C$



$A \times C$



=


Programming GPUs

- CUDA (NVIDIA only)
 - Write C-like code that runs directly on the GPU
 - Optimized APIs: cuBLAS, cuFFT, cuDNN, etc
- OpenCL
 - Similar to CUDA, but runs on anything
 - Usually slower on NVIDIA hardware
- HIP <https://github.com/ROCm-Developer-Tools/HIP>
 - New project that automatically converts CUDA code to something that can run on AMD GPUs
- Udacity: Intro to Parallel Programming
<https://www.udacity.com/course/cs344>
 - For deep learning just use existing libraries

CPU / GPU Communication


Model
is here

Data is here



CPU / GPU Communication

Model
is here



Data is here

If you aren't careful, training can bottleneck on reading data and transferring to GPU!

Solutions:

- Read all data into RAM
- Use SSD instead of HDD
- Use multiple CPU threads to prefetch data

Deep Learning Software

A zoo of frameworks!

Caffe
(UC Berkeley)



Caffe2
(Facebook)

Torch
(NYU / Facebook)



PyTorch
(Facebook)

Theano
(U Montreal)



TensorFlow
(Google)

PaddlePaddle
(Baidu)

Chainer

MXNet
(Amazon)

Developed by U Washington, CMU, MIT, Hong Kong U, etc but main framework of choice at AWS

CNTK
(Microsoft)

Deeplearning4j

And others...

A zoo of frameworks!

Caffe
(UC Berkeley)



Caffe2
(Facebook)

Torch
(NYU / Facebook)



PyTorch
(Facebook)

Theano
(U Montreal)



TensorFlow
(Google)

We'll focus on these

PaddlePaddle
(Baidu)

MXNet
(Amazon)

Developed by U Washington, CMU, MIT, Hong Kong U, etc but main framework of choice at AWS

Chainer

CNTK
(Microsoft)

Deeplearning4j

And others...

A zoo of frameworks!

Caffe
(UC Berkeley)



Caffe2
(Facebook)

Torch
(NYU / Facebook)



PyTorch
(Facebook)

Theano
(U Montreal)



TensorFlow
(Google)

I've mostly used these

PaddlePaddle
(Baidu)

MXNet
(Amazon)

Developed by U Washington, CMU, MIT, Hong Kong U, etc but main framework of choice at AWS


Chainer

CNTK
(Microsoft)

Deeplearning4j

And others...

Recall: Computational Graphs



Recall: Computational Graphs

input image

weights

loss




Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Recall: Computational Graphs

input image

loss




Figure reproduced with permission from a [Twitter post](#) by Andrej Karpathy.

The point of deep learning frameworks

- (1) Quick to develop and test new ideas
- (2) Automatically compute gradients
- (3) Run it all efficiently on GPU (wrap cuDNN, cuBLAS, etc)

Computational Graphs


Numpy

```
import numpy as np
np.random.seed(0)

N, D = 3, 4

x = np.random.randn(N, D)
y = np.random.randn(N, D)
z = np.random.randn(N, D)

a = x * y
b = a + z
c = np.sum(b)
```



Computational Graphs

Numpy


```
import numpy as np
np.random.seed(0)

N, D = 3, 4

x = np.random.randn(N, D)
y = np.random.randn(N, D)
z = np.random.randn(N, D)

a = x * y
b = a + z
c = np.sum(b)

grad_c = 1.0
grad_b = grad_c * np.ones((N, D))
grad_a = grad_b.copy()
grad_z = grad_b.copy()
grad_x = grad_a * y
grad_y = grad_a * x
```



Computational Graphs

Numpy


```
import numpy as np
np.random.seed(0)

N, D = 3, 4

x = np.random.randn(N, D)
y = np.random.randn(N, D)
z = np.random.randn(N, D)

a = x * y
b = a + z
c = np.sum(b)

grad_c = 1.0
grad_b = grad_c * np.ones((N, D))
grad_a = grad_b.copy()
grad_z = grad_b.copy()
grad_x = grad_a * y
grad_y = grad_a * x
```



Good:

- Clean API, easy to write numeric code

Bad:

- Have to compute our own gradients
- Can't run on GPU

Computational Graphs

Numpy


```
import numpy as np
np.random.seed(0)

N, D = 3, 4

x = np.random.randn(N, D)
y = np.random.randn(N, D)
z = np.random.randn(N, D)

a = x * y
b = a + z
c = np.sum(b)

grad_c = 1.0
grad_b = grad_c * np.ones((N, D))
grad_a = grad_b.copy()
grad_z = grad_b.copy()
grad_x = grad_a * y
grad_y = grad_a * x
```



PyTorch

```
import torch

N, D = 3, 4
x = torch.randn(N, D)
y = torch.randn(N, D)
z = torch.randn(N, D)

a = x * y
b = a + z
c = torch.sum(b)
```

Looks exactly like numpy!

Computational Graphs

Numpy


```
import numpy as np
np.random.seed(0)

N, D = 3, 4

x = np.random.randn(N, D)
y = np.random.randn(N, D)
z = np.random.randn(N, D)

a = x * y
b = a + z
c = np.sum(b)

grad_c = 1.0
grad_b = grad_c * np.ones((N, D))
grad_a = grad_b.copy()
grad_z = grad_b.copy()
grad_x = grad_a * y
grad_y = grad_a * x
```



PyTorch

```
import torch

N, D = 3, 4
x = torch.randn(N, D, requires_grad=True)
y = torch.randn(N, D)
z = torch.randn(N, D)

a = x * y
b = a + z
c = torch.sum(b)

c.backward()
print(x.grad)
```

PyTorch handles gradients for us!

Computational Graphs

Numpy


```
import numpy as np
np.random.seed(0)

N, D = 3, 4

x = np.random.randn(N, D)
y = np.random.randn(N, D)
z = np.random.randn(N, D)

a = x * y
b = a + z
c = np.sum(b)

grad_c = 1.0
grad_b = grad_c * np.ones((N, D))
grad_a = grad_b.copy()
grad_z = grad_b.copy()
grad_x = grad_a * y
grad_y = grad_a * x
```



PyTorch

```
import torch

device = 'cuda:0'
N, D = 3, 4
x = torch.randn(N, D, requires_grad=True,
                device=device)
y = torch.randn(N, D, device=device)
z = torch.randn(N, D, device=device)

a = x * y
b = a + z
c = torch.sum(b)

c.backward()
print(x.grad)
```

Trivial to run on GPU - just construct arrays on a different device!

PyTorch

(More detail)

PyTorch: Fundamental Concepts

Tensor: Like a numpy array, but can run on GPU

Autograd: Package for building computational graphs out of Tensors, and automatically computing gradients

Module: A neural network layer; may store state or learnable weights

PyTorch: Versions

For this class we are using **PyTorch version 0.4** which was released Tuesday 4/24

This version makes a lot of changes to some of the core APIs around autograd, Tensor construction, Tensor datatypes / devices, etc

Be careful if you are looking at older PyTorch code!

PyTorch: Tensors

Running example: Train
a two-layer ReLU
network on random data
with L2 loss

```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Tensors

PyTorch Tensors are just like numpy arrays, but they can run on GPU.

PyTorch Tensor API looks almost exactly like numpy!

Here we fit a two-layer net using PyTorch Tensors:

```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Tensors

Create random tensors
for data and weights



```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Tensors

Forward pass: compute predictions and loss



```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Tensors

Backward pass:
manually compute
gradients



```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Tensors

Gradient descent
step on weights

```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Tensors

To run on GPU, just use a different device!

```
import torch
device = torch.device('cuda:0')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Autograd

Creating Tensors with
requires_grad=True enables
autograd

Operations on Tensors with
requires_grad=True cause PyTorch
to build a computational graph

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd

We will not want gradients
(of loss) with respect to data

Do want gradients with
respect to weights

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd

Forward pass looks exactly the same as before, but we don't need to track intermediate values - PyTorch keeps track of them for us in the graph

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd

Compute gradient of loss
with respect to w1 and w2

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd

Make gradient step on weights, then zero them. Torch.no_grad means “don’t build a computational graph for this part”

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch methods that end in underscore
modify the Tensor in-place; methods that
don't return a new Tensor

PyTorch: New Autograd Functions

Define your own autograd functions by writing forward and backward functions for Tensors

Very similar to modular layers in A2! Use ctx object to “cache” values for the backward pass, just like cache objects from A2

```
class MyReLU(torch.autograd.Function):
    @staticmethod
    def forward(ctx, x):
        ctx.save_for_backward(x)
        return x.clamp(min=0)

    @staticmethod
    def backward(ctx, grad_y):
        x, = ctx.saved_tensors
        grad_input = grad_y.clone()
        grad_input[x < 0] = 0
        return grad_input
```

PyTorch: New Autograd Functions

Define your own autograd functions by writing forward and backward functions for Tensors

Very similar to modular layers in A2! Use ctx object to “cache” values for the backward pass, just like cache objects from A2

Define a helper function to make it easy to use the new function

```
class MyReLU(torch.autograd.Function):
    @staticmethod
    def forward(ctx, x):
        ctx.save_for_backward(x)
        return x.clamp(min=0)

    @staticmethod
    def backward(ctx, grad_y):
        x, = ctx.saved_tensors
        grad_input = grad_y.clone()
        grad_input[x < 0] = 0
        return grad_input

def my_relu(x):
    return MyReLU.apply(x)
```

PyTorch: New Autograd Functions

```
class MyReLU(torch.autograd.Function):
    @staticmethod
    def forward(ctx, x):
        ctx.save_for_backward(x)
        return x.clamp(min=0)

    @staticmethod
    def backward(ctx, grad_y):
        x, = ctx.saved_tensors
        grad_input = grad_y.clone()
        grad_input[x < 0] = 0
        return grad_input

def my_relu(x):
    return MyReLU.apply(x)
```

Can use our new autograd
function in the forward pass

```
N, D_in, H, D_out = 64, 1000, 100, 10

x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = my_relu(x.mm(w1)).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: New Autograd Functions

```
def my_relu(x):
    return x.clamp(min=0)
```

In practice you almost never need to define new autograd functions! Only do it when you need custom backward. In this case we can just use a normal Python function

```
N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = my_relu(x.mm(w1)).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: nn

Higher-level wrapper for working with neural nets

Use this! It will make your life easier

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
    model.zero_grad()
```

PyTorch: nn

Define our model as a sequence of layers; each layer is an object that holds learnable weights



```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
    model.zero_grad()
```

PyTorch: nn

Forward pass: feed data to model, and compute loss

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
    model.zero_grad()
```

PyTorch: nn

Forward pass: feed data to model, and compute loss

torch.nn.functional has useful helpers like loss functions

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
    model.zero_grad()
```

PyTorch: nn

Backward pass: compute gradient with respect to all model weights (they have `requires_grad=True`)

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
    model.zero_grad()
```

PyTorch: nn

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()
```

```
with torch.no_grad():
    for param in model.parameters():
        param -= learning_rate * param.grad
model.zero_grad()
```

Make gradient step on
each model parameter
(with gradients disabled)



PyTorch: optim

Use an **optimizer** for different update rules

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-4
optimizer = torch.optim.Adam(model.parameters(),
                             lr=learning_rate)

for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: optim

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-4
optimizer = torch.optim.Adam(model.parameters(),
                             lr=learning_rate)

for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    optimizer.step()
    optimizer.zero_grad()
```

After computing gradients, use
optimizer to update params
and zero gradients



```
optimizer.step()  
optimizer.zero_grad()
```

Aside: Lua Torch

Direct ancestor of PyTorch
(they used to share a lot of C
backend)

Written in Lua, not Python

Torch has Tensors and Modules
like PyTorch, but no full-featured
autograd; much more painful to
work with

More details: Check 2016 slides

```
require 'torch'
require 'nn'
require 'optim'

local N, D, H, C = 64, 256, 512, 10

local model = nn.Sequential()
model:add(nn.Linear(D, H))
model:add(nn.ReLU())
model:add(nn.Linear(H, C))
local loss_fn = nn.CrossEntropyCriterion()

local x = torch.randn(N, D)
local y = torch.Tensor(N):random(C)
local weights, grad_weights = model:getParameters()

local function f(w)
    assert(w == weights)
    local scores = model:forward(x)
    local loss = loss_fn:forward(scores, y)

    grad_weights:zero()
    local grad_scores = loss_fn:backward(scores, y)
    local grad_x = model:backward(x, grad_scores)

    return loss, grad_weights
end

local state = {learningRate=1e-3}
for t = 1, 100 do
    optim.adam(f, weights, state)
end
```

PyTorch: nn

Define new Modules

A PyTorch **Module** is a neural net layer; it inputs and outputs Tensors

Modules can contain weights or other modules

You can define your own Modules using autograd!

```
import torch

class TwoLayerNet(torch.nn.Module):
    def __init__(self, D_in, H, D_out):
        super(TwoLayerNet, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, H)
        self.linear2 = torch.nn.Linear(H, D_out)

    def forward(self, x):
        h_relu = self.linear1(x).clamp(min=0)
        y_pred = self.linear2(h_relu)
        return y_pred

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: nn

Define new Modules

Define our whole model
as a single Module

```
import torch

class TwoLayerNet(torch.nn.Module):
    def __init__(self, D_in, H, D_out):
        super(TwoLayerNet, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, H)
        self.linear2 = torch.nn.Linear(H, D_out)

    def forward(self, x):
        h_relu = self.linear1(x).clamp(min=0)
        y_pred = self.linear2(h_relu)
        return y_pred
```

```
N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: nn

Define new Modules

Initializer sets up two children (Modules can contain modules)

```
import torch

class TwoLayerNet(torch.nn.Module):
    def __init__(self, D_in, H, D_out):
        super(TwoLayerNet, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, H)
        self.linear2 = torch.nn.Linear(H, D_out)

    def forward(self, x):
        h_relu = self.linear1(x).clamp(min=0)
        y_pred = self.linear2(h_relu)
        return y_pred

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: nn

Define new Modules

Define forward pass using child modules

No need to define backward - autograd will handle it

```
import torch

class TwoLayerNet(torch.nn.Module):
    def __init__(self, D_in, H, D_out):
        super(TwoLayerNet, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, H)
        self.linear2 = torch.nn.Linear(H, D_out)
```

```
def forward(self, x):
    h_relu = self.linear1(x).clamp(min=0)
    y_pred = self.linear2(h_relu)
    return y_pred
```

```
N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: nn

Define new Modules

Construct and train an instance of our model

```
import torch

class TwoLayerNet(torch.nn.Module):
    def __init__(self, D_in, H, D_out):
        super(TwoLayerNet, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, H)
        self.linear2 = torch.nn.Linear(H, D_out)

    def forward(self, x):
        h_relu = self.linear1(x).clamp(min=0)
        y_pred = self.linear2(h_relu)
        return y_pred
```

```
N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
```

```
model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: nn

Define new Modules

Very common to mix and match
custom Module subclasses and
Sequential containers

```
import torch

class ParallelBlock(torch.nn.Module):
    def __init__(self, D_in, D_out):
        super(ParallelBlock, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, D_out)
        self.linear2 = torch.nn.Linear(D_in, D_out)
    def forward(self, x):
        h1 = self.linear1(x)
        h2 = self.linear2(x)
        return (h1 * h2).clamp(min=0)

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    ParallelBlock(D_in, H),
    ParallelBlock(H, H),
    torch.nn.Linear(H, D_out))

optimizer = torch.optim.Adam(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)
    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: nn

Define new Modules

Define network component
as a Module subclass



```
import torch

class ParallelBlock(torch.nn.Module):
    def __init__(self, D_in, D_out):
        super(ParallelBlock, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, D_out)
        self.linear2 = torch.nn.Linear(D_in, D_out)
    def forward(self, x):
        h1 = self.linear1(x)
        h2 = self.linear2(x)
        return (h1 * h2).clamp(min=0)

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    ParallelBlock(D_in, H),
    ParallelBlock(H, H),
    torch.nn.Linear(H, D_out))

optimizer = torch.optim.Adam(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)
    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: nn

Define new Modules

Stack multiple instances of the component in a sequential




```
import torch

class ParallelBlock(torch.nn.Module):
    def __init__(self, D_in, D_out):
        super(ParallelBlock, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, D_out)
        self.linear2 = torch.nn.Linear(D_in, D_out)
    def forward(self, x):
        h1 = self.linear1(x)
        h2 = self.linear2(x)
        return (h1 * h2).clamp(min=0)

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    ParallelBlock(D_in, H),
    ParallelBlock(H, H),
    torch.nn.Linear(H, D_out))

optimizer = torch.optim.Adam(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)
    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```



```

import torch

class ParallelBlock(torch.nn.Module):
    def __init__(self, D_in, D_out):
        super(ParallelBlock, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, D_out)
        self.linear2 = torch.nn.Linear(D_in, D_out)

    def forward(self, x):
        h1 = self.linear1(x)
        h2 = self.linear2(x)
        return (h1 * h2).clamp(min=0)

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    ParallelBlock(D_in, H),
    ParallelBlock(H, H),
    torch.nn.Linear(H, D_out))

optimizer = torch.optim.Adam(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)
    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
  
```

PyTorch: DataLoaders

A **DataLoader** wraps a **Dataset** and provides minibatching, shuffling, multithreading, for you

When you need to load custom data, just write your own Dataset class

```
import torch
from torch.utils.data import TensorDataset, DataLoader

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

# loader = DataLoader(TensorDataset(x, y), batch_size=8)
model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-2)
for epoch in range(20):
    for x_batch, y_batch in loader:
        y_pred = model(x_batch)
        loss = torch.nn.functional.mse_loss(y_pred, y_batch)

        loss.backward()
        optimizer.step()
        optimizer.zero_grad()
```

PyTorch: DataLoaders

Iterate over loader to form minibatches

```
import torch
from torch.utils.data import TensorDataset, DataLoader

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

loader = DataLoader(TensorDataset(x, y), batch_size=8)
model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-2)
for epoch in range(20):
    for x_batch, y_batch in loader:
        y_pred = model(x_batch)
        loss = torch.nn.functional.mse_loss(y_pred, y_batch)

        loss.backward()
        optimizer.step()
        optimizer.zero_grad()
```

PyTorch: Pretrained Models

Super easy to use pretrained models with torchvision
<https://github.com/pytorch/vision>


```
import torch
import torchvision

alexnet = torchvision.models.alexnet(pretrained=True)
vgg16 = torchvision.models.vgg16(pretrained=True)
resnet101 = torchvision.models.resnet101(pretrained=True)
```

PyTorch: Visdom

Visualization tool: add logging to your code, then visualize in a browser

Can't visualize computational graph structure (yet?)



<https://github.com/facebookresearch/visdom>

This image is licensed under CC-BY 4.0; no changes were made to the image

PyTorch: Dynamic Computation Graphs

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

PyTorch: Dynamic Computation Graphs

x

w1

w2

y

```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Create Tensor objects

PyTorch: Dynamic Computation Graphs



```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Build graph data structure AND
perform computation

PyTorch: Dynamic Computation Graphs



```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Build graph data structure AND
perform computation

PyTorch: Dynamic Computation Graphs



```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Search for path between loss and w1, w2
(for backprop) AND perform computation

PyTorch: Dynamic Computation Graphs

x

w1

w2

y

```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Throw away the graph, backprop path, and rebuild it from scratch on every iteration

PyTorch: Dynamic Computation Graphs



```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Build graph data structure AND
perform computation

PyTorch: Dynamic Computation Graphs



```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Build graph data structure AND
perform computation

PyTorch: Dynamic Computation Graphs



```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Search for path between loss and w1, w2
(for backprop) AND perform computation

PyTorch: Dynamic Computation Graphs

Building the graph and
computing the graph happen at
the same time.

Seems inefficient, especially if we
are building the same graph over
and over again...

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Static Computation Graphs


Alternative: **Static** graphs

Step 1: Build computational graph
describing our computation
(including finding paths for
backprop)

Step 2: Reuse the same graph on
every iteration

```
graph = build_graph()

for x_batch, y_batch in loader:
    run_graph(graph, x=x_batch, y=y_batch)
```



TensorFlow

TensorFlow: Neural Net

```
import numpy as np
import tensorflow as tf
```

(Assume imports at the top of each snippet)

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D),}
    out = sess.run([loss, grad_w1, grad_w2],
                  feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow: Neural Net

First **define**
computational graph



```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])
```

Then **run** the graph
many times



```
with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D),}
    out = sess.run([loss, grad_w1, grad_w2],
                  feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow: Neural Net

Create **placeholders** for
input x, weights w1 and
w2, and targets y


```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D),}
    out = sess.run([loss, grad_w1, grad_w2],
                  feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow: Neural Net



Forward pass: compute prediction for y and loss. No computation - just building graph


```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D)}
    out = sess.run([loss, grad_w1, grad_w2],
                  feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow: Neural Net



Tell TensorFlow to compute loss of gradient with respect to $w1$ and $w2$.
No compute - just building the graph


```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D)}
    out = sess.run([loss, grad_w1, grad_w2],
                  feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow: Neural Net



Find paths between loss and w_1 , w_2


```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D),}
    out = sess.run([loss, grad_w1, grad_w2],
                  feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow: Neural Net



Add new operators to the graph which compute grad_{w1} and grad_{w2}


```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D),}
    out = sess.run([loss, grad_w1, grad_w2],
                  feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow: Neural Net



Now done building our graph,
so we enter a **session** so we
can actually run the graph


```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D)}
    out = sess.run([loss, grad_w1, grad_w2],
                  feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow: Neural Net



Create numpy arrays that will fill in the placeholders above


```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D),}
    out = sess.run([loss, grad_w1, grad_w2],
                  feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow: Neural Net



Run the graph: feed in the numpy arrays for x, y, w1, and w2; get numpy arrays for loss, grad_w1, and grad_w2


```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D,)}
    out = sess.run([loss, grad_w1, grad_w2],
                  feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow: Neural Net



Train the network: Run the graph over and over, use gradient to update weights

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))
grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D),}
    learning_rate = 1e-5
    for t in range(50):
        out = sess.run([loss, grad_w1, grad_w2],
                      feed_dict=values)
        loss_val, grad_w1_val, grad_w2_val = out
        values[w1] -= learning_rate * grad_w1_val
        values[w2] -= learning_rate * grad_w2_val
```

TensorFlow: Neural Net

Problem: copying
weights between CPU /
GPU each step

Train the network: Run
the graph over and over,
use gradient to update
weights

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))
grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D),}
    learning_rate = 1e-5
    for t in range(50):
        out = sess.run([loss, grad_w1, grad_w2],
                      feed_dict=values)
        loss_val, grad_w1_val, grad_w2_val = out
        values[w1] -= learning_rate * grad_w1_val
        values[w2] -= learning_rate * grad_w2_val
```

TensorFlow: Neural Net

Change w1 and w2 from
placeholder (fed on
each call) to **Variable**
(persists in the graph
between calls)

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.Variable(tf.random_normal((D, H)))
w2 = tf.Variable(tf.random_normal((H, D)))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(tf.square(diff), axis=1))
grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

learning_rate = 1e-5
new_w1 = w1.assign(w1 - learning_rate * grad_w1)
new_w2 = w2.assign(w2 - learning_rate * grad_w2)

with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D),}
    for t in range(50):
        loss_val, = sess.run([loss], feed_dict=values)
```

TensorFlow: Neural Net

Add **assign** operations
to update w1 and w2 as
part of the graph!

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.Variable(tf.random_normal((D, H)))
w2 = tf.Variable(tf.random_normal((H, D)))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))
grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])
```

```
learning_rate = 1e-5
new_w1 = w1.assign(w1 - learning_rate * grad_w1)
new_w2 = w2.assign(w2 - learning_rate * grad_w2)
```

```
with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D),}
    for t in range(50):
        loss_val, = sess.run([loss], feed_dict=values)
```

TensorFlow: Neural Net

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.Variable(tf.random_normal((D, H)))
w2 = tf.Variable(tf.random_normal((H, D)))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))
grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])


learning_rate = 1e-5
new_w1 = w1.assign(w1 - learning_rate * grad_w1)
new_w2 = w2.assign(w2 - learning_rate * grad_w2)

with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D),}
    for t in range(50):
        loss_val, = sess.run([loss], feed_dict=values)
```

Run graph once to
initialize w1 and w2

Run many times to train

TensorFlow: Neural Net



Problem: loss not going down! Assign calls not actually being executed!


```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.Variable(tf.random_normal((D, H)))
w2 = tf.Variable(tf.random_normal((H, D)))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))
grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

learning_rate = 1e-5
new_w1 = w1.assign(w1 - learning_rate * grad_w1)
new_w2 = w2.assign(w2 - learning_rate * grad_w2)

with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D),}
    for t in range(50):
        loss_val, = sess.run([loss], feed_dict=values)
```

TensorFlow: Neural Net



Add dummy graph node
that depends on updates

Tell TensorFlow to
compute dummy node

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.Variable(tf.random_normal((D, H)))
w2 = tf.Variable(tf.random_normal((H, D)))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))
grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

learning_rate = 1e-5
new_w1 = w1.assign(w1 - learning_rate * grad_w1)
new_w2 = w2.assign(w2 - learning_rate * grad_w2)
updates = tf.group(new_w1, new_w2)

with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D),}
    losses = []
    for t in range(50):
        loss_val, _ = sess.run([loss, updates],
                             feed_dict=values)
```

TensorFlow: Optimizer

Can use an **optimizer** to
compute gradients and
update weights

Remember to execute the
output of the optimizer!

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.Variable(tf.random_normal((D, H)))
w2 = tf.Variable(tf.random_normal((H, D)))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff * diff, axis=1))
```

```
optimizer = tf.train.GradientDescentOptimizer(1e-5)
updates = optimizer.minimize(loss)
```

```
with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D),}
    losses = []
    for t in range(50):
        loss_val, _ = sess.run([loss, updates],
                              feed_dict=values)
```

TensorFlow: LOSS

Use predefined
common losseses

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.Variable(tf.random_normal((D, H)))
w2 = tf.Variable(tf.random_normal((H, D)))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
loss = tf.losses.mean_squared_error(y_pred, y)

optimizer = tf.train.GradientDescentOptimizer(1e-3)
updates = optimizer.minimize(loss)

with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D),}
    for t in range(50):
        loss_val, _ = sess.run([loss, updates],
                              feed_dict=values)
```

TensorFlow: Layers

tf.layers automatically
sets up weight and
(and bias) for us!

Use He
initializer

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))

init = tf.variance_scaling_initializer(2.0)
h = tf.layers.dense(inputs=x, units=H,
                     activation=tf.nn.relu, kernel_initializer=init)
y_pred = tf.layers.dense(inputs=h, units=D,
                         kernel_initializer=init)

loss = tf.losses.mean_squared_error(y_pred, y)

optimizer = tf.train.GradientDescentOptimizer(1e-0)
updates = optimizer.minimize(loss)

with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D),}
    for t in range(50):
        loss_val, _ = sess.run([loss, updates],
                              feed_dict=values)
```

Keras: High-Level Wrapper

Keras is a layer on top of
TensorFlow, makes common
things easy to do

(Used to be third-party, now
merged into TensorFlow)

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))

model = tf.keras.Sequential()
model.add(tf.keras.layers.Dense(H, input_shape=(D,), activation=tf.nn.relu))
model.add(tf.keras.layers.Dense(D))
y_pred = model(x)
loss = tf.losses.mean_squared_error(y_pred, y)

optimizer = tf.train.GradientDescentOptimizer(1e-0)
updates = optimizer.minimize(loss)

with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D)}
    for t in range(50):
        loss_val, _ = sess.run([loss, updates],
                              feed_dict=values)
```

Keras: High-Level Wrapper

Define model as a sequence of layers

Get output by calling the model

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))

model = tf.keras.Sequential()
model.add(tf.keras.layers.Dense(H, input_shape=(D,), activation=tf.nn.relu))
model.add(tf.keras.layers.Dense(D))
y_pred = model(x)
loss = tf.losses.mean_squared_error(y_pred, y)

optimizer = tf.train.GradientDescentOptimizer(1e-0)
updates = optimizer.minimize(loss)

with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D)}
    for t in range(50):
        loss_val, _ = sess.run([loss, updates],
                              feed_dict=values)
```

Keras: High-Level Wrapper

```
N, D, H = 64, 1000, 100
model = tf.keras.Sequential()
model.add(tf.keras.layers.Dense(H, input_shape=(D,), 
                               activation=tf.nn.relu))
model.add(tf.keras.layers.Dense(D))

model.compile(loss=tf.keras.losses.mean_squared_error,
              optimizer=tf.keras.optimizers.SGD(lr=1e-0))
```

```
x = np.random.randn(N, D)
y = np.random.randn(N, D)
```

Keras can handle the training loop for you!

No sessions or feed_dict

→ `history = model.fit(x, y, epochs=50, batch_size=N)`

TensorFlow: High-Level Wrappers

tf.keras (https://www.tensorflow.org/api_docs/python/tf/keras)

tf.layers (https://www.tensorflow.org/api_docs/python/tf/layers)

TensorFlow: High-Level Wrappers

Keras (<https://keras.io/>)

tf.keras (https://www.tensorflow.org/api_docs/python/tf/keras)

tf.layers (https://www.tensorflow.org/api_docs/python/tf/layers)

TensorFlow: High-Level Wrappers

Keras (<https://keras.io/>)

tf.keras (https://www.tensorflow.org/api_docs/python/tf/keras)

tf.layers (https://www.tensorflow.org/api_docs/python/tf/layers)

tf.estimator (https://www.tensorflow.org/api_docs/python/tf/estimator)

TensorFlow: High-Level Wrappers

Keras (<https://keras.io/>)

Ships with TensorFlow

tf.keras (https://www.tensorflow.org/api_docs/python/tf/keras)

tf.layers (https://www.tensorflow.org/api_docs/python/tf/layers)

tf.estimator (https://www.tensorflow.org/api_docs/python/tf/estimator)

tf.contrib.estimator (https://www.tensorflow.org/api_docs/python/tf/contrib/estimator)

tf.contrib.layers (https://www.tensorflow.org/api_docs/python/tf/contrib/layers)

tf.contrib.slim (<https://github.com/tensorflow/tensorflow/tree/master/tensorflow/contrib/slim>)

tf.contrib.learn (https://www.tensorflow.org/api_docs/python/tf/contrib/learn)

TensorFlow: High-Level Wrappers

Keras (<https://keras.io/>)

Ships with TensorFlow

tf.keras (https://www.tensorflow.org/api_docs/python/tf/keras)

tf.layers (https://www.tensorflow.org/api_docs/python/tf/layers)

tf.estimator (https://www.tensorflow.org/api_docs/python/tf/estimator)

tf.contrib.estimator (https://www.tensorflow.org/api_docs/python/tf/contrib/estimator)

tf.contrib.layers (https://www.tensorflow.org/api_docs/python/tf/contrib/layers)

tf.contrib.slim (<https://github.com/tensorflow/tensorflow/tree/master/tensorflow/contrib/slim>)

~~tf.contrib.learn~~ (https://www.tensorflow.org/api_docs/python/tf/contrib/learn) DEPRECATED

TensorFlow: High-Level Wrappers

Keras (<https://keras.io/>)

Ships with TensorFlow

tf.keras (https://www.tensorflow.org/api_docs/python/tf/keras)

tf.layers (https://www.tensorflow.org/api_docs/python/tf/layers)

tf.estimator (https://www.tensorflow.org/api_docs/python/tf/estimator)

tf.contrib.estimator (https://www.tensorflow.org/api_docs/python/tf/contrib/estimator)

tf.contrib.layers (https://www.tensorflow.org/api_docs/python/tf/contrib/layers)

tf.contrib.slim (<https://github.com/tensorflow/tensorflow/tree/master/tensorflow/contrib/slim>)

tf.contrib.learn (https://www.tensorflow.org/api_docs/python/tf/contrib/learn) DEPRECATED

Sonnet (<https://github.com/deepmind/sonnet>)

By DeepMind

TensorFlow: High-Level Wrappers

Keras (<https://keras.io/>)

Ships with TensorFlow

tf.keras (https://www.tensorflow.org/api_docs/python/tf/keras)

tf.layers (https://www.tensorflow.org/api_docs/python/tf/layers)

tf.estimator (https://www.tensorflow.org/api_docs/python/tf/estimator)

tf.contrib.estimator (https://www.tensorflow.org/api_docs/python/tf/contrib/estimator)

tf.contrib.layers (https://www.tensorflow.org/api_docs/python/tf/contrib/layers)

tf.contrib.slim (<https://github.com/tensorflow/tensorflow/tree/master/tensorflow/contrib/slim>)

tf.contrib.learn (https://www.tensorflow.org/api_docs/python/tf/contrib/learn) DEPRECATED

Sonnet (<https://github.com/deepmind/sonnet>) By DeepMind

TFLearn (<http://tflearn.org/>)


TensorLayer (<http://tensorlayer.readthedocs.io/en/latest/>)

Third-Party

TensorFlow: Pretrained Models


tf.keras: (https://www.tensorflow.org/api_docs/python/tf/keras/applications)

TF-Slim: (<https://github.com/tensorflow/models/tree/master/slim/nets>)




TensorFlow: Tensorboard

Add logging to code to record loss, stats, etc
Run server and get pretty graphs!



TensorFlow: Distributed Version



Split one graph
over multiple
machines!



<https://www.tensorflow.org/deploy/distributed>

TensorFlow: Tensor Processing Units



Google Cloud TPU
= 180 TFLOPs of compute!

TensorFlow: Tensor Processing Units



Google Cloud TPU
= 180 TFLOPs of compute!



NVIDIA Tesla V100
= 125 TFLOPs of compute

TensorFlow: Tensor Processing Units



Google Cloud TPU
= 180 TFLOPs of compute!



NVIDIA Tesla V100
= 125 TFLOPs of compute

NVIDIA Tesla P100 = 11 TFLOPs of compute
GTX 580 = 0.2 TFLOPs

TensorFlow: Tensor Processing Units



Google Cloud TPU
= 180 TFLOPs of compute!



Google Cloud TPU Pod
= 64 Cloud TPUs
= 11.5 PFLOPs of compute!

https://www.tensorflow.org/versions/master/programmers_guide/using_tpu

Static vs Dynamic Graphs

TensorFlow: Build graph once, then run many times (**static**)

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.Variable(tf.random_normal((D, H)))
w2 = tf.Variable(tf.random_normal((H, D)))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))
grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

learning_rate = 1e-5
new_w1 = w1.assign(w1 - learning_rate * grad_w1)
new_w2 = w2.assign(w2 - learning_rate * grad_w2)
updates = tf.group(new_w1, new_w2)

with tf.Session() as sess:
    sess.run(tf.global_variables_initializer())
    values = {x: np.random.randn(N, D),
              y: np.random.randn(N, D)}
    losses = []
    for t in range(50):
        loss_val, _ = sess.run([loss, updates],
                              feed_dict=values)
```

Build graph

Run each iteration

PyTorch: Each forward pass defines a new graph (**dynamic**)

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()


    loss.backward()
```

New graph each iteration

Static vs Dynamic: Optimization

With static graphs,
framework can
optimize the
graph for you
before it runs!

The graph you wrote



Equivalent graph with
fused operations



Static vs Dynamic: Serialization

Static

Once graph is built, can **serialize** it and run it without the code that built the graph!

Dynamic

Graph building and execution are intertwined, so always need to keep code around

Static vs Dynamic: Conditional

$$y = \begin{cases} w_1 * x & \text{if } z > 0 \\ w_2 * x & \text{otherwise} \end{cases}$$

Static vs Dynamic: Conditional

$$y = \begin{cases} w_1 * x & \text{if } z > 0 \\ w_2 * x & \text{otherwise} \end{cases}$$

PyTorch: Normal Python

```
N, D, H = 3, 4, 5

x = torch.randn(N, D, requires_grad=True)
w1 = torch.randn(D, H)
w2 = torch.randn(D, H)

z = 10
if z > 0:
    y = x.mm(w1)
else:
    y = x.mm(w2)
```

Static vs Dynamic: Conditional

$$y = \begin{cases} w_1 * x & \text{if } z > 0 \\ w_2 * x & \text{otherwise} \end{cases}$$

PyTorch: Normal Python

```
N, D, H = 3, 4, 5

x = torch.randn(N, D, requires_grad=True)
w1 = torch.randn(D, H)
w2 = torch.randn(D, H)

z = 10
if z > 0:
    y = x.mm(w1)
else:
    y = x.mm(w2)
```

TensorFlow: Special TF control flow operator!

```
N, D, H = 3, 4, 5
x = tf.placeholder(tf.float32, shape=(N, D))
z = tf.placeholder(tf.float32, shape=None)
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(D, H))


def f1(): return tf.matmul(x, w1)
def f2(): return tf.matmul(x, w2)
y = tf.cond(tf.less(z, 0), f1, f2)

with tf.Session() as sess:
    values = {
        x: np.random.randn(N, D),
        z: 10,
        w1: np.random.randn(D, H),
        w2: np.random.randn(D, H),
    }
    y_val = sess.run(y, feed_dict=values)
```



Static vs Dynamic: Loops

$$y_t = (y_{t-1} + x_t) * w$$




Static vs Dynamic: Loops

$$y_t = (y_{t-1} + x_t) * w$$

PyTorch: Normal Python

```
T, D = 3, 4
y0 = torch.randn(D, requires_grad=True)
x = torch.randn(T, D)
w = torch.randn(D)

y = [y0]
for t in range(T):
    prev_y = y[-1]
    next_y = (prev_y + x[t]) * w
    y.append(next_y)
```



Static vs Dynamic: Loops

$$y_t = (y_{t-1} + x_t) * w$$

PyTorch: Normal Python

```
T, D = 3, 4
y0 = torch.randn(D, requires_grad=True)
x = torch.randn(T, D)
w = torch.randn(D)

y = [y0]
for t in range(T):
    prev_y = y[-1]
    next_y = (prev_y + x[t]) * w
    y.append(next_y)
```

TensorFlow: Special TF control flow

```
T, N, D = 3, 4, 5
x = tf.placeholder(tf.float32, shape=(T, D))
y0 = tf.placeholder(tf.float32, shape=(D,))
w = tf.placeholder(tf.float32, shape=(D,))


def f(prev_y, cur_x):
    return (prev_y + cur_x) * w

y = tf.foldl(f, x, y0)

with tf.Session() as sess:
    values = {
        x: np.random.randn(T, D),
        y0: np.random.randn(D),
        w: np.random.randn(D),
    }
    y_val = sess.run(y, feed_dict=values)
```

Dynamic Graph Applications


- Recurrent networks



Karpathy and Fei-Fei, "Deep Visual-Semantic Alignments for Generating Image Descriptions", CVPR 2015
Figure copyright IEEE, 2015. Reproduced for educational purposes.


Dynamic Graph Applications

- Recurrent networks
- Recursive networks



Dynamic Graph Applications

- Recurrent networks
- Recursive networks
- Modular Networks



Andreas et al, "Neural Module Networks", CVPR 2016

Andreas et al, "Learning to Compose Neural Networks for Question Answering", NAACL 2016

Johnson et al, "Inferring and Executing Programs for Visual Reasoning", ICCV 2017

Figure copyright Justin Johnson, 2017. Reproduced with permission.

Dynamic Graph Applications

- Recurrent networks
- Recursive networks
- Modular Networks
- (Your creative idea here)

PyTorch vs TensorFlow, Static vs Dynamic

PyTorch
Dynamic Graphs

TensorFlow
Static Graphs

PyTorch vs TensorFlow, Static vs Dynamic

PyTorch
Dynamic Graphs

TensorFlow
Static Graphs

Lines are blurring! PyTorch is adding static features, and TensorFlow is adding dynamic features.

Dynamic TensorFlow: Dynamic Batching

TensorFlow Fold make dynamic graphs easier in TensorFlow through **dynamic batching**

Looks et al, "Deep Learning with Dynamic Computation Graphs", ICLR 2017
<https://github.com/tensorflow/fold>

Dynamic TensorFlow: Eager Execution

TensorFlow 1.7 added
eager execution which
allows dynamic graphs!

```
import tensorflow as tf
import tensorflow.contrib.eager as tfe

tf.enable_eager_execution()

N, D = 3, 4
x = tfe.Variable(tf.random_normal((N, D)))
y = tfe.Variable(tf.random_normal((N, D)))
z = tfe.Variable(tf.random_normal((N, D)))
with tfe.GradientTape() as tape:
    a = x * z
    b = a + z
    c = tf.reduce_sum(b)

grad_x, grad_y, grad_z = tape.gradient(c, [x, y, z])
print(grad_x)
```

Dynamic TensorFlow: Eager Execution

Enable eager mode at
the start of the program:
it's a global switch

```
import tensorflow as tf
import tensorflow.contrib.eager as tfe

tf.enable_eager_execution()

N, D = 3, 4
x = tfe.Variable(tf.random_normal((N, D)))
y = tfe.Variable(tf.random_normal((N, D)))
z = tfe.Variable(tf.random_normal((N, D)))
with tfe.GradientTape() as tape:
    a = x * z
    b = a + z
    c = tf.reduce_sum(b)

grad_x, grad_y, grad_z = tape.gradient(c, [x, y, z])
print(grad_x)
```

Dynamic TensorFlow: Eager Execution

These calls to
tf.random_normal produce
concrete values! No need
for placeholders / sessions

Wrap values in a
tfe.Variable if we might
want to compute grads for
them

```
import tensorflow as tf
import tensorflow.contrib.eager as tfe

tf.enable_eager_execution()

N, D = 3, 4
x = tfe.Variable(tf.random_normal((N, D)))
y = tfe.Variable(tf.random_normal((N, D)))
z = tfe.Variable(tf.random_normal((N, D)))

with tfe.GradientTape() as tape:
    a = x * z
    b = a + z
    c = tf.reduce_sum(b)

grad_x, grad_y, grad_z = tape.gradient(c, [x, y, z])
print(grad_x)
```

Dynamic TensorFlow: Eager Execution

```
import tensorflow as tf
import tensorflow.contrib.eager as tfe

tf.enable_eager_execution()

N, D = 3, 4
x = tfe.Variable(tf.random_normal((N, D)))
y = tfe.Variable(tf.random_normal((N, D)))
z = tfe.Variable(tf.random_normal((N, D)))

with tfe.GradientTape() as tape:
    a = x * z
    b = a + z
    c = tf.reduce_sum(b)

grad_x, grad_y, grad_z = tape.gradient(c, [x, y, z])
print(grad_x)
```

Operations scoped under a GradientTape will build a dynamic graph, similar to PyTorch

Dynamic TensorFlow: Eager Execution

```
import tensorflow as tf
import tensorflow.contrib.eager as tfe

tf.enable_eager_execution()

N, D = 3, 4
x = tfe.Variable(tf.random_normal((N, D)))
y = tfe.Variable(tf.random_normal((N, D)))
z = tfe.Variable(tf.random_normal((N, D)))
with tfe.GradientTape() as tape:
    a = x * z
    b = a + z
    c = tf.reduce_sum(b)

grad_x, grad_y, grad_z = tape.gradient(c, [x, y, z])
print(grad_x)
```

Use the tape to compute gradients, like .backward() in PyTorch. The print statement works!

Dynamic TensorFlow: Eager Execution

Eager execution still pretty new, not fully supported in all TensorFlow APIs

Try it out!

```
import tensorflow as tf
import tensorflow.contrib.eager as tfe

tf.enable_eager_execution()

N, D = 3, 4
x = tfe.Variable(tf.random_normal((N, D)))
y = tfe.Variable(tf.random_normal((N, D)))
z = tfe.Variable(tf.random_normal((N, D)))
with tfe.GradientTape() as tape:
    a = x * z
    b = a + z
    c = tf.reduce_sum(b)

grad_x, grad_y, grad_z = tape.gradient(c, [x, y, z])
print(grad_x)
```

Static PyTorch: Caffe2 <https://caffe2.ai/>

- Deep learning framework developed by Facebook
- Static graphs, somewhat similar to TensorFlow
- Core written in C++
- Nice Python interface
- Can train model in Python, then serialize and deploy without Python
- Works on iOS / Android, etc

Static PyTorch: ONNX Support

ONNX is an open-source standard for neural network models

Goal: Make it easy to train a network in one framework, then run it in another framework

Supported by PyTorch, Caffe2, Microsoft CNTK, Apache MXNet

<https://github.com/onnx/onnx>

Static PyTorch: ONNX Support

You can export a PyTorch model to ONNX

Run the graph on a dummy input, and save the graph to a file

Will only work if your model doesn't actually make use of dynamic graph - must build same graph on every forward pass, no loops / conditionals

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

dummy_input = torch.randn(N, D_in)
torch.onnx.export(model, dummy_input,
                  'model.proto',
                  verbose=True)
```

Static PyTorch: ONNX Support

```
graph(%0 : Float(64, 1000)
      %1 : Float(100, 1000)
      %2 : Float(100)
      %3 : Float(10, 100)
      %4 : Float(10)) {
    %5 : Float(64, 100) =
    onnx::Gemm[alpha=1, beta=1, broadcast=1,
    transB=1](%0, %1, %2), scope:
    Sequential/Linear[0]
    %6 : Float(64, 100) = onnx::Relu(%5),
    scope: Sequential/ReLU[1]
    %7 : Float(64, 10) = onnx::Gemm[alpha=1,
    beta=1, broadcast=1, transB=1](%6, %3,
    %4), scope: Sequential/Linear[2]
    return (%7);
}
```

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

dummy_input = torch.randn(N, D_in)
torch.onnx.export(model, dummy_input,
                  'model.proto',
                  verbose=True)
```

After exporting to ONNX, can run the PyTorch model in Caffe2

Static PyTorch: Future???

The screenshot shows a GitHub repository page for `pytorch / pytorch`. The top navigation bar includes links for `Pull requests`, `Issues`, `Marketplace`, and `Explore`. On the right, there are icons for notifications, a plus sign, and a user profile. Below the header, the repository name is displayed along with metrics: `Watch` (763), `Unstar`, `14,502`, `Fork` (3,233). A navigation bar below the repository name offers links to `Code`, `Issues` (829), `Pull requests` (120), `Projects` (3), `Wiki`, and `Insights`.

A specific commit is highlighted:

- Merge caffe2 with pytorch.**
- Branch: `master (#1)` Tag: `v0.4.0`
- Committer: `ezyang` committed 27 days ago
- Parents: 2 parents `1e9a16c + eca84e2`
- Commit hash: `90afedb6e222d430d5c9333ff27adb42aa4bb900`

Below the commit details, it says `Showing 1,983 changed files with 369,779 additions and 20 deletions.` There are `Unified` and `Split` buttons for viewing the diff.

<https://github.com/pytorch/pytorch/commit/90afedb6e222d430d5c9333ff27adb42aa4bb900>

PyTorch vs TensorFlow, Static vs Dynamic

PyTorch

Dynamic Graphs

Static: ONNX, Caffe2

TensorFlow

Static Graphs

Dynamic: Eager

My Advice:

PyTorch is my personal favorite. Clean API, dynamic graphs make it very easy to develop and debug. Can build model in PyTorch then export to Caffe2 with ONNX for production / mobile

TensorFlow is a safe bet for most projects. Not perfect but has huge community, wide usage. Can use same framework for research and production. Probably use a high-level framework. Only choice if you want to run on TPUs.

Next Time: CNN Architecture Case Studies