

Implementation of Programming Languages

– Praktikum WS08/09 –

Software Technology Group,
Fachbereich Informatik, TU-Darmstadt.

(Version 1.4)

Anthony Anjorin

Supervised by Vaidas Gasiunas

15th October 2008

Contents

Introduction	4
1 Contracts between features	5
1.1 The problem	5
1.2 The solution	5
1.2.1 What does <i>abstract</i> and <i>concrete</i> mean?	5
1.2.2 What changes with contracts?	6
1.2.3 Design decisions and fine details	7
1.3 Implementation status	8
1.4 Knowledge base	9
Glossary	10
References	11
Version History	11

Introduction

Context	<p>The goal of the AMPLE¹ project is to identify and develop methodologies to help cope with the challenges that arise when enabling and supporting SPL²s.</p> <p>In this practicum, new concepts and extensions to existing OO³-technologies are to be implemented in the Caesar-J [1] compiler, using the JastAdd [2] framework.</p>
Aim	<p>The aim of this document is threefold: It serves as a reference for the actual implementation, as information and results gleaned from discussions with my supervisor are carefully recorded. In this way nothing important can be lost or “forgotten”.</p> <p>Documenting planned tasks and related complications and expressing solution concepts in my own words, provides a simple means for my supervisor to validate the respective points and avoid misunderstandings and an erroneous implementation.</p> <p>Last but not least, this document serves as an informal documentation of not only what was implemented but also why and reasons for making certain decisions and simplifications. This complements comments in code and will be extremely helpful for anyone trying to get an overview of the implementation.</p>
Scope	<p>This document is neither a complete documentation of parts of the Caesar-J compiler nor an exact or formal description of implemented features.</p> <p>There is furthermore no guarantee that discussed solutions correspond exactly to what is finally implemented.</p>
Structure	<p>Each chapter treats a certain feature to be implemented in the Caesar-J compiler. A glossary on page 10 defines important terms and acronyms used in the document while the bibliography on page 11 lists related references.</p>

¹Aspect-Oriented, Model-Driven, Product Line Engineering

²Software Product Line

³Object-oriented

1 Contracts between features

Families of virtual classes enable feature-oriented programming, whereby each sub-family can provide a further-binding for certain virtual classes and thus implement a single feature. This leads to a decomposition according to features – enabling a flexible means of combining and composing features to realise a *complete* implementation. Numerous sub-families, each implementing a certain feature are combined via multiple-inheritance and mixin-composition.

1.1 The problem

A sub-family can be a provider of a certain feature, a client depending on other sub-families that provide certain features, or both. How can contracts for these different roles be expressed? In OO languages the keyword **abstract** can be used to convey that a class is *incomplete* and thus can not be instantiated.

Using **abstract** alone is however insufficient, as one is unable to differentiate between sub-families that *fulfil their contracts* but are still incomplete as they only implement a single feature, and sub-families that *break their contracts* and are thus incomplete – even w.r.t. the feature they promise to implement. For huge projects with various teams implementing different features, this differentiation is of vital importance.

This problem doesn't occur in OO languages as a similar decomposition in features would have to be realised via multiple interfaces and a multi-level inheritance hierarchy. This solution however, doesn't provide the same ease of composition necessary for supporting SPLs. A solution using composition would be similarly awkward and result in a myriad of interfaces and uses-associations. A further disadvantage of composition is not being able to overwrite certain aspects of an aggregated provider.

1.2 The solution

In the following, a *normal class* is a cclass, that neither contains any classes nor is itself contained in any class.

A *virtual class* is a class that is contained in another class. Virtual classes are different from inner classes as they can have further bindings and can thus be overridden and changed via multiple-inheritance and mixin-composition.

A *family* is a class containing 1 or more virtual classes. A family can itself be a virtual class contained in another family.

A *top-level family* is a family, which is itself not contained in any other family. In other words, a top-level family is at the top of the virtual class include hierarchy. According to this definition a top-level family is not a virtual class.

1.2.1 What does *abstract* and *concrete* mean?

A normal class is declared as being *abstract* when it is not to be instantiated. This is specified with the keyword **abstract**. Abstract normal classes do not have to have abstract methods – instantiating such a class might be forbidden for various semantic reasons. Normal classes with abstract methods on the other hand, must be declared as abstract.

A normal class is regarded as being *concrete* when it is not declared as abstract. Concrete normal classes can be instantiated.

A virtual class is declared as being *abstract* when it is never to be instantiated. Abstract virtual classes do not have to contain abstract methods. Since families can however be used to create member virtual classes via polymorphism, it would be wrong to enforce that virtual classes containing abstract methods have to be themselves abstract. Instead it suffices to demand that for virtual classes with abstract methods, at least one family in the include hierarchy be abstract. This prevents any unsafe instantiation.

A virtual class is therefore *concrete* when it is not abstract. This means concrete virtual classes can contain abstract methods as long as at least one family in the include hierarchy is abstract.

Families that are themselves virtual classes have the same semantic for being *abstract* and *concrete* as virtual classes.

A top-level family however must be *abstract* and thus can not be instantiated, if it contains any abstract members – virtual classes or methods – either directly or in member virtual classes.

A *concrete* top-level family is not abstract and can be instantiated.

In summary *abstract* means “can not be instantiated” while *concrete* means “can be instantiated”.

1.2.2 What changes with contracts?

In the following, the keywords **abstract** and **requires** as well as the terms *complete*, *incomplete* and *contract* are defined and used to differentiate between client-contracts and provider-contracts.

Complete should mean “can be instantiated”.

Incomplete should mean not complete and thus “can not be instantiated”.

A *contract* of a class constitutes all inherited abstract members that must be implemented for the class to be complete.

Abstract should mean “does not have to fulfil its contract” or “does not have a contract”. Abstract classes are declared as such using the keyword **abstract** and are per definition incomplete.

Concrete and thus not abstract should mean “fulfils its contract”. Concrete classes do not have to be complete.

A class can act as a client by *requiring* a part of its contract. Abstract methods inherited via a **requires** as opposed to an **extends** do not need to be implemented for a class to be concrete.

A class can act as a provider by inheriting a part of its contract via **extends**. These methods must be implemented for the class to be concrete.

A normal class is complete when it is concrete and has no requirements.

A top-level family is complete when it is concrete and has no requirements.

Presently, requirements are only allowed for top-level families and of course normal classes. Virtual classes and families that are virtual classes *cannot* have requirements and are thus complete when they are concrete (same as without introducing **requires** keyword).

In the future, allowing requirements for virtual classes shall be considered.

Inheritance relationships of superclasses are propagated as follows:

- If A **extends** B and B **extends** C, then A **extends** C. B's provider-contract is defined by C. B can fulfil this contract completely or partially and even extend it by new abstract methods. As A fulfils the provider-contract specified by B it obviously fulfils B's contract as well.
- If A **extends** B and B **requires** C, then A **requires** C. This means A fulfils the provider-contract specified by B. B's client-contract does not have to be fulfilled and thus all requirements are inherited.
- If A **requires** B and B **requires** C, then A **requires** C. B's client-contract is inherited...
- If A **requires** B and B **extends** C, then A **requires** C. B fulfils the provider-contract defined by C. However, since B specifies A's client-contract, A doesn't provide an implementation and thus requires B which of course entails requiring at least C and possibly more.

1.2.3 Design decisions and fine details

The following decisions were made while implementing. Reasons and arguments are briefly presented and alternative solutions discussed.

Redundant requirements:

A requirement is considered redundant if it is already part of the *direct* provider contract of a class. This is the case is when a class requires and extends the same class:

```
Class A extends B requires B { ... }
```

Although senseless, redundant requirements are allowed and are simply treated as requirements that happen to be fulfilled. This means abstract methods inherited by a concrete class via **extends** are *always* to be implemented, even if the same methods happen to be required as well.

An improvement would be to issue a warning when a requirement is redundant.

Implementing requirements directly:

Implementing required methods might seem contradictory but actually makes sense: A class may wish to perform certain tasks before and after calling the required core functionality supplied by another class in a complete product. This is semantically similar to an around advice of an aspect. Unfortunately, enabling this with the current implementation of mixin-composition is problematic: Calls to **super** would result in requests to the required abstract contract classes and not to the appropriate providers.

Implementing this feature is therefore not a trivial task and is for the time being postponed – a direct implementation of requirements is currently disallowed to avoid potential problems.

Required methods in virtual classes:

Although only top-level families or normal classes can have requirements, the required methods can of course actually be present in enclosed virtual classes (family members).

Determining if a method is required or not can be a little tricky and involves the so called [ETL](#)⁴: To decide if a certain method of an arbitrarily nested virtual class is required, the enclosing top-level family is determined. All enclosed methods in the required classes of the [ETL](#), either as direct members or as member methods of an arbitrarily nested family member, are then compared with the current method. A match means the method is required and doesn't need to be implemented!

Formal definition of completeness:

The check for completeness is based on the following definition:

⁴Enclosing Top Level

- All concrete (not declared as abstract) classes implement all inherited abstract methods.
- Provides and [requires] are not symmetric as cyclic inheritance is disallowed.
- All classes are either normal classes or top-level families.

$$\frac{[abstract] \text{ class } A \text{ extends } B \in P}{A \langle extends \rangle B} \quad (1)$$

$$\frac{\neg(A \text{ abstract}), A \langle extends \rangle B}{A \text{ provides } B} \quad (2)$$

$$\frac{A \langle extends \rangle B, B \text{ provides } C}{A \text{ provides } C} \quad (3)$$

$$\frac{[abstract] \text{ class } A \text{ requires } B \in P}{A \langle requires \rangle B} \quad (4)$$

$$\frac{A \langle extends \rangle B}{A \text{ subtypeof } B} \quad (5)$$

$$\frac{A \langle requires \rangle B}{A \text{ subtypeof } B} \quad (6)$$

$$\frac{A \langle extends \rangle B, B \text{ subtypeof } C}{A \text{ subtypeof } C} \quad (7)$$

$$\frac{A \langle requires \rangle B, B \text{ subtypeof } C}{A \text{ subtypeof } C} \quad (8)$$

$$\frac{A \langle requires \rangle B}{A [requires] B} \quad (9)$$

$$\frac{A \langle requires \rangle B, B \text{ subtypeof } C}{A [requires] C} \quad (10)$$

$$\frac{A \langle extends \rangle B, B [requires] C}{A [requires] C} \quad (11)$$

$$\frac{\neg(A \text{ abstract}), \forall B : A [requires] B \Rightarrow A \text{ provides } B}{\text{complete } A} \quad (12)$$

1.3 Implementation status

- 16.09.08 The first step is to extend the parser to recognise **requires** as a keyword. This should serve as a small task to get used to the testing framework and the general syntax and format of .jrag and .ast files.
- 23.09.08 Implemented parsing of **requires**.
- 23.09.08 The next step is to extend or overwrite the methods that determine the complete list of superclasses - these should include all required classes. When this is working and has been tested, existing type-checks have to be extended to implement the extra semantics of requirements. A further step is then to implement the transformation to valid java and if necessary byte-code.

24.09.08 Implemented adding required classes to list of superclasses. The next step is now to extend or change checks in `ASTNode::CollectErrors(...)`. Changes should be test-driven and take possible rewrites into consideration.

A tentative plan:

1. Change checks to allow concrete but incomplete classes (successful compilation).
2. Bytecode of incomplete classes should nonetheless contain abstract flag (necessary for valid bytecode).
3. Check to disallow requirements for virtual classes.
4. Check that only complete classes are instantiated with appropriate and comprehensible error message.
5. Propagation of requires relationship from super to subclasses.

30.09.08 Concrete but incomplete classes now compile. Essentially removed required methods from the list of unimplemented methods. Required methods do not need to be implemented and should thus not be regarded as being unimplemented.

01.10.08 Concrete, incomplete classes now retain their abstract flag in byte-code. This is unfortunately not testable as an automated junit test, since the class-loader doesn't mind loading "invalid" byte-code containing classes with abstract methods but without a corresponding abstract flag. Therefore, manual tests were carried out to ensure that classes with requirements are now abstract classes in byte-code.

02.10.08 Instantiation of incomplete classes (classes with requirements) is now disallowed.

02.10.08 Requirements for virtual classes are now disallowed.

04.10.08 Requirements are now propagated. This has to be tested further...

12.10.08 Improved implementation of completeness check. Defined completeness formally. Implemented handling of redundant requirements. Forbid direct implementation of requirements.

14.10.08 Some regression tests are failing and have to be investigated. Allowing java interfaces as requirements proves to be quite challenging – have to decide if this is worth the extra complexity.

1.4 Knowledge base

- List of requirements implemented to be after extends and implements.
- Number of combinations for instantiation in parser grows exponentially with new keywords! Adding a further keyword might require refactoring and a solution to cope with this.
- Syntactic tests are not possible with current test framework - compilation always fails instead of checking if a specific error was expected. Test-framework would have to be extended to support this.
- Possible tests are: `compile`, `compile-run` with tests in a `test` block and `compile-check-error` with a `Test` class.
- Logging can be enabled in `test.properties`
- Synthesised attributes are to be specified in all subclasses – this enables an upward flow of information in the AST.
- Inherited attributes are to be specified in parent-nodes – this enables a downward flow of information in the AST.

Glossary

AMPLE Aspect-Oriented, Model-Driven, Product Line Engineering

SPL Software Product Line

OO Object-oriented

ETL Enclosing Top Level

References

- [1] I. Aracic, V. Gasiunas, M. Mezini and K.Ostermann:
Overview of CaesarJ
- [2] G. Hedin, E. Magnusson:
The JastAdd system - an aspect-oriented compiler construction system,
Science of Computer Programming 47 (2003) 37-58, Elsevier.

Version History

Version	Date	Changes
0.1	15.09.2008	Created document.
1.0	22.09.2008	Reduced scope of requires to only top-level families.
1.1	23.09.2008	Added next steps for implementation.
1.2	24.09.2008	Implemented determining list of superclasses, added concrete plan for next steps.
1.3	30.09.2008	Implemented concrete but incomplete classes.
1.4	15.10.2008	Added formal definition of completeness.