


# Chapter 8: Memory Management





# Background

- Program must be brought into memory and placed within a process for it to be run
- **Input queue** – collection of processes on the disk that are waiting to be brought into memory to run the program






# Memory-Management Unit (MMU)

- Hardware device that maps virtual to physical address
- In MMU scheme, the value in the relocation register is added to every address generated by a user process at the time it is sent to memory
- The user program deals with *logical* addresses; it never sees the *real* physical addresses





# Dynamic relocation using a relocation register






# Swapping

- A process can be swapped temporarily out of memory to a backing store, and then brought back into memory for continued execution
- **Backing store** – fast disk large enough to accommodate copies of all memory images for all users
- Major part of swap time is transfer time; total transfer time is directly proportional to the amount of memory swapped
- Modified versions of swapping are found on many systems (i.e., UNIX, Linux, and Windows)





# Schematic View of Swapping






# Contiguous Allocation

- Main memory usually into two partitions:
  - Resident operating system, usually held in low memory with interrupt vector
  - User processes then held in high memory
  
- Single-partition allocation
  - Relocation-register scheme used to protect user processes from each other, and from changing operating-system code and data
  - Relocation register contains value of smallest physical address; limit register contains range of logical addresses – each logical address must be less than the limit register






# A base and a limit register define a logical address space








# HW address protection with base and limit registers





# Contiguous Allocation (Cont.)

- Multiple-partition allocation
  - *Hole* – block of available memory; holes of various size are scattered throughout memory
  - When a process arrives, it is allocated memory from a hole large enough to accommodate it
  - Operating system maintains information about:
    - a) allocated partitions
    - b) free partitions (hole)





# Dynamic Storage-Allocation Problem

How to satisfy a request of size  $n$  from a list of free holes

- **First-fit:** Allocate the *first* hole that is big enough
- **Best-fit:** Allocate the *smallest* hole that is big enough; must search entire list, unless ordered by size. Produces the smallest leftover hole.
- **Worst-fit:** Allocate the *largest* hole; must also search entire list. Produces the largest leftover hole.

First-fit and best-fit better than worst-fit in terms of speed and storage utilization





# Fragmentation

- **External Fragmentation** – total memory space exists to satisfy a request, but it is not contiguous
- **Internal Fragmentation** – allocated memory may be slightly larger than requested memory; this size difference is memory internal to a partition, but not being used





# Paging

- Logical address space of a process can be noncontiguous; process is allocated physical memory whenever the latter is available
- Divide physical memory into fixed-sized blocks called **frames** (size is power of 2, between 512 bytes and 8192 bytes)
- Divide logical memory into blocks of same size called **pages**.
- Keep track of all free frames
- To run a program of size  $n$  pages, need to find  $n$  free frames and load program
- Set up a page table to translate logical to physical addresses
- Internal fragmentation






# Address Translation Scheme

- Address generated by CPU is divided into:
  - *Page number ( $p$ )* – used as an index into a *page table* which contains base address of each page in physical memory
  - *Page offset ( $d$ )* – combined with base address to define the physical memory address that is sent to the memory unit






# Address Translation Architecture






# Paging Example







# Paging Example





# Free Frames

