

Nutrimetabolomics:
Biomarker Discover,
Data Quality Control,
Bioinformatics Tools
and Computing Hardware

Tu Hu¹

Sep, 2019

¹Supervised by Lars Ove Dragsted and Gözde Gürdeniz

Contents

1	A Mini-review on Biomarkers of Whole Grain Barley and Whole Grain Wheat Intake	4
2	Discovering Barley Intake Biomarkers in Urine by UPLC-MS Based Untargeted Metabolomics	5
3	Barley Intake Biomarker: Compound Identification and Structure Elucidation	6
3.1	Abstract	6
3.2	Introduction	6
3.2.1	Phytosterol and Fragmentation Behaviour	6
3.3	Materials and methods	6
3.3.1	Chemicals	6
3.3.2	Apparatus	6
3.3.3	UPLC-MS/MS analysis of Sitostanol	7
4	Discovering Novel Intake Biomarkers of Whole Grain Wheat Intake by LC-MS Based Untargeted Metabolomics	8
5	Data Quality Control (QC) and Quality Assurance (QA) in LC-MS Based Untargeted Metabolomics	9
5.1	Introduction	1
6	Several R Functions Facilitating LC-MS Based Metabolomics Data Analysis Workflow	2
6.1	abstract	2
6.2	"Tidy" High-throughout Analysis Data, Exemplified by RNA sequencing data	2
6.3	m2r	2
6.4	plot_excretion	2
6.5	plot_intervention	2
7	Implementing A Streamlined Metabolomics Data Analysis Workflow (EZMS) Based on R Programming Language	3

8	Using a Budgeted Device to Compute High-throughout Metabolomics	
	Data	4
8.1	Abstract	4
8.2	Introduction	5

Acronyms

GC-MS Gas Chromatography-Mass Spectrometry. 4

LC-MS Liquid Chromatography-Mass Spectrometry. 4

Chapter 1

A Mini-review on Biomarkers of Whole Grain Barley and Whole Grain Wheat Intake

Chapter 2

Discovering Barley Intake Biomarkers in Urine by UPLC-MS Based Untargeted Metabolomics

Chapter 3

Barley Intake Biomarker: Compound Identification and Structure Elucidation

3.1 Abstract

3.2 Introduction

3.2.1 Phytosterol and Fragmentation Behaviour

Phytosterols ubiquitously occur in plant-based food[sterolmsms]. They were claimed to have health beneficial effects, such as lowering cholesterol. They occur in food as free sterols (FS), steryl esters (SE), and glycosylated conjugates comprised of steryl glucosides (SG) and acylated steryl glucosides (ASG).

Specific sterol profiles characteristic to certain plant families have been identified showing that a broad range of minor sterols occurs as free sterols or glycosylated conjugates

3.3 Materials and methods

3.3.1 Chemicals

Sitostanol standard (CAS Number 83-45-4, Avanti Polar Lipids Inc., USA) was transported and stored in -20 °C. Ethanol

3.3.2 Apparatus

UPLC-MS system (column: C18,) QTOF (VION, Waters, Milford, USA)

3.3.3 UPLC-MS/MS analysis of Sitostanol

[doi:10.1021/jf501509m] Mobile phase A: H₂O Mobile phase B: Methanol

Binary methods developed and optimized

Analysis methods referred[sterolmsms]. Sitostanol stock solution (1 mg/mL) was prepared in 100% ethanol. Further, stock solution was diluted by methanol, with the concentration of 0.02 mg/mL.

ESI positive mode was used to ionize.

Chapter 4

Discovering Novel Intake Biomarkers of Whole Grain Wheat Intake by LC-MS Based Untargeted Metabolomics

Chapter 5

Data Quality Control (QC) and Quality Assurance (QA) in LC-MS Based Untargeted Metabolomics

Abstract

This is an abstract

Keywords:

5.1 Introduction

Chapter 6

Several R Functions Facilitating LC-MS Based Metabolomics Data Analysis Workflow

6.1 abstract

I would like to test whether it's possible to input an abstract here.,

6.2 "Tidy" High-throughout Analysis Data, Ex- amplified by RNA sequencing data

6.3 m2r

6.4 plot_excretion

6.5 plot_intervention

Chapter 7

Implementing A Streamlined Metabolomics Data Analysis Workflow (EZMS) Based on R Programming Language

Chapter 8

Using a Budgeted Device to Compute High-throughout Metabolomics Data

8.1 Abstract

High-throughout metabolomics data is characterized as high computing and storage resource demanding.

How to compute the data locally (without sending it to a high-performance server) with a budgeted device could be an interesting topic to explore. Because this would provide possibilities to protect privacies in home-appliance or fulfil the real-time analysis tasks in some extreme conditions (such as in polar region or some areas with poor Internet connectivity)

why do i do this? because in the future, metabolomics analysis could become smart-home appliance, such as smart toilet or smart mirror. people can get their metabolome examined daily in their home. such a good vision raised several problems. data privacy problem and cost. because metabolome is considered as personal privacy. therefore, leak these privacy could result in bad results. however, if computed locally, whether it's possible to control the cost.

In this study, we simulated a computing task.

Not only limited to human metabolome for risk analysis. it could also be applied in the fridge for example, to detect microorganisms' characteristic metabolome.

in less developed countries, or in portable devices, transmitting the data could be very expensive (via satellite for example, in polar areas), therefore, computing such a dataset whether it's possible.

8.2 Introduction

Potential Use environment

hello