

Lab Practice Sheet 1

CS G526: Advanced Algorithms & Complexity

Instructor: Tulasimohan Molli

Date: 2026-09-06

! Evaluation Instructions for Students

- **Practice all 8 problems below.**
- In the next lab session, **one question will be chosen at random** for on-the-spot coding and evaluation.
- Your code will be evaluated by running it against automated test cases.
- You may use **Python; C++ and Java.**

Q1: The Student Merit System

Description: Define a struct/class/object for **Student** with fields: **ID** (integer), **Name** (string), and **Marks** (3 subject scores). Write a program to:

1. Read details for N students.
2. Calculate the average marks for each student.
3. Print a “Merit List” of students whose average score is strictly above 75% in the order they appear in the input.
4. Identify and print the Topper (the student with the highest average score). If multiple students share the same highest average score, choose the one whose name comes first in lexicographical (dictionary) order.

• Input Format:

- Line 1: An integer N , the number of students.
- Next N lines: Each line contains an integer **ID**, a string **Name**, and 3 space-separated integers representing marks in three subjects.

• Output Format:

- First print **Merit List:** followed by lines of the form **ID Name (Avg: XX.XX)** for every student with average marks > 75.00 .
- Then print **Topper: Name** indicating the student with the highest average score (breaking ties in favor of lexicographically smaller name).

i Sample Input

```
2
101 Alice 80 90 85
102 Bob 60 50 55
```

i Sample Output

```
Merit List:
101 Alice (Avg: 85.00)
Topper: Alice
```

Q2: Matrix Multiplication

Description: Write a program to multiply two matrices A and B .

1. Read matrix A of dimensions $R_1 \times C_1$.
2. Read matrix B of dimensions $R_2 \times C_2$.
3. If multiplication is not possible ($C_1 \neq R_2$), output **Not Possible**.
4. Otherwise, compute and print the product matrix $C = A \times B$.

- **Input Format:**

- Line 1: Two space-separated integers R_1 and C_1 , representing dimensions of matrix A .
- Next R_1 lines: Each line contains C_1 space-separated integers representing the elements of matrix A .
- Next line: Two space-separated integers R_2 and C_2 , representing dimensions of matrix B .
- Next R_2 lines: Each line contains C_2 space-separated integers representing the elements of matrix B .

- **Output Format:**

- If $C_1 \neq R_2$, output a single line **Not Possible**.
- Otherwise, print R_1 lines, each containing C_2 space-separated integers representing the resulting product matrix $C = A \times B$.

i Sample Input 1

```
2 2
1 2
3 4
2 2
1 0
0 1
```

i Sample Output 1

```
1 2
3 4
```

i Sample Input 2

```
2 3
1 2 3
4 5 6
2 2
1 0
0 1
```

i Sample Output 2

```
Not Possible
```

Q3: Merge Two Sorted Arrays

Description: Given two sorted arrays A of size N_1 and B of size N_2 , merge them into a single sorted sequence in non-decreasing order using a linear two-pointer scan.

- **Input Format:**

- Line 1: An integer N_1 , the size of array A .
- Line 2: N_1 space-separated sorted integers representing array A .
- Line 3: An integer N_2 , the size of array B .
- Line 4: N_2 space-separated sorted integers representing array B .

- **Output Format:**

- A single line containing $N_1 + N_2$ space-separated integers representing the merged sorted sequence.

i Sample Input

```
3
1 3 5
3
2 4 6
```

i Sample Output

```
1 2 3 4 5 6
```

Q4: String Compression

Description: Given a string of lowercase alphabetic characters, compress consecutive repeating characters using run-length encoding. For example, consecutive occurrences of character `c` repeated k times should be represented as `c` followed by k .

- **Input Format:**

- A single line containing a string consisting of lowercase English letters.

- **Output Format:**

- A single line containing the compressed string.

i Sample Input

aaabbc

i Sample Output

a3b2c1

Q5: The Array Rotator

Description: Given an array of N integers, rotate the array by K positions.

- Direction $D = 0$ means **Left Rotation**.
- Direction $D = 1$ means **Right Rotation**.
- **Input Format:**
 - Line 1: An integer N , the size of the array.
 - Line 2: N space-separated integers representing the array.
 - Line 3: An integer $D \in \{0, 1\}$, where 0 indicates Left Rotation and 1 indicates Right Rotation.
 - Line 4: An integer K , the number of positions to rotate.
- **Output Format:**
 - A single line containing N space-separated integers representing the rotated array.

Sample Input

```
5
1 2 3 4 5
0
1
```

Sample Output

```
2 3 4 5 1
```

Q6: Segregate Even and Odd Values

Description: Given a sequence of N integers, rearrange the sequence so that all **even** numbers appear before all **odd** numbers, while strictly preserving their relative order from the original sequence (stable partition).

- **Input Format:**

- Line 1: An integer N , the number of elements.
- Line 2: N space-separated integers representing the sequence.

- **Output Format:**

- A single line containing N space-separated integers, with all even numbers listed first in original relative order, followed by all odd numbers in original relative order.

Sample Input

```
7
17 15 8 12 10 5 4
```

Sample Output

```
8 12 10 4 17 15 5
```

Q7: Insert After Pairs (Sum & Skip)

Description: Given a sequence of N integers, process the elements pairwise from left to right. After every pair of consecutive elements, insert a new element equal to their sum. If an odd element is left at the end without a pair, leave it as is.

- **Input Format:**

- Line 1: An integer N , the number of elements.
- Line 2: N space-separated integers representing the sequence.

- **Output Format:**

- A single line containing space-separated integers representing the modified sequence with sum elements inserted after each pair.

i Sample Input

```
4
2 4 5 3
```

i Sample Output

```
2 4 6 5 3 8
```

Q8: Move All Occurrences of Value X to the End

Description: Given a sequence of N integers and a target value X , rearrange the sequence such that all occurrences of X are moved to the end of the sequence, while the relative order of all other elements remains unchanged.

- **Input Format:**

- Line 1: An integer N , the number of elements.
- Line 2: N space-separated integers representing the sequence.
- Line 3: An integer X , the target value to be moved to the end.

- **Output Format:**

- A single line containing N space-separated integers representing the rearranged sequence.

i Sample Input

```
7
1 2 3 2 4 2 5
2
```

i Sample Output

```
1 3 4 5 2 2 2
```