


Lecture Notes on  
Pattern Recognition

Session 05(A): Non-Parametric Estimation (I)

Gang Li  
School of Information Technology  
Deakin University, VIC 3125, Australia

**TULIP** Team for Universal Learning and Intelligent Processing



Non-Parametric Estimation

- Non-Parameter Estimation
- Histogram

**TULIP** Team for Universal Learning and Intelligent Processing

Motivation

- Classical parametric densities are unimodal.
  - Many practical problems involve multimodal densities.
    - Example: model probability p(x,y) for a raindrop to hit a location(x,y) in Australia

• Common parametric forms rarely fit the densities actually encountered in practice.

**TULIP** Team for Universal Learning and Intelligent Processing

Non-Parameter Estimation

- Based on a set of observations
  - Estimate class-conditional densities

$$p(\mathbf{x} | \omega_i)$$

- Estimate posterior probabilities

$$P(\omega_i | \mathbf{x})$$

**TULIP** Team for Universal Learning and Intelligent Processing


Non-Parameter Estimation

- Task: model the likelihood function without making any assumption about its functional form.
  - Need to deal with the choice of smoothing parameters that govern the smoothness of the estimated density.
- Three main types of methods:
  - Histograms
  - Parzen Window (Kernels)
  - K-nearest neighbors

**TULIP** Team for Universal Learning and Intelligent Processing

## Histogram

- Suppose each data point  $\mathbf{x}$  is represented by an  $n$ -dimensional feature vector  $(x_1, x_2, \dots, x_n)$ .
- The histogram is obtained by dividing each  $x_i$ -axis into a number of bins  $M$  and approximating the density at each value of  $x_i$  by the **fraction** of the points that fall inside the corresponding bin.



FLIP: Pattern Recognition (G. Li)

7




TULIP Team for Universal Learning and Intelligent Processing



## Histogram

- The number of bins  $M$  (or bin size) is acting as a **smoothing** parameter.
  - If bin width is small (big  $M$ ), then the estimated density is very spiky (i.e., noisy).
  - If bin width is large (small  $M$ ), then the true structure of the density is smoothed out.
- In practice, we need to find an optimal value for  $M$  that compromises between these two issues.



FLIP: Pattern Recognition (G. Li)

8



TULIP Team for Universal Learning and Intelligent Processing



## Histogram

### Pros

- Once the histogram has been constructed, the data is not needed anymore
  - i.e., memory efficient
- Retain only info on the size and location of histogram bins.
- Histogram can be built sequentially
  - i.e., consider the data one at a time and then discard

### Cons

- The estimated density is not smooth and has discontinuities at the boundaries of the histogram bins.
- Histograms do **not** generalize well in high dimensions.
  - Consider a  $d$ -dimensional feature space; if we divide each variable in  $M$  intervals, we will end up with  $M^d$  bins.
  - A huge number of examples would be required to obtain good estimates (i.e., otherwise, most bins would be empty and the density will be approximated by zero).



TULIP Team for Universal Learning and Intelligent Processing

FLIP: Pattern Recognition (G. Li)

9



## Density Estimation

- Two Approximations
- Density Estimation



FLIP: Pattern Recognition (G. Li)

10




TULIP Team for Universal Learning and Intelligent Processing

## Density Estimation

- Approximation 1:** Assume  $p(\mathbf{x})$  is continuous &  $R$  is small

$$P(\mathbf{X} \in R) = \int_R p(\mathbf{x}') d\mathbf{x}' = p(\mathbf{x}) \int_R d\mathbf{x}' \\ = p(\mathbf{x})V_R = P_R$$

 $n$  samples

- Approximation 2:** Randomly take  $n$  samples, let  $K$  denote the number of samples inside  $R$ .

$$\Rightarrow K \sim B(n, P_R) \\ P(K=k) = \binom{n}{k} P_R^k (1-P_R)^{n-k}$$



TULIP Team for Universal Learning and Intelligent Processing

FLIP: Pattern Recognition (G. Li)

11



## Density Estimation

- Approximation 1:** Assume  $p(\mathbf{x})$  is continuous & small

$$P(\mathbf{X} \in R) = \int_R p(\mathbf{x}') d\mathbf{x}' = p(\mathbf{x}) \int_R d\mathbf{x}' \\ = p(\mathbf{x})V_R = P_R$$

- Approximation 2:** Randomly take  $n$  samples, let  $K$  denote the number of samples inside  $R$ .

$$\begin{aligned} - E[k] &= nP_R \\ - E[k/n] &= P_R \\ - Var[k/n] &= E[(k/n - P_R)^2] = \frac{P_R(1-P_R)}{n} \end{aligned}$$

$n$  samples




FLIP: Pattern Recognition (G. Li)

12



$$E[K/n] = P_R$$



FLIP: Pattern Recognition (G. Li)

12

## Density Estimation

- Combining these two approximations we have:

$$p(\mathbf{x}) \approx \frac{k_{\mathbf{x}} / n}{V_{\mathbf{x}}}$$

- The above approximation is based on **contradictory** assumptions:
  - R is relatively **small** so that  $p(\mathbf{x})$  is approximately constant inside the integration region – **Approximation 1**
  - R is relatively **large** (i.e., it contains many samples so that  $P_k$  is sharply peaked) – **Approximation 2**
- We need to choose an optimum R in practice ...



FLIP: Pattern Recognition (G. Li)

13

## Notation

- Suppose we form regions  $R_1, R_2, \dots$  containing  $\mathbf{x}$ .
- $R_i$  contains 1 sample,  $R_2$  contains 2 samples, etc.
- $R_i$  has volume  $V_i$  and contains  $k_i$  samples.
- The  $n$ -th estimate  $p_n(\mathbf{x})$  of  $p(\mathbf{x})$  is given by:

$$p_n(\mathbf{x}) \equiv \frac{k_n / n}{V_n}$$



FLIP: Pattern Recognition (G. Li)

14

## Main conditions for convergence

- The following conditions must be satisfied in order for  $p_n(\mathbf{x})$  to converge to  $p(\mathbf{x})$ :

$$p_n(\mathbf{x}) = \frac{k_n / n}{V_n} \quad \begin{array}{l} \lim_{n \rightarrow \infty} V_n = 0 \\ \lim_{n \rightarrow \infty} k_n = \infty \\ \lim_{n \rightarrow \infty} k_n / n = 0 \end{array} \quad \begin{array}{l} \bullet \text{ Approximation 1} \\ \bullet \text{ Approximation 2} \\ \bullet \text{ to allow } p_n(\mathbf{x}) \text{ to converge} \end{array}$$




FLIP: Pattern Recognition (G. Li)

15

## Density Estimation

- How this process can be controlled?
  - choose the optimum values for  $V_n$  and  $k_n$
- Two leading approaches:
  - Fix the volume  $V_n$  and determine  $k_n$  from the data
    - Parzen Windows (Kernel-based Method)**
  - Control  $k_n$ 
    - KNN**



FLIP: Pattern Recognition (G. Li)

16

## Parzen Windows



- Window Function
- Parzen Window Estimation
- Convergence




FLIP: Pattern Recognition (G. Li)

17

## Window Function

$$\phi(\mathbf{u}) = \begin{cases} 1 & |u_j| \leq 1/2, \quad j = 1, 2, \dots, d \\ 0 & \text{otherwise} \end{cases}$$



FLIP: Pattern Recognition (G. Li)


18

## Window Function

$$\phi(\mathbf{u}) = \begin{cases} 1 & |u_j| \leq 1/2, \quad j = 1, 2, \dots, d \\ 0 & \text{otherwise} \end{cases}$$

$$\int \phi(\mathbf{u}) d\mathbf{u} = 1$$

$$\phi\left(\frac{\mathbf{x}}{h_n}\right) = \begin{cases} 1 & |x_j| \leq h_n/2 \\ 0 & \text{otherwise} \end{cases}$$




## Window Function

$$\phi(\mathbf{u}) = \begin{cases} 1 & |u_j| \leq 1/2, \quad j = 1, 2, \dots, d \\ 0 & \text{otherwise} \end{cases}$$

$$\int \phi(\mathbf{u}) d\mathbf{u} = 1$$

$$\phi\left(\frac{\mathbf{x}}{h_n}\right) = \begin{cases} 1 & |x_j| \leq h_n/2 \\ 0 & \text{otherwise} \end{cases}$$

$$\phi\left(\frac{\mathbf{x}-\mathbf{x}'}{h_n}\right) = \begin{cases} 1 & |x_j - x'_j| \leq h_n/2 \\ 0 & \text{otherwise} \end{cases}$$



## Parzen-Window Estimation


$$\mathcal{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n\}$$

$$\int \phi(\mathbf{u}) d\mathbf{u} = 1$$

**k<sub>n</sub>**: # samples inside hypercube centered at **x**.

$$k_n = \sum_{i=1}^n \phi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right) \quad V_n = h_n^d$$

$$\phi\left(\frac{\mathbf{x} - \mathbf{x}'}{h_n}\right) = \begin{cases} 1 & |x_j - x'_j| \leq h_n/2 \\ 0 & \text{otherwise} \end{cases}$$



### Parzen Window Estimation

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \phi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

## Parzen-Window Estimation

The density estimate is a **superposition** of kernel functions and the samples  $\mathbf{x}_i$ .


- $\phi(\mathbf{u})$  interpolates the density between samples.
- Each  $\mathbf{x}_i$  contributes to the estimate based on its distance from  $\mathbf{x}$ .

### Parzen Window Estimation

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \phi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

$$\int \phi(\mathbf{u}) d\mathbf{u} = 1$$

$$\phi\left(\frac{\mathbf{x} - \mathbf{x}'}{h_n}\right) = \begin{cases} 1 & |x_j - x'_j| \leq h_n/2 \\ 0 & \text{otherwise} \end{cases}$$




## Parzen-Window Estimation

Prove that  $\int p_n(\mathbf{x}) d\mathbf{x} = 1$

$$\int \phi(\mathbf{u}) d\mathbf{u} = 1$$

$$\begin{aligned} & \int \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \phi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right) d\mathbf{x} \\ &= \frac{1}{n} \sum_{i=1}^n \int \frac{1}{V_n} \phi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right) d\mathbf{x} \quad \text{Set } \mathbf{x}/h_n = \mathbf{u}. \\ &= \frac{1}{n} \sum_{i=1}^n \int \phi(\mathbf{u}) d\mathbf{u} = \frac{1}{n} n = 1 \end{aligned}$$

$$\phi\left(\frac{\mathbf{x} - \mathbf{x}'}{h_n}\right) = \begin{cases} 1 & |x_j - x'_j| \leq h_n/2 \\ 0 & \text{otherwise} \end{cases}$$



## Parzen-Window Estimation

### Parzen-Window


– The window is **not** necessary a hypercube.

– **h<sub>n</sub>** is an important parameter.

- It depends on sample size.
- As  $h_n \rightarrow 0$ ,  $\delta_n(\mathbf{x})$  is a *Dirac delta function*.

$$\int \phi(\mathbf{u}) d\mathbf{u} = 1$$

$$\phi\left(\frac{\mathbf{x} - \mathbf{x}'}{h_n}\right) = \begin{cases} 1 & |x_j - x'_j| \leq h_n/2 \\ 0 & \text{otherwise} \end{cases}$$



## Parzen-Window Estimation

- $\delta_n(\mathbf{x})$  as a function of  $h_n$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 25

## Parzen-Window Estimation

- $p_n(\mathbf{x})$  as a function of  $h_n$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 26

## Parzen-Window Estimation

- Expected Value/Variance of  $p_n(\mathbf{x})$
- The expected estimates approaches  $p(\mathbf{x})$  as  $V_n \rightarrow 0$
- $E[p_n(\mathbf{x})] = \int \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}'}{h_n}\right) p(\mathbf{x}') d\mathbf{x}'$
- The variance of the estimate is given by:

$$\text{Var}[p_n(\mathbf{x})] \leq \frac{\sup(\varphi(\cdot)) E[p_n(\mathbf{x})]}{n V_n}$$

- variance can be decreased when  $n V_n \rightarrow 0$  (e.g.,  $V_n = 1/\sqrt{n}$ )

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 27

## Parzen-Window Estimation

- Convergence Conditions
- $\lim_{n \rightarrow \infty} E[p_n(\mathbf{x})] = p(\mathbf{x})$
- $\lim_{n \rightarrow \infty} \text{Var}[p_n(\mathbf{x})] = 0$
- We have the following additional constraints:

$\sup_{\mathbf{u}} \varphi(\mathbf{u}) < \infty$	$\lim_{\ \mathbf{u}\  \rightarrow \infty} \varphi(\mathbf{u}) \prod_{i=1}^d u_i = 0$
$\lim_{n \rightarrow \infty} V_n = 0$	$\lim_{n \rightarrow \infty} n V_n = \infty$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 28

## Parzen-Window Estimation

- Choosing the Window Function
- $V_n$  must approach 0 when  $n \rightarrow \infty$ , but at a rate slower than  $1/n$ , e.g.,

$$V_n = V_1 / \sqrt{n}$$

- The value of initial volume  $V_1$  is important.
- In some cases, a cell volume is proper for one region but unsuitable in a different region.

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

$$\lim_{n \rightarrow \infty} V_n = 0$$

$$\lim_{n \rightarrow \infty} n V_n = \infty$$

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 29

## Parzen-Window Estimation

- 1D Illustration

$$\varphi(\mathbf{u}) = \frac{1}{\sqrt{2\pi}} e^{-u^2/2}$$

$$h_n = h_1 / \sqrt{n}$$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 30

## Parzen-Window Estimation

- 1D Illustration

$$\phi(\mathbf{u}) = \frac{1}{\sqrt{2\pi}} e^{-u^2/2}$$

$$h_n = h_1 / \sqrt{n}$$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \phi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 31

## Parzen-Window Estimation

- 2D Illustration

$$\phi(\mathbf{u}) = N(u, 1)$$

$$h_n = h_1 / \sqrt{n}$$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \phi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 32

## Classification using Parzen-Window Estimation

- Estimate density for each class.
- Classify a test point by computing the posterior probabilities and picking the max.
- The decision regions depend on the choice of the kernel function and  $h_n$ .

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 33

## Pros and Cons of Parzen-Window Estimation

<b>Pros</b> <ul style="list-style-type: none"> <li>Generality: no assumption on the form of the density</li> <li>It approximates to the true density when the samples are infinity</li> </ul>	<b>Cons</b> <ul style="list-style-type: none"> <li>Require a <u>large number</u> of samples to be <u>stored</u>.</li> <li>Evaluation of the density could be very <u>slow</u> if the number of data points is large.           <ul style="list-style-type: none"> <li><b>Possible solution:</b> use fewer kernels and adapt the positions and widths in response to the data (e.g., mixtures of Gaussians!)</li> </ul> </li> </ul>
---	--

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 34

## Pros and Cons of Parzen-Window Estimation

- When the  $p(x)$  is not even, one window size may not fit all.

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 35

## PNN (Probabilistic Neural Network)

- PNN
- Theory and Model

TULIP Team for Universal Learning and Intelligent Processing FLIP: Pattern Recognition (G. Li) 36

## Probabilistic Neural Network

- The PNN is a hardware implementation of the kernel-based method of density estimation and Bayesian optimal classification (providing minimization of the average probability of the classification error)
  - Optimal Bayes' classification rule
  - (Parzen-Window) Estimation of a probability density function

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

$$p(\mathbf{x} | \omega_i)$$



FLIP: Pattern Recognition (G. Li)

37

## Probabilistic Neural Network

$$\mathcal{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n\}$$

$$\varphi\left(\frac{\mathbf{x} - \mathbf{x}_k}{h_n}\right) = \alpha \exp\left[-\frac{1}{2h_n^2}(\mathbf{x} - \mathbf{x}_k)^T(\mathbf{x} - \mathbf{x}_k)\right] = \alpha \exp\left[-\frac{1}{2h_n^2}(\mathbf{x}^T \mathbf{x} - 2\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k)^T\right]$$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{k=1}^n \frac{1}{V_n} \alpha \exp\left[-\frac{1}{2h_n^2}(\mathbf{x}^T \mathbf{x} - 2\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k)^T\right]$$

$$= \sum_{k=1}^n \alpha' \exp\left[-\frac{1}{2h_n^2}(\mathbf{x}^T \mathbf{x} - 2\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k)^T\right] \approx \sum_{k=1}^n \exp\left[\frac{1}{h_n^2}(\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k / 2)^T\right]$$

Irrelevant for discriminant analysis

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

$$p(\mathbf{x} | \omega_i)$$

FLIP: Pattern Recognition (G. Li)

38

## Probabilistic Neural Network

$$\mathcal{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n\} \quad \Sigma = \mathbf{I}$$

$$\varphi\left(\frac{\mathbf{x} - \mathbf{x}_k}{h_n}\right) = \alpha \exp\left[-\frac{1}{2h_n^2}(\mathbf{x} - \mathbf{x}_k)^T(\mathbf{x} - \mathbf{x}_k)\right] = \alpha \exp\left[-\frac{1}{2h_n^2}(\mathbf{x}^T \mathbf{x} - 2\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k)^T\right]$$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{k=1}^n \frac{1}{V_n} \alpha \exp\left[-\frac{1}{2h_n^2}(\mathbf{x}^T \mathbf{x} - 2\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k)^T\right]$$

$$= \sum_{k=1}^n \alpha' \exp\left[-\frac{1}{2h_n^2}(\mathbf{x}^T \mathbf{x} - 2\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k)^T\right] \approx \sum_{k=1}^n \exp\left[\frac{1}{h_n^2}(\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k / 2)^T\right]$$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$

$$p(\mathbf{x} | \omega_i)$$



FLIP: Pattern Recognition (G. Li)

39

## Probabilistic Neural Network

$$\mathcal{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n\} \quad \Sigma = \mathbf{I}$$

$$\varphi\left(\frac{\mathbf{x} - \mathbf{x}_k}{h_n}\right) = \alpha \exp\left[-\frac{1}{2h_n^2}(\mathbf{x} - \mathbf{x}_k)^T(\mathbf{x} - \mathbf{x}_k)\right] = \alpha \exp\left[-\frac{1}{2h_n^2}(\mathbf{x}^T \mathbf{x} - 2\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k)^T\right]$$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{k=1}^n \frac{1}{V_n} \alpha \exp\left[-\frac{1}{2h_n^2}(\mathbf{x}^T \mathbf{x} - 2\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k)^T\right]$$

$$= \sum_{k=1}^n \alpha' \exp\left[-\frac{1}{2h_n^2}(\mathbf{x}^T \mathbf{x} - 2\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k)^T\right] \approx \sum_{k=1}^n \exp\left[\frac{1}{h_n^2}(\mathbf{x}^T \mathbf{x}_k + \mathbf{x}_k^T \mathbf{x}_k / 2)^T\right]$$

$$p_n(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \frac{1}{V_n} \varphi\left(\frac{\mathbf{x} - \mathbf{x}_i}{h_n}\right)$$




FLIP: Pattern Recognition (G. Li)

40

## Probabilistic Neural Network

**Assign patterns to the class with maximum output values.**

$$p(\mathbf{x} | \omega_1) \propto o_1 \quad p(\mathbf{x} | \omega_2) \propto o_2 \quad p(\mathbf{x} | \omega_c) \propto o_c$$



FLIP: Pattern Recognition (G. Li)

41

## Seminar S07

### Topics


- Present one specific application of the Parzen-window (kernel-estimator) classifier.
- Present/Design one method to incorporate Prior Probabilities into PNN

### Requirements

- Prepare a **15 minutes** talk on your chosen topic
- Make **ppt** to assist your talk
- Prepare **at least 3 questions** to ask the audience after your talk
- Get ready to **take questions** from the audience

### Hints

- You can search for research articles from Google Scholar



FLIP: Pattern Recognition (G. Li)

42

